

**Internet Systems Consortium** 

## **CONTENTS**

1	ALL	
	1.1	ALLOC_ENGINE_IGNORING_UNSUITABLE_GLOBAL_ADDRESS
	1.2	ALLOC_ENGINE_IGNORING_UNSUITABLE_GLOBAL_ADDRESS6
	1.3	ALLOC_ENGINE_LEASE_RECLAIMED
	1.4	ALLOC_ENGINE_V4_ALLOC_ERROR
	1.5	ALLOC_ENGINE_V4_ALLOC_FAIL
	1.6	ALLOC_ENGINE_V4_ALLOC_FAIL_CLASSES
	1.7	ALLOC_ENGINE_V4_ALLOC_FAIL_NO_POOLS
	1.8	ALLOC_ENGINE_V4_ALLOC_FAIL_SHARED_NETWORK
	1.9	ALLOC_ENGINE_V4_ALLOC_FAIL_SUBNET
	1.10	ALLOC_ENGINE_V4_DECLINED_RECOVERED
	1.11	ALLOC_ENGINE_V4_DISCOVER_ADDRESS_CONFLICT
	1.12	ALLOC_ENGINE_V4_DISCOVER_HR
	1.13	
		ALLOC_ENGINE_V4_LEASES_RECLAMATION_FAILED
		ALLOC_ENGINE_V4_LEASES_RECLAMATION_SLOW 6
		ALLOC_ENGINE_V4_LEASES_RECLAMATION_START 6
	1.17	ALLOC_ENGINE_V4_LEASES_RECLAMATION_TIMEOUT 6
	1.18	ALLOC_ENGINE_V4_LEASE_RECLAIM
	1.19	ALLOC_ENGINE_V4_LEASE_RECLAMATION_FAILED
	1.20	
	1.21	
		ALLOC_ENGINE_V4_OFFER_NEW_LEASE
		ALLOC_ENGINE_V4_OFFER_REQUESTED_LEASE
		ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE
		ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_COMPLETE
	1.26	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_FAILED
	1.27	
	1.28	ALLOC_ENGINE_V4_REQUEST_ALLOC_REQUESTED
		ALLOC_ENGINE_V4_REQUEST_EXTEND_LEASE
		ALLOC_ENGINE_V4_REQUEST_INVALID
		ALLOC_ENGINE_V4_REQUEST_IN_USE
	1.32	ALLOC_ENGINE_V4_REQUEST_OUT_OF_POOL
	1.33	
	1.34	ALLOC_ENGINE_V4_REQUEST_REMOVE_LEASE
	1.35	ALLOC_ENGINE_V4_REQUEST_USE_HR 10
	1.36	ALLOC_ENGINE_V4_REUSE_EXPIRED_LEASE_DATA
	1.37	ALLOC_ENGINE_V6_ALLOC_ERROR
	1.38	
	1.39	ALLOC_ENGINE_V6_ALLOC_FAIL_CLASSES

	1.40	ALLOC_ENGINE_V6_ALLOC_FAIL_NO_POOLS	11
	1.41	ALLOC_ENGINE_V6_ALLOC_FAIL_SHARED_NETWORK	11
	1.42	ALLOC_ENGINE_V6_ALLOC_FAIL_SUBNET	12
		ALLOC_ENGINE_V6_ALLOC_HR_LEASE_EXISTS	12
		ALLOC_ENGINE_V6_ALLOC_LEASES_HR	12
		ALLOC_ENGINE_V6_ALLOC_LEASES_NO_HR	12
		ALLOC_ENGINE_V6_ALLOC_NO_LEASES_HR	13
		ALLOC_ENGINE_V6_ALLOC_NO_V6_HR	13
	1.47	ALLOC_ENGINE_V6_ALLOC_UNRESERVED	13
	1.49	ALLOC_ENGINE_V6_CALCULATED_PREFERRED_LIFETIME	
			13
	1.50	ALLOC_ENGINE_V6_DECLINED_RECOVERED	13
		ALLOC_ENGINE_V6_EXPIRED_HINT_RESERVED	14
		ALLOC_ENGINE_V6_EXTEND_ALLOC_UNRESERVED	14
		ALLOC_ENGINE_V6_EXTEND_ERROR	14
		ALLOC_ENGINE_V6_EXTEND_LEASE	14
		ALLOC_ENGINE_V6_EXTEND_LEASE_DATA	14
		ALLOC_ENGINE_V6_EXTEND_NEW_LEASE_DATA	15
	1.57	ALLOC_ENGINE_V6_HINT_RESERVED	15
	1.58	ALLOC_ENGINE_V6_HR_ADDR_GRANTED	15
	1.59	ALLOC_ENGINE_V6_HR_PREFIX_GRANTED	15
	1.60	ALLOC_ENGINE_V6_LEASES_RECLAMATION_COMPLETE	15
	1.61	ALLOC_ENGINE_V6_LEASES_RECLAMATION_FAILED	16
	1.62	ALLOC_ENGINE_V6_LEASES_RECLAMATION_SLOW	16
	1.63	ALLOC_ENGINE_V6_LEASES_RECLAMATION_START	16
	1.64	ALLOC_ENGINE_V6_LEASES_RECLAMATION_TIMEOUT	16
		ALLOC_ENGINE_V6_LEASE_RECLAIM	16
		ALLOC_ENGINE_V6_LEASE_RECLAMATION_FAILED	17
	1.67	ALLOC_ENGINE_V6_NO_MORE_EXPIRED_LEASES	17
	1.68	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE	17
	1.69	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_COMPLETE	17
	1.70	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_FAILED	17
	1.71	ALLOC_ENGINE_V6_RENEW_HR	18
	1.72	ALLOC_ENGINE_V6_RENEW_REMOVE_RESERVED	18
	1.72	ALLOC_ENGINE_V6_REUSE_EXPIRED_LEASE_DATA	18
		ALLOC ENGINE V6 REVOKED ADDR LEASE	
	1.74		18
	1.75	ALLOC_ENGINE_V6_REVOKED_PREFIX_LEASE	18
	1./6	ALLOC_ENGINE_V6_REVOKED_SHARED_ADDR_LEASE	19
2	ASIC	DDNS	21
_	2.1	ASIODNS_FETCH_COMPLETED	21
	2.2	ASIODNS_FETCH_STOPPED	21
	2.3	ASIODNS_OPEN_SOCKET	21
	2.4		21
		ASIODNS_READ_DATA	
	2.5	ASIODNS_READ_TIMEOUT	22
	2.6	ASIODNS_SEND_DATA	22
	2.7	ASIODNS_UNKNOWN_ORIGIN	22
3	воо	ТР	23
	3.1	BOOTP_BOOTP_QUERY	23
	3.2	BOOTP_LOAD	23
	3.3	BOOTP_PACKET_OPTIONS_SKIPPED	23
	3.4	BOOTP_PACKET_PACK	23
	3.5	BOOTP_PACKET_PACK	24
	3.6	BOOTP_PACKET_PACK_FAILED	24 24
	5.0	DUUTI_IACKET_UNIACK_FAILED	- 44

4	COM	IMAND	25
	4.1	COMMAND_ACCEPTOR_START	25
	4.2	COMMAND_DEREGISTERED	25
	4.3	COMMAND_EXTENDED_REGISTERED	25
	4.4	COMMAND_HTTP_LISTENER_COMMAND_REJECTED	25
	4.5	COMMAND_HTTP_LISTENER_STARTED	26
	4.6	COMMAND_HTTP_LISTENER_STOPPED	26
	4.7	COMMAND_HTTP_LISTENER_STOPPING	26
	4.8	COMMAND_PROCESS_ERROR1	26
	4.9	COMMAND_PROCESS_ERROR2	26
	4.10	COMMAND_RECEIVED	27
	4.11	COMMAND_REGISTERED	27
	4.12	COMMAND_RESPONSE_ERROR	27
	4.13	COMMAND_SOCKET_ACCEPT_FAIL	27
	4.14	COMMAND_SOCKET_CLOSED_BY_FOREIGN_HOST	27
	4.15	COMMAND_SOCKET_CONNECTION_CANCEL_FAIL	27
	4.16	COMMAND_SOCKET_CONNECTION_CLOSED	28
	4.17	COMMAND_SOCKET_CONNECTION_CLOSE_FAIL	28
	4.18	COMMAND_SOCKET_CONNECTION_OPENED	28
	4.19	COMMAND_SOCKET_CONNECTION_SHUTDOWN_FAIL	28
	4.20	COMMAND_SOCKET_CONNECTION_TIMEOUT	28
	4.21	COMMAND_SOCKET_READ	28
		COMMAND_SOCKET_READ_FAIL	29
	4.23	COMMAND_SOCKET_WRITE	29
		COMMAND_SOCKET_WRITE_FAIL	29
		COMMAND_WATCH_SOCKET_CLEAR_ERROR	29
		COMMAND_WATCH_SOCKET_CLOSE_ERROR	29
	4.27	COMMAND_WATCH_SOCKET_MARK_READY_ERROR	29
5	CTR	L	31
	5.1	CTRL_AGENT_COMMAND_FORWARDED	31
	5.2	CTRL_AGENT_COMMAND_FORWARD_BEGIN	31
	5.3	CTRL_AGENT_COMMAND_FORWARD_FAILED	31
	5.4	CTRL_AGENT_COMMAND_RECEIVED	31
	5.5	CTRL_AGENT_CONFIG_CHECK_FAIL	32
	5.6	CTRL_AGENT_CONFIG_FAIL	32
	5.7	CTRL_AGENT_CONFIG_SYNTAX_WARNING	32
	5.8	CTRL_AGENT_FAILED	32
	5.9	CTRL_AGENT_HTTPS_SERVICE_REUSED	32
	5.10	CTRL_AGENT_HTTPS_SERVICE_STARTED	32
	5.11	CTRL_AGENT_HTTP_SERVICE_REUSED	33
	5.12	CTRL_AGENT_HTTP_SERVICE_STARTED	33
	5.13	CTRL_AGENT_RUN_EXIT	33
	-		
6		ABASE	35
	6.1	DATABASE_INVALID_ACCESS	35
	6.2	DATABASE_MYSQL_COMMIT	35
	6.3	DATABASE_MYSQL_FATAL_ERROR	35
	6.4	DATABASE_MYSQL_INITIALIZE_SCHEMA	35
	6.5	DATABASE_MYSQL_ROLLBACK	36
	6.6	DATABASE_MYSQL_START_TRANSACTION	36
	6.7	DATABASE_PGSQL_COMMIT	36
	6.8	DATABASE_PGSQL_CREATE_SAVEPOINT	36
	6.9	DATABASE_PGSQL_DEALLOC_ERROR	36

	6.10	DATABASE_PGSQL_FATAL_ERROR	37
	6.11	DATABASE_PGSQL_INITIALIZE_SCHEMA	37
	6.12	DATABASE_PGSQL_ROLLBACK	37
	6.13	DATABASE_PGSQL_ROLLBACK_SAVEPOINT	37
	6.14	DATABASE_PGSQL_START_TRANSACTION	37
	6.15	DATABASE_PGSQL_TCP_USER_TIMEOUT_UNSUPPORTED	38
	6.16	DATABASE_TO_JSON_BOOLEAN_ERROR	38
		DATABASE_TO_JSON_INTEGER_ERROR	38
	0.17	DITIONSD_TO_9001(_INTEGER_BIRROR	50
7	DCT	${f L}$	39
	7.1	DCTL_ALREADY_RUNNING	39
	7.2	DCTL CFG FILE RELOAD ERROR	39
	7.3	DCTL_CFG_FILE_RELOAD_SIGNAL_RECVD	39
	7.4	DCTL_CONFIG_CHECK_COMPLETE	39
	7.5	DCTL_CONFIG_COMPLETE	40
	7.6	DCTL_CONFIG_DEPRECATED	40
	7.7	DCTL_CONFIG_FETCH	40
	7.8	DCTL_CONFIG_FILE_LOAD_FAIL	40
	7.9	DCTL_CONFIG_START	40
	7.10	DCTL DB OPEN CONNECTION WITH RETRY FAILED	41
			41
	7.11	DCTL_DEPRECATED_OUTPUT_OPTIONS	
		DCTL_DEVELOPMENT_VERSION	41
	7.13	DCTL_INIT_PROCESS	41
		DCTL_INIT_PROCESS_FAIL	41
	7.15	DCTL_NOT_RUNNING	41
		DCTL_OPEN_CONFIG_DB	42
		DCTL_PARSER_FAIL	42
		DCTL_PID_FILE_ERROR	42
		DCTL_PROCESS_FAILED	42
		DCTL_RUN_PROCESS	42
	7.21	DCTL_SHUTDOWN	43
	7.22	DCTL_SHUTDOWN_SIGNAL_RECVD	43
	7.23	DCTL_STANDALONE	43
	7.24	DCTL_STARTING	43
	7.25	DCTL_UNLOAD_LIBRARIES_ERROR	43
8	DHC		45
	8.1	DHCP4_ADDITIONAL_CLASS_EVAL_ERROR	45
	8.2	DHCP4_ADDITIONAL_CLASS_EVAL_RESULT	45
	8.3	DHCP4_ADDITIONAL_CLASS_NO_TEST	45
	8.4	DHCP4_ADDITIONAL_CLASS_UNDEFINED	45
	8.5	DHCP4_ALREADY_RUNNING	46
	8.6	DHCP4_BUFFER_RECEIVED	46
	8.7	DHCP4_BUFFER_RECEIVE_FAIL	46
	8.8	DHCP4_BUFFER_UNPACK	46
	8.9	DHCP4_BUFFER_WAIT_SIGNAL	46
	8.10	DHCP4_CB_ON_DEMAND_FETCH_UPDATES_FAIL	47
	8.11	DHCP4_CB_PERIODIC_FETCH_UPDATES_FAIL	47
	8.12	DHCP4_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED	47
	8.13	DHCP4_CLASSES_ASSIGNED	47
	8.14	DHCP4_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION	47
	8.15	DHCP4_CLASS_ASSIGNED	48
	8.16	DHCP4_CLASS_UNCONFIGURED	48
	8.17	DHCP4_CLIENTID_IGNORED_FOR_LEASES	48

8.18	DHCP4_CLIENT_FQDN_DATA	48
8.19	DHCP4_CLIENT_FQDN_PROCESS	48
8.20	DHCP4_CLIENT_HOSTNAME_DATA	49
8.21	DHCP4_CLIENT_HOSTNAME_MALFORMED	49
8.22	DHCP4_CLIENT_HOSTNAME_PROCESS	49
8.23	DHCP4_CLIENT_NAME_PROC_FAIL	49
8.24	DHCP4_CONFIG_COMPLETE	49
8.25	DHCP4_CONFIG_LOAD_FAIL	50
8.26	DHCP4_CONFIG_PACKET_QUEUE	50
8.27	DHCP4_CONFIG_RECEIVED	50
8.28	DHCP4_CONFIG_START	50
8.29	DHCP4_CONFIG_SYNTAX_WARNING	50
8.30	DHCP4_CONFIG_UNRECOVERABLE_ERROR	51
8.31	DHCP4_CONFIG_UNSUPPORTED_OBJECT	51
8.32	DHCP4_DB_RECONNECT_DISABLED	51
8.33	DHCP4_DB_RECONNECT_FAILED	51
8.34	DHCP4_DB_RECONNECT_LOST_CONNECTION	51
8.35	DHCP4_DB_RECONNECT_NO_DB_CTL	52
8.36	DHCP4_DB_RECONNECT_SUCCEEDED	52
8.37	DHCP4_DDNS_REQUEST_SEND_FAILED	52
8.38	DHCP4_DECLINE_FAIL	52
8.39	DHCP4_DECLINE_LEASE	52
8.40	DHCP4_DECLINE_LEASE_MISMATCH	53
8.41	DHCP4_DECLINE_LEASE_NOT_FOUND	53
8.42	DHCP4_DEFERRED_OPTION_MISSING	53
8.43	DHCP4_DEFERRED_OPTION_UNPACK_FAIL	53
8.44	DHCP4_DEVELOPMENT_VERSION	53
8.45	DHCP4_DHCP4O6_BAD_PACKET	54
8.46	DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_DROP	54
8.47	DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_SKIP	54
8.48	DHCP4_DHCP4O6_PACKET_RECEIVED	54
8.49	DHCP4_DHCP4O6_PACKET_SEND	54 55
8.50	DHCP4_DHCP4O6_PACKET_SEND_FAIL	55 55
8.51	DHCP4_DHCP4O6_RECEIVE_FAIL	55 55
8.52 8.53	DHCP4_DHCP4O6_RECEIVING	55 55
	DHCP4_DHCP4O6_SUBNET_DATA	55 55
	DHCP4_DHCP4O6_SUBNET_SELECTED	55 56
	DHCP4_DHCP4O6_SUBNET_SELECTION_FAILED	56
8.57	DHCP4_DISCOVER	56
8.58	DHCP4_DYNAMIC_RECONFIGURATION	56
8.59	DHCP4 DYNAMIC RECONFIGURATION FAIL	56
8.60	DHCP4_DYNAMIC_RECONFIGURATION_SUCCESS	57
8.61	DHCP4_EMPTY_HOSTNAME	57
8.62	DHCP4_FLEX_ID	57
8.63	DHCP4_GENERATE_FQDN	57
8.64	DHCP4_HOOK_BUFFER_RCVD_DROP	57
8.65	DHCP4_HOOK_BUFFER_RCVD_SKIP	58
8.66	DHCP4_HOOK_BUFFER_SEND_SKIP	58
8.67	DHCP4_HOOK_DDNS_UPDATE	58
8.68	DHCP4_HOOK_DECLINE_SKIP	58
8.69	DHCP4_HOOK_LEASE4_OFFER_ARGUMENT_MISSING	58
8.70	DHCP4_HOOK_LEASE4_OFFER_DROP	59
8.71	DHCP4_HOOK_LEASE4_OFFER_PARK	59

8.72	DHCP4_HOOK_LEASE4_OFFER_PARKING_LOT_FULL	59
8.73	DHCP4_HOOK_LEASE4_RELEASE_SKIP	59
8.74	DHCP4_HOOK_LEASES4_COMMITTED_DROP	59
8.75	DHCP4_HOOK_LEASES4_COMMITTED_PARK	59
8.76	DHCP4_HOOK_LEASES4_COMMITTED_PARKING_LOT_FULL	60
8.77	DHCP4_HOOK_PACKET_RCVD_SKIP	60
8.78	DHCP4_HOOK_PACKET_SEND_DROP	60
8.79	DHCP4_HOOK_PACKET_SEND_SKIP	60
8.80	DHCP4_HOOK_SUBNET4_SELECT_4O6_PARKING_LOT_FULL	60
8.81	DHCP4_HOOK_SUBNET4_SELECT_DROP	61
8.82	DHCP4_HOOK_SUBNET4_SELECT_PARK	61
8.83	DHCP4_HOOK_SUBNET4_SELECT_PARKING_LOT_FULL	61
8.84	DHCP4_HOOK_SUBNET4_SELECT_SKIP	61
8.85	DHCP4_HOOK_SUBNET6_SELECT_PARKING_LOT_FULL	61
8.86	DHCP4_INFORM_DIRECT_REPLY	62
	DHCP4_INIT_FAIL	62
	DHCP4_INIT_REBOOT	62
8.89	DHCP4_LEASE_ALLOC	62
	DHCP4_LEASE_OFFER	62
8.91	DHCP4_LEASE_REUSE	63
8.92	DHCP4_MULTI_THREADING_INFO	63
8.93	DHCP4_NCR_CREATION_FAILED	63
	DHCP4_NOT_RUNNING	63
8.95	DHCP4_NO_LEASE_INIT_REBOOT	63
	DHCP4_OPEN_SOCKET	64
8.97	DHCP4_OPEN_SOCKETS_FAILED	64
	DHCP4_OPEN_SOCKETS_NO_RECONNECT_CTL	64
	DHCP4_PACKET_DROP_0001	64
	DHCP4_PACKET_DROP_0002	64
	DHCP4_PACKET_DROP_0003	65
	DHCP4_PACKET_DROP_0004	65
	DHCP4_PACKET_DROP_0005	65
	DHCP4_PACKET_DROP_0006	65
	DHCP4_PACKET_DROP_0007	65
	DHCP4_PACKET_DROP_0008	66
	DHCP4_PACKET_DROP_0009	66
	DHCP4 PACKET DROP 0010	66
		66
	DHCP4_PACKET_DROP_0012	66
	DHCP4_PACKET_DROP_0013	67
	DHCP4_PACKET_DROP_0014	67
	DHCP4_PACKET_NAK_0001	67
	DHCP4_PACKET_NAK_0002	67
	DHCP4 PACKET NAK 0003	67
	DHCP4_PACKET_NAK_0004	68
	DHCP4_PACKET_OPTIONS_SKIPPED	68
	DHCP4_PACKET_PACK	68
	DHCP4_PACKET_PACK_FAIL	68
	DHCP4_PACKET_PROCESS_EXCEPTION	68
	DHCP4_PACKET_PROCESS_EXCEPTION_MAIN	69
	DHCP4_PACKET_PROCESS_STD_EXCEPTION	69
	DHCP4_PACKET_PROCESS_STD_EXCEPTION_MAIN	69
	DHCP4_PACKET_QUEUE_FULL	69
8.125	DHCP4_PACKET_RECEIVED	69

8.126 DHCP4_PACKET_SEND	70
8.127 DHCP4_PACKET_SEND_FAIL	70
8.128 DHCP4_PARSER_COMMIT_EXCEPTION	70
8.129 DHCP4_PARSER_COMMIT_FAIL	70
	70
	71
	71
	71
	71
	71
	72
	72
	72
	72
	72
	73
	73
	73
	73
	73
	74
	74
	74
	74
	74
8.151 DHCP4_SERVER_FAILED	75
8.152 DHCP4_SERVER_INITIATED_DECLINE	75
8.153 DHCP4_SERVER_INITIATED_DECLINE_ADD_FAILED	75
8.154 DHCP4_SERVER_INITIATED_DECLINE_RESOURCE_BUSY	75
	75
	76
	76
	76
	76
	76
	77
	77
	77
<del>-</del>	77
	77
	78
	78
	78
	78 70
`	78
8.171 DHCP4_V6_ONLY_PREFERRED_MISSING_IN_ACK	79
DHCDC	01
	81
	81
	81
	81
	81
	82
9.6 DHCP6_ADD_STATUS_CODE_FOR_IA	82

9

9.7	DHCP6_ALREADY_RUNNING	82
9.8	DHCP6_BUFFER_RECEIVED	82
9.9	DHCP6_BUFFER_UNPACK	82
9.10	DHCP6_BUFFER_WAIT_SIGNAL	83
9.11	DHCP6_CB_ON_DEMAND_FETCH_UPDATES_FAIL	83
9.12	DHCP6_CB_PERIODIC_FETCH_UPDATES_FAIL	83
9.13	DHCP6_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED	83
9.14	DHCP6_CLASSES_ASSIGNED	83
9.15	DHCP6_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION	84
9.16	DHCP6_CLASS_ASSIGNED	84
9.17	DHCP6_CLASS_UNCONFIGURED	84
9.18	DHCP6_CONFIG_COMPLETE	84
9.19	DHCP6_CONFIG_LOAD_FAIL	84
9.20	DHCP6_CONFIG_PACKET_QUEUE	85
9.21	DHCP6_CONFIG_RECEIVED	85
9.22	DHCP6_CONFIG_START	85
9.23	DHCP6_CONFIG_SYNTAX_WARNING	85
9.24	DHCP6_CONFIG_UNRECOVERABLE_ERROR	85
9.25	DHCP6_CONFIG_UNSUPPORTED_OBJECT	86
9.26	DHCP6_DB_RECONNECT_DISABLED	86
9.27	DHCP6_DB_RECONNECT_FAILED	86
9.28	DHCP6_DB_RECONNECT_LOST_CONNECTION	86
9.29	DHCP6_DB_RECONNECT_NO_DB_CTL	86
9.30	DHCP6_DB_RECONNECT_SUCCEEDED	86
9.31	DHCP6_DDNS_CREATE_ADD_NAME_CHANGE_REQUEST	87
9.32	DHCP6_DDNS_FQDN_GENERATED	87
9.33	DHCP6_DDNS_GENERATED_FQDN_UPDATE_FAIL	87
9.34	DHCP6_DDNS_GENERATE_FQDN	87
9.35	DHCP6_DDNS_RECEIVE_FQDN	87
9.36	DHCP6_DDNS_REMOVE_OLD_LEASE_FQDN	88
9.37	DHCP6_DDNS_REQUEST_SEND_FAILED	88
9.38	DHCP6_DDNS_RESPONSE_FQDN_DATA	88
9.39	DHCP6_DECLINE_FAIL	88
9.40	DHCP6_DECLINE_FAIL_DUID_MISMATCH	88
9.41	DHCP6_DECLINE_FAIL_IAID_MISMATCH	89
9.42	DHCP6_DECLINE_FAIL_LEASE_WITHOUT_DUID	89
9.43	DHCP6_DECLINE_FAIL_NO_LEASE	89
	DHCP6_DECLINE_LEASE	89
	DHCP6_DECLINE_PROCESS_IA	89
9.46	DHCP6_DEVELOPMENT_VERSION	90
9.47	DHCP6_DHCP406_PACKET_RECEIVED	90
9.48	DHCP6_DHCP406_RECEIVE_FAIL	90
9.49	DHCP6_DHCP406_RECEIVING	90
9.50	DHCP6_DHCP406_RESPONSE_DATA	90
9.51	DHCP6_DHCP4O6_SEND_FAIL	91
9.52	DHCP6_DYNAMIC_RECONFIGURATION	91
9.53	DHCP6_DYNAMIC_RECONFIGURATION_FAIL	91
9.54	DHCP6_DYNAMIC_RECONFIGURATION_SUCCESS	91
9.55	DHCP6_FLEX_ID	91
9.56	DHCP6_HOOK_BUFFER_RCVD_DROP	91
9.57	DHCP6_HOOK_BUFFER_RCVD_SKIP	92
9.58	DHCP6_HOOK_BUFFER_SEND_SKIP	92
9.59	DHCP6_HOOK_DDNS_UPDATE	92
9.60	DHCP6_HOOK_DECLINE_DROP	92

9.61	DHCP6_HOOK_DECLINE_SKIP	93
9.62	DHCP6_HOOK_LEASE6_RELEASE_NA_SKIP	93
9.63	DHCP6_HOOK_LEASE6_RELEASE_PD_SKIP	93
9.64	DHCP6_HOOK_LEASES6_COMMITTED_DROP	93
9.65	DHCP6_HOOK_LEASES6_COMMITTED_PARK	93
9.66	DHCP6_HOOK_LEASES6_PARKING_LOT_FULL	94
9.67	DHCP6_HOOK_PACKET_RCVD_SKIP	94
9.68	DHCP6_HOOK_PACKET_SEND_DROP	94
9.69	DHCP6_HOOK_PACKET_SEND_SKIP	94
9.70	DHCP6_HOOK_SUBNET6_SELECT_DROP	94
9.71	DHCP6_HOOK_SUBNET6_SELECT_PARK	95
9.72	DHCP6_HOOK_SUBNET6_SELECT_SKIP	95
9.73	DHCP6_INIT_FAIL	95
	DHCP6_LEASE_ADVERT	95
9.75	DHCP6_LEASE_ADVERT_FAIL	95
	DHCP6_LEASE_ALLOC	96
9.77	DHCP6_LEASE_ALLOC_FAIL	96
	DHCP6_LEASE_DATA	96
9.79	DHCP6 LEASE NA WITHOUT DUID	96
	DHCP6_LEASE_PD_WITHOUT_DUID	96
9.81	DHCP6_LEASE_RENEW	97
9.82	DHCP6_LEASE_REUSE	97
9.83	DHCP6_MULTI_THREADING_INFO	97
9.84	DHCP6_NOT_RUNNING	97
	DHCP6_NO_INTERFACES	97
	DHCP6_OPEN_SOCKET	98
9.80	DHCP6_OPEN_SOCKETS_FAILED	98 98
9.88		98 98
	DHCP6_OPEN_SOCKETS_NO_RECONNECT_CTL	
9.89	DHCP6_PACKET_DROP_DHCP_DISABLED	98
9.90	DHCP6_PACKET_DROP_DROP_CLASS	98
9.91	DHCP6_PACKET_DROP_DROP_CLASS2	99
9.92	DHCP6_PACKET_DROP_DROP_CLASS_EARLY	99
	DHCP6_PACKET_DROP_DUPLICATE	99
9.94	DHCP6_PACKET_DROP_PARSE_FAIL	99
9.95	DHCP6_PACKET_DROP_SERVERID_MISMATCH	99
9.96		100
9.97	DHCP6_PACKET_OPTIONS_SKIPPED	
		100
	DHCP6_PACKET_PROCESS_EXCEPTION_MAIN	
	DHCP6_PACKET_PROCESS_FAIL	
	DHCP6_PACKET_PROCESS_STD_EXCEPTION	
	DHCP6_PACKET_PROCESS_STD_EXCEPTION_MAIN	
	DHCP6_PACKET_QUEUE_FULL	
	DHCP6_PACKET_RECEIVED	
	DHCP6_PACKET_RECEIVE_FAIL	
	DHCP6_PACKET_SEND	
	DHCP6_PACKET_SEND_FAIL	
	DHCP6_PACK_FAIL	
	DHCP6_PARSER_COMMIT_EXCEPTION	
	DHCP6_PARSER_COMMIT_FAIL	
	DHCP6_PARSER_EXCEPTION	
	DHCP6_PARSER_FAIL	
	DHCP6_PD_LEASE_ADVERT	
9.114	DHCP6 PD LEASE ADVERT FAIL	103

	9.115 DHCP6_PD_LEASE_ALLOC	
	9.116 DHCP6_PD_LEASE_ALLOC_FAIL	
	9.117 DHCP6_PD_LEASE_RENEW	
	9.118 DHCP6_PD_LEASE_REUSE	
	9.119 DHCP6_PROCESS_IA_NA_EXTEND	
	9.120 DHCP6_PROCESS_IA_NA_RELEASE	104
	9.121 DHCP6_PROCESS_IA_NA_REQUEST	105
	9.122 DHCP6_PROCESS_IA_NA_SOLICIT	105
	9.123 DHCP6_PROCESS_IA_PD_EXTEND	105
	9.124 DHCP6_PROCESS_IA_PD_REQUEST	
	9.125 DHCP6_PROCESS_IA_PD_SOLICIT	
	9.126 DHCP6_QUERY_DATA	
	9.127 DHCP6_QUERY_LABEL	
	9.128 DHCP6_RAPID_COMMIT	
	9.129 DHCP6_RECLAIM_EXPIRED_LEASES_FAIL	
	9.130 DHCP6_RELEASE_NA	
	9.131 DHCP6_RELEASE_NA_DELETED	
	9.132 DHCP6_RELEASE_NA_EXPIRED	
	9.133 DHCP6_RELEASE_NA_FAIL	
	9.134 DHCP6 RELEASE NA FAIL WRONG DUID	
	9.135 DHCP6_RELEASE_NA_FAIL_WRONG_IAID	
	9.136 DHCP6_RELEASE_PD	
	9.137 DHCP6_RELEASE_PD_DELETED	
	9.138 DHCP6_RELEASE_PD_EXPIRED	
	9.139 DHCP6_RELEASE_PD_FAIL	
	9.140 DHCP6_RELEASE_PD_FAIL_WRONG_DUID	
	9.141 DHCP6_RELEASE_PD_FAIL_WRONG_IAID	
	9.142 DHCP6_REQUIRED_OPTIONS_CHECK_FAIL	
	9.143 DHCP6_RESERVATIONS_LOOKUP_FIRST_ENABLED	
	9.144 DHCP6_RESPONSE_DATA	
	9.145 DHCP6_SERVER_FAILED	
	9.146 DHCP6_SHUTDOWN	
	9.147 DHCP6_SHUTDOWN_REQUEST	
	9.148 DHCP6_SRV_CONSTRUCT_ERROR	
	9.149 DHCP6_SRV_D2STOP_ERROR	
	9.150 DHCP6_SRV_UNLOAD_LIBRARIES_ERROR	
	9.151 DHCP6_STARTED	
	9.152 DHCP6_STARTING	
	9.153 DHCP6_START_INFO	
	9.154 DHCP6_SUBNET_DATA	
	9.155 DHCP6_SUBNET_DYNAMICALLY_CHANGED	
	9.156 DHCP6_SUBNET_SELECTED	112
	9.157 DHCP6_SUBNET_SELECTION_FAILED	112
	9.158 DHCP6_UNKNOWN_MSG_RECEIVED	112
10	DHCPSRV	113
	10.2 DHCPSRV_CFGMGR_ADD_SUBNET4	
	10.3 DHCPSRV_CFGMGR_ADD_SUBNET6	
	10.4 DHCPSRV_CFGMGR_ALL_IFACES_ACTIVE	
	10.5 DHCPSRV_CFGMGR_CFG_DHCP_DDNS	
	10.6 DHCPSRV_CFGMGR_CONFIG4_MERGED	
	10.7 DHCPSRV_CFGMGR_CONFIG6_MERGED	
	10.8 DHCPSRV_CFGMGR_CONFIGURE_SERVERID	114

	DHCPSRV_CFGMGR_DEL_SUBNET4	
	DHCPSRV_CFGMGR_DEL_SUBNET6	
	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES	
	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES_DONE	
10.13	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES	115
10.14	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES_DONE	115
10.15	DHCPSRV_CFGMGR_IPV4_RESERVATIONS_NON_UNIQUE_IGNORED	116
10.16	DHCPSRV_CFGMGR_IPV6_RESERVATIONS_NON_UNIQUE_IGNORED	116
10.17	DHCPSRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_DETECTED	116
10.18	DHCPSRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_POSSIBLE	116
	DHCPSRV_CFGMGR_NEW_SUBNET4	
	DHCPSRV_CFGMGR_NEW_SUBNET6	
	DHCPSRV_CFGMGR_OPTION_DUPLICATE	
	DHCPSRV_CFGMGR_RENEW_GTR_REBIND	
	DHCPSRV_CFGMGR_SOCKET_RAW_UNSUPPORTED	
	DHCPSRV_CFGMGR_SOCKET_TYPE_DEFAULT	
	DHCPSRV_CFGMGR_SOCKET_TYPE_SELECT	
	DHCPSRV_CFGMGR_SUBNET4	
	DHCPSRV_CFGMGR_SUBNET4_ADDR	
	DHCPSRV_CFGMGR_SUBNET4_IFACE	
	DHCPSRV_CFGMGR_SUBNET4_RELAY	
	DHCPSRV_CFGMGR_SUBNET6	
	DHCPSRV_CFGMGR_SUBNET6_IFACE	
	DHCPSRV_CFGMGR_SUBNET6_IFACE_ID	
	DHCPSRV_CFGMGR_SUBNET6_RELAY	
	DHCPSRV_CFGMGR_UNICAST_LINK_LOCAL	
10.35	DHCPSRV_CFGMGR_UPDATE_SUBNET4	120
	DHCPSRV_CFGMGR_UPDATE_SUBNET6	
	DHCPSRV_CFGMGR_USE_ADDRESS	
	DHCPSRV_CFGMGR_USE_ALLOCATOR	
10.30	DHCPSRV_CFGMGR_USE_UNICAST	120
	DHCPSRV_CLASS_WITH_ADDITIONAL_AND_LIFETIMES	
	DHCPSRV_CLIENT_CLASS_DEPRECATED	
10.41	DHCPSRV_CLOSE_DB	121
10.42	DHCPSRV_DDNS_TTL_PERCENT_TOO_SMALL	121
	DHCPSRV_DHCP4O6_RECEIVED_BAD_PACKET	
	DHCPSRV DHCP DDNS ERROR EXCEPTION	
	DHCPSRV_DHCP_DDNS_HANDLER_NULL	
	DHCPSRV_DHCP_DDNS_NCR_REJECTED	
	DHCPSRV_DHCP_DDNS_NCR_SENT	
	DHCPSRV DHCP DDNS SENDER STARTED	
	DHCPSRV_DHCP_DDNS_SENDER_STOPPED	
	DHCPSRV_DHCP_DDNS_SUSPEND_UPDATES	
	DHCPSRV_EVAL_ERROR	
	DHCPSRV_EVAL_RESULT	
	DHCPSRV_HOOK_LEASE4_RECOVER_SKIP	
	DHCPSRV_HOOK_LEASE4_RENEW_SKIP	
	DHCPSRV_HOOK_LEASE4_KENEW_SKIF	
	DHCPSRV_HOOK_LEASE4_SELECT_SKIP	
	DHCPSRV_HOOK_LEASE6_RECOVER_SKIP	
	DHCPSRV_HOOK_LEASE6_SELECT_SKIP	
	DHCPSRV_HOOK_LEASE6_SELECI_SKIP	
	DHCPSRV_HOST_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	
10.02	DHCPSRV_LEASE4_EXTENDED_INFO_UPGRADED	123

10.63 DHCPSRV_LEASE6_EXTENDED_INFO_SANITY_FAIL	125
10.64 DHCPSRV_LEASE6_EXTENDED_INFO_UPGRADED	125
10.65 DHCPSRV_LEASE_MGR_BACKENDS_REGISTERED	125
10.66 DHCPSRV_LEASE_MGR_BACKEND_DEREGISTER	126
10.67 DHCPSRV_LEASE_MGR_BACKEND_REGISTER	126
10.68 DHCPSRV_LEASE_MGR_CALLBACK_EXCEPTION	126
10.69 DHCPSRV_LEASE_MGR_CALLBACK_UNKNOWN_EXCEPTION	
10.70 DHCPSRV_LEASE_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	
10.71 DHCPSRV_LEASE_SANITY_FAIL	
10.72 DHCPSRV_LEASE_SANITY_FAIL_DISCARD	
10.73 DHCPSRV_LEASE_SANITY_FIXED	
10.74 DHCPSRV_MEMFILE_ADD_ADDR4	
10.75 DHCPSRV_MEMFILE_ADD_ADDR6	
10.76 DHCPSRV MEMFILE BEGIN BUILD EXTENDED INFO TABLES6	
10.77 DHCPSRV_MEMFILE_BEGIN_EXTRACT_EXTENDED_INFO4	
10.78 DHCPSRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6	
10.79 DHCPSRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6_ERROR	
10.80 DHCPSRV_MEMFILE_COMMIT	
10.81 DHCPSRV_MEMFILE_CONVERTING_LEASE_FILES	128
10.82 DHCPSRV_MEMFILE_DB	
10.83 DHCPSRV MEMFILE DELETE ADDR4	
10.84 DHCPSRV_MEMFILE_DELETE_ADDR6	
10.85 DHCPSRV MEMFILE DELETE EXPIRED RECLAIMED4	
10.86 DHCPSRV MEMFILE DELETE EXPIRED RECLAIMED6	
10.87 DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED_START	
10.88 DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4	
10.89 DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4_ERROR	
10.90 DHCPSRV_MEMFILE_GET4	
10.91 DHCPSRV_MEMFILE_GET6	
10.92 DHCPSRV_MEMFILE_GET6_DUID	
10.93 DHCPSRV_MEMFILE_GET_ADDR4	
10.94 DHCPSRV_MEMFILE_GET_ADDR6	
10.95 DHCPSRV_MEMFILE_GET_CLIENTID	
10.96 DHCPSRV_MEMFILE_GET_EXPIRED4	
10.97 DHCPSRV_MEMFILE_GET_EXPIRED6	
10.98 DHCPSRV_MEMFILE_GET_HOSTNAME4	
10.99 DHCPSRV_MEMFILE_GET_HOSTNAME6	
10.100DHCPSRV_MEMFILE_GET_HWADDR	
10.10IDHCPSRV_MEMFILE_GET_IAID_DUID	
10.102DHCPSRV_MEMFILE_GET_IAID_SUBID_DUID	
10.103DHCPSRV_MEMFILE_GET_PAGE4	
10.104DHCPSRV_MEMFILE_GET_PAGE6	
10.105DHCPSRV_MEMFILE_GET_RELAYID4	
10.106DHCPSRV_MEMFILE_GET_RELAYID6	133
10.107DHCPSRV_MEMFILE_GET_REMOTEID4	133
10.108DHCPSRV_MEMFILE_GET_REMOTEID6	
10.109DHCPSRV_MEMFILE_GET_SUBID4	134
10.110DHCPSRV_MEMFILE_GET_SUBID6	134
10.11 IDHCPSRV_MEMFILE_GET_SUBID_CLIENTID	134
10.112DHCPSRV_MEMFILE_GET_SUBID_HWADDR	134
10.113DHCPSRV_MEMFILE_GET_SUBID_PAGE6	
10.114DHCPSRV_MEMFILE_LEASE_FILE_LOAD	
10.115DHCPSRV_MEMFILE_LEASE_LOAD	
10.116DHCPSRV_MEMFILE_LEASE_LOAD_ROW_ERROR	135

	10.117DHCPSRV_MEMFILE_LFC_EXECUTE	
	10.118DHCPSRV_MEMFILE_LFC_LEASE_FILE_RENAME_FAIL	135
	10.119DHCPSRV_MEMFILE_LFC_LEASE_FILE_REOPEN_FAIL	135
	10.120DHCPSRV_MEMFILE_LFC_SETUP	136
	10.121DHCPSRV_MEMFILE_LFC_SPAWN_FAIL	136
	10.122DHCPSRV_MEMFILE_LFC_START	136
	10.123DHCPSRV_MEMFILE_LFC_UNREGISTER_TIMER_FAILED	136
	10.124DHCPSRV_MEMFILE_NEEDS_DOWNGRADING	136
	10.125DHCPSRV_MEMFILE_NEEDS_UPGRADING	
	10.126DHCPSRV_MEMFILE_NO_STORAGE	
	10.127DHCPSRV_MEMFILE_READ_HWADDR_FAIL	
	10.128DHCPSRV_MEMFILE_ROLLBACK	
	10.129DHCPSRV_MEMFILE_UPDATE_ADDR4	
	10.130DHCPSRV_MEMFILE_UPDATE_ADDR6	
	10.131DHCPSRV_MEMFILE_WIPE_LEASES4	
	10.132DHCPSRV_MEMFILE_WIPE_LEASES4_FINISHED	
	10.133DHCPSRV_MEMFILE_WIPE_LEASES6	
	10.134DHCPSRV_MEMFILE_WIPE_LEASES6_FINISHED	
	10.135DHCPSRV_MT_DISABLED_QUEUE_CONTROL	138
	10.136DHCPSRV_MULTIPLE_RAW_SOCKETS_PER_IFACE	
	10.137DHCPSRV_NOTYPE_DB	
	10.138DHCPSRV_NO_SOCKETS_OPEN	
	10.139DHCPSRV_ONLY_IF_REQUIRED_DEPRECATED	
	10.140DHCPSRV_OPEN_SOCKET_FAIL	
	10.14IDHCPSRV_QUEUE_NCR	
	10.142DHCPSRV_QUEUE_NCR_FAILED	
	10.142DHCPSRV_QUEUE_NCR_FAILED	
	10.144DHCPSRV_REQUIRE_CLIENT_CLASSES_DEPRECATED	
	10.144DHCPSRV_REQUIRE_CLIENT_CLASSES_DEPRECATED	
	10.146DHCPSRV_SUBNET4_SELECT_BY_ADDRESS_NO_MATCH	
	10.147DHCPSRV_SUBNET4_SELECT_BY_INTERFACE_NO_MATCH	
	10.14&DHCPSRV_SUBNET4_SELECT_BY_RELAY_ADDRESS_NO_MATCH	
	10.149DHCPSRV_SUBNET4_SELECT_NO_RAI_OPTIONS	
	10.150DHCPSRV_SUBNET4_SELECT_NO_RELAY_ADDRESS	
	10.15IDHCPSRV_SUBNET4_SELECT_NO_USABLE_ADDRESS	
	10.152DHCPSRV_SUBNET6_SELECT_BY_ADDRESS_NO_MATCH	
	10.153DHCPSRV_SUBNET6_SELECT_BY_INTERFACE_ID_NO_MATCH	
	10.154DHCPSRV_SUBNET6_SELECT_BY_INTERFACE_NO_MATCH	
	10.155DHCPSRV_TEMPLATE_EVAL_ERROR	
	10.15@HCPSRV_TEMPLATE_EVAL_RESULT	
	10.157DHCPSRV_TIMERMGR_CALLBACK_FAILED	
	10.158DHCPSRV_TIMERMGR_REGISTER_TIMER	
	10.159DHCPSRV_TIMERMGR_RUN_TIMER_OPERATION	
	10.160DHCPSRV_TIMERMGR_START_TIMER	
	10.16IDHCPSRV_TIMERMGR_STOP_TIMER	
	10.162DHCPSRV_TIMERMGR_UNREGISTER_ALL_TIMERS	
	10.163DHCPSRV_TIMERMGR_UNREGISTER_TIMER	144
11	DHCD	145
11	DHCP 11.1 DHCP_DDNS_ADD_FAILED	145
	11.2 DHCP_DDNS_AT_MAY_TRANSACTIONS	
	11.3 DHCP_DDNS_AT_MAX_TRANSACTIONS	
	11.4 DHCP_DDNS_CLEARED_FOR_SHUTDOWN	145 146
	THE PROPERTY OF THE PROPERTY O	1/40

11.6	DHCP_DDNS_CONFIGURED_CALLOUT_DROP	146
11.7	DHCP_DDNS_CONFIG_CHECK_FAIL	146
11.8	DHCP_DDNS_CONFIG_FAIL	146
	DHCP_DDNS_CONFIG_SYNTAX_WARNING	
11.10	DHCP_DDNS_FAILED	146
11.11	DHCP DDNS FORWARD ADD BAD DNSCLIENT STATUS	147
	DHCP_DDNS_FORWARD_ADD_BUILD_FAILURE	
	DHCP_DDNS_FORWARD_ADD_IO_ERROR	
	DHCP_DDNS_FORWARD_ADD_REJECTED	
	DHCP_DDNS_FORWARD_ADD_RESP_CORRUPT	
	DHCP_DDNS_FORWARD_ADD_TIMEOUT	
	DHCP_DDNS_FORWARD_REMOVE_ADDRS_BAD_DNSCLIENT_STATUS	
	DHCP_DDNS_FORWARD_REMOVE_ADDRS_BUILD_FAILURE	
	DHCP_DDNS_FORWARD_REMOVE_ADDRS_IO_ERROR	
	DHCP_DDNS_FORWARD_REMOVE_ADDRS_REJECTED	
	DHCP_DDNS_FORWARD_REMOVE_ADDRS_RESP_CORRUPT	
	DHCP_DDNS_FORWARD_REMOVE_ADDRS_TIMEOUT	
	DHCP_DDNS_FORWARD_REMOVE_RRS_BAD_DNSCLIENT_STATUS	
	DHCP DDNS FORWARD REMOVE RRS BUILD FAILURE	
	DHCP_DDNS_FORWARD_REMOVE_RRS_IO_ERROR	
	DHCP_DDNS_FORWARD_REMOVE_RRS_REJECTED	
	DHCP_DDNS_FORWARD_REMOVE_RRS_RESP_CORRUPT	
	DHCP_DDNS_FORWARD_REMOVE_RRS_TIMEOUT	
	DHCP_DDNS_FORWARD_REPLACE_BAD_DNSCLIENT_STATUS	
	DHCP_DDNS_FORWARD_REPLACE_BUILD_FAILURE	
	DHCP_DDNS_FORWARD_REPLACE_IO_ERROR	
	DHCP_DDNS_FORWARD_REPLACE_REJECTED	
	DHCP_DDNS_FORWARD_REPLACE_RESP_CORRUPT	
	DHCP_DDNS_FORWARD_REPLACE_TIMEOUT	
	DHCP_DDNS_FWD_REQUEST_IGNORED	
	DHCP_DDNS_INVALID_NCR	
	DHCP_DDNS_INVALID_RESPONSE	
	DHCP_DDNS_LISTENING_ON_ALL_INTERFACES	
	DHCP_DDNS_NCR_FLUSH_IO_ERROR	
	DHCP_DDNS_NCR_LISTEN_CLOSE_ERROR	
	DHCP_DDNS_NCR_RECV_NEXT_ERROR	
11.42	DHCP_DDNS_NCR_SEND_CLOSE_ERROR	153
11.43	DHCP_DDNS_NCR_SEND_NEXT_ERROR	153
11.44	DHCP_DDNS_NCR_UDP_CLEAR_READY_ERROR	153
11.45	DHCP_DDNS_NCR_UDP_RECV_CANCELED	153
11.46	DHCP_DDNS_NCR_UDP_RECV_ERROR	154
11.47	DHCP_DDNS_NCR_UDP_SEND_CANCELED	154
11.48	DHCP_DDNS_NCR_UDP_SEND_ERROR	154
	DHCP_DDNS_NOT_ON_LOOPBACK	
	DHCP_DDNS_NO_ELIGIBLE_JOBS	
	DHCP_DDNS_NO_FWD_MATCH_ERROR	
	DHCP_DDNS_NO_MATCH	
	DHCP_DDNS_NO_REV_MATCH_ERROR	
	DHCP_DDNS_QUEUE_MGR_QUEUE_FULL	
	DHCP_DDNS_QUEUE_MGR_QUEUE_RECEIVE	
	DHCP_DDNS_QUEUE_MGR_RECONFIGURING	
	DHCP_DDNS_QUEUE_MGR_RECOVERING	
	DHCP_DDNS_QUEUE_MGR_RECV_ERROR	
	DHCP DDNS QUEUE MGR RESUME ERROR	
11.0/	PILOI PENO QUEUD MOR REDUME DIMOR	100

11.60 DHCP_DDNS_QUEUE_MGR_RESUMING	 	156
11.61 DHCP_DDNS_QUEUE_MGR_STARTED	 	157
11.62 DHCP_DDNS_QUEUE_MGR_START_ERROR	 	157
11.63 DHCP_DDNS_QUEUE_MGR_STOPPED	 	157
11.64 DHCP_DDNS_QUEUE_MGR_STOPPING		
11.65 DHCP_DDNS_QUEUE_MGR_STOP_ERROR	 	157
11.66 DHCP_DDNS_QUEUE_MGR_UNEXPECTED_HANDLER_ERROR		
11.67 DHCP_DDNS_QUEUE_MGR_UNEXPECTED_STOP		
11.68 DHCP_DDNS_REMOVE_FAILED		
11.69 DHCP_DDNS_REMOVE_SUCCEEDED		
11.70 DHCP_DDNS_REQUEST_DROPPED		
11.71 DHCP_DDNS_REVERSE_REMOVE_BAD_DNSCLIENT_STATUS		
11.72 DHCP_DDNS_REVERSE_REMOVE_BUILD_FAILURE		
11.73 DHCP_DDNS_REVERSE_REMOVE_IO_ERROR		
11.74 DHCP_DDNS_REVERSE_REMOVE_REJECTED		
11.75 DHCP_DDNS_REVERSE_REMOVE_RESP_CORRUPT		
11.75 DHCF_DDNS_REVERSE_REMOVE_RESF_CORROFT		
11.76 DHCP_DDNS_REVERSE_REMOVE_TIMEOUT		
11.78 DHCP_DDNS_REVERSE_REPLACE_BUILD_FAILURE		
11.79 DHCP_DDNS_REVERSE_REPLACE_IO_ERROR		
11.80 DHCP_DDNS_REVERSE_REPLACE_REJECTED		
11.81 DHCP_DDNS_REVERSE_REPLACE_RESP_CORRUPT		
11.82 DHCP_DDNS_REVERSE_REPLACE_TIMEOUT		
11.83 DHCP_DDNS_REV_REQUEST_IGNORED		
11.84 DHCP_DDNS_RUN_EXIT		
11.85 DHCP_DDNS_SHUTDOWN_COMMAND		
11.86 DHCP_DDNS_STARTED		
11.87 DHCP_DDNS_STARTING_TRANSACTION		
11.88 DHCP_DDNS_STATE_MODEL_UNEXPECTED_ERROR		
11.89 DHCP_DDNS_TRANS_SEND_ERROR		
11.90 DHCP_DDNS_UDP_SENDER_WATCH_SOCKET_CLOSE_ERROR		
11.91 DHCP_DDNS_UNCAUGHT_NCR_RECV_HANDLER_ERROR		
11.92 DHCP_DDNS_UPDATE_REQUEST_SENT	 	163
12 EVAL		165
12.1 EVAL_DEBUG_AND		
12.2 EVAL_DEBUG_BRANCH		
12.3 EVAL_DEBUG_CONCAT		165
12.4 EVAL_DEBUG_EQUAL		165
12.5 EVAL_DEBUG_HEXSTRING		166
12.6 EVAL_DEBUG_IFELSE_FALSE	 	166
12.7 EVAL_DEBUG_IFELSE_TRUE	 	166
12.8 EVAL_DEBUG_INT16TOTEXT	 	166
12.9 EVAL_DEBUG_INT32TOTEXT	 	166
12.10 EVAL_DEBUG_INT8TOTEXT	 	166
12.11 EVAL_DEBUG_IPADDRESS	 	167
12.12 EVAL_DEBUG_IPADDRESSTOTEXT		167
12.13 EVAL_DEBUG_LCASE		167
12.14 EVAL DEBUG MATCH		167
12.15 EVAL_DEBUG_MATCH_ERROR		167
12.16 EVAL_DEBUG_MEMBER		167
12.17 EVAL_DEBUG_NOT		168
12.18 EVAL_DEBUG_OPTION		168
12.19 EVAL_DEBUG_OR		

	12.20 EVAL_DEBUG_PKT	
	12.21 EVAL_DEBUG_PKT4	
	12.22 EVAL_DEBUG_PKT6	
	12.23 EVAL_DEBUG_POP_AND_BRANCH_FALSE	169
	12.24 EVAL_DEBUG_POP_OR_BRANCH_FALSE	169
	12.25 EVAL_DEBUG_POP_OR_BRANCH_TRUE	
	12.26 EVAL_DEBUG_RELAY6	
	12.27 EVAL_DEBUG_RELAY6_RANGE	
	12.28 EVAL DEBUG SPLIT	
	12.29 EVAL_DEBUG_SPLIT_DELIM_EMPTY	
	12.30 EVAL_DEBUG_SPLIT_EMPTY	
	12.31 EVAL_DEBUG_SPLIT_FIELD_OUT_OF_RANGE	
	12.32 EVAL_DEBUG_STRING	
	12.33 EVAL_DEBUG_SUBSTRING	
	12.34 EVAL_DEBUG_SUBSTRING_EMPTY	171
	12.35 EVAL_DEBUG_SUBSTRING_RANGE	171
	12.36 EVAL_DEBUG_SUB_OPTION	171
	12.37 EVAL_DEBUG_SUB_OPTION_NO_OPTION	
	12.38 EVAL_DEBUG_TOHEXSTRING	
	12.39 EVAL_DEBUG_UCASE	
	12.40 EVAL_DEBUG_UINT16TOTEXT	
	12.41 EVAL_DEBUG_UINT32TOTEXT	
	12.42 EVAL DEBUG UINT8TOTEXT	
	12.43 EVAL_DEBUG_VENDOR_CLASS_DATA	
	12.44 EVAL_DEBUG_VENDOR_CLASS_DATA_NOT_FOUND	
	12.45 EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID	
	12.46 EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID_MISMATCH	
	12.47 EVAL_DEBUG_VENDOR_CLASS_EXISTS	
	12.48 EVAL_DEBUG_VENDOR_CLASS_NO_OPTION	174
	12.49 EVAL_DEBUG_VENDOR_ENTERPRISE_ID	174
	12.50 EVAL_DEBUG_VENDOR_ENTERPRISE_ID_MISMATCH	
	12.51 EVAL_DEBUG_VENDOR_EXISTS	
13	FLEX	175
	13.1 FLEX_OPTION_LOAD_ERROR	175
	13.2 FLEX_OPTION_PROCESS_ADD	
	13.3 FLEX_OPTION_PROCESS_CLIENT_CLASS	
	13.4 FLEX_OPTION_PROCESS_ERROR	
	13.5 FLEX_OPTION_PROCESS_REMOVE	
	13.6 FLEX_OPTION_PROCESS_SUB_ADD	
	13.7 FLEX_OPTION_PROCESS_SUB_CLIENT_CLASS	
	13.8 FLEX_OPTION_PROCESS_SUB_REMOVE	
	13.9 FLEX_OPTION_PROCESS_SUB_SUPERSEDE	
	13.10 FLEX_OPTION_PROCESS_SUPERSEDE	
	13.11 FLEX_OPTION_PROCESS_VENDOR_ID_MISMATCH	177
4.0		4=0
14	FUZZ	179
	14.2 FUZZ_INIT_COMPLETE	
	14.3 FUZZ_INIT_FAIL	179
	14.4 FUZZ_READ_FAIL	179
	14.5 FUZZ_SEND	
	14.6 FUZZ_SEND_ERROR	
	14.7 FUZZ_SHORT_SEND	
		- 55

15	HA		181
	15.1	HA_BUFFER4_RECEIVE_FAILED	181
	15.2	HA_BUFFER4_RECEIVE_NOT_FOR_US	181
		HA_BUFFER4_RECEIVE_PACKET_OPTIONS_SKIPPED	
		HA_BUFFER4_RECEIVE_UNPACK_FAILED	
		HA_BUFFER6_RECEIVE_FAILED	
		HA_BUFFER6_RECEIVE_NOT_FOR_US	
		HA_BUFFER6_RECEIVE_PACKET_OPTIONS_SKIPPED	
		HA_BUFFER6_RECEIVE_UNPACK_FAILED	
		HA_COMMAND_PROCESSED_FAILED	
		HA_COMMUNICATION_INTERRUPTED	
		HA_COMMUNICATION_INTERRUPTED_CLIENT4	
		HA_COMMUNICATION_INTERRUPTED_CLIENT4_UNACKED	
		HA_COMMUNICATION_INTERRUPTED_CLIENT6	
		HA_COMMUNICATION_INTERRUPTED_CLIENT6_UNACKED	
		HA_CONFIGURATION_FAILED	
		HA_CONFIGURATION_SUCCESSFUL	
		HA_CONFIG_AUTO_FAILOVER_DISABLED	
		HA_CONFIG_DHCP_MT_DISABLED	
		HA_CONFIG_DHCP_MT_DISABLED_AND_KEA_MT_ENABLED	
		HA_CONFIG_LEASE_SYNCING_DISABLED	
		HA_CONFIG_LEASE_SYNCING_DISABLED_REMINDER	
		HA_CONFIG_LEASE_UPDATES_AND_SYNCING_DIFFER	
		HA_CONFIG_LEASE_UPDATES_DISABLED	
		HA_CONFIG_LEASE_UPDATES_DISABLED_REMINDER	
		HA_CONFIG_SYSTEM_MT_UNSUPPORTED	
		HA_CONTINUE_HANDLER_FAILED	
		HA_DEINIT_OK	
		HA_DHCP4_START_SERVICE_FAILED	
		HA_DHCP6_START_SERVICE_FAILED	
		HA_DHCP_DISABLE_COMMUNICATIONS_FAILED	
		HA_DHCP_DISABLE_FAILED	
		HA_DHCP_ENABLE_COMMUNICATIONS_FAILED	
		HA_DHCP_ENABLE_FAILED	
		HA_HEARTBEAT_COMMUNICATIONS_FAILED	
		HA_HEARTBEAT_FAILED	
		HA_HEARTBEAT_HANDLER_FAILED	
		HA_HIGH_CLOCK_SKEW	
		HA_HIGH_CLOCK_SKEW_CAUSED_TERMINATION	
		HA_INIT_OK	
		HA_INVALID_PARTNER_STATE_COMMUNICATION_RECOVERY	
		HA_INVALID_PARTNER_STATE_HOT_STANDBY	
		HA_INVALID_PARTNER_STATE_LOAD_BALANCING	
		HA_LEASE4_SERVER_DECLINE_FAILED	
		HA_LEASES4_COMMITTED_FAILED	
		HA_LEASES4_COMMITTED_NO_PELATIONSHIP	
		HA_LEASES4_COMMITTED_NO_RELATIONSHIP	
		HA_LEASES6_COMMITTED_NOTHING_TO_LIDDATE	
		HA_LEASES6_COMMITTED_NO_PELATIONSHIP	
		HA_LEASES_COMMITTED_NO_RELATIONSHIP	
		HA_LEASES_BACKLOG_COMMUNICATIONS_FAILED	
		HA_LEASES_BACKLOG_FAILED	
		HA_LEASES_BACKLOG_NOTHING_TO_SEND	
	13.53	HA LEASES BACKLOG START	191

15.54 HA_LEASES_BACKLOG_SUCCESS	192
15.55 HA LEASES SYNC APPLIED LEASES	
15.56 HA_LEASES_SYNC_COMMUNICATIONS_FAILED	
15.57 HA_LEASES_SYNC_FAILED	
15.58 HA_LEASES_SYNC_LEASE_PAGE_RECEIVED	
15.59 HA LEASE SYNC FAILED	
15.60 HA_LEASE_SYNC_STALE_LEASE4_SKIP	
15.61 HA_LEASE_SYNC_STALE_LEASE6_SKIP	
15.62 HA_LEASE_UPDATES_DISABLED	
15.63 HA_LEASE_UPDATES_ENABLED	
15.64 HA LEASE UPDATE COMMUNICATIONS FAILED	
15.65 HA LEASE UPDATE CONFLICT	
15.66 HA_LEASE_UPDATE_CREATE_UPDATE_FAILED_ON_PEER	
15.60 HA_LEASE_UPDATE_CREATE_UPDATE_FAILED_ON_PEER	
15.68 HA_LEASE_UPDATE_FAILED	
15.69 HA_LEASE_UPDATE_REJECTS_CAUSED_TERMINATION	
15.70 HA_LOAD_BALANCING_DUID_MISSING	
15.71 HA_LOAD_BALANCING_IDENTIFIER_MISSING	
15.72 HA_LOCAL_DHCP_DISABLE	
15.73 HA_LOCAL_DHCP_ENABLE	
15.74 HA_MAINTENANCE_CANCEL_HANDLER_FAILED	
15.75 HA_MAINTENANCE_NOTIFY_CANCEL_COMMUNICATIONS_FAILED	
15.76 HA_MAINTENANCE_NOTIFY_CANCEL_FAILED	
15.77 HA_MAINTENANCE_NOTIFY_COMMUNICATIONS_FAILED	
15.78 HA_MAINTENANCE_NOTIFY_FAILED	
15.79 HA_MAINTENANCE_NOTIFY_HANDLER_FAILED	
15.80 HA_MAINTENANCE_SHUTDOWN_SAFE	
15.81 HA_MAINTENANCE_STARTED	
15.82 HA_MAINTENANCE_STARTED_IN_PARTNER_DOWN	
15.83 HA_MAINTENANCE_START_HANDLER_FAILED	
15.84 HA_MISSING_CONFIGURATION	
15.85 HA_PAUSE_CLIENT_LISTENER_FAILED	
15.86 HA_PAUSE_CLIENT_LISTENER_ILLEGAL	
15.87 HA_RESET_COMMUNICATIONS_FAILED	
15.88 HA_RESET_FAILED	
15.89 HA_RESET_HANDLER_FAILED	
15.90 HA_RESUME_CLIENT_LISTENER_FAILED	
15.91 HA_SCOPES_HANDLER_FAILED	
15.92 HA_SERVICE_STARTED	
15.93 HA_STATE_MACHINE_CONTINUED	. 200
15.94 HA_STATE_MACHINE_PAUSED	
15.95 HA_STATE_TRANSITION	
15.96 HA_STATE_TRANSITION_PASSIVE_BACKUP	. 200
15.97 HA_SUBNET4_SELECT_FAILED	. 200
15.98 HA_SUBNET4_SELECT_INVALID_HA_SERVER_NAME	. 201
15.99 HA_SUBNET4_SELECT_NOT_FOR_US	. 201
15.100HA_SUBNET4_SELECT_NO_RELATIONSHIP_FOR_SUBNET	. 201
15.101HA_SUBNET4_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET	. 201
15.102HA_SUBNET4_SELECT_NO_SUBNET_SELECTED	
15.103HA_SUBNET6_SELECT_FAILED	
15.104HA_SUBNET6_SELECT_INVALID_HA_SERVER_NAME	
15.105HA_SUBNET6_SELECT_NOT_FOR_US	
15.106HA_SUBNET6_SELECT_NO_RELATIONSHIP_FOR_SUBNET	
15.107HA SUBNET6 SELECT NO RELATIONSHIP SELECTOR FOR SUBNET	

	15.108HA_SUBNET6_SELECT_NO_SUBNET_SELECTED 15.109HA_SYNC_COMPLETE_NOTIFY_COMMUNICATIONS_FAILED 15.110HA_SYNC_COMPLETE_NOTIFY_FAILED 15.111HA_SYNC_COMPLETE_NOTIFY_HANDLER_FAILED 15.112HA_SYNC_FAILED 15.113HA_SYNC_HANDLER_FAILED 15.114HA_SYNC_START 15.115HA_SYNC_SUCCESSFUL 15.116HA_TERMINATED 15.117HA_TERMINATED_PARTNER_DID_NOT_RESTART	203 203 203 203 204 204 204 204
16	HOOKS	205
	16.1 HOOKS_ALL_CALLOUTS_DEREGISTERED	205
	16.2 HOOKS_CALLOUTS_BEGIN	
	16.3 HOOKS_CALLOUTS_COMPLETE	
	16.4 HOOKS_CALLOUTS_REMOVED	
	16.5 HOOKS_CALLOUT_CALLED	
	16.6 HOOKS_CALLOUT_DEREGISTERED	
	16.7 HOOKS_CALLOUT_ERROR	
	16.8 HOOKS_CALLOUT_EXCEPTION	
	16.9 HOOKS_CALLOUT_REGISTRATION	
	16.10 HOOKS_CLOSE_ERROR	
	16.11 HOOKS_HOOK_LIST_RESET	
	16.12 HOOKS_INCORRECT_VERSION	
	16.13 HOOKS_LIBRARY_CLOSED	
	16.14 HOOKS_LIBRARY_LOADED	
	16.16 HOOKS_LIBRARY_MULTI_THREADING_COMPATIBLE	
	16.17 HOOKS_LIBRARY_MULTI_THREADING_NOT_COMPATIBLE	
	16.18 HOOKS_LIBRARY_UNLOADED	
	16.19 HOOKS_LIBRARY_UNLOADING	
	16.20 HOOKS_LIBRARY_VERSION	
	16.21 HOOKS_LOAD_ERROR	
	16.22 HOOKS_LOAD_EXCEPTION	
	16.23 HOOKS_LOAD_FRAMEWORK_EXCEPTION	
	16.24 HOOKS_LOAD_SUCCESS	
	16.25 HOOKS_MULTI_THREADING_COMPATIBLE_EXCEPTION	
	16.26 HOOKS_NO_LOAD	
	16.27 HOOKS_NO_UNLOAD	
	16.28 HOOKS_NO_VERSION	
	16.29 HOOKS_OPEN_ERROR	210
	16.30 HOOKS_STD_CALLOUT_REGISTERED	210
	16.31 HOOKS_UNLOAD_ERROR	211
	16.32 HOOKS_UNLOAD_EXCEPTION	211
	16.33 HOOKS_UNLOAD_FRAMEWORK_EXCEPTION	211
	16.34 HOOKS_UNLOAD_SUCCESS	211
17	HOCTC	212
1/	HOSTS 17.1 HOSTS_BACKENDS_REGISTERED	<b>213</b> 213
	17.1 HOSTS_BACKENDS_REGISTERED	
	17.3 HOSTS_BACKEND_REGISTER	
	17.4 HOSTS_CFG_ADD_HOST	
	17.5 HOSTS_CFG_CACHE_HOST_DATA_SOURCE	
	17.6 HOSTS_CFG_CLOSE_HOST_DATA_SOURCE	

17.7	HOSTS CFG DEL	214
17.8	HOSTS CFG DEL4	214
17.9	HOSTS_CFG_DEL6	214
	HOSTS_CFG_DEL_ALL_SUBNET4	
	HOSTS_CFG_DEL_ALL_SUBNET6	
	HOSTS_CFG_GET_ALL	
	HOSTS_CFG_GET_ALL_ADDRESS4	
	HOSTS_CFG_GET_ALL_ADDRESS4_COUNT	
	HOSTS_CFG_GET_ALL_ADDRESS4_HOST	
	HOSTS_CFG_GET_ALL_ADDRESS6	
	HOSTS_CFG_GET_ALL_ADDRESS6_COUNT	
	HOSTS_CFG_GET_ALL_ADDRESS6_HOST	
17.10	HOSTS_CFG_GET_ALL_GOUNT	210
17.19	HOSTS_CFG_GET_ALL_COUNT	216
	HOSTS_CFG_GET_ALL_HOST	
	HOSTS_CFG_GET_ALL_HOSTNAME	
	HOSTS_CFG_GET_ALL_HOSTNAME_COUNT	
	HOSTS_CFG_GET_ALL_HOSTNAME_HOST	
	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4	
	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_COUNT	
17.26	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_HOST	217
17.27	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6	218
17.28	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_COUNT	218
	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_HOST	
	HOSTS CFG GET ALL IDENTIFIER	
	HOSTS_CFG_GET_ALL_IDENTIFIER_COUNT	
	HOSTS_CFG_GET_ALL_IDENTIFIER_HOST	
	HOSTS_CFG_GET_ALL_SUBNET_ID4	
	HOSTS_CFG_GET_ALL_SUBNET_ID4_COUNT	
	HOSTS_CFG_GET_ALL_SUBNET_ID4_COUNT	
	HOSTS_CFG_GET_ALL_SUBNET_ID6	
	HOSTS_CFG_GET_ALL_SUBNET_ID6_COUNT	
	HOSTS_CFG_GET_ALL_SUBNET_ID6_HOST	
	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4	
	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_COUNT	
	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_HOST	
	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6	
	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_COUNT	
17.44	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_HOST	221
17.45	HOSTS_CFG_GET_ONE_PREFIX	221
17.46	HOSTS_CFG_GET_ONE_PREFIX_HOST	221
17.47	HOSTS_CFG_GET_ONE_PREFIX_NULL	221
	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4	
	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_HOST	
	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_NULL	
	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6	
	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_HOST	
	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_NULL	
	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER	
	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_HOST	
	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_NULL	
	HOSTS_CFG_UPDATE_ADD	
	HOSTS_CFG_UPDATE_DEL4	
	HOSTS_CFG_UPDATE_DEL6	
17.60	HOSTS MGR ALTERNATE GET4 SUBNET ID ADDRESS4	224

	17.61 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER	
	17.62 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_HOST	
	17.63 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_NULL	224
	17.64 HOSTS_MGR_ALTERNATE_GET6_PREFIX	224
	17.65 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_ADDRESS6	225
	17.66 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER	
	17.67 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_HOST	
	17.68 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_NULL	
	17.69 HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS4	
	17.70 HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS6	
	17.70 HOOTS_WOR_NEITER(WITE_ODT_NED_GODINET_ID_NEDERGOOD	220
18	HTTPS	227
	18.1 HTTPS_REQUEST_RECEIVE_START	
	Total Intro_NEQUEST_NEGET / D_ONINCT	,
19	HTTP	229
	19.1 HTTP_BAD_CLIENT_REQUEST_RECEIVED	
	19.2 HTTP_BAD_CLIENT_REQUEST_RECEIVED_DETAILS	
	19.3 HTTP_BAD_SERVER_RESPONSE_RECEIVED	
	19.4 HTTP_BAD_SERVER_RESPONSE_RECEIVED_DETAILS	
	19.5 HTTP_CLIENT_MT_STARTED	
	19.6 HTTP_CLIENT_QUEUE_SIZE_GROWING	
	19.7 HTTP_CLIENT_REQUEST_AUTHORIZED	
	19.8 HTTP_CLIENT_REQUEST_BAD_AUTH_HEADER	230
	19.9 HTTP_CLIENT_REQUEST_NOT_AUTHORIZED	231
	19.10 HTTP_CLIENT_REQUEST_RECEIVED	231
	19.11 HTTP_CLIENT_REQUEST_RECEIVED_DETAILS	231
	19.12 HTTP_CLIENT_REQUEST_SEND	
	19.13 HTTP_CLIENT_REQUEST_SEND_DETAILS	
	19.14 HTTP_CLIENT_REQUEST_TIMEOUT_OCCURRED	
	19.15 HTTP_COMMAND_MGR_IGNORED_TLS_SETUP_CHANGES	232
	19.16 HTTP_COMMAND_MGR_SERVICE_STARTED	232
	19.17 HTTP_CONNECTION_CLOSE_CALLBACK_FAILED	232
	19.18 HTTP_CONNECTION_HANDSHAKE_FAILED	232
	19.19 HTTP_CONNECTION_HANDSHAKE_START	233
	19.20 HTTP_CONNECTION_SHUTDOWN	
	19.21 HTTP_CONNECTION_SHUTDOWN_FAILED	
	19.22 HTTP_CONNECTION_STOP	
	19.23 HTTP CONNECTION STOP FAILED	
	19.24 HTTP_CONNECTION_WATCH_SOCKET_CLEAR_ERROR	
	19.25 HTTP_CONNECTION_WATCH_SOCKET_CLOSE_ERROR	
	19.26 HTTP_CONNECTION_WATCH_SOCKET_MARK_READY_ERROR	
	19.27 HTTP_DATA_RECEIVED	
	19.29 HTTP_PREMATURE_CONNECTION_TIMEOUT_OCCURRED	
	19.30 HTTP_REQUEST_RECEIVE_START	
	19.31 HTTP_SERVER_RESPONSE_RECEIVED	
	19.32 HTTP_SERVER_RESPONSE_RECEIVED_DETAILS	
	19.33 HTTP_SERVER_RESPONSE_SEND	235
<b>20</b>	LEASE	237
	20.1 LEASE_CMDS_ADD4	
	20.2 LEASE_CMDS_ADD4_CONFLICT	
	20.3 LEASE_CMDS_ADD4_FAILED	237
	20.4 LEASE_CMDS_ADD6	237

	20.5 LEASE_CMDS_ADD6_CONFLICT	. 238
	20.6 LEASE_CMDS_ADD6_FAILED	. 238
	20.7 LEASE_CMDS_BULK_APPLY6	. 238
	20.8 LEASE_CMDS_BULK_APPLY6_FAILED	
	20.9 LEASE_CMDS_DEINIT_OK	
	20.10 LEASE_CMDS_DEL4	
	20.11 LEASE_CMDS_DEL4_FAILED	
	20.12 LEASE_CMDS_DEL6	
	20.13 LEASE CMDS DEL6 FAILED	
	20.14 LEASE_CMDS_GET4_FAILED	
	20.14 LEASE_CMDS_GET4_FAILED	
	20.16 LEASE_CMDS_INIT_OK	
	20.17 LEASE_CMDS_RESEND_DDNS4	
	20.18 LEASE_CMDS_RESEND_DDNS4_FAILED	
	20.19 LEASE_CMDS_RESEND_DDNS6	
	20.20 LEASE_CMDS_RESEND_DDNS6_FAILED	
	20.21 LEASE_CMDS_UPDATE4	. 240
	20.22 LEASE_CMDS_UPDATE4_CONFLICT	. 240
	20.23 LEASE_CMDS_UPDATE4_FAILED	. 241
	20.24 LEASE_CMDS_UPDATE6	. 241
	20.25 LEASE_CMDS_UPDATE6_CONFLICT	
	20.26 LEASE_CMDS_UPDATE6_FAILED	
	20.27 LEASE_CMDS_WIPE4	
	20.28 LEASE_CMDS_WIPE4_DEPRECATED	
	20.29 LEASE_CMDS_WIPE4_FAILED	
	20.30 LEASE_CMDS_WIPE6	
	/U 31 LEANE UMIDS WIPED DEPRELATED	747
	20.31 LEASE_CMDS_WIPE6_DEPRECATED	. 242
21		
21	LFC	243
21	LFC 21.1 LFC_FAIL_PID_CREATE	<b>243</b> . 243
21	LFC 21.1 LFC_FAIL_PID_CREATE	243 . 243 . 243
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS	243 . 243 . 243
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE	243 . 243 . 243 . 243
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING	243 . 243 . 243 . 243 . 243 . 244
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS	243 . 243 . 243 . 243 . 244 . 244
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING	243 · 243 · 243 · 243 · 244 · 244 · 244
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING	243 · 243 · 243 · 243 · 244 · 244 · 244 · 244
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START	243 · 243 · 243 · 243 · 244 · 244 · 244 · 244
21	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING	243 · 243 · 243 · 243 · 244 · 244 · 244 · 244
	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE	243 . 243 . 243 . 243 . 244 . 244 . 244 . 244 . 244
	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE	243 . 243 . 243 . 243 . 244 . 244 . 244 . 244 . 244 . 244
	LFC  21.1 LFC_FAIL_PID_CREATE  21.2 LFC_FAIL_PID_DEL  21.3 LFC_FAIL_PROCESS  21.4 LFC_FAIL_ROTATE  21.5 LFC_PROCESSING  21.6 LFC_READ_STATS  21.7 LFC_ROTATING  21.8 LFC_RUNNING  21.9 LFC_START  21.10 LFC_TERMINATE  LOGIMPL  22.1 LOGIMPL_ABOVE_MAX_DEBUG	243 . 243 . 243 . 243 . 244 . 244 . 244 . 244 . 244 . 244 . 245
	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE	243 . 243 . 243 . 243 . 244 . 244 . 244 . 244 . 244 . 244 . 245
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING	243 . 243 . 243 . 244 . 244 . 244 . 244 . 244 . 245 . 245
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG LOG	243 . 243 . 243 . 244 . 244 . 244 . 244 . 244 . 245 . 245 . 245
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY	243 . 243 . 243 . 244 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY 23.3 LOG_BAD_STREAM	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY 23.3 LOG_BAD_STREAM 23.4 LOG_DUPLICATE_MESSAGE_ID	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247 . 247
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY 23.3 LOG_BAD_STREAM 23.4 LOG_DUPLICATE_MESSAGE_ID 23.5 LOG_DUPLICATE_NAMESPACE	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247 . 247 . 248
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY 23.3 LOG_BAD_STREAM 23.4 LOG_DUPLICATE_MESSAGE_ID 23.5 LOG_DUPLICATE_MESSAGE_ID 23.5 LOG_INPUT_OPEN_FAIL	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247 . 247 . 248 . 248
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY 23.3 LOG_BAD_STREAM 23.4 LOG_DUPLICATE_MESSAGE_ID 23.5 LOG_DUPLICATE_NAMESPACE 23.6 LOG_INPUT_OPEN_FAIL 23.7 LOG_INVALID_MESSAGE_ID	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247 . 247 . 248 . 248 . 248
22	LFC 21.1 LFC_FAIL_PID_CREATE 21.2 LFC_FAIL_PID_DEL 21.3 LFC_FAIL_PROCESS 21.4 LFC_FAIL_ROTATE 21.5 LFC_PROCESSING 21.6 LFC_READ_STATS 21.7 LFC_ROTATING 21.8 LFC_RUNNING 21.9 LFC_START 21.10 LFC_TERMINATE  LOGIMPL 22.1 LOGIMPL_ABOVE_MAX_DEBUG 22.2 LOGIMPL_BAD_DEBUG_STRING  LOG 23.1 LOG_BAD_DESTINATION 23.2 LOG_BAD_SEVERITY 23.3 LOG_BAD_STREAM 23.4 LOG_DUPLICATE_MESSAGE_ID 23.5 LOG_DUPLICATE_MESSAGE_ID 23.5 LOG_INPUT_OPEN_FAIL	243 . 243 . 243 . 244 . 244 . 244 . 244 . 245 . 245 . 247 . 247 . 247 . 248 . 248 . 248

	23.10 LOG_NAMESPACE_NO_ARGS	249
	23.12 LOG_NO_MESSAGE_TEXT	
	23.13 LOG_NO_SUCH_MESSAGE	
	23.14 LOG_OPEN_OUTPUT_FAIL	
	23.15 LOG_PREFIX_EXTRA_ARGS	
	23.16 LOG_PREFIX_INVALID_ARG	
	23.17 LOG_READING_LOCAL_FILE	
	23.18 LOG_READ_ERROR	
	23.19 LOG_UNRECOGNIZED_DIRECTIVE	250
2.4		0.51
24	MT	251
	24.1 MT_TCP_LISTENER_MGR_STARTED	
	24.2 MT_TCP_LISTENER_MGR_STOPPED	
	24.3 MT_TCP_LISTENER_MGR_STOPPING	251
25	MYSQL	253
45	WITSQL 25.1 MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4	
	25.2 MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6	
	25.3 MYSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6	
	25.4 MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4	
	25.5 MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6	
	25.6 MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS4	
	25.7 MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS6	
	25.8 MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4	
	25.9 MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6	
	25.10 MYSQL_CB_CREATE_UPDATE_OPTION4	
	25.11 MYSQL_CB_CREATE_UPDATE_OPTION6	
	25.12 MYSQL_CB_CREATE_UPDATE_OPTION_DEF4	
	25.13 MYSQL_CB_CREATE_UPDATE_OPTION_DEF6	
	25.14 MYSQL_CB_CREATE_UPDATE_SERVER4	
	25.15 MYSQL_CB_CREATE_UPDATE_SERVER6	
	25.16 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK4	
	25.17 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK6	256
	25.18 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4	256
	25.19 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6	256
	25.20 MYSQL_CB_CREATE_UPDATE_SUBNET4	256
	25.21 MYSQL_CB_CREATE_UPDATE_SUBNET6	256
	25.22 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4	256
	25.23 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT	257
	25.24 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6	257
	25.25 MYSQL CB DELETE ALL CLIENT CLASSES6 RESULT	257
	25.26 MYSQL CB DELETE ALL GLOBAL PARAMETERS4	257
	25.27 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT	257
	25.28 MYSQL CB DELETE ALL GLOBAL PARAMETERS6	257
	25.29 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT	258
	25.30 MYSQL_CB_DELETE_ALL_OPTION_DEFS4	258
	25.31 MYSQL CB DELETE ALL OPTION DEFS4 RESULT	258
	25.32 MYSQL_CB_DELETE_ALL_OPTION_DEFS6	258
	25.33 MYSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT	258
	25.34 MYSQL_CB_DELETE_ALL_SERVERS4	258
	25.35 MYSQL_CB_DELETE_ALL_SERVERS4_RESULT	259
	25.36 MYSQL_CB_DELETE_ALL_SERVERS6	259
	25.37 MYSQL_CB_DELETE_ALL_SERVERS6_RESULT	
	FO'S   TITTO K TO TO TO THE TIME DON'S DINOCINED OF THE TOTAL STATE OF	237

25.38 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4	259
25.39 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT	
25.40 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6	259
25.41 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT	
25.42 MYSQL_CB_DELETE_ALL_SUBNETS4	
25.43 MYSQL_CB_DELETE_ALL_SUBNETS4_RESULT	
25.44 MYSQL_CB_DELETE_ALL_SUBNETS6	
25.45 MYSQL_CB_DELETE_ALL_SUBNETS6_RESULT	
25.46 MYSQL_CB_DELETE_BY_POOL_OPTION4	
25.47 MYSQL_CB_DELETE_BY_POOL_OPTION4_RESULT	
25.48 MYSQL_CB_DELETE_BY_POOL_OPTION6	
25.49 MYSQL_CB_DELETE_BY_POOL_OPTION6_RESULT	
25.50 MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6	
25.51 MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT	
25.52 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4	201
25.52 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4	201
25.53 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT	
25.54 MYSQL_CB_DELETE_BY_PREFIX_SUBNET6	
25.55 MYSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT	
25.56 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4	
25.57 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT	
25.58 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6	
25.59 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT	
25.60 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4	
25.61 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT	
25.62 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6	263
25.63 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT	263
25.64 MYSQL_CB_DELETE_CLIENT_CLASS4	263
25.65 MYSQL_CB_DELETE_CLIENT_CLASS4_RESULT	264
25.66 MYSQL_CB_DELETE_CLIENT_CLASS6	264
25.67 MYSQL_CB_DELETE_CLIENT_CLASS6_RESULT	
25.68 MYSQL_CB_DELETE_GLOBAL_PARAMETER4	
25.69 MYSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT	
25.70 MYSQL_CB_DELETE_GLOBAL_PARAMETER6	
25.71 MYSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT	
25.72 MYSQL_CB_DELETE_OPTION4	
25.73 MYSQL_CB_DELETE_OPTION4_RESULT	
25.74 MYSQL_CB_DELETE_OPTION6	
25.75 MYSQL_CB_DELETE_OPTION6_RESULT	
25.76 MYSQL_CB_DELETE_OPTION_DEF4	
25.77 MYSQL CB DELETE OPTION DEF4 RESULT	
25.78 MYSQL_CB_DELETE_OPTION_DEF4_RESULT	
25.79 MYSQL_CB_DELETE_OPTION_DEF6_RESULT	
25.80 MYSQL_CB_DELETE_SERVER4	
25.81 MYSQL_CB_DELETE_SERVER4_RESULT	
25.82 MYSQL_CB_DELETE_SERVER6	266
25.83 MYSQL_CB_DELETE_SERVER6_RESULT	
25.84 MYSQL_CB_DELETE_SHARED_NETWORK4	
25.85 MYSQL_CB_DELETE_SHARED_NETWORK4_RESULT	
25.86 MYSQL_CB_DELETE_SHARED_NETWORK6	
25.87 MYSQL_CB_DELETE_SHARED_NETWORK6_RESULT	
25.88 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4	
25.89 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT	
25.90 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6	268
25.91 MYSQL CB DELETE SHARED NETWORK OPTION6 RESULT	

25.92 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4	
25.93 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	268
25.94 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6	
25.95 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT	269
25.96 MYSQL_CB_GET_ALL_CLIENT_CLASSES4	
25.97 MYSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT	269
25.98 MYSQL_CB_GET_ALL_CLIENT_CLASSES6	
25.99 MYSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT	
25.100MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	
25.101MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	
25.102MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6	
25.103MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	
25.104MYSQL_CB_GET_ALL_OPTIONS4	
25.105MYSQL_CB_GET_ALL_OPTIONS4_RESULT	
25.106MYSQL_CB_GET_ALL_OPTIONS6	
25.107MYSQL_CB_GET_ALL_OPTIONS6_RESULT	
25.108MYSQL_CB_GET_ALL_OPTION_DEFS4	271
25.109MYSQL_CB_GET_ALL_OPTION_DEFS4_RESULT	
25.110MYSQL_CB_GET_ALL_OPTION_DEFS6	271
25.111MYSQL_CB_GET_ALL_OPTION_DEFS6_RESULT	
25.112MYSQL_CB_GET_ALL_SERVERS4	271
25.113MYSQL_CB_GET_ALL_SERVERS4_RESULT	272
25.114MYSQL_CB_GET_ALL_SERVERS6	272
25.115MYSQL_CB_GET_ALL_SERVERS6_RESULT	
25.116MYSQL_CB_GET_ALL_SHARED_NETWORKS4	272
25.117MYSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT	
25.118MYSQL_CB_GET_ALL_SHARED_NETWORKS6	
25.119MYSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT	
25.120MYSQL_CB_GET_ALL_SUBNETS4	273
25.121MYSQL_CB_GET_ALL_SUBNETS4_RESULT	273
25.122MYSQL_CB_GET_ALL_SUBNETS6	273
25.123MYSQL_CB_GET_ALL_SUBNETS6_RESULT	273
25.124MYSQL_CB_GET_CLIENT_CLASS4	273
25.125MYSQL_CB_GET_CLIENT_CLASS6	274
25.126MYSQL_CB_GET_GLOBAL_PARAMETER4	274
25.127MYSQL_CB_GET_GLOBAL_PARAMETER6	274
25.128MYSQL_CB_GET_HOST4	274
25.129MYSQL_CB_GET_HOST6	274
25.130MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4	
25.131MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT	275
25.132MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6	275
25.133MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT	275
25.134MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4	275
25.135MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT	275
25.136MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6	
25.137MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT	276
25.138MYSQL_CB_GET_MODIFIED_OPTIONS4	276
25.139MYSQL_CB_GET_MODIFIED_OPTIONS4_RESULT	
25.140MYSQL_CB_GET_MODIFIED_OPTIONS6	
25.141MYSQL_CB_GET_MODIFIED_OPTIONS6_RESULT	
25.142MYSQL_CB_GET_MODIFIED_OPTION_DEFS4	
25.143MYSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT	
25.144MYSQL_CB_GET_MODIFIED_OPTION_DEFS6	
25.145MYSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT	

25.146MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4	
25.147MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT	277
25.148MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6	277
25.149MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT	278
25.150MYSQL_CB_GET_MODIFIED_SUBNETS4	278
25.151MYSQL CB GET MODIFIED SUBNETS4 RESULT	278
25.152MYSQL_CB_GET_MODIFIED_SUBNETS6	278
25.153MYSQL_CB_GET_MODIFIED_SUBNETS6_RESULT	
25.154MYSQL_CB_GET_OPTION4	
25.155MYSQL_CB_GET_OPTION6	
25.156MYSQL_CB_GET_OPTION_DEF4	
25.157MYSQL_CB_GET_OPTION_DEF6	
25.158MYSQL_CB_GET_PORT4	
25.159MYSQL_CB_GET_PORT6	
25.160MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4	
25.161MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT	
25.162MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6	
25.163MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT	
25.164MYSQL_CB_GET_SERVER4	
25.165MYSQL_CB_GET_SERVER6	
25.166MYSQL_CB_GET_SHARED_NETWORK4	
25.167MYSQL_CB_GET_SHARED_NETWORK6	
25.168MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4	
25.169MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT	
25.171MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT	281
25.172MYSQL_CB_GET_SUBNET4_BY_PREFIX	
25.173MYSQL_CB_GET_SUBNET4_BY_SUBNET_ID	
25.174MYSQL_CB_GET_SUBNET6_BY_PREFIX	
25.175MYSQL_CB_GET_SUBNET6_BY_SUBNET_ID	
25.176MYSQL_CB_GET_TYPE4	
25.177MYSQL_CB_GET_TYPE6	
25.178MYSQL_CB_NO_TLS	
25.179MYSQL_CB_RECONNECT_ATTEMPT_FAILED4	
25.180MYSQL_CB_RECONNECT_ATTEMPT_FAILED6	
25.181MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4	
25.182MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6	
25.183MYSQL_CB_RECONNECT_FAILED4	
25.184MYSQL_CB_RECONNECT_FAILED6	
25.185MYSQL_CB_REGISTER_BACKEND_TYPE4	
25.186MYSQL_CB_REGISTER_BACKEND_TYPE6	
25.187MYSQL_CB_TLS_CIPHER	
25.188MYSQL_CB_UNREGISTER_BACKEND_TYPE4	
25.189MYSQL_DEINIT_OK	
25.190MYSQL_HB_DB	284
25.191MYSQL_HB_DB_GET_VERSION	285
25.192MYSQL_HB_DB_READONLY	285
25.193MYSQL_HB_DB_RECONNECT_ATTEMPT_FAILED	285
25.194MYSQL_HB_DB_RECONNECT_ATTEMPT_SCHEDULE	285
25.195MYSQL_HB_DB_RECONNECT_FAILED	
25.196MYSQL_HB_NO_TLS	
25.197MYSQL_INIT_OK	
25.198MYSQL_LB_ADD_ADDR4	
25.199MYSQL LB ADD ADDR6	

	25.200MYSQL_LB_COMMIT	
	25.201MYSQL_LB_DB	286
	25.202MYSQL_LB_DB_RECONNECT_ATTEMPT_FAILED	286
	25.203MYSQL_LB_DB_RECONNECT_ATTEMPT_SCHEDULE	287
	25.204MYSQL_LB_DB_RECONNECT_FAILED	287
	25.205MYSQL_LB_DELETED_EXPIRED_RECLAIMED	287
	25.206MYSQL_LB_DELETE_ADDR4	287
	25.207MYSQL_LB_DELETE_ADDR6	
	25.208MYSQL_LB_DELETE_EXPIRED_RECLAIMED4	
	25.209MYSQL_LB_DELETE_EXPIRED_RECLAIMED6	
	25.210MYSQL_LB_GET4	
	25.211MYSQL_LB_GET6	
	25.212MYSQL_LB_GET_ADDR4	
	25.213MYSQL_LB_GET_ADDR6	
	25.214MYSQL_LB_GET_CLIENTID	
	25.215MYSQL_LB_GET_DUID	
	25.216MYSQL_LB_GET_EXPIRED4	
	25.217MYSQL_LB_GET_EXPIRED6	
	25.218MYSQL_LB_GET_HOSTNAME4	
	25.219MYSQL LB GET HOSTNAME6	
	25.220MYSQL LB GET HWADDR	
	25.22IMYSQL_LB_GET_IAID_DUID	
	25.222MYSQL LB GET IAID SUBID DUID	
	25.223MYSQL_LB_GET_PAGE4	
	25.224MYSQL_LB_GET_PAGE6	
	25.225MYSQL_LB_GET_RELAYID4	
	25.226MYSQL_LB_GET_RELAYID6	
	25.227MYSQL_LB_GET_REMOTEID4	
	25.228MYSQL_LB_GET_REMOTEID6	
	25.229MYSQL_LB_GET_SUBID4	
	25.230MYSQL_LB_GET_SUBID6	
	25.231MYSQL_LB_GET_SUBID_CLIENTID	
	25.232MYSQL_LB_GET_SUBID_HWADDR	
	25.233MYSQL_LB_GET_SUBID_PAGE6	
	25.234MYSQL_LB_GET_VERSION	
	25.235MYSQL_LB_NEGATIVE_LEASES_STAT	
	25.236MYSQL_LB_NO_TLS	
	25.237MYSQL_LB_ROLLBACK	
	25.23&MYSQL_LB_TLS_CIPHER	
	25.239MYSQL_LB_UPDATE_ADDR4	
	25.240MYSQL_LB_UPDATE_ADDR6	
	25.241MYSQL_LB_UPGRADE_EXTENDED_INFO4	
	25.242MYSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR	
	25.243MYSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE	
	25.244MYSQL_LB_UPGRADE_EXTENDED_INFO6	
	25.245MYSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR	294
26	METCOME	205
20	NETCONE POOT LIBRATE COMPLETED	295
	26.1 NETCONF_BOOT_UPDATE_COMPLETED	
	26.2 NETCONF_CONFIG_CHANGE_EVENT	
	26.3 NETCONF_CONFIG_CHANGE_EVENT	
	26.4 NETCONF_CONFIG_CHECK_FAIL	
	26.5 NETCONF_CONFIG_FAIL	
	26.6 NETCONF_CONFIG_SYNTAX_WARNING	. 296

	26.7 NETCONF_FAILED	. 296
	26.8 NETCONF_GET_CONFIG	. 296
	26.9 NETCONF_GET_CONFIG_FAILED	. 296
	26.10 NETCONF_GET_CONFIG_STARTED	. 296
	26.11 NETCONF_MODULE_CHANGE_INTERNAL_ERROR	
	26.12 NETCONF_MODULE_MISSING_ERR	
	26.13 NETCONF_MODULE_MISSING_WARN	
	26.14 NETCONF_MODULE_REVISION_ERR	
	26.15 NETCONF_MODULE_REVISION_WARN	
	26.16 NETCONF_NOTIFICATION_INTERNAL_ERROR	
	26.17 NETCONF_NOTIFICATION_RECEIVED	
	26.18 NETCONF_NOT_SUBSCRIBED_TO_NOTIFICATIONS	
	26.19 NETCONF_RUN_EXIT	
	26.20 NETCONF_SET_CONFIG	
	26.21 NETCONF_SET_CONFIG_FAILED	
	26.22 NETCONF_SET_CONFIG_STARTED	
	26.23 NETCONF_STARTED	
	26.24 NETCONF_SUBSCRIBE_CONFIG	
	26.25 NETCONF_SUBSCRIBE_CONFIG_FAILED	. 299
	26.26 NETCONF_SUBSCRIBE_NOTIFICATIONS	. 299
	26.27 NETCONF_UPDATE_CONFIG	. 300
	26.28 NETCONF_UPDATE_CONFIG_COMPLETED	
	26.29 NETCONF_UPDATE_CONFIG_FAILED	
	26.30 NETCONF_UPDATE_CONFIG_STARTED	
	26.31 NETCONF_VALIDATE_CONFIG	
	26.32 NETCONF_VALIDATE_CONFIG_COMPLETED	
	26.33 NETCONF_VALIDATE_CONFIG_FAILED	
	26.34 NETCONF_VALIDATE_CONFIG_REJECTED	
	20.54 NETCONF_VALIDATE_CONFIG_REJECTED	. 301
27	PERFMON	303
	27.1 PERFMON_ALARM_CLEARED	
	27.2 PERFMON_ALARM_TRIGGERED	
	27.3 PERFMON_CMDS_CONTROL_ERROR	
	27.4 PERFMON_CMDS_CONTROL_OK	
	27.5 PERFMON_CMDS_GET_ALL_DURATIONS_ERROR	
	27.6 PERFMON_CMDS_GET_ALL_DURATIONS_OK	
	27.7 PERFMON_DEINIT_OK	
	27.8 PERFMON_DHCP4_PKT_EVENTS	
	27.9 PERFMON_DHCP4_PKT_PROCESS_ERROR	
	27.10 PERFMON_DHCP4_SOCKET_RECEIVED_TIME_SUPPORT	
	27.11 PERFMON_DHCP6_PKT_EVENTS	
	27.12 PERFMON_DHCP6_PKT_PROCESS_ERROR	. 305
	27.13 PERFMON_DHCP6_SOCKET_RECEIVED_TIME_SUPPORT	. 305
	27.14 PERFMON_INIT_FAILED	. 305
28	3 PGSQL	307
	28.1 PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4	
	28.2 PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6	
	28.3 PGSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6	. 307
	28.4 PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4	. 307
	28.5 PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6	. 308
	28.6 PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS4	
	28.7 PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS6	
	28.8 PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4	

28.9 PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6	308
28.10 PGSQL_CB_CREATE_UPDATE_OPTION4	308
28.11 PGSQL_CB_CREATE_UPDATE_OPTION6	309
28.12 PGSQL_CB_CREATE_UPDATE_OPTION_DEF4	309
28.13 PGSQL_CB_CREATE_UPDATE_OPTION_DEF6	
28.14 PGSQL_CB_CREATE_UPDATE_SERVER4	
28.15 PGSQL_CB_CREATE_UPDATE_SERVER6	
28.16 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK4	
28.17 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK6	
28.18 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4	
28.19 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6	
28.20 PGSQL_CB_CREATE_UPDATE_SUBNET4	
28.21 PGSQL_CB_CREATE_UPDATE_SUBNET6	
28.22 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4	
28.23 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT	211
28.24 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6	211
28.25 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT	
28.26 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4	
28.27 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT	
28.28 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6	
28.29 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT	
28.30 PGSQL_CB_DELETE_ALL_OPTION_DEFS4	
28.31 PGSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT	
28.32 PGSQL_CB_DELETE_ALL_OPTION_DEFS6	
28.33 PGSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT	
28.34 PGSQL_CB_DELETE_ALL_SERVERS4	
28.35 PGSQL_CB_DELETE_ALL_SERVERS4_RESULT	
28.36 PGSQL_CB_DELETE_ALL_SERVERS6	
28.37 PGSQL_CB_DELETE_ALL_SERVERS6_RESULT	
28.38 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4	313
28.39 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT	
28.40 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6	313
28.41 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT	314
28.42 PGSQL_CB_DELETE_ALL_SUBNETS4	314
28.43 PGSQL CB DELETE ALL SUBNETS4 RESULT	
28.44 PGSQL CB DELETE ALL SUBNETS6	
28.45 PGSQL_CB_DELETE_ALL_SUBNETS6_RESULT	
28.46 PGSQL_CB_DELETE_BY_POOL_OPTION4	
28.47 PGSQL_CB_DELETE_BY_POOL_OPTION4_RESULT	
28.48 PGSQL_CB_DELETE_BY_POOL_OPTION6	
28.49 PGSQL_CB_DELETE_BY_POOL_OPTION6_RESULT	
28.50 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6	
28.51 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT	
28.52 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4	
28.53 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT	
28.54 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6	
28.55 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT	
28.56 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4	
28.50 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4	
28.58 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6	
28.59 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT	
28.60 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4	
28.61 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT	
28.62 PGSQL CB DELETE BY SUBNET ID SUBNET6	317

	217
28.63 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT	317
28.64 PGSQL_CB_DELETE_CLIENT_CLASS4	317
28.65 PGSQL_CB_DELETE_CLIENT_CLASS4_RESULT	
28.66 PGSQL_CB_DELETE_CLIENT_CLASS6	318
28.67 PGSQL_CB_DELETE_CLIENT_CLASS6_RESULT	318
28.68 PGSQL_CB_DELETE_GLOBAL_PARAMETER4	318
28.69 PGSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT	
28.70 PGSQL_CB_DELETE_GLOBAL_PARAMETER6	
28.71 PGSQL CB DELETE GLOBAL PARAMETER6 RESULT	
28.72 PGSQL_CB_DELETE_OPTION4	
28.73 PGSQL_CB_DELETE_OPTION4_RESULT	
28.74 PGSQL_CB_DELETE_OPTION6	
28.75 PGSQL_CB_DELETE_OPTION6_RESULT	
28.76 PGSQL_CB_DELETE_OPTION_DEF4	
28.77 PGSQL_CB_DELETE_OPTION_DEF4_RESULT	320
28.78 PGSQL_CB_DELETE_OPTION_DEF6	320
28.79 PGSQL_CB_DELETE_OPTION_DEF6_RESULT	
28.80 PGSQL_CB_DELETE_SERVER4	
28.81 PGSQL_CB_DELETE_SERVER4_RESULT	
28.82 PGSQL_CB_DELETE_SERVER6	
28.83 PGSQL_CB_DELETE_SERVER6_RESULT	
28.84 PGSQL_CB_DELETE_SHARED_NETWORK4	
28.85 PGSQL_CB_DELETE_SHARED_NETWORK4_RESULT	
28.86 PGSQL_CB_DELETE_SHARED_NETWORK6	
28.87 PGSQL_CB_DELETE_SHARED_NETWORK6_RESULT	
28.88 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4	
28.89 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT	
28.90 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6	322
28.91 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT	
28.92 PGSOL CB DELETE SHARED NETWORK SUBNETS4	
28.92 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4	322
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322 322
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322 322 323
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322 322 323 323
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322 322 323 323 323
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322 322 323 323 323 323
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	322 322 322 323 323 323 323 323
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	322 322 322 323 323 323 323 323 323
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	322 322 323 323 323 323 323 323 323 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	322 322 323 323 323 323 323 323 323 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	322 322 323 323 323 323 323 323 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	322 322 323 323 323 323 323 323 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT 28.104PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	322 322 323 323 323 323 323 323 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS4_RESULT	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS6	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.104PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS4 28.106PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6_RESULT	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.10PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.10PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.10PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.10PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.10PGSQL_CB_GET_ALL_OPTIONS4 28.10PGSQL_CB_GET_ALL_OPTIONS4 28.10PGSQL_CB_GET_ALL_OPTIONS6 28.10PGSQL_CB_GET_ALL_OPTIONS6 28.10PGSQL_CB_GET_ALL_OPTIONS6_RESULT 28.10PGSQL_CB_GET_ALL_OPTIONS6_RESULT	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6_RESULT 28.108PGSQL_CB_GET_ALL_OPTION_DEFS4 28.109PGSQL_CB_GET_ALL_OPTION_DEFS4_RESULT	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6_RESULT 28.108PGSQL_CB_GET_ALL_OPTION_DEFS4 28.109PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS4	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.100PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.105PGSQL_CB_GET_ALL_OPTIONS4_RESULT 28.106PGSQL_CB_GET_ALL_OPTIONS6_RESULT 28.106PGSQL_CB_GET_ALL_OPTIONS6_RESULT 28.108PGSQL_CB_GET_ALL_OPTION_DEFS4 28.109PGSQL_CB_GET_ALL_OPTION_DEFS4 28.110PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT 28.111PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.102PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS6 28.104PGSQL_CB_GET_ALL_OPTIONS6 28.104PGSQL_CB_GET_ALL_OPTIONS6 28.104PGSQL_CB_GET_ALL_OPTIOND_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.111PGSQL_CB_GET_ALL_OPTION_DEFS6 28.111PGSQL_CB_GET_ALL_OPTION_DEFS6 28.111PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT 28.112PGSQL_CB_GET_ALL_SERVERS4	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS6 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_SERVERS4	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.102PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTIONS6 28.107PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_SERVERS4 28.114PGSQL_CB_GET_ALL_SERVERS4 28.114PGSQL_CB_GET_ALL_SERVERS4 28.114PGSQL_CB_GET_ALL_SERVERS4 28.114PGSQL_CB_GET_ALL_SERVERS4 28.114PGSQL_CB_GET_ALL_SERVERS6	322 322 323 323 323 323 323 324 324 324
28.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT 28.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6 28.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT 28.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4 28.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6 28.100PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4 28.101PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.103PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS4 28.104PGSQL_CB_GET_ALL_OPTIONS6 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS4 28.104PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_OPTION_DEFS6 28.114PGSQL_CB_GET_ALL_SERVERS4	322 322 323 323 323 323 323 324 324 324

28.117PGSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT	
28.118PGSQL_CB_GET_ALL_SHARED_NETWORKS6	326
28.119PGSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT	327
28.120PGSQL_CB_GET_ALL_SUBNETS4	327
28.121PGSQL_CB_GET_ALL_SUBNETS4_RESULT	
28.122PGSQL_CB_GET_ALL_SUBNETS6	
28.123PGSQL_CB_GET_ALL_SUBNETS6_RESULT	
28.124PGSQL_CB_GET_CLIENT_CLASS4	
28.125PGSQL_CB_GET_CLIENT_CLASS6	
28.126PGSQL_CB_GET_GLOBAL_PARAMETER4	328
28.127PGSQL_CB_GET_GLOBAL_PARAMETER6	
28.128PGSQL_CB_GET_HOST4	
28.129PGSQL_CB_GET_HOST6	
28.130PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4	
28.131PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT	
28.132PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6	
28.133PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT	
28.134PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4	
28.135PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT	
28.136PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6	
28.137PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT	
28.138PGSQL_CB_GET_MODIFIED_OPTIONS4	
28.139PGSQL_CB_GET_MODIFIED_OPTIONS4_RESULT	
28.140PGSQL_CB_GET_MODIFIED_OPTIONS6	
28.14IPGSQL_CB_GET_MODIFIED_OPTIONS6_RESULT	
28.142PGSQL_CB_GET_MODIFIED_OPTION_DEFS4	
28.143PGSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT	
28.144PGSQL_CB_GET_MODIFIED_OPTION_DEFS6	
28.145PGSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT	
28.14@PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4	
28.147PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT	
28.14&PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6	
28.149PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT	
28.150PGSQL_CB_GET_MODIFIED_SUBNETS4	
28.151PGSQL_CB_GET_MODIFIED_SUBNETS4_RESULT	
28.152PGSQL_CB_GET_MODIFIED_SUBNETS6	
28.153PGSQL_CB_GET_MODIFIED_SUBNETS6_RESULT	332
28.154PGSQL_CB_GET_OPTION4	332
28.155PGSQL_CB_GET_OPTION6	333
28.15@PGSQL_CB_GET_OPTION_DEF4	333
28.157PGSQL_CB_GET_OPTION_DEF6	333
28.158PGSQL_CB_GET_PORT4	333
28.159PGSQL_CB_GET_PORT6	333
28.160PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4	
28.161PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT	
28.162PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6	
28.163PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT	
28.164PGSQL_CB_GET_SERVER4	
28.165PGSQL_CB_GET_SERVER6	
28.16@GSQL_CB_GET_SHARED_NETWORK4	
28.167PGSQL_CB_GET_SHARED_NETWORK6	
28.168PGSQL_CB_GET_SHARED_NETWORK SUBNETS4	
28.169PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT	
28.170PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6	
FOULT OF OUR CD OF THE STRAINED THE STRAIN SUDDIFFERDUTION OF THE STRAIN	درر

28.171PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT	
28.172PGSQL_CB_GET_SUBNET4_BY_PREFIX	335
28.173PGSQL_CB_GET_SUBNET4_BY_SUBNET_ID	336
28.174PGSQL_CB_GET_SUBNET6_BY_PREFIX	336
28.175PGSQL_CB_GET_SUBNET6_BY_SUBNET_ID	
28.176PGSQL_CB_GET_TYPE4	
28.177PGSQL_CB_GET_TYPE6	
28.17&PGSQL_CB_NO_TLS_SUPPORT	
28.179PGSQL_CB_RECONNECT_ATTEMPT_FAILED4	
28.180PGSQL_CB_RECONNECT_ATTEMPT_FAILED6	
28.181PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4	
28.182PGSQL CB RECONNECT ATTEMPT SCHEDULE6	
28.183PGSQL_CB_RECONNECT_FAILED4	
28.184PGSQL_CB_RECONNECT_FAILED6	
28.185PGSQL_CB_REGISTER_BACKEND_TYPE4	
28.186PGSQL_CB_REGISTER_BACKEND_TYPE6	
28.187PGSQL_CB_TLS_SUPPORT	
28.18&PGSQL_CB_UNREGISTER_BACKEND_TYPE4	
28.189PGSQL_DEINIT_OK	
28.190PGSQL_HB_DB	
28.19IPGSQL_HB_DB_GET_VERSION	
28.192PGSQL_HB_DB_READONLY	
28.193PGSQL_HB_DB_RECONNECT_ATTEMPT_FAILED	
28.194PGSQL_HB_DB_RECONNECT_ATTEMPT_SCHEDULE	
28.195PGSQL_HB_DB_RECONNECT_FAILED	
28.19@PGSQL_HB_NO_TLS_SUPPORT	
28.197PGSQL_INIT_OK	
28.19&PGSQL_LB_ADD_ADDR4	
28.199PGSQL_LB_ADD_ADDR6	
28.200PGSQL_LB_COMMIT	
28.201PGSQL_LB_DB	
28.202PGSQL_LB_DB_RECONNECT_ATTEMPT_FAILED	
28.203PGSQL_LB_DB_RECONNECT_ATTEMPT_SCHEDULE	
28.204PGSQL_LB_DB_RECONNECT_FAILED	
28.205PGSQL_LB_DELETE_ADDR4	341
28.206PGSQL_LB_DELETE_ADDR6	341
28.207PGSQL_LB_DELETE_EXPIRED_RECLAIMED4	341
28.20&PGSQL_LB_DELETE_EXPIRED_RECLAIMED6	342
28.209PGSQL_LB_GET4	342
28.210PGSQL_LB_GET6	
28.211PGSQL_LB_GET_ADDR4	
28.212PGSQL_LB_GET_ADDR6	
28.213PGSQL_LB_GET_CLIENTID	
28.214PGSQL LB GET DUID	
28.215PGSQL LB GET EXPIRED4	
28.216PGSQL LB GET EXPIRED6	
28.217PGSQL LB GET HOSTNAME4	
28.218PGSQL_LB_GET_HOSTNAME6	
28.219PGSQL_LB_GET_HOSTNAMED	
28.220PGSQL_LB_GET_IAID_DUID	
28.22IPGSQL_LB_GET_IAID_DUID	
28.222PGSQL_LB_GET_PAGE4	
28.223PGSQL_LB_GET_PAGE6	
28.224PGSQL LB GET RELAYID4	345

	28.225PGSQL_LB_GET_RELAYID6	
	28.22@PGSQL_LB_GET_REMOTEID4	
	28.228PGSQL_LB_GET_SUBID4	
	28.229PGSQL_LB_GET_SUBID6	
	28.230PGSQL_LB_GET_SUBID_CLIENTID	
	28.231PGSQL_LB_GET_SUBID_HWADDR	
	28.232PGSQL_LB_GET_SUBID_PAGE6	
	28.233PGSQL_LB_GET_VERSION	
	28.23\$PGSQL_LB_NEGATIVE_LEASES_STAT	
	28.235PGSQL_LB_NO_TLS_SUPPORT	
	28.23@GSQL_LB_ROLLBACK	
	28.237PGSQL_LB_TLS_SUPPORT	
	28.23%PGSQL_LB_UPDATE_ADDR4	
	28.239PGSQL_LB_UPDATE_ADDR6	
	28.240PGSQL_LB_UPGRADE_EXTENDED_INFO4	
	28.241PGSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR	
	28.242PGSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE	
	28.243PGSQL_LB_UPGRADE_EXTENDED_INFO6	
	28.244PGSQL LB UPGRADE EXTENDED INFO6 ERROR	
29	RUN	349
	29.1 RUN_SCRIPT_LOAD	
	29.2 RUN_SCRIPT_LOAD_ERROR	349
20	STAT	351
<b>3</b> 0	30.1 STAT_CMDS_DEINIT_OK	
	30.2 STAT_CMDS_INIT_OK	
	30.3 STAT_CMDS_LEASE4_FAILED	
	30.4 STAT_CMDS_LEASE4_GET	
	30.5 STAT_CMDS_LEASE4_GET_FAILED	
	30.6 STAT_CMDS_LEASE4_GET_INVALID	
	30.7 STAT_CMDS_LEASE4_GET_NO_SUBNETS	
	30.8 STAT_CMDS_LEASE4_ORPHANED_STATS	
	30.9 STAT_CMDS_LEASE6_FAILED	
	30.10 STAT_CMDS_LEASE6_GET	
	30.11 STAT_CMDS_LEASE6_GET_FAILED	
	30.12 STAT_CMDS_LEASE6_GET_INVALID	
	30.13 STAT CMDS LEASE6 GET NO SUBNETS	
	· · · · · · · · · · · · · · · · · · ·	
31	TCP	355
	31.1 TCP_CLIENT_REQUEST_RECEIVED	
	31.2 TCP_CONNECTION_REJECTED_BY_FILTER	
	31.3 TCP_CONNECTION_SHUTDOWN	
	31.4 TCP_CONNECTION_SHUTDOWN_FAILED	
	31.5 TCP_CONNECTION_STOP	
	31.6 TCP_CONNECTION_STOP_FAILED	
	31.7 TCP_DATA_RECEIVED	
	31.8 TCP_DATA_SENT	
	31.9 TCP_IDLE_CONNECTION_TIMEOUT_OCCURRED	
	31.10 TCP_REQUEST_RECEIVED_FAILED	
	31.11 TCP_REQUEST_RECEIVE_START	
	31.12 TCP_SERVER_RESPONSE_SEND	357
32	TIS	350

	32.1	TLS_CONNECTION_HANDSHAKE_FAILED	359
	32.2	TLS_CONNECTION_HANDSHAKE_START	359
	32.3	TLS_REQUEST_RECEIVE_START	359
33	USE	R	361
	33.1	USER_CHK_HOOK_LOAD_ERROR	361
	33.2	USER_CHK_HOOK_UNLOAD_ERROR	361
	33.3	USER_CHK_SUBNET4_SELECT_ERROR	361
	33.4	USER_CHK_SUBNET4_SELECT_REGISTRY_NULL	361
	33.5	USER_CHK_SUBNET6_SELECT_ERROR	362
34	Kea l	Debug Messages By Log Level	363
			000
		Messages printed on debuglevel 0	
	34.1		363
	34.1 34.2	Messages printed on debuglevel 0	363 363
	34.1 34.2 34.3	Messages printed on debuglevel 0	363 363 364
	34.1 34.2 34.3 34.4	Messages printed on debuglevel 0       3         Messages printed on debuglevel 10       3         Messages printed on debuglevel 15       3	363 363 364 365
	34.1 34.2 34.3 34.4	Messages printed on debuglevel 0 Messages printed on debuglevel 10 Messages printed on debuglevel 15 Messages printed on debuglevel 20 Messages printed on debuglevel 40	363 363 364 365 365
	34.1 34.2 34.3 34.4 34.5	Messages printed on debuglevel 0 Messages printed on debuglevel 10 Messages printed on debuglevel 15 Messages printed on debuglevel 20 Messages printed on debuglevel 40	363 363 364 365 365 382
	34.1 34.2 34.3 34.4 34.5 34.6 34.7	Messages printed on debuglevel 0 Messages printed on debuglevel 10 Messages printed on debuglevel 15 Messages printed on debuglevel 20 Messages printed on debuglevel 40 Messages printed on debuglevel 45 Messages printed on debuglevel 50	363 363 364 365 365 382

Kea is an open source implementation of the Dynamic Host Configuration Protocol (DHCP) servers, developed and maintained by Internet Systems Consortium (ISC).

This is the reference guide for Kea version 2.7.5. Links to the most up-to-date version of this document (in PDF, HTML, and plain text formats), along with other useful information about Kea, can be found in ISC's Knowledgebase.

Please note that in the messages below, the percent sign (%) followed by a number is used to indicate a placeholder for data that is provided by the Kea code during its operation.

CONTENTS 1

2 CONTENTS

**CHAPTER** 

ONE

**ALLOC** 

#### 1.1 ALLOC ENGINE IGNORING UNSUITABLE GLOBAL ADDRESS

%1: ignoring globally reserved address %2, it falls outside %3

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the globally reserved address falls outside the selected subnet or shared-network. The server should ignore the reserved address and attempt a dynamic allocation.

#### 1.2 ALLOC\_ENGINE\_IGNORING\_UNSUITABLE\_GLOBAL\_ADDRESS6

%1: ignoring globally reserved address %2, it falls outside %3

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the globally reserved address falls outside the selected subnet or shared-network. The server should ignore the reserved address and attempt a dynamic allocation.

## 1.3 ALLOC ENGINE LEASE RECLAIMED

successfully reclaimed lease %1

Logged at debug log level 40. This debug message is logged when the allocation engine successfully reclaims a lease. The lease is now available for assignment.

# 1.4 ALLOC\_ENGINE\_V4\_ALLOC\_ERROR

%1: error during attempt to allocate an IPv4 address: %2

An error occurred during an attempt to allocate an IPv4 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

### 1.5 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL

%1: failed to allocate an IPv4 address after %2 attempt(s)

This is an old warning message issued when the allocation engine fails to allocate a lease for a client. This message includes a number of lease allocation attempts that the engine made before giving up. If the number of attempts is 0 because the engine was unable to use any of the address pools for the particular client, this message is not logged. Even though, several more detailed logs precede this message, it was left for backward compatibility. This message may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if the you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. This way, addresses allocated to clients that are no longer active on the network will become available sooner.

#### 1.6 ALLOC ENGINE V4 ALLOC FAIL CLASSES

%1: Failed to allocate an IPv4 address for client with classes: %2

This warning message is printed when Kea failed to allocate an address and the client's packet belongs to one or more classes. There may be several reasons why a lease was not assigned. One of them may be a case when all pools require packet to belong to certain classes and the incoming packet didn't belong to any of them. Another case where this information may be useful is to point out that the pool reserved to a given class has ran out of addresses. When you see this message, you may consider checking your pool size and your classification definitions.

### 1.7 ALLOC ENGINE V4 ALLOC FAIL NO POOLS

%1: no pools were available for the address allocation

This warning message is issued when the allocation engine fails to allocate a lease because it could not use any configured pools for the particular client. It is also possible that all of the subnets from which the allocation engine attempted to assign an address lack address pools. In this case, it should be considered misconfiguration if an operator expects that some clients should be assigned dynamic addresses. A subnet may lack any pools only when all clients should be assigned reserved IP addresses. Suppose the subnets connected to a shared network or a single subnet to which the client belongs have pools configured. In that case, this message is an indication that none of the pools could be used for the client because the client does not belong to appropriate client classes.

### 1.8 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL\_SHARED\_NETWORK

%1: failed to allocate an IPv4 address in the shared network %2: %3 subnets have no →available addresses, %4 subnets have no matching pools

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a shared network. The shared network should contain at least one subnet, but typically it aggregates multiple subnets. This log message indicates that the allocation engine could not find and allocate any suitable lease in any of the subnets within the shared network. The first argument includes the client identification information. The second argument specifies the shared network name. The remaining two arguments provide additional information useful for debugging why the allocation engine could not assign a lease. The allocation engine tries to allocate addresses from different subnets in the shared network, and it may fail for some subnets because there are no leases available in those subnets or the free

leases are reserved to other clients. The number of such subnets is specified in the third argument. For other subnets the allocation may fail because their pools may not be available to the particular client. These pools are guarded by client classes that the client does not belong to. The fourth argument specifies the number of such subnets. By looking at the values in the third and fourth argument, an operator can identify the situations when there are no addresses left in some of the pools. He or she can also identify a client classification misconfigurations causing some clients to be refused the service.

#### 1.9 ALLOC ENGINE V4 ALLOC FAIL SUBNET

%1: failed to allocate an IPv4 lease in the subnet %2, subnet-id %3, shared network %4

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a subnet. The first argument includes the client identification information. The second and third arguments identify the subnet. The fourth argument specifies the shared network, if the subnet belongs to a shared network. There are many reasons for failing lease allocations. One of them may be the pools exhaustion or existing reservations for the free leases. However, in some cases, the allocation engine may fail to find a suitable pool for the client when the pools are only available to certain client classes, but the requesting client does not belong to them. Further log messages provide more information to distinguish between these different cases.

#### 1.10 ALLOC ENGINE V4 DECLINED RECOVERED

IPv4 address %1 was recovered after %2 seconds of probation-period

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes the decline recovery process.

## 1.11 ALLOC\_ENGINE\_V4\_DISCOVER\_ADDRESS\_CONFLICT

%1: conflicting reservation for address %2 with existing lease %3

This warning message is issued when the DHCP server finds that the address reserved for the client can't be offered because this address is currently allocated to another client. The server will try to allocate a different address to the client to use until the conflict is resolved. The first argument includes the client identification information.

## 1.12 ALLOC\_ENGINE\_V4\_DISCOVER\_HR

client %1 sending DHCPDISCOVER has reservation for the address %2

Logged at debug log level 40. This message is issued when the allocation engine determines that the client sending the DHCPDISCOVER has a reservation for the specified address. The allocation engine will try to offer this address to the client.

### 1.13 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_COMPLETE

reclaimed %1 leases in %2

Logged at debug log level 40. This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

### 1.14 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_FAILED

reclamation of expired leases failed: %1

This error message is issued when the reclamation of the expired leases failed. The error message is displayed.

#### 1.15 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_SLOW

expired leases still exist after %1 reclamations

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

## 1.16 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_START

starting reclamation of expired leases (limit = %1 leases or %2 milliseconds)

Logged at debug log level 40. This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

### 1.17 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_TIMEOUT

timeout of %1 ms reached while reclaiming IPv4 leases

Logged at debug log level 40. This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

### 1.18 ALLOC\_ENGINE\_V4\_LEASE\_RECLAIM

%1: reclaiming expired lease for address %2

Logged at debug log level 40. This debug message is issued when the server begins reclamation of the expired DHCPv4 lease. The first argument specifies the client identification information. The second argument holds the leased IPv4 address.

#### 1.19 ALLOC ENGINE V4 LEASE RECLAMATION FAILED

failed to reclaim the lease %1: %2

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

### 1.20 ALLOC\_ENGINE\_V4\_NO\_MORE\_EXPIRED\_LEASES

all expired leases have been reclaimed

Logged at debug log level 40. This debug message is issued when the server reclaims all expired DHCPv4 leases in the database.

### 1.21 ALLOC\_ENGINE\_V4\_OFFER\_EXISTING\_LEASE

allocation engine will try to offer existing lease to the client %1

Logged at debug log level 40. This message is issued when the allocation engine determines that the client has a lease in the lease database, it doesn't have reservation for any other lease, and the leased address is not reserved for any other client. The allocation engine will try to offer the same lease to the client.

### 1.22 ALLOC\_ENGINE\_V4\_OFFER\_NEW\_LEASE

allocation engine will try to offer new lease to the client %1

Logged at debug log level 40. This message is issued when the allocation engine will try to offer a new lease to the client. This is the case when the client doesn't have any existing lease, it has no reservation or the existing or reserved address is leased to another client. Also, the client didn't specify a hint, or the address in the hint is in use.

### 1.23 ALLOC\_ENGINE\_V4\_OFFER\_REQUESTED\_LEASE

allocation engine will try to offer requested lease %1 to the client %2

Logged at debug log level 40. This message is issued when the allocation engine will try to offer the lease specified in the hint. This situation may occur when: (a) client doesn't have any reservations, (b) client has reservation but the reserved address is leased to another client.

#### 1.24 ALLOC ENGINE V4 RECLAIMED LEASES DELETE

begin deletion of reclaimed leases expired more than %1 seconds ago

Logged at debug log level 40. This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

#### 1.25 ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_COMPLETE

successfully deleted %1 expired-reclaimed leases

Logged at debug log level 40. This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

## 1.26 ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_FAILED

deletion of expired-reclaimed leases failed: %1

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

## 1.27 ALLOC\_ENGINE\_V4\_REQUEST\_ADDRESS\_RESERVED

%1: requested address %2 is reserved

Logged at debug log level 40. This message is issued when the allocation engine refused to allocate address requested by the client because this address is reserved for another client. The first argument includes the client identification information.

### 1.28 ALLOC ENGINE V4 REQUEST ALLOC REQUESTED

%1: trying to allocate requested address %2

Logged at debug log level 40. This message is issued when the allocation engine is trying to allocate (or reuse an expired) address which has been requested by the client. The first argument includes the client identification information.

#### 1.29 ALLOC\_ENGINE\_V4\_REQUEST\_EXTEND\_LEASE

%1: extending lifetime of the lease for address %2

Logged at debug log level 40. This message is issued when the allocation engine determines that the client already has a lease whose lifetime can be extended, and which can be returned to the client. The first argument includes the client identification information.

### 1.30 ALLOC\_ENGINE\_V4\_REQUEST\_INVALID

client %1 having a reservation for address %2 is requesting invalid address %3

Logged at debug log level 40. This message is logged when the client, having a reservation for one address, is requesting a different address. The client is only allowed to do this when the reserved address is in use by another client. However, the allocation engine has determined that the reserved address is available and the client should request the reserved address.

## 1.31 ALLOC\_ENGINE\_V4\_REQUEST\_IN\_USE

%1: requested address %2 is in use

Logged at debug log level 40. This message is issued when the client is requesting or has a reservation for an address which is in use. The first argument includes the client identification information.

## 1.32 ALLOC\_ENGINE\_V4\_REQUEST\_OUT\_OF\_POOL

client %1, which doesn't have a reservation, requested address %2 out of the dynamic pool

Logged at debug log level 40. This message is issued when the client has requested allocation of the address which doesn't belong to any address pool from which addresses are dynamically allocated. The client also doesn't have reservation for this address. This address could only be allocated if the client had reservation for it.

### 1.33 ALLOC\_ENGINE\_V4\_REQUEST\_PICK\_ADDRESS

client %1 hasn't specified an address - picking available address from the pool

Logged at debug log level 40. This message is logged when the client hasn't specified any preferred address (the client should always do it, but Kea tries to be forgiving). The allocation engine will try to pick an available address from the dynamic pool and allocate it to the client.

#### 1.34 ALLOC ENGINE V4 REQUEST REMOVE LEASE

%1: removing previous client's lease %2

Logged at debug log level 40. This message is logged when the allocation engine removes previous lease for the client because the client has been allocated new one.

### 1.35 ALLOC\_ENGINE\_V4\_REQUEST\_USE\_HR

client %1 hasn't requested specific address, using reserved address %2

Logged at debug log level 40. This message is issued when the client is not requesting any specific address but the allocation engine has determined that there is a reservation for this client. The allocation engine will try to allocate the reserved address.

### 1.36 ALLOC\_ENGINE\_V4\_REUSE\_EXPIRED\_LEASE\_DATA

%1: reusing expired lease, updated lease information: %2

Logged at debug log level 55. This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

## 1.37 ALLOC\_ENGINE\_V6\_ALLOC\_ERROR

%1: error during attempt to allocate an IPv6 address: %2

An error occurred during an attempt to allocate an IPv6 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

### 1.38 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL

%1: failed to allocate an IPv6 lease after %2 attempt(s)

This is an old warning message issued when the allocation engine fails to allocate a lease for a client. This message includes a number of lease allocation attempts that the engine made before giving up. If the number of attempts is 0 because the engine was unable to use any of the pools for the particular client, this message is not logged. Even though, several more detailed logs precede this message, it was left for backward compatibility. This message may indicate that your pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if the you know that the number of concurrently active clients is less than the leases you have available, you may want to consider reducing the lease lifetime. This way, leases allocated to clients that are no longer active on the network will become available sooner.

#### 1.39 ALLOC ENGINE V6 ALLOC FAIL CLASSES

%1: Failed to allocate an IPv6 address for client with classes: %2

This warning message is printed when Kea failed to allocate an address and the client's packet belongs to one or more classes. There may be several reasons why a lease was not assigned. One of them may be a case when all pools require packet to belong to certain classes and the incoming packet didn't belong to any of them. Another case where this information may be useful is to point out that the pool reserved to a given class has ran out of addresses. When you see this message, you may consider checking your pool size and your classification definitions.

### 1.40 ALLOC ENGINE V6 ALLOC FAIL NO POOLS

%1: no pools were available for the lease allocation

This warning message is issued when the allocation engine fails to allocate a lease because it could not use any configured pools for the particular client. It is also possible that all of the subnets from which the allocation engine attempted to assign an address lack address pools. In this case, it should be considered misconfiguration if an operator expects that some clients should be assigned dynamic addresses. A subnet may lack any pools only when all clients should be assigned reserved leases. Suppose the subnets connected to a shared network or a single subnet to which the client belongs have pools configured. In that case, this message is an indication that none of the pools could be used for the client because the client does not belong to appropriate client classes.

### 1.41 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL\_SHARED\_NETWORK

%1: failed to allocate a lease in the shared network %2: %3 subnets have no available\_ = leases, %4 subnets have no matching pools

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a shared network. The shared network should contain at least one subnet, but typically it aggregates multiple subnets. This log message indicates that the allocation engine could not find and allocate any suitable lease in any of the subnets within the shared network. The first argument includes the client identification information. The second argument specifies the shared network name. The remaining two arguments provide additional information useful for debugging why the allocation engine could not assign a lease. The allocation engine tries to allocate leases from different subnets in the shared network, and it may fail for some subnets because there are no leases available in those subnets or the free leases

are reserved to other clients. The number of such subnets is specified in the third argument. For other subnets the allocation may fail because their pools may not be available to the particular client. These pools are guarded by client classes that the client does not belong to. The fourth argument specifies the number of such subnets. By looking at the values in the third and fourth argument, an operator can identify the situations when there are no leases left in some of the pools. He or she can also identify client classification misconfigurations causing some clients to be refused the service.

#### 1.42 ALLOC ENGINE V6 ALLOC FAIL SUBNET

%1: failed to allocate an IPv6 lease in the subnet %2, subnet-id %3, shared network %4

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a subnet. The first argument includes the client identification information. The second and third arguments identify the subnet. The fourth argument specifies the shared network, if the subnet belongs to a shared network. There are many reasons for failing lease allocations. One of them may be the pools exhaustion or existing reservations for the free leases. However, in some cases, the allocation engine may fail to find a suitable pool for the client when the pools are only available to certain client classes, but the requesting client does not belong to them. Further log messages provide more information to distinguish between these different cases.

#### 1.43 ALLOC ENGINE V6 ALLOC HR LEASE EXISTS

%1: lease type %2 for reserved address/prefix %3 already exists

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the lease for the IPv6 address or prefix has already been allocated for the client and the client can continue using it. The first argument includes the client identification information.

## 1.44 ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_HR

leases and static reservations found for client %1

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client, it found existing leases and static reservations for the client. The allocation engine will verify if existing leases match reservations. Those leases that are reserved for other clients and those that are not reserved for the client will be removed. All leases matching the reservations will be renewed and returned.

### 1.45 ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_NO\_HR

no reservations found but leases exist for client %1

Logged at debug log level 40. This message is logged when the allocation engine is in the process if allocating leases for the client, there are no static reservations, but lease(s) exist for the client. The allocation engine will remove leases which are reserved for other clients, and return all remaining leases to the client.

### 1.46 ALLOC\_ENGINE\_V6\_ALLOC\_NO\_LEASES\_HR

no leases found but reservations exist for client %1

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client. It hasn't found any existing leases for this client, but the client appears to have static reservations. The allocation engine will try to allocate the reserved resources for the client.

#### 1.47 ALLOC ENGINE V6 ALLOC NO V6 HR

%1: unable to allocate reserved leases - no IPv6 reservations

Logged at debug log level 40. This message is logged when the allocation engine determines that the client has no IPv6 reservations and thus the allocation engine will have to try to allocate allocating leases from the dynamic pool or stop the allocation process if none can be allocated. The first argument includes the client identification information.

### 1.48 ALLOC\_ENGINE\_V6\_ALLOC\_UNRESERVED

no static reservations available - trying to dynamically allocate leases for client %1

Logged at debug log level 40. This debug message is issued when the allocation engine will attempt to allocate leases from the dynamic pools. This may be due to one of (a) there are no reservations for this client, (b) there are reservations for the client but they are not usable because the addresses are in use by another client or (c) we had a reserved lease but that has now been allocated to another client.

## 1.49 ALLOC ENGINE V6 CALCULATED PREFERRED LIFETIME

%1: using a calculated preferred-lifetime of %2

Logged at debug log level 40. This debug message indicates that the preferred-lifetime being returned to the client is defaulting to 62.5% of the valid-lifetime. This may occur if either the preferred-lifetime has not been explicitly configured, or the configured value is larger than the valid-lifetime. The arguments detail the client and the preferred-lifetime that will be used.

## 1.50 ALLOC\_ENGINE\_V6\_DECLINED\_RECOVERED

IPv6 address %1 was recovered after %2 seconds of probation-period

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes the decline recovery process.

### 1.51 ALLOC\_ENGINE\_V6\_EXPIRED\_HINT\_RESERVED

%1: expired lease for the client's hint %2 is reserved for another client

Logged at debug log level 40. This message is logged when the allocation engine finds that the expired lease for the client's hint can't be reused because it is reserved for another client. The first argument includes the client identification information.

#### 1.52 ALLOC ENGINE V6 EXTEND ALLOC UNRESERVED

allocate new (unreserved) leases for the renewing client %1

Logged at debug log level 40. This debug message is issued when the allocation engine is trying to allocate new leases for the renewing client because it was unable to renew any of the existing client's leases, e.g. because leases are reserved for another client or for any other reason.

### 1.53 ALLOC\_ENGINE\_V6\_EXTEND\_ERROR

%1: allocation engine experienced error with attempting to extend lease lifetime: %2

This error message indicates that an error was experienced during Renew or Rebind processing. Additional explanation is provided with this message. Depending on its nature, manual intervention may be required to continue processing messages from this particular client; other clients will be unaffected. The first argument includes the client identification information.

### 1.54 ALLOC ENGINE V6 EXTEND LEASE

%1: extending lifetime of the lease type %2, address %3

Logged at debug log level 50. This debug message is issued when the allocation engine is trying to extend lifetime of the lease. The first argument includes the client identification information.

## 1.55 ALLOC\_ENGINE\_V6\_EXTEND\_LEASE\_DATA

%1: detailed information about the lease being extended: %2

Logged at debug log level 55. This debug message prints detailed information about the lease which lifetime is being extended (renew or rebind). The first argument includes the client identification information.

### 1.56 ALLOC ENGINE V6 EXTEND NEW LEASE DATA

%1: new lease information for the lease being extended: %2

Logged at debug log level 55. This debug message prints updated information about the lease to be extended. If the lease update is successful, the information printed by this message will be stored in the database. The first argument includes the client identification information.

#### 1.57 ALLOC ENGINE V6 HINT RESERVED

%1: lease for the client's hint %2 is reserved for another client

Logged at debug log level 40. This message is logged when the allocation engine cannot allocate the lease using the client's hint because the lease for this hint is reserved for another client. The first argument includes the client identification information.

### 1.58 ALLOC\_ENGINE\_V6\_HR\_ADDR\_GRANTED

reserved address %1 was assigned to client %2

This informational message signals that the specified client was assigned the address reserved for it.

### 1.59 ALLOC\_ENGINE\_V6\_HR\_PREFIX\_GRANTED

reserved prefix %1/%2 was assigned to client %3

This informational message signals that the specified client was assigned the prefix reserved for it.

# 1.60 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_COMPLETE

reclaimed %1 leases in %2

Logged at debug log level 40. This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

### 1.61 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_FAILED

reclamation of expired leases failed: %1

This error message is issued when the reclamation of the expired leases failed. The error message is displayed.

# 1.62 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_SLOW

expired leases still exist after %1 reclamations

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

#### 1.63 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_START

starting reclamation of expired leases (limit = %1 leases or %2 milliseconds)

Logged at debug log level 40. This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

## 1.64 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_TIMEOUT

timeout of %1 ms reached while reclaiming IPv6 leases

Logged at debug log level 40. This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

### 1.65 ALLOC\_ENGINE\_V6\_LEASE\_RECLAIM

%1: reclaiming expired lease for prefix %2/%3

Logged at debug log level 40. This debug message is issued when the server begins reclamation of the expired DHCPv6 lease. The reclaimed lease may either be an address lease or delegated prefix. The first argument provides the client identification information. The other arguments specify the prefix and the prefix length for the lease. The prefix length for address lease is equal to 128.

### 1.66 ALLOC\_ENGINE\_V6\_LEASE\_RECLAMATION\_FAILED

failed to reclaim the lease %1: %2

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

#### 1.67 ALLOC ENGINE V6 NO MORE EXPIRED LEASES

all expired leases have been reclaimed

Logged at debug log level 40. This debug message is issued when the server reclaims all expired DHCPv6 leases in the database.

### 1.68 ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE

begin deletion of reclaimed leases expired more than %1 seconds ago

Logged at debug log level 40. This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

### 1.69 ALLOC ENGINE V6 RECLAIMED LEASES DELETE COMPLETE

successfully deleted %1 expired-reclaimed leases

Logged at debug log level 40. This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

### 1.70 ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_FAILED

deletion of expired-reclaimed leases failed: %1

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

### 1.71 ALLOC ENGINE V6 RENEW HR

allocating leases reserved for the client %1 as a result of Renew

Logged at debug log level 40. This debug message is issued when the allocation engine tries to allocate reserved leases for the client sending a Renew message. The server will also remove any leases that the client is trying to renew that are not reserved for the client.

#### 1.72 ALLOC ENGINE V6 RENEW REMOVE RESERVED

%1: checking if existing client's leases are reserved for another client

Logged at debug log level 40. This message is logged when the allocation engine finds leases for the client and will check if these leases are reserved for another client. If they are, they will not be renewed for the client requesting their renewal. The first argument includes the client identification information.

### 1.73 ALLOC\_ENGINE\_V6\_REUSE\_EXPIRED\_LEASE\_DATA

%1: reusing expired lease, updated lease information: %2

Logged at debug log level 55. This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

### 1.74 ALLOC\_ENGINE\_V6\_REVOKED\_ADDR\_LEASE

%1: address %2 was revoked from client %3 as it is reserved for client %4

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

## 1.75 ALLOC\_ENGINE\_V6\_REVOKED\_PREFIX\_LEASE

%1: prefix %2/%3 was revoked from client %4 as it is reserved for client %5

This informational message is an indication that the specified IPv6 prefix was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their prefixes.

# 1.76 ALLOC\_ENGINE\_V6\_REVOKED\_SHARED\_ADDR\_LEASE

%1: address %2 was revoked from client %3 as it is reserved for %4 other clients

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for multiple other clients. Client A has been told to stop using it so that it can be leased to one of the clients having the reservation for it. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding reservations for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

**CHAPTER** 

**TWO** 

#### **ASIODNS**

### 2.1 ASIODNS\_FETCH\_COMPLETED

upstream fetch to %1(%2) has now completed

Logged at debug log level 70. A debug message, this records that the upstream fetch (a query made by the resolver on behalf of its client) to the specified address has completed.

#### 2.2 ASIODNS FETCH STOPPED

upstream fetch to %1(%2) has been stopped

Logged at debug log level 40. An external component has requested the halting of an upstream fetch. This is an allowed operation, and the message should only appear if debug is enabled.

## 2.3 ASIODNS OPEN SOCKET

error %1 opening %2 socket to %3(%4)

The asynchronous I/O code encountered an error when trying to open a socket of the specified protocol in order to send a message to the target address. The number of the system error that caused the problem is given in the message.

## 2.4 ASIODNS\_READ\_DATA

error %1 reading %2 data from %3(%4)

The asynchronous I/O code encountered an error when trying to read data from the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

### 2.5 ASIODNS\_READ\_TIMEOUT

receive timeout while waiting for data from %1(%2)

Logged at debug log level 50. An upstream fetch from the specified address timed out. This may happen for any number of reasons and is most probably a problem at the remote server or a problem on the network. The message will only appear if debug is enabled.

#### 2.6 ASIODNS SEND DATA

error %1 sending data using %2 to %3(%4)

The asynchronous I/O code encountered an error when trying to send data to the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

### 2.7 ASIODNS\_UNKNOWN\_ORIGIN

unknown origin for ASIO error code %1 (protocol: %2, address %3)

An internal consistency check on the origin of a message from the asynchronous I/O module failed. This may indicate an internal error; please submit a bug report.

**CHAPTER** 

THREE

**BOOTP** 

#### 3.1 BOOTP BOOTP QUERY

recognized a BOOTP query: %1

Logged at debug log level 40. This debug message is printed when the BOOTP query was recognized. The BOOTP client class was added and the message type set to DHCPREQUEST. The query client and transaction identification are displayed.

#### 3.2 BOOTP LOAD

Bootp hooks library has been loaded

This info message indicates that the Bootp hooks library has been loaded.

## 3.3 BOOTP\_PACKET\_OPTIONS\_SKIPPED

an error unpacking an option, caused subsequent options to be skipped: %1

Logged at debug log level 40. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

## 3.4 BOOTP\_PACKET\_PACK

%1: preparing on-wire format of the packet to be sent

Logged at debug log level 40. This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

### 3.5 BOOTP\_PACKET\_PACK\_FAIL

%1: preparing on-wire-format of the packet to be sent failed %2

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the BOOTP transaction. The second argument includes the error string.

### 3.6 BOOTP\_PACKET\_UNPACK\_FAILED

failed to parse query from %1 to %2, received over interface %3, reason: %4

Logged at debug log level 40. This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the buffer4\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

24 Chapter 3. BOOTP

**CHAPTER** 

**FOUR** 

#### **COMMAND**

#### 4.1 COMMAND ACCEPTOR START

Starting to accept connections via unix domain socket bound to %1

This informational message is issued when the Kea server starts an acceptor via which it is going to accept new control connections. The acceptor is bound to the endpoint associated with the filename provided as an argument. If starting the acceptor fails, subsequent error messages will provide a reason for failure.

#### 4.2 COMMAND DEREGISTERED

Command %1 deregistered

Logged at debug log level 10. This debug message indicates that the daemon stopped supporting specified command. This command can no longer be issued. If the command socket is open and this command is issued, the daemon will not be able to process it.

## 4.3 COMMAND\_EXTENDED\_REGISTERED

Command %1 registered

Logged at debug log level 10. This debug message indicates that the daemon started supporting specified command. The handler for the registered command includes a parameter holding entire command to be processed.

# 4.4 COMMAND\_HTTP\_LISTENER\_COMMAND\_REJECTED

Command HTTP listener rejected command '%1' from '%2'

Logged at debug log level 10. This debug messages is issued when a command is rejected. Arguments detail the command and the address the request was received from.

### 4.5 COMMAND HTTP LISTENER STARTED

Command HTTP listener started with %1 threads, listening on %2:%3, use TLS: %4

Logged at debug log level 10. This debug messages is issued when an HTTP listener has been started to accept connections from Command API clients through which commands can be received and responses sent. Arguments detail the number of threads that the listener is using, the address and port at which it is listening, and if HTTPS/TLS is used or not.

#### 4.6 COMMAND HTTP LISTENER STOPPED

Command HTTP listener for %1:%2 stopped.

Logged at debug log level 10. This debug messages is issued when the Command HTTP listener, listening at the given address and port, has completed shutdown.

# 4.7 COMMAND\_HTTP\_LISTENER\_STOPPING

Stopping Command HTTP listener for %1:%2

Logged at debug log level 10. This debug messages is issued when the Command HTTP listener, listening at the given address and port, has begun to shutdown.

### 4.8 COMMAND\_PROCESS\_ERROR1

Error while processing command: %1

This warning message indicates that the server encountered an error while processing received command. Additional information will be provided, if available. Additional log messages may provide more details.

## 4.9 COMMAND\_PROCESS\_ERROR2

Error while processing command: %1

This warning message indicates that the server encountered an error while processing received command. The difference, compared to COMMAND\_PROCESS\_ERROR1 is that the initial command was well formed and the error occurred during logic processing, not the command parsing. Additional information will be provided, if available. Additional log messages may provide more details.

### 4.10 COMMAND\_RECEIVED

Received command '%1'

This informational message indicates that a command was received over command socket. The nature of this command and its possible results will be logged with separate messages.

#### 4.11 COMMAND\_REGISTERED

Command %1 registered

Logged at debug log level 10. This debug message indicates that the daemon started supporting specified command. If the command socket is open, this command can now be issued.

#### 4.12 COMMAND RESPONSE ERROR

Server failed to generate response for command: %1

This error message indicates that the server failed to generate response for specified command. This likely indicates a server logic error, as the server is expected to generate valid responses for all commands, even malformed ones.

#### 4.13 COMMAND\_SOCKET\_ACCEPT\_FAIL

Failed to accept incoming connection on command socket %1: %2

This error indicates that the server detected incoming connection and executed accept system call on said socket, but this call returned an error. Additional information may be provided by the system as second parameter.

## 4.14 COMMAND SOCKET CLOSED BY FOREIGN HOST

Closed command socket %1 by foreign host, %2

This is an information message indicating that the command connection has been closed by a command control client, and whether any partially read data was discarded.

## 4.15 COMMAND\_SOCKET\_CONNECTION\_CANCEL\_FAIL

Failed to cancel read operation on socket %1: %2

This error message is issued to indicate an error to cancel asynchronous read of the control command over the control socket. The cancel operation is performed when the timeout occurs during communication with a client. The error message includes details about the reason for failure.

### 4.16 COMMAND\_SOCKET\_CONNECTION\_CLOSED

Closed socket %1 for existing command connection

Logged at debug log level 10. This is a debug message indicating that the socket created for handling client's connection is closed. This usually means that the client disconnected, but may also mean a timeout.

#### 4.17 COMMAND\_SOCKET\_CONNECTION\_CLOSE\_FAIL

Failed to close command connection: %1

This error message is issued when an error occurred when closing a command connection and/or removing it from the connections pool. The detailed error is provided as an argument.

#### 4.18 COMMAND SOCKET CONNECTION OPENED

Opened socket %1 for incoming command connection

Logged at debug log level 10. This is a debug message indicating that a new incoming command connection was detected and a dedicated socket was opened for that connection.

#### 4.19 COMMAND\_SOCKET\_CONNECTION\_SHUTDOWN\_FAIL

Encountered error %1 while trying to gracefully shutdown socket

This message indicates an error while trying to gracefully shutdown command connection. The type of the error is included in the message.

## 4.20 COMMAND\_SOCKET\_CONNECTION\_TIMEOUT

Timeout occurred for connection over socket %1

This is an informational message that indicates that the timeout has occurred for one of the command channel connections. The response sent by the server indicates a timeout and is then closed.

## 4.21 COMMAND\_SOCKET\_READ

Received %1 bytes over command socket %2

Logged at debug log level 10. This debug message indicates that specified number of bytes was received over command socket identified by specified file descriptor.

### 4.22 COMMAND\_SOCKET\_READ\_FAIL

Encountered error %1 while reading from command socket %2

This error message indicates that an error was encountered while reading from command socket.

#### 4.23 COMMAND\_SOCKET\_WRITE

Sent response of %1 bytes (%2 bytes left to send) over command socket %3

Logged at debug log level 10. This debug message indicates that the specified number of bytes was sent over command socket identifier by the specified file descriptor.

### 4.24 COMMAND\_SOCKET\_WRITE FAIL

Error while writing to command socket %1 : %2

This error message indicates that an error was encountered while attempting to send a response to the command socket.

#### 4.25 COMMAND WATCH SOCKET CLEAR ERROR

watch socket failed to clear: %1

This error message is issued when the command manager was unable to reset the ready status after completing a send. This is a programmatic error that should be reported. The command manager may or may not continue to operate correctly.

## 4.26 COMMAND WATCH SOCKET CLOSE ERROR

watch socket failed to close: %1

This error message is issued when command manager attempted to close the socket used for indicating the ready status for send operations. This should not have any negative impact on the operation of the command manager as it happens when the connection is being terminated.

## 4.27 COMMAND\_WATCH\_SOCKET\_MARK\_READY\_ERROR

watch socket failed to mark ready: %1

This error message is issued when the command manager was unable to set ready status after scheduling asynchronous send. This is programmatic error that should be reported. The command manager may or may not continue to operate correctly.

**CHAPTER** 

**FIVE** 

**CTRL** 

### 5.1 CTRL\_AGENT\_COMMAND\_FORWARDED

command %1 successfully forwarded to the service %2 from remote address %3

This informational message is issued when the CA successfully forwards the control message to the specified Kea service and receives a response.

#### 5.2 CTRL AGENT COMMAND FORWARD BEGIN

begin forwarding command %1 to service %2

Logged at debug log level 10. This debug message is issued when the Control Agent starts forwarding a received command to one of the Kea servers.

## 5.3 CTRL\_AGENT\_COMMAND\_FORWARD\_FAILED

failed forwarding command %1: %2

Logged at debug log level 10. This debug message is issued when the Control Agent failed forwarding a received command to one of the Kea servers. The second argument provides the details of the error.

## 5.4 CTRL\_AGENT\_COMMAND\_RECEIVED

command %1 received from remote address %2

This informational message is issued when the CA receives a control message, whether it is destined to the control agent itself, or to be forwarded on.

### 5.5 CTRL\_AGENT\_CONFIG\_CHECK\_FAIL

Control Agent configuration check failed: %1

This error message indicates that the CA had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

#### 5.6 CTRL AGENT CONFIG FAIL

Control Agent configuration failed: %1

This error message indicates that the CA had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

#### 5.7 CTRL AGENT CONFIG SYNTAX WARNING

Control Agent configuration syntax warning: %1

This warning message indicates that the CA configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

#### 5.8 CTRL\_AGENT\_FAILED

application experienced a fatal error: %1

This is a fatal error message issued when the Control Agent application encounters an unrecoverable error from within the event loop.

## 5.9 CTRL\_AGENT\_HTTPS\_SERVICE\_REUSED

reused HTTPS service bound to address %1:%2

This informational message indicates that the server has reused existing HTTPS service on the specified address and port. Note that any change in the TLS setup was ignored.

## 5.10 CTRL\_AGENT\_HTTPS\_SERVICE\_STARTED

HTTPS service bound to address %1:%2

This informational message indicates that the server has started HTTPS service on the specified address and port. All control commands should be sent to this address and port over a TLS channel.

32 Chapter 5. CTRL

# 5.11 CTRL\_AGENT\_HTTP\_SERVICE\_REUSED

reused HTTP service bound to address %1:%2

This informational message indicates that the server has reused existing HTTPS service on the specified address and port.

## 5.12 CTRL\_AGENT\_HTTP\_SERVICE\_STARTED

HTTP service bound to address %1:%2

This informational message indicates that the server has started HTTP service on the specified address and port. All control commands should be sent to this address and port.

#### 5.13 CTRL AGENT RUN EXIT

application is exiting the event loop

Logged at debug log level 0. This is a debug message issued when the Control Agent exits its event loop.

34 Chapter 5. CTRL

**CHAPTER** 

SIX

#### **DATABASE**

### 6.1 DATABASE\_INVALID\_ACCESS

invalid database access string: %1

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

#### 6.2 DATABASE MYSQL COMMIT

committing to MySQL database

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

## 6.3 DATABASE\_MYSQL\_FATAL\_ERROR

Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not, then the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

## 6.4 DATABASE\_MYSQL\_INITIALIZE\_SCHEMA

Initializing the MySQL schema with command: %1.

This is logged before running the kea-admin command to automatically initialize the schema from Kea after getting the schema version initially failed. The full kea-admin command is shown.

#### 6.5 DATABASE MYSQL ROLLBACK

rolling back MySQL database

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

### 6.6 DATABASE\_MYSQL\_START\_TRANSACTION

starting new MySQL transaction

A debug message issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

#### 6.7 DATABASE PGSQL COMMIT

committing to PostgreSQL database

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

## 6.8 DATABASE\_PGSQL\_CREATE\_SAVEPOINT

creating a new PostgreSQL savepoint: %1

The code is issuing a call to create a savepoint within the current transaction. Database modifications made up to this point will be preserved should a subsequent call to rollback to this savepoint occurs prior to the transaction being committed.

## 6.9 DATABASE\_PGSQL\_DEALLOC\_ERROR

An error occurred deallocating SQL statements while closing the PostgreSQL lease\_database: %1

This is an error message issued when a DHCP server (either V4 or V6) experienced and error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

## 6.10 DATABASE\_PGSQL\_FATAL\_ERROR

Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3).

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not, then the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

## 6.11 DATABASE\_PGSQL\_INITIALIZE\_SCHEMA

Initializing the PostgreSQL schema with command: %1.

This is logged before running the kea-admin command to automatically initialize the schema from Kea after getting the schema version initially failed. The full kea-admin command is shown.

## 6.12 DATABASE\_PGSQL\_ROLLBACK

rolling back PostgreSQL database

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

## 6.13 DATABASE\_PGSQL\_ROLLBACK\_SAVEPOINT

rolling back PostgreSQL database to savepoint: \$1

The code is issuing a call to rollback to the given savepoint. Any database modifications that were made after the savepoint was created will be rolled back and not committed to the database.

# 6.14 DATABASE\_PGSQL\_START\_TRANSACTION

starting a new PostgreSQL transaction

A debug message issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

# 6.15 DATABASE\_PGSQL\_TCP\_USER\_TIMEOUT\_UNSUPPORTED

tcp\_user\_timeout is not supported in this PostgreSQL version

This warning message is issued when a user has configured the tcp\_user\_timeout parameter in the connection to the PostgreSQL database but the installed database does not support this parameter. It is supported by the PostgreSQL version 12 or later. The parameter setting will be ignored.

#### 6.16 DATABASE TO JSON BOOLEAN ERROR

Internal logic error: invalid boolean value found in database connection parameters: %1 = -%2

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains a boolean parameter with invalid value. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The culprit parameter will not be converted.

#### 6.17 DATABASE\_TO\_JSON\_INTEGER\_ERROR

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains the integer parameter with a wrong value. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The culprit parameter will not be converted.

**CHAPTER** 

SEVEN

**DCTL** 

#### 7.1 DCTL ALREADY RUNNING

%1 already running? %2

This is an error message that occurs when a module encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of a module using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than Kea process. In such an event, it would be necessary to manually remove the PID file. The first argument is the process name, the second contains the PID and PID file.

# 7.2 DCTL\_CFG\_FILE\_RELOAD\_ERROR

configuration reload failed: %1, reverting to current configuration.

This is an error message indicating that the application attempted to reload its configuration from file and encountered an error. This is likely due to invalid content in the configuration file. The application should continue to operate under its current configuration.

# 7.3 DCTL\_CFG\_FILE\_RELOAD\_SIGNAL\_RECVD

OS signal %1 received, reloading configuration from file: %2

This is an informational message indicating the application has received a signal instructing it to reload its configuration from file.

# 7.4 DCTL CONFIG CHECK COMPLETE

server has completed configuration check: %1, result: %2

This is an informational message announcing the successful processing of a new configuration check is complete. The result of that check is printed. This informational message is printed when configuration check is requested.

## 7.5 DCTL CONFIG COMPLETE

server has completed configuration: %1

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

#### 7.6 DCTL CONFIG DEPRECATED

server configuration includes a deprecated object: %1

This error message is issued when the configuration includes a deprecated object (i.e. a top level element) which will be ignored.

## 7.7 DCTL\_CONFIG\_FETCH

Fetching configuration data from config backends.

This is an informational message emitted when the Kea server is about to begin retrieving configuration data from one or more configuration backends.

## 7.8 DCTL\_CONFIG\_FILE\_LOAD\_FAIL

%1 reason: %2

This fatal error message indicates that the application attempted to load its initial configuration from file and has failed. The service will exit.

## 7.9 DCTL\_CONFIG\_START

parsing new configuration: %1

Logged at debug log level 10. A debug message indicating that the application process has received an updated configuration and has passed it to its configuration manager for parsing.

40 Chapter 7. DCTL

# 7.10 DCTL\_DB\_OPEN\_CONNECTION\_WITH\_RETRY\_FAILED

Failed to connect to database: %1 with error: %2

This is an informational message issued when the server failed to connect to the configuration database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

#### 7.11 DCTL DEPRECATED OUTPUT OPTIONS

The output\_options parameter is deprecated. Use output-options parameter instead.

This warning message is displayed when deprecated output\_options is used instead of output-options.

## 7.12 DCTL\_DEVELOPMENT\_VERSION

This software is a development branch of Kea. It is not recommended for production use.

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

## 7.13 DCTL\_INIT\_PROCESS

%1 initializing the application

Logged at debug log level 0. This debug message is issued just before the controller attempts to create and initialize its application instance.

# 7.14 DCTL\_INIT\_PROCESS\_FAIL

%1 application initialization failed: %2

This error message is issued if the controller could not initialize the application and will exit.

# 7.15 DCTL\_NOT\_RUNNING

%1 application instance is not running

A warning message is issued when an attempt is made to shut down the application when it is not running.

## 7.16 DCTL OPEN CONFIG DB

Opening configuration database: %1

This message is printed when the Kea server is attempting to open a configuration database. The database access string with password redacted is logged.

#### 7.17 DCTL\_PARSER\_FAIL

Parser error: %1

On receipt of a new configuration, the server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

## 7.18 DCTL\_PID\_FILE\_ERROR

%1 could not create a PID file: %2

This is an error message that occurs when the server is unable to create its PID file. The log message should contain details sufficient to determine the underlying cause. The most likely culprits are that some portion of the pathname does not exist or a permissions issue. The default path is determined by --local stated or --runstated or configure parameters but may be overridden by setting environment variable, KEA PIDFILE DIR. The first argument is the process name.

## 7.19 DCTL PROCESS FAILED

%1 application execution failed: %2

The controller has encountered a fatal error while running the application and is terminating. The reason for the failure is included in the message.

## 7.20 DCTL\_RUN\_PROCESS

%1 starting application event loop

Logged at debug log level 0. This debug message is issued just before the controller invokes the application run method.

42 Chapter 7. DCTL

## 7.21 DCTL\_SHUTDOWN

%1 has shut down, pid: %2, version: %3

Logged at debug log level 0. This is an informational message indicating that the service has shut down. The argument specifies a name of the service.

#### 7.22 DCTL\_SHUTDOWN\_SIGNAL\_RECVD

OS signal %1 received, starting shutdown

Logged at debug log level 0. This is a debug message indicating the application has received a signal instructing it to shutdown.

#### 7.23 DCTL STANDALONE

%1 skipping message queue, running standalone

Logged at debug log level 0. This is a debug message indicating that the controller is running in the application in standalone mode. This means it will not connected to the Kea message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

## 7.24 DCTL\_STARTING

%1 starting, pid: %2, version: %3 (%4)

This is an informational message issued when controller for the service first starts. Version is also reported.

## 7.25 DCTL UNLOAD LIBRARIES ERROR

error unloading hooks libraries during shutdown: %1

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

44 Chapter 7. DCTL

**CHAPTER** 

**EIGHT** 

DHCP4

#### 8.1 DHCP4 ADDITIONAL CLASS EVAL ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating the expression of an additional client class. A description of the problem is printed.

#### 8.2 DHCP4 ADDITIONAL CLASS EVAL RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of an additional client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

# 8.3 DHCP4\_ADDITIONAL\_CLASS\_NO\_TEST

additional class %1 has no test expression, adding it to client's classes unconditionally

Logged at debug log level 40. This debug message informs that a class was listed for additional evaluation but its definition does not include a test expression to evaluate. The class is unconditionally added to the query.

# 8.4 DHCP4\_ADDITIONAL\_CLASS\_UNDEFINED

additional class %1 has no definition

Logged at debug log level 40. This debug message informs that a class is listed for additional evaluation but has no definition. The class is ignored.

#### 8.5 DHCP4 ALREADY RUNNING

#### %1 already running? %2

This is an error message that occurs when the DHCPv4 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv4 process name, the second contains the PID and PID file.

#### 8.6 DHCP4 BUFFER RECEIVED

received buffer from %1:%2 to %3:%4 over interface %5

Logged at debug log level 40. This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination IPv4 addresses/ports.

#### 8.7 DHCP4 BUFFER RECEIVE FAIL

error on attempt to receive packet: %1

The DHCPv4 server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

# 8.8 DHCP4\_BUFFER\_UNPACK

parsing buffer received from %1 to %2 over interface %3

Logged at debug log level 50. This debug message is issued when the server starts parsing the received buffer holding the DHCPv4 message. The arguments specify the source and destination IPv4 addresses as well as the interface over which the buffer has been received.

# 8.9 DHCP4\_BUFFER\_WAIT\_SIGNAL

signal received while waiting for next packet

Logged at debug log level 50. This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets.

## 8.10 DHCP4\_CB\_ON\_DEMAND\_FETCH\_UPDATES\_FAIL

error on demand attempt to fetch configuration updates from the configuration →backend(s): %1

This error message is issued when the server attempted to fetch configuration updates from the database and this on demand attempt failed. The sole argument which is returned to the config-backend-pull command caller too contains the reason for failure.

#### 8.11 DHCP4 CB PERIODIC FETCH UPDATES FAIL

This error message is issued when the server attempted to fetch configuration updates from the database and this periodic attempt failed. The server will re-try according to the configured value of the config-fetch-wait-time parameter. The sole argument contains the reason for failure.

#### 8.12 DHCP4\_CB\_PERIODIC\_FETCH\_UPDATES\_RETRIES\_EXHAUSTED

maximum number of configuration fetch attempts: 10, has been exhausted without success

This error indicates that the server has made a number of unsuccessful periodic attempts to fetch configuration updates from a configuration backend. The server will continue to operate but won't make any further attempts to fetch configuration updates. The administrator must fix the configuration in the database and reload (or restart) the server.

# 8.13 DHCP4 CLASSES ASSIGNED

%1: client packet has been assigned on %2 message to the following classes: %3

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument specifies the DHCPv4 message type. The third argument includes all classes to which the packet has been assigned.

# 8.14 DHCP4\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION

%1: client packet has been assigned to the following classes: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

#### 8.15 DHCP4 CLASS ASSIGNED

%1: client packet has been assigned to the following class: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified class. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes the new class to which the packet has been assigned.

#### 8.16 DHCP4 CLASS UNCONFIGURED

%1: client packet belongs to an unconfigured class: %2

Logged at debug log level 40. This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

#### 8.17 DHCP4\_CLIENTID\_IGNORED\_FOR\_LEASES

%1: not using client identifier for lease allocation for subnet %2

Logged at debug log level 50. This debug message is issued when the server is processing the DHCPv4 message for which client identifier will not be used when allocating new lease or renewing existing lease. The server is explicitly configured to not use client identifier to lookup existing leases for the client and will not record client identifier in the lease database. This mode of operation is useful when clients don't use stable client identifiers, e.g. multi stage booting. The first argument includes the client and transaction identification information. The second argument specifies the identifier of the subnet where the client is connected and for which this mode of operation is configured on the server.

## 8.18 DHCP4\_CLIENT\_FQDN\_DATA

%1: Client sent FQDN option: %2

Logged at debug log level 55. This debug message includes the detailed information extracted from the Client FQDN option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the detailed information about the FQDN option received by the server.

# 8.19 DHCP4\_CLIENT\_FQDN\_PROCESS

%1: processing Client FQDN option

Logged at debug log level 50. This debug message is issued when the server starts processing the Client FQDN option sent in the client's query. The argument includes the client and transaction identification information.

## 8.20 DHCP4\_CLIENT\_HOSTNAME\_DATA

%1: client sent Hostname option: %2

Logged at debug log level 55. This debug message includes the detailed information extracted from the Hostname option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the hostname carried in the Hostname option sent by the client.

#### 8.21 DHCP4 CLIENT HOSTNAME MALFORMED

%1: client hostname option malformed: %2

Logged at debug log level 50. This debug message is issued when the DHCP server was unable to process the the host-name option sent by the client because the content is malformed. The first argument includes the client and transaction identification information. The second argument contains a description of the data error.

#### 8.22 DHCP4 CLIENT HOSTNAME PROCESS

%1: processing client's Hostname option

Logged at debug log level 50. This debug message is issued when the server starts processing the Hostname option sent in the client's query. The argument includes the client and transaction identification information.

## 8.23 DHCP4\_CLIENT\_NAME\_PROC\_FAIL

%1: failed to process the fqdn or hostname sent by a client: %2

Logged at debug log level 55. This debug message is issued when the DHCP server was unable to process the FQDN or Hostname option sent by a client. This is likely because the client's name was malformed or due to internal server error. The first argument contains the client and transaction identification information. The second argument holds the detailed description of the error.

# 8.24 DHCP4\_CONFIG\_COMPLETE

DHCPv4 server has completed configuration: %1

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

## 8.25 DHCP4 CONFIG LOAD FAIL

configuration error using file: %1, reason: %2

This error message indicates that the DHCPv4 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

#### 8.26 DHCP4 CONFIG PACKET QUEUE

DHCPv4 packet queue info after configuration: %1

This informational message is emitted during DHCPv4 server configuration, immediately after configuring the DHCPv4 packet queue. The information shown depends upon the packet queue type selected.

#### 8.27 DHCP4\_CONFIG\_RECEIVED

received configuration %1

Logged at debug log level 10. A debug message listing the configuration received by the DHCPv4 server. The source of that configuration depends on used configuration backend.

## 8.28 DHCP4\_CONFIG\_START

DHCPv4 server is processing the following configuration: %1

Logged at debug log level 10. This is a debug message that is issued every time the server receives a configuration. That happens at start up and also when a server configuration change is committed by the administrator.

## 8.29 DHCP4\_CONFIG\_SYNTAX\_WARNING

configuration syntax warning: %1

This warning message indicates that the DHCPv4 configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 8.30 DHCP4 CONFIG UNRECOVERABLE ERROR

DHCPv4 server new configuration failed with an error which cannot be recovered

This fatal error message is issued when a new configuration raised an error which cannot be recovered. A correct configuration must be applied as soon as possible as the server is no longer working. The configuration can be fixed in several ways. If the control channel is open, config-set with a valid configuration can be used. Alternatively, the original config file on disk could be fixed and SIGHUP signal could be sent (or the config-reload command issued). Finally, the server could be restarted completely.

# 8.31 DHCP4\_CONFIG\_UNSUPPORTED\_OBJECT

DHCPv4 server configuration includes an unsupported object: %1

This error message is issued when the configuration includes an unsupported object (i.e. a top level element).

#### 8.32 DHCP4\_DB\_RECONNECT\_DISABLED

database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

# 8.33 DHCP4\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

# 8.34 DHCP4\_DB\_RECONNECT\_LOST\_CONNECTION

database connection lost.

This info message indicates that the connection has been lost and the dhcp service might have been disabled, as specified in the configuration, in order to try to recover the connection.

## 8.35 DHCP4\_DB\_RECONNECT\_NO\_DB\_CTL

unexpected error in database reconnect

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to reconnect to its databases if connectivity is lost, and the server exits. This error should be reported.

#### 8.36 DHCP4\_DB\_RECONNECT\_SUCCEEDED

database connection recovered.

This info message indicates that the connection has been recovered and the dhcp service has been restored.

#### 8.37 DHCP4\_DDNS\_REQUEST\_SEND\_FAILED

failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2

This error message indicates that DHCP4 server attempted to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

#### 8.38 DHCP4 DECLINE FAIL

%1: error on decline lease for address %2: %3

This error message indicates that the software failed to decline a lease from the lease database due to an error during a database operation. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which decline was attempted. The last one contains the reason for failure.

## 8.39 DHCP4 DECLINE LEASE

Received DHCPDECLINE for addr %1 from client %2. The lease will be unavailable for %3. →seconds.

This informational message is printed when a client received an address, but discovered that it is being used by some other device and notified the server by sending a DHCPDECLINE message. The server checked that this address really was leased to the client and marked this address as unusable for a certain amount of time. This message may indicate a misconfiguration in a network, as there is either a buggy client or more likely a device that is using an address that it is not supposed to. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

## 8.40 DHCP4 DECLINE LEASE MISMATCH

Received DHCPDECLINE for addr %1 from client %2, but the data doesn't match: received\_ hwaddr: %3, lease hwaddr: %4, received client-id: %5, lease client-id: %6

This informational message means that a client attempted to report his address as declined (i.e. used by unknown entity). The server has information about a lease for that address, but the client's hardware address or client identifier does not match the server's stored information. The client's request will be ignored.

## 8.41 DHCP4\_DECLINE\_LEASE\_NOT\_FOUND

Received DHCPDECLINE for addr %1 from client %2, but no such lease found.

This warning message indicates that a client reported that his address was detected as a duplicate (i.e. another device in the network is using this address). However, the server does not have a record for this address. This may indicate a client's error or a server's purged database.

#### 8.42 DHCP4 DEFERRED OPTION MISSING

%1: cannot find deferred option code %2 in the query

Logged at debug log level 50. This debug message is printed when a deferred option cannot be found in the query.

## 8.43 DHCP4\_DEFERRED\_OPTION\_UNPACK\_FAIL

%1: An error unpacking the deferred option %2: %3

Logged at debug log level 50. A debug message issued when deferred unpacking of an option failed, making it to be left unpacked in the packet. The first argument is the option code, the second the error.

# 8.44 DHCP4\_DEVELOPMENT\_VERSION

This software is a development branch of Kea. It is not recommended for production use.

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

#### 8.45 DHCP4 DHCP4O6 BAD PACKET

%1: received malformed DHCPv4o6 packet: %2

Logged at debug log level 50. A malformed DHCPv4o6 packet was received.

## 8.46 DHCP4 DHCP4O6 HOOK SUBNET4 SELECT DROP

%1: packet was dropped, because a callout set the next step to 'drop'

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

#### 8.47 DHCP4 DHCP4O6 HOOK SUBNET4 SELECT SKIP

%1: no subnet was selected, because a callout set the next skip flag

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

## 8.48 DHCP4\_DHCP4O6\_PACKET\_RECEIVED

received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 on interface %3

Logged at debug log level 40. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

## 8.49 DHCP4\_DHCP4O6\_PACKET\_SEND

%1: trying to send packet %2 (type %3) to %4 port %5 on interface %6 encapsulating %7: 
→%8 (type %9)

Logged at debug log level 40. The arguments specify the client identification information (HW address and client identifier), DHCPv6 message name and type, source IPv6 address and port, and interface name, DHCPv4 client identification, message name and type.

## 8.50 DHCP4\_DHCP4O6\_PACKET\_SEND\_FAIL

%1: failed to send DHCPv4o6 packet: %2

This error is output if the IPv4 DHCP server fails to send an DHCPv4o6 message to the IPv6 DHCP server. The reason for the error is included in the message.

#### 8.51 DHCP4\_DHCP4O6\_RECEIVE\_FAIL

failed to receive DHCPv4o6: %1

Logged at debug log level 50. This debug message indicates the inter-process communication with the DHCPv6 server failed. The reason for the error is included in the message.

#### 8.52 DHCP4 DHCP4O6 RECEIVING

receiving DHCPv4o6 packet from DHCPv6 server

Logged at debug log level 50. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication socket.

#### 8.53 DHCP4\_DHCP4O6\_RESPONSE\_DATA

%1: responding with packet %2 (type %3), packet details: %4

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the DHCPv6 server to be forwarded to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

# 8.54 DHCP4\_DHCP4O6\_SUBNET\_DATA

%1: the selected subnet details: %2

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

#### 8.55 DHCP4\_DHCP4O6\_SUBNET\_SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

#### 8.56 DHCP4 DHCP4O6 SUBNET SELECTION FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

#### 8.57 DHCP4\_DISCOVER

%1: server is processing DHCPDISCOVER with hint=%2

Logged at debug log level 50. This is a debug message that indicates the processing of a received DHCPDISCOVER message. The first argument contains the client and the transaction identification information. The second argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

# 8.58 DHCP4\_DYNAMIC\_RECONFIGURATION

initiate server reconfiguration using file: %1, after receiving SIGHUP signal or configuration described by the signal or configuration of the signal of the signal or configuration of the signal of the signal or configuration of the signal or conf

This is the info message logged when the DHCPv4 server starts reconfiguration as a result of receiving SIGHUP signal or config-reload command.

# 8.59 DHCP4\_DYNAMIC\_RECONFIGURATION\_FAIL

dynamic server reconfiguration failed with file: %1

This is a fatal error message logged when the dynamic reconfiguration of the DHCP server failed.

## 8.60 DHCP4\_DYNAMIC\_RECONFIGURATION\_SUCCESS

dynamic server reconfiguration succeeded with file: %1

This is info message logged when the dynamic reconfiguration of the DHCP server succeeded.

## 8.61 DHCP4 EMPTY HOSTNAME

%1: received empty hostname from the client, skipping processing of this option

Logged at debug log level 50. This debug message is issued when the server received an empty Hostname option from a client. Server does not process empty Hostname options and therefore option is skipped. The argument holds the client and transaction identification information.

# 8.62 DHCP4\_FLEX\_ID

%1: flexible identifier generated for incoming packet: %2

Logged at debug log level 40. This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

## 8.63 DHCP4\_GENERATE\_FQDN

%1: client did not send a FQDN or hostname; FQDN will be generated for the client

Logged at debug log level 55. This debug message is issued when the server did not receive a Hostname option from the client and hostname generation is enabled. This provides a means to create DNS entries for unsophisticated clients.

# 8.64 DHCP4\_HOOK\_BUFFER\_RCVD\_DROP

Logged at debug log level 15. This debug message is printed when a callout installed on buffer4\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

## 8.65 DHCP4\_HOOK\_BUFFER\_RCVD\_SKIP

received buffer from %1 to %2 over interface %3 is not parsed because a callout set the  $_{\!\!\!\!-}$  next step to SKIP.

Logged at debug log level 50. This debug message is printed when a callout installed on buffer4\_receive hook point set the next step to SKIP. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

## 8.66 DHCP4\_HOOK\_BUFFER\_SEND\_SKIP

%1: prepared response is dropped because a callout set the next step to SKIP.

Logged at debug log level 40. This debug message is printed when a callout installed on buffer4\_send hook point set the next step to SKIP. For this particular hook point, the SKIP value set by a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be send to the client.

#### 8.67 DHCP4\_HOOK\_DDNS\_UPDATE

A hook has updated the DDNS parameters: hostname %1=>%2, forward update %3=>%4, reverse\_  $_{\!\!\!\!\!-}$  update %5=>%6

Logged at debug log level 15. This message indicates that there was a hook called on ddns4\_update hook point and that hook updated the DDNS update parameters: hostname, or whether to conduct forward (A record) or reverse (PTR record) DDNS updates.

## 8.68 DHCP4\_HOOK\_DECLINE\_SKIP

Decline4 hook callouts set status to DROP, ignoring packet.

Logged at debug log level 15. This message indicates that the server received DHCPDECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for decline4 hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

## 8.69 DHCP4\_HOOK\_LEASE4\_OFFER\_ARGUMENT\_MISSING

hook callouts did not set an argument as expected %1 for %2

This error message is printed when none of the callouts installed on the lease4\_offer hook point set an expected argument in the callout status. This is a programming error in the installed hook libraries. Details of the argument and the query in process at the time are provided log arguments.

## 8.70 DHCP4\_HOOK\_LEASE4\_OFFER\_DROP

%1: packet is dropped, because a callout set the next step to DROP

This debug message is printed when a callout installed on the lease4\_offer hook point sets the next step to DROP.

## 8.71 DHCP4 HOOK LEASE4 OFFER PARK

%1: packet is parked, because a callout set the next step to PARK

This debug message is printed when a callout installed on the lease4\_offer hook point sets the next step to PARK.

# 8.72 DHCP4\_HOOK\_LEASE4\_OFFER\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. ping-check) that implement the "lease4\_offer" callout and client queries are arriving faster than those callouts can fulfill them.

#### 8.73 DHCP4\_HOOK\_LEASE4\_RELEASE\_SKIP

%1: lease was not released because a callout set the next step to SKIP

Logged at debug log level 15. This debug message is printed when a callout installed on lease4\_release hook point set the next step status to SKIP. For this particular hook point, the value set by a callout instructs the server to not release a lease.

## 8.74 DHCP4\_HOOK\_LEASES4\_COMMITTED\_DROP

%1: packet is dropped, because a callout set the next step to DROP

This debug message is printed when a callout installed on the leases4\_committed hook point sets the next step to DROP.

## 8.75 DHCP4\_HOOK\_LEASES4\_COMMITTED\_PARK

%1: packet is parked, because a callout set the next step to PARK

This debug message is printed when a callout installed on the leases4\_committed hook point sets the next step to PARK.

## 8.76 DHCP4\_HOOK\_LEASES4\_COMMITTED\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when keadhcp4 is using hook libraries (e.g. HA) that implement the "leases4-committed" callout and client queries are arriving faster than those callouts can fulfill them.

#### 8.77 DHCP4 HOOK PACKET RCVD SKIP

%1: packet is dropped, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt4\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting of the flag instructs the server to drop the packet.

#### 8.78 DHCP4 HOOK PACKET SEND DROP

%1: prepared DHCPv4 response was not sent because a callout set the next ste to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the pkt4\_send hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

# 8.79 DHCP4\_HOOK\_PACKET\_SEND\_SKIP

%1: prepared response is not sent, because a callout set the next stp to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt4\_send hook point sets the next step to SKIP. For this particular hook point, this setting instructs the server to drop the packet. This means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease).

## 8.80 DHCP4\_HOOK\_SUBNET4\_SELECT\_406\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet4\_select" callout and DHCP4O6 client queries are arriving faster than those callouts can fulfill them.

## 8.81 DHCP4\_HOOK\_SUBNET4\_SELECT\_DROP

%1: packet was dropped, because a callout set the next step to 'drop'

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

#### 8.82 DHCP4 HOOK SUBNET4 SELECT PARK

%1: packet was parked

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point set the park flag. The argument holds the client and transaction identification information.

#### 8.83 DHCP4\_HOOK\_SUBNET4\_SELECT\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet4\_select" callout and client queries are arriving faster than those callouts can fulfill them.

# 8.84 DHCP4\_HOOK\_SUBNET4\_SELECT\_SKIP

%1: no subnet was selected, because a callout set the next skip flag

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

# 8.85 DHCP4\_HOOK\_SUBNET6\_SELECT\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet6\_select" callout and client queries are arriving faster than those callouts can fulfill them.

#### 8.86 DHCP4\_INFORM\_DIRECT\_REPLY

%1: DHCPACK in reply to the DHCPINFORM will be sent directly to %2 over %3

Logged at debug log level 50. This debug message is issued when the DHCPACK will be sent directly to the client, rather than via a relay. The first argument contains the client and transaction identification information. The second argument contains the client's IPv4 address to which the response will be sent. The third argument contains the local interface name.

## 8.87 DHCP4\_INIT\_FAIL

failed to initialize Kea server: %1

The server has failed to initialize. This may be because the configuration was not successful, or it encountered any other critical error on startup. Attached error message provides more details about the issue.

#### 8.88 DHCP4\_INIT\_REBOOT

%1: client is in INIT-REBOOT state and requests address %2

This informational message is issued when the client is in the INIT-REBOOT state and is requesting an IPv4 address it is using to be allocated for it. The first argument includes the client and transaction identification information. The second argument specifies the requested IPv4 address.

# 8.89 DHCP4\_LEASE\_ALLOC

%1: lease %2 has been allocated for %3 seconds

This informational message indicates that the server successfully granted a lease in response to client's DHCPRE-QUEST message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address. The third argument is the validity lifetime.

## 8.90 DHCP4\_LEASE\_OFFER

%1: lease %2 will be offered

This informational message indicates that the server has found the lease to be offered to the client. It is up to the client to choose one server out of those which offered leases and continue allocation with that server. The first argument specifies the client and the transaction identification information. The second argument specifies the IPv4 address to be offered.

## 8.91 DHCP4\_LEASE\_REUSE

%1: lease %2 has been reused for %3 seconds

This informational message indicates that the server successfully reused a lease in response to client's message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address. The third argument is the validity lifetime.

#### 8.92 DHCP4 MULTI THREADING INFO

enabled: %1, number of threads: %2, queue size: %3

This is a message listing some information about the multi-threading parameters with which the server is running.

#### 8.93 DHCP4 NCR CREATION FAILED

%1: failed to generate name change requests for DNS: %2

This message indicates that server was unable to generate NameChangeRequests which should be sent to the keadhcp\_ddns module to create new DNS records for the lease being acquired or to update existing records for the renewed lease. The first argument contains the client and transaction identification information. The second argument includes the reason for the failure.

## 8.94 DHCP4 NOT RUNNING

DHCPv4 server is not running

A warning message is issued when an attempt is made to shut down the DHCPv4 server but it is not running.

# 8.95 DHCP4\_NO\_LEASE\_INIT\_REBOOT

%1: no lease for address %2 requested by INIT-REBOOT client

Logged at debug log level 50. This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address but this client is unknown. The server will not respond. The first argument includes the client and the transaction id identification information. The second argument includes the IPv4 address requested by the client.

## 8.96 DHCP4 OPEN SOCKET

opening service sockets on port %1

Logged at debug log level 0. A debug message issued during startup, this indicates that the DHCPv4 server is about to open sockets on the specified port.

#### 8.97 DHCP4\_OPEN\_SOCKETS\_FAILED

maximum number of open service sockets attempts: %1, has been exhausted without success

This error indicates that the server failed to bind service sockets after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration.

#### 8.98 DHCP4 OPEN SOCKETS NO RECONNECT CTL

unexpected error in bind service sockets.

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to bind to its service sockets if they are unavailable, and the server exits. This error should be reported.

#### 8.99 DHCP4\_PACKET\_DROP\_0001

%1: failed to parse packet from %2 to %3, received over interface %4, reason: %5, %6

Logged at debug log level 15. The DHCPv4 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

# 8.100 DHCP4\_PACKET\_DROP\_0002

%1, from interface %2: no suitable subnet configured for a direct client

Logged at debug log level 15. This info message is logged when received a message from a directly connected client but there is no suitable subnet configured for the interface on which this message has been received. The IPv4 address assigned on this interface must belong to one of the configured subnets. Otherwise received message is dropped.

#### 8.101 DHCP4\_PACKET\_DROP\_0003

#### %1, from interface %2: it contains a foreign server identifier

Logged at debug log level 15. This debug message is issued when received DHCPv4 message is dropped because it is addressed to a different server, i.e. a server identifier held by this message doesn't match the identifier used by our server. The arguments of this message hold the name of the transaction id and interface on which the message has been received.

#### 8.102 DHCP4 PACKET DROP 0004

#### %1, from interface %2: missing msg-type option

Logged at debug log level 15. This is a debug message informing that incoming DHCPv4 packet did not have mandatory DHCP message type option and thus was dropped. The arguments specify the client and transaction identification information, as well as the interface on which the message has been received.

#### 8.103 DHCP4 PACKET DROP 0005

#### %1: unrecognized type %2 in option 53

Logged at debug log level 15. This debug message indicates that the message type carried in DHCPv4 option 53 is unrecognized by the server. The valid message types are listed on the IANA website: http://www.iana.org/assignments/bootp-dhcp-parameters/bootp-dhcp-parameters.xhtml#message-type-53. The message will not be processed by the server. The arguments specify the client and transaction identification information, as well as the received message type.

## 8.104 DHCP4\_PACKET\_DROP\_0006

#### %1: unsupported DHCPv4 message type %2

Logged at debug log level 15. This debug message indicates that the message type carried in DHCPv4 option 53 is valid but the message will not be processed by the server. This includes messages being normally sent by the server to the client, such as DHCPOFFER, DHCPACK, DHCPNAK etc. The first argument specifies the client and transaction identification information. The second argument specifies the message type.

## 8.105 DHCP4\_PACKET\_DROP\_0007

#### %1: failed to process packet: %2

Logged at debug log level 15. This is a general catch-all message indicating that the processing of a received packet failed. The reason is given in the message. The server will not send a response but will instead ignore the packet. The first argument contains the client and transaction identification information. The second argument includes the details of the error.

#### 8.106 DHCP4 PACKET DROP 0008

%1: DHCP service is globally disabled

Logged at debug log level 15. This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

#### 8.107 DHCP4 PACKET DROP 0009

%1: Option 53 missing (no DHCP message type), is this a BOOTP packet?

Logged at debug log level 15. This debug message is issued when a packet is dropped because it did contain option 53 and thus has no DHCP message type. The most likely explanation is that it was BOOTP packet.

#### 8.108 DHCP4\_PACKET\_DROP\_0010

dropped as member of the special class 'DROP': %1, %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'DROP' and dropped. The packet details are displayed.

## 8.109 DHCP4\_PACKET\_DROP\_0011

dropped as sent by the same client than a packet being processed by another thread: 
→dropped %1, %2 by thread %3 as duplicate of %4, %5 processed by %6

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by a client using the same client id option by dropping new packets until processing is finished. Packet details and thread identifiers are included for both packets in this warning message.

## 8.110 DHCP4\_PACKET\_DROP\_0012

dropped as sent by the same client than a packet being processed by another thread: ⊸dropped %1, %2 by thread %3 as duplicate of %4, %5 processed by %6

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by a client using the same hardware address by dropping new packets until processing is finished. Packet details and thread identifiers are included for both packets in this warning message.

## 8.111 DHCP4 PACKET DROP 0013

dropped as member of the special class 'DROP' after host reservation lookup: %1, %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after host reservation lookup into the special class 'DROP' and dropped. The packet details are displayed.

#### 8.112 DHCP4\_PACKET\_DROP\_0014

dropped as member of the special class 'DROP' after early global host reservations →lookup: %1, %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after early global host reservations lookup into the special class 'DROP' and dropped. The packet details are displayed.

#### 8.113 DHCP4\_PACKET\_NAK\_0001

%1: failed to select a subnet for incoming packet, src %2, type %3

This error message is output when a packet was received from a subnet for which the DHCPv4 server has not been configured. The most probable cause is a misconfiguration of the server. The first argument contains the client and transaction identification information. The second argument contains the source IPv4 address of the packet. The third argument contains the name of the received packet.

## 8.114 DHCP4 PACKET NAK 0002

%1: invalid address %2 requested by INIT-REBOOT

Logged at debug log level 50. This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address which is not assigned to him. The server will respond to this client with DHCPNAK. The first argument contains the client and the transaction identification information. The second arguments holds the IPv4 address requested by the client.

# 8.115 DHCP4\_PACKET\_NAK\_0003

%1: failed to advertise a lease, client sent ciaddr %2, requested-ip-address %3

Logged at debug log level 50. This message indicates that the server has failed to offer a lease to the specified client after receiving a DISCOVER message from it. There are many possible reasons for such a failure. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

#### 8.116 DHCP4 PACKET NAK 0004

%1: failed to grant a lease, client sent ciaddr %2, requested-ip-address %3

Logged at debug log level 50. This message indicates that the server failed to grant a lease to the specified client after receiving a REQUEST message from it. There are many possible reasons for such a failure. Additional messages will indicate the reason. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

## 8.117 DHCP4\_PACKET\_OPTIONS\_SKIPPED

%1: An error unpacking an option, caused subsequent options to be skipped: %2

Logged at debug log level 50. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

#### 8.118 DHCP4 PACKET PACK

%1: preparing on-wire format of the packet to be sent

Logged at debug log level 50. This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

# 8.119 DHCP4\_PACKET\_PACK\_FAIL

%1: preparing on-wire-format of the packet to be sent failed %2

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the DHCP transaction. The second argument includes the error string.

# 8.120 DHCP4\_PACKET\_PROCESS\_EXCEPTION

%1: exception occurred during packet processing

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

## 8.121 DHCP4 PACKET PROCESS EXCEPTION MAIN

exception occurred during packet processing

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

# 8.122 DHCP4\_PACKET\_PROCESS STD EXCEPTION

%1: exception occurred during packet processing: %2

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

# 8.123 DHCP4\_PACKET\_PROCESS\_STD\_EXCEPTION\_MAIN

exception occurred during packet processing: %1

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

## 8.124 DHCP4\_PACKET\_QUEUE\_FULL

multi-threading packet queue is full

Logged at debug log level 40. A debug message noting that the multi-threading packet queue is full so the oldest packet of the queue was dropped to make room for the received one.

# 8.125 DHCP4\_PACKET\_RECEIVED

%1: %2 (type %3) received from %4 to %5 on interface %6

An INFO message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv4 message and its numeric type respectively. The remaining arguments specify the source IPv4 address, destination IPv4 address and the name of the interface on which the message has been received.

#### 8.126 DHCP4\_PACKET\_SEND

%1: trying to send packet %2 (type %3) from %4:%5 to %6:%7 on interface %8

An INFO message noting that the server is attempting to send the specified type of packet. The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv4 address and port, destination IPv4 address and port and the interface name. This debug message is issued when the server is trying to send the response to the client. When the server is using an UDP socket to send the packet there are cases when this operation may be unsuccessful and no error message will be displayed. One such situation occurs when the server is unicasting the response to the 'ciaddr' of a DHCPINFORM message. This often requires broadcasting an ARP message to obtain the link layer address of the unicast destination. If broadcast ARP messages are blocked in the network, according to the firewall policy, the ARP message will not cause a response. Consequently, the response to the DHCPINFORM will not be sent. Since the ARP communication is under the OS control, Kea is not notified about the drop of the packet which it is trying to send and it has no means to display an error message.

# 8.127 DHCP4\_PACKET\_SEND\_FAIL

%1: failed to send DHCPv4 packet: %2

This error is output if the DHCPv4 server fails to send an assembled DHCP message to a client. The first argument includes the client and the transaction identification information. The second argument includes the reason for failure.

#### 8.128 DHCP4 PARSER COMMIT EXCEPTION

parser failed to commit changes

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

# 8.129 DHCP4\_PARSER\_COMMIT\_FAIL

parser failed to commit changes: %1

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

# 8.130 DHCP4\_PARSER\_EXCEPTION

failed to create or run parser for configuration element %1

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

## 8.131 DHCP4\_PARSER\_FAIL

failed to create or run parser for configuration element %1: %2

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

#### 8.132 DHCP4 POST ALLOCATION NAME UPDATE FAIL

%1: failed to update hostname %2 in a lease after address allocation: %3

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server or reserved for the client belonging to a shared network. The latter is the case when the server dynamically switches to another subnet (than initially selected for allocation) from the same shared network.

# 8.133 DHCP4\_QUERY\_DATA

%1, packet details: %2

Logged at debug log level 55. A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

## 8.134 DHCP4\_QUERY\_LABEL

received query: %1

This information message indicates that a query was received. It displays the client and the transaction identification information.

# 8.135 DHCP4\_RECLAIM\_EXPIRED\_LEASES\_FAIL

failed to reclaim expired leases: %1

This error message indicates that the reclaim expired leases operation failed and provides the cause of failure.

## 8.136 DHCP4\_RECOVERED\_STASHED\_RELAY\_AGENT\_INFO

recovered for query %1 relay agent option from lease %2: %3

Logged at debug log level 55. This debug message indicates that agent options were stashed in the lease for the client address of the request and were recovered. The first argument includes the request information, the second the client address and the last argument the content of the dhcp-agent-options option.

#### 8.137 DHCP4 RELEASE

%1: address %2 was released properly.

Logged at debug log level 50. This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

#### 8.138 DHCP4\_RELEASE\_DELETED

%1: address %2 was deleted on release.

This informational message indicates that an address was deleted on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

# 8.139 DHCP4\_RELEASE\_EXCEPTION

%1: while trying to release address %2 an exception occurred: %3

This message is output when an error was encountered during an attempt to process a DHCPRELEASE message. The error will not affect the client, which does not expect any response from the server for DHCPRELEASE messages. Depending on the nature of problem, it may affect future server operation. The first argument includes the client and the transaction identification information. The second argument includes the IPv4 address which release was attempted. The last argument includes the detailed error description.

# 8.140 DHCP4\_RELEASE\_EXPIRED

%1: address %2 expired on release.

This informational message indicates that an address expired on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

#### 8.141 DHCP4\_RELEASE\_FAIL

%1: failed to remove lease for address %2

Logged at debug log level 50. This error message indicates that the software failed to remove a lease from the lease database. It is probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which release was attempted.

### 8.142 DHCP4\_RELEASE\_FAIL\_NO\_LEASE

%1: client is trying to release non-existing lease %2

Logged at debug log level 50. This debug message is printed when client attempts to release a lease, but no such lease is known to the server. The first argument contains the client and transaction identification information. The second argument contains the IPv4 address which the client is trying to release.

### 8.143 DHCP4 RELEASE FAIL WRONG CLIENT

%1: client is trying to release the lease %2 which belongs to a different client

Logged at debug log level 50. This debug message is issued when a client is trying to release the lease for the address which is currently used by another client, i.e. the 'client identifier' or 'chaddr' doesn't match between the client and the lease. The first argument includes the client and the transaction identification information. The second argument specifies the leased address.

## 8.144 DHCP4\_REQUEST

%1: server is processing DHCPREQUEST with hint=%2

Logged at debug log level 50. This is a debug message that indicates the processing of a received DHCPREQUEST message. The first argument contains the client and the transaction identification information. The second argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 8.145 DHCP4\_RESERVATIONS\_LOOKUP\_FIRST\_ENABLED

Multi-threading is enabled and host reservations lookup is always performed first.

This is a message informing that host reservations lookup is performed before lease lookup when multi-threading is enabled overwriting configured value.

### 8.146 DHCP4 RESERVED HOSTNAME ASSIGNED

%1: server assigned reserved hostname %2

Logged at debug log level 55. This debug message is issued when the server found a hostname reservation for a client and uses this reservation in a hostname option sent back to this client. The reserved hostname is qualified with a value of 'ddns-qualifying-suffix' parameter, if this parameter is specified.

#### 8.147 DHCP4 RESPONSE DATA

%1: responding with packet %2 (type %3), packet details: %4

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

### 8.148 DHCP4\_RESPONSE\_FQDN\_DATA

%1: including FQDN option in the server's response: %2

Logged at debug log level 55. This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

## 8.149 DHCP4 RESPONSE HOSTNAME DATA

%1: including Hostname option in the server's response: %2

Logged at debug log level 55. This debug message is issued when the server is adding the Hostname option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the Hostname option may be modified by the server when the lease is acquired for the client.

## 8.150 DHCP4\_RESPONSE\_HOSTNAME\_GENERATE

%1: server has generated hostname %2 for the client

Logged at debug log level 50. This debug message includes the auto-generated hostname which will be used for the client which message is processed. Hostnames may need to be generated when required by the server's configuration or when the client hasn't supplied its hostname. The first argument includes the client and the transaction identification information. The second argument holds the generated hostname.

### 8.151 DHCP4\_SERVER\_FAILED

server failed: %1

The DHCPv4 server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

### 8.152 DHCP4\_SERVER\_INITIATED\_DECLINE

%1: Lease for addr %2 has been found to be already in use. The lease will be unavailable →for %3 seconds.

This informational message is printed when the server has detected via ICMP ECHO (i.e. ping check) or other means that a lease which should be free to offer is actually in use. This message may indicate a misconfiguration in a network or more likely a device that is using an address that it is not supposed to use. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

#### 8.153 DHCP4\_SERVER\_INITIATED\_DECLINE\_ADD\_FAILED

%1: error adding a lease for address %2

This error message indicates that the server failed to add a DECLINED lease to the lease store. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

## 8.154 DHCP4\_SERVER\_INITIATED\_DECLINE\_RESOURCE\_BUSY

%1: error declining a lease for address %2

This error message indicates that while one server thread was attempting to mark a lease as DECLINED, it was already locked by another thread. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

## 8.155 DHCP4\_SERVER\_INITIATED\_DECLINE\_UPDATE\_FAILED

%1: error updating lease for address %2

This error message indicates that the server failed to update a lease in the lease store to the DECLINED state. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

### 8.156 DHCP4 SHUTDOWN

server shutdown

Logged at debug log level 40. The DHCPv4 server has terminated normally.

#### 8.157 DHCP4\_SHUTDOWN\_REQUEST

shutdown of server requested

Logged at debug log level 40. This debug message indicates that a shutdown of the DHCPv4 server has been requested via a call to the 'shutdown' method of the core Dhcpv4Srv object.

### 8.158 DHCP4\_SRV\_CONSTRUCT\_ERROR

error creating Dhcpv4Srv object, reason: %1

This error message indicates that during startup, the construction of a core component within the DHCPv4 server (the Dhcpv4 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

### 8.159 DHCP4 SRV D2STOP ERROR

error stopping IO with DHCP\_DDNS during shutdown: %1

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

## 8.160 DHCP4 SRV DHCP4O6 ERROR

error stopping IO with DHCPv4o6 during shutdown: %1

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCPv4o6 server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

### 8.161 DHCP4\_SRV\_UNLOAD\_LIBRARIES\_ERROR

error unloading hooks libraries during shutdown: %1

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

#### 8.162 DHCP4 STARTED

Kea DHCPv4 server version %1 started

This informational message indicates that the DHCPv4 server has processed all configuration information and is ready to process DHCPv4 packets. The version is also printed.

#### 8.163 DHCP4\_STARTING

Kea DHCPv4 server version %1 (%2) starting

This informational message indicates that the DHCPv4 server has processed any command-line switches and is starting. The version is also printed.

## 8.164 DHCP4\_START\_INFO

pid: %1, server port: %2, client port: %3, verbose: %4

Logged at debug log level 0. This is a debug message issued during the DHCPv4 server startup. It lists some information about the parameters with which the server is running.

## 8.165 DHCP4\_SUBNET\_DATA

%1: the selected subnet details: %2

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

## 8.166 DHCP4\_SUBNET\_DYNAMICALLY\_CHANGED

%1: changed selected subnet %2 to subnet %3 from shared network %4 for client assignments

Logged at debug log level 45. This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

### 8.167 DHCP4 SUBNET SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

#### 8.168 DHCP4 SUBNET SELECTION FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

## 8.169 DHCP4 TESTING MODE SEND TO SOURCE ENABLED

All packets will be send to source address of an incoming packet - use only for testing

This message is printed then KEA\_TEST\_SEND\_RESPONSES\_TO\_SOURCE environment variable is set. It's causing Kea to send packets to source address of incoming packet. Usable just in testing environment to simulate multiple subnet traffic from single source.

# 8.170 DHCP4\_UNKNOWN\_ADDRESS\_REQUESTED

%1: client requested an unknown address, client sent ciaddr %2, requested-ip-address %3

Logged at debug log level 50. This message indicates that the client requested an address that does not belong to any dynamic pools managed by this server. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

# 8.171 DHCP4\_V6\_ONLY\_PREFERRED\_MISSING\_IN\_ACK

v6-only-preferred option missing in 0.0.0.0 reply to query: %1

An DHCPACK for the 0.0.0.0 address was generated for a client requesting the v6-only-preferred (108) option but the option is not in the response as expected: the erroneous response is dropped, the request query is displayed.

**CHAPTER** 

NINE

#### DHCP6

### 9.1 DHCP6\_ADDITIONAL\_CLASS\_EVAL\_ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating the expression of an additional client class. A description of the problem is printed.

#### 9.2 DHCP6 ADDITIONAL CLASS EVAL RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of an additional client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 9.3 DHCP6\_ADDITIONAL\_CLASS\_NO\_TEST

additional class %1 has no test expression, adding it to client's classes unconditionally

Logged at debug log level 40. This debug message informs that a class was listed for additional evaluation but its definition does not include a test expression to evaluate. The class is unconditionally added to the query.

## 9.4 DHCP6\_ADDITIONAL\_CLASS\_UNDEFINED

additional class %1 has no definition

Logged at debug log level 40. This debug message informs that a class is listed for additional evaluation but has no definition. The class is ignored.

## 9.5 DHCP6\_ADD\_GLOBAL\_STATUS\_CODE

%1: adding Status Code to DHCPv6 packet: %2

Logged at debug log level 50. This message is logged when the server is adding the top-level Status Code option. The first argument includes the client and the transaction identification information. The second argument includes the details of the status code.

#### 9.6 DHCP6 ADD STATUS CODE FOR IA

%1: adding Status Code to IA with iaid=%2: %3

Logged at debug log level 50. This message is logged when the server is adding the Status Code option to an IA. The first argument includes the client and the transaction identification information. The second argument specifies the IAID. The third argument includes the details of the status code.

#### 9.7 DHCP6\_ALREADY\_RUNNING

%1 already running? %2

This is an error message that occurs when the DHCPv6 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv6 process name, the second contains the PID and PID file

## 9.8 DHCP6\_BUFFER\_RECEIVED

received buffer from %1:%2 to %3:%4 over interface %5

Logged at debug log level 40. This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination addresses/ports.

## 9.9 DHCP6\_BUFFER\_UNPACK

parsing buffer received from %1 to %2 over interface %3

Logged at debug log level 50. This debug message is issued when the server starts parsing the received buffer holding the DHCPv6 message. The arguments specify the source and destination addresses as well as the interface over which the buffer has been received.

#### 9.10 DHCP6 BUFFER WAIT SIGNAL

signal received while waiting for next packet

Logged at debug log level 50. This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets.

#### 9.11 DHCP6 CB ON DEMAND FETCH UPDATES FAIL

error on demand attempt to fetch configuration updates from the configuration.

→backend(s): %1

This error message is issued when the server attempted to fetch configuration updates from the database and this on demand attempt failed. The sole argument which is returned to the config-backend-pull command caller too contains the reason for failure.

#### 9.12 DHCP6 CB PERIODIC FETCH UPDATES FAIL

error on periodic attempt to fetch configuration updates from the configuration.

→backend(s): %1

This error message is issued when the server attempted to fetch configuration updates from the database and this periodic attempt failed. The server will re-try according to the configured value of the config-fetch-wait-time parameter. The sole argument contains the reason for failure.

## 9.13 DHCP6 CB PERIODIC FETCH UPDATES RETRIES EXHAUSTED

maximum number of configuration fetch attempts: 10, has been exhausted without success

This error indicates that the server has made a number of unsuccessful periodic attempts to fetch configuration updates from a configuration backend. The server will continue to operate but won't make any further attempts to fetch configuration updates. The administrator must fix the configuration in the database and reload (or restart) the server.

## 9.14 DHCP6\_CLASSES\_ASSIGNED

%1: client packet has been assigned on %2 message to the following classes: %3

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument specifies the DHCPv6 message type. The third argument includes all classes to which the packet has been assigned.

## 9.15 DHCP6\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION

%1: client packet has been assigned to the following classes: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

#### 9.16 DHCP6 CLASS ASSIGNED

%1: client packet has been assigned to the following class: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified class. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes the new class to which the packet has been assigned.

### 9.17 DHCP6\_CLASS\_UNCONFIGURED

%1: client packet belongs to an unconfigured class: %2

Logged at debug log level 40. This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

## 9.18 DHCP6 CONFIG COMPLETE

DHCPv6 server has completed configuration: %1

This is an informational message announcing the successful processing of a new configuration. it is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

## 9.19 DHCP6\_CONFIG\_LOAD\_FAIL

configuration error using file: %1, reason: %2

This error message indicates that the DHCPv6 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

## 9.20 DHCP6\_CONFIG\_PACKET\_QUEUE

DHCPv6 packet queue info after configuration: %1

This informational message is emitted during DHCPv6 server configuration, immediately after configuring the DHCPv6 packet queue. The information shown depends upon the packet queue type selected.

#### 9.21 DHCP6\_CONFIG\_RECEIVED

received configuration: %1

Logged at debug log level 10. A debug message listing the configuration received by the DHCPv6 server. The source of that configuration depends on used configuration backend.

### 9.22 DHCP6 CONFIG START

DHCPv6 server is processing the following configuration: %1

Logged at debug log level 10. This is a debug message that is issued every time the server receives a configuration. That happens start up and also when a server configuration change is committed by the administrator.

### 9.23 DHCP6\_CONFIG\_SYNTAX\_WARNING

configuration syntax warning: %1

This warning message indicates that the DHCPv6 configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 9.24 DHCP6\_CONFIG\_UNRECOVERABLE\_ERROR

DHCPv6 server new configuration failed with an error which cannot be recovered

This fatal error message is issued when a new configuration raised an error which cannot be recovered. A correct configuration must be applied as soon as possible as the server is no longer working. The configuration can be fixed in several ways. If the control channel is open, config-set with a valid configuration can be used. Alternatively, the original config file on disk could be fixed and SIGHUP signal could be sent (or the config-reload command issued). Finally, the server could be restarted completely.

## 9.25 DHCP6\_CONFIG\_UNSUPPORTED\_OBJECT

DHCPv6 server configuration includes an unsupported object: %1

This error message is issued when the configuration includes an unsupported object (i.e. a top level element).

#### 9.26 DHCP6\_DB\_RECONNECT\_DISABLED

database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

#### 9.27 DHCP6 DB RECONNECT FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

### 9.28 DHCP6\_DB\_RECONNECT\_LOST\_CONNECTION

database connection lost.

This info message indicates that the connection has been lost and the dhcp service might have been disabled, as specified in the configuration, in order to try to recover the connection.

## 9.29 DHCP6 DB RECONNECT NO DB CTL

unexpected error in database reconnect

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to reconnect to its databases if connectivity is lost, and the server exits. This error should be reported.

## 9.30 DHCP6\_DB\_RECONNECT\_SUCCEEDED

database connection recovered.

This info message indicates that the connection has been recovered and the dhcp service has been restored.

## 9.31 DHCP6\_DDNS\_CREATE\_ADD\_NAME\_CHANGE\_REQUEST

%1: created name change request: %2

Logged at debug log level 50. This debug message is logged when the new NameChangeRequest has been created to perform the DNS Update, which adds new RRs.

### 9.32 DHCP6\_DDNS\_FQDN\_GENERATED

%1: generated FQDN for the client: %2

Logged at debug log level 55. This debug message is logged when the server generated FQDN (name) for the client which message is processed. The names may be generated by the server when required by the server's policy or when the client doesn't provide any specific FQDN in its message to the server. The first argument includes the client and transaction identification information. The second argument includes the generated FQDN.

### 9.33 DHCP6\_DDNS\_GENERATED\_FQDN\_UPDATE\_FAIL

%1: failed to update the lease using address %2, after generating FQDN for a client, □ → reason: %3

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server from the acquired address. The first argument includes the client and the transaction identification information. The second argument is a leased address. The third argument includes the reason for the failure.

## 9.34 DHCP6 DDNS GENERATE FQDN

%1: client did not send a FQDN option; FQDN will be

Logged at debug log level 50. generated for the client. This debug message is issued when the server did not receive a FQDN option from the client and client name replacement is enabled. This provides a means to create DNS entries for unsophisticated clients.

## 9.35 DHCP6\_DDNS\_RECEIVE\_FQDN

%1: received DHCPv6 Client FQDN option: %2

Logged at debug log level 50. This debug message is logged when server has found the DHCPv6 Client FQDN Option sent by a client and started processing it. The first argument includes the client and transaction identification information. The second argument includes the received FQDN.

### 9.36 DHCP6 DDNS REMOVE OLD LEASE FQDN

%1: FQDN for a lease: %2 has changed. New values: hostname = %3, reverse mapping = %4,  $_{\odot}$  forward mapping = %5

Logged at debug log level 50. This debug message is logged during lease renewal when an old lease that is no longer being offered has a different FQDN than the renewing lease. Thus the old DNS entries need to be removed. The first argument includes the client and the transaction identification information. The second argument holds the details about the lease for which the FQDN information and/or mappings have changed. The remaining arguments hold the new FQDN information and flags for mappings.

### 9.37 DHCP6 DDNS REQUEST SEND FAILED

```
failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2
```

This error message indicates that IPv6 DHCP server failed to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

#### 9.38 DHCP6\_DDNS\_RESPONSE\_FQDN\_DATA

```
%1: including FQDN option in the server's response: %2
```

Logged at debug log level 50. This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

## 9.39 DHCP6\_DECLINE\_FAIL

```
%1: error on decline lease for address %2: %3
```

This error message indicates that the software failed to decline a lease from the lease database due to an error during a database operation. The first argument includes the client and the transaction identification information. The second argument holds the IPv6 address which decline was attempted. The last one contains the reason for failure.

## 9.40 DHCP6\_DECLINE\_FAIL\_DUID\_MISMATCH

```
Client %1 sent DECLINE for address %2, but it belongs to client with DUID %3
```

This informational message is printed when a client attempts to decline a lease, but that lease belongs to a different client. The decline request will be rejected.

## 9.41 DHCP6\_DECLINE\_FAIL\_IAID\_MISMATCH

Client %1 sent DECLINE for address %2, but used a wrong IAID (%3), instead of expected %4

This informational message is printed when a client attempts to decline a lease. The server has a lease for this address, it belongs to this client, but the recorded IAID does not match what client has sent. This means the server will reject this Decline.

#### 9.42 DHCP6 DECLINE FAIL LEASE WITHOUT DUID

Client %1 sent DECLINE for address %2, but the associated lease has no DUID

This error condition likely indicates database corruption, as every IPv6 lease is supposed to have a DUID, even if it is an empty one.

#### 9.43 DHCP6\_DECLINE\_FAIL\_NO\_LEASE

Client %1 sent DECLINE for address %2, but there's no lease for it

This informational message is printed when a client tried to decline an address, but the server has no lease for said address. This means that the server's and client's perception of the leases are different. The likely causes of this could be: a confused (e.g. skewed clock) or broken client (e.g. client moved to a different location and didn't notice) or possibly an attack (a rogue client is trying to decline random addresses). The server will inform the client that his decline request was rejected and client should be able to recover from that.

## 9.44 DHCP6 DECLINE LEASE

Client %1 sent DECLINE for address %2 and the server marked it as declined. The lease... will be recovered in %3 seconds.

This informational message indicates that the client leased an address, but discovered that it is being used by some other device and reported this to the server by sending a Decline message. The server marked the lease as declined. This likely indicates a misconfiguration in the network. Either the server is configured with an incorrect pool or there are devices that have statically assigned addresses that are supposed to be assigned by the DHCP server. Both client (will request a different address) and server (will recover the lease after decline-probation-time elapses) will recover automatically. However, if the underlying problem is not solved, the conditions leading to this message may reappear.

## 9.45 DHCP6\_DECLINE\_PROCESS\_IA

Processing of IA (IAID: %1) from client %2 started.

Logged at debug log level 50. This debug message is printed when the server starts processing an IA\_NA option received in Decline message. It's expected that the option will contain an address that is being declined. Specific information will be printed in a separate message.

## 9.46 DHCP6\_DEVELOPMENT\_VERSION

This software is a development branch of Kea. It is not recommended for production use.

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

#### 9.47 DHCP6\_DHCP4O6\_PACKET\_RECEIVED

received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 port %3 on interface %4

Logged at debug log level 40. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

### 9.48 DHCP6 DHCP4O6 RECEIVE FAIL

failed to receive DHCPv4o6: %1

Logged at debug log level 50. This debug message indicates the inter-process communication with the DHCPv4 server failed. The reason for the error is included in the message.

#### 9.49 DHCP6\_DHCP4O6\_RECEIVING

receiving DHCPv4o6 packet from DHCPv4 server

Logged at debug log level 50. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication socket.

## 9.50 DHCP6\_DHCP4O6\_RESPONSE\_DATA

%1: responding with packet %2 (type %3), packet details: %4

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

## 9.51 DHCP6\_DHCP4O6\_SEND\_FAIL

%1: failed to send DHCPv4o6 packet: %2

This error is output if the IPv6 DHCP server fails to send an assembled DHCPv4o6 message to a client. The reason for the error is included in the message.

### 9.52 DHCP6\_DYNAMIC\_RECONFIGURATION

initiate server reconfiguration using file: %1, after receiving SIGHUP signal or config-→reload command

This is the info message logged when the DHCPv6 server starts reconfiguration as a result of receiving SIGHUP signal or config-reload command.

#### 9.53 DHCP6\_DYNAMIC\_RECONFIGURATION\_FAIL

dynamic server reconfiguration failed with file: %1

This is a fatal error message logged when the dynamic reconfiguration of the DHCP server failed.

#### 9.54 DHCP6\_DYNAMIC\_RECONFIGURATION\_SUCCESS

dynamic server reconfiguration succeeded with file: %1

This is info message logged when the dynamic reconfiguration of the DHCP server succeeded.

## 9.55 DHCP6 FLEX ID

%1: flexible identifier generated for incoming packet: %2

Logged at debug log level 40. This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

## 9.56 DHCP6\_HOOK\_BUFFER\_RCVD\_DROP

received buffer from %1 to %2 over interface %3 was dropped because a callout set the drop flag

Logged at debug log level 15. This debug message is printed when a callout installed on buffer6\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

### 9.57 DHCP6 HOOK BUFFER RCVD SKIP

Logged at debug log level 50. This debug message is printed when a callout installed on buffer6\_receive hook point set the next step status to skip. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

## 9.58 DHCP6\_HOOK\_BUFFER\_SEND\_SKIP

%1: prepared DHCPv6 response was dropped because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on buffer6\_send hook point set the next step to SKIP value. For this particular hook point, the SKIP setting a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be send to the client. The argument includes the client and transaction identification information.

#### 9.59 DHCP6\_HOOK\_DDNS\_UPDATE

A hook has updated the DDNS parameters: hostname %1=>%2, forward update %3=>%4, reverse\_  $_{\hookrightarrow}$  update %5=>%6

Logged at debug log level 15. This message indicates that there was a hook called on ddns6\_update hook point and that hook updated the DDNS update parameters: hostname, or whether to conduct forward (A record) or reverse (PTR record) DDNS updates.

## 9.60 DHCP6\_HOOK\_DECLINE\_DROP

During Decline processing (client=%1, interface=%2, addr=%3) hook callout set next step → to DROP, dropping packet.

Logged at debug log level 15. This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

## 9.61 DHCP6\_HOOK\_DECLINE\_SKIP

During Decline processing (client=%1, interface=%2, addr=%3) hook callout set status to 
→SKIP, skipping decline.

Logged at debug log level 50. This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to SKIP. The server will skip the operation of moving the lease to the declined state and will continue processing the packet. In particular, it will send a REPLY message as if the decline actually took place.

#### 9.62 DHCP6\_HOOK\_LEASE6\_RELEASE\_NA\_SKIP

%1: DHCPv6 address lease was not released because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the lease6\_release hook point set the next step to SKIP. For this particular hook point, this setting by a callout instructs the server to not release a lease. If a client requested the release of multiples leases (by sending multiple IA options), the server will retain this particular lease and proceed with other releases as usual. The argument holds the client and transaction identification information.

#### 9.63 DHCP6 HOOK LEASE6 RELEASE PD SKIP

%1: prefix lease was not released because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_release hook point set the next step to SKIP value. For this particular hook point, that setting by a callout instructs the server to not release a lease. If client requested release of multiples leases (by sending multiple IA options), the server will retains this particular lease and will proceed with other renewals as usual. The argument holds the client and transaction identification information.

## 9.64 DHCP6\_HOOK\_LEASES6\_COMMITTED\_DROP

%1: packet is dropped, because a callout set the next step to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the leases6\_committed hook point sets the next step to DROP.

## 9.65 DHCP6\_HOOK\_LEASES6\_COMMITTED\_PARK

%1: packet is parked, because a callout set the next step to PARK

Logged at debug log level 40. This debug message is printed when a callout installed on the leases6\_committed hook point sets the next step to PARK.

## 9.66 DHCP6\_HOOK\_LEASES6\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp6 is using hook libraries (e.g. HA) that implement the "leases6-committed" callout and client queries are arriving faster than those callouts can fulfill them.

### 9.67 DHCP6\_HOOK\_PACKET\_RCVD\_SKIP

%1: packet is dropped, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt6\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting instructs the server to drop the packet.

## 9.68 DHCP6\_HOOK\_PACKET\_SEND\_DROP

%1: prepared DHCPv6 response was not sent because a callout set the next ste to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

## 9.69 DHCP6\_HOOK\_PACKET\_SEND\_SKIP

%1: prepared DHCPv6 response is not built because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to SKIP. For this particular hook point, the setting of the value by a callout instructs the server to not build the wire data (pack) because it was already done by the book. The argument specifies the client and transaction identification information.

## 9.70 DHCP6 HOOK SUBNET6 SELECT DROP

%1: packet was dropped because a callout set the drop flag

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet6\_select hook point set the drop flag. For this particular hook point, the setting of the flag instructs the server to drop the received packet. The argument holds the client and transaction identification information.

## 9.71 DHCP6\_HOOK\_SUBNET6\_SELECT\_PARK

%1: packet was parked

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet6\_select hook point set the park flag. The argument holds the client and transaction identification information.

#### 9.72 DHCP6\_HOOK\_SUBNET6\_SELECT\_SKIP

%1: no subnet was selected because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet6\_select hook point set the next step to SKIP value. For this particular hook point, the setting of this value instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses or prefixes will be assigned. The argument holds the client and transaction identification information.

## 9.73 DHCP6\_INIT\_FAIL

failed to initialize Kea server: %1

The server has failed to establish communication with the rest of Kea, failed to read JSON configuration file or encountered any other critical issue that prevents it from starting up properly. Attached error message provides more details about the issue.

## 9.74 DHCP6 LEASE ADVERT

%1: lease for address %2 and iaid=%3 will be advertised

Logged at debug log level 50. This informational message indicates that the server will advertise an address to the client in the ADVERTISE message. The client will request allocation of this address with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

## 9.75 DHCP6\_LEASE\_ADVERT\_FAIL

%1: failed to advertise an address lease for iaid=%2

Logged at debug log level 50. This message indicates that in response to a received SOLICIT, the server failed to advertise a non-temporary lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

## 9.76 DHCP6\_LEASE\_ALLOC

%1: lease for address %2 and iaid=%3 has been allocated for %4 seconds

Logged at debug log level 50. This informational message indicates that in response to a client's REQUEST message, the server successfully granted a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address, IAID and validity lifetime.

### 9.77 DHCP6\_LEASE\_ALLOC\_FAIL

%1: failed to grant an address lease for iaid=%2

Logged at debug log level 50. This message indicates that in response to a received REQUEST, the server failed to grant a non-temporary address lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

#### 9.78 DHCP6\_LEASE\_DATA

%1: detailed lease information for iaid=%2: %3

Logged at debug log level 55. This debug message is used to print the detailed information about the allocated lease or a lease which will be advertised to the client. The first argument holds the client and the transaction identification information. The second argument holds the IAID. The third argument holds the detailed lease information.

## 9.79 DHCP6\_LEASE\_NA\_WITHOUT\_DUID

%1: address lease for address %2 does not have a DUID

This error message indicates a database consistency problem. The lease database has an entry indicating that the given address is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes the client and transaction identification information. The second argument holds the address to be released.

## 9.80 DHCP6\_LEASE\_PD\_WITHOUT\_DUID

%1: lease for prefix %2/%3 does not have a DUID

This error message indicates a database consistency failure. The lease database has an entry indicating that the given prefix is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes client and transaction identification information. The second and third argument hold the prefix and the prefix length.

## 9.81 DHCP6\_LEASE\_RENEW

%1: lease for address %2 and iaid=%3 has been allocated

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

### 9.82 DHCP6 LEASE REUSE

%1: lease for address %2 and iaid=%3 has been reused for %4 seconds

This informational message indicates that in response to a client's message, the server successfully reused a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address, IAID and validity lifetime.

### 9.83 DHCP6\_MULTI\_THREADING\_INFO

enabled: %1, number of threads: %2, queue size: %3

This is a message listing some information about the multi-threading parameters with which the server is running.

## 9.84 DHCP6\_NOT\_RUNNING

IPv6 DHCP server is not running

A warning message is issued when an attempt is made to shut down the IPv6 DHCP server but it is not running.

## 9.85 DHCP6\_NO\_INTERFACES

failed to detect any network interfaces

During startup the IPv6 DHCP server failed to detect any network interfaces and is therefore shutting down.

### 9.86 DHCP6 OPEN SOCKET

opening service sockets on port %1

Logged at debug log level 0. A debug message issued during startup, this indicates that the IPv6 DHCP server is about to open sockets on the specified port.

#### 9.87 DHCP6\_OPEN\_SOCKETS\_FAILED

maximum number of open service sockets attempts: %1, has been exhausted without success

This error indicates that the server failed to bind service sockets after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration.

### 9.88 DHCP6 OPEN SOCKETS NO RECONNECT CTL

unexpected error in bind service sockets.

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to bind to its service sockets if they are unavailable, and the server exits. This error should be reported.

#### 9.89 DHCP6\_PACKET\_DROP\_DHCP\_DISABLED

%1: DHCP service is globally disabled

Logged at debug log level 15. This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

## 9.90 DHCP6\_PACKET\_DROP\_DROP\_CLASS

dropped as member of the special class 'DROP': %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'DROP' and dropped. The packet details are displayed.

### 9.91 DHCP6 PACKET DROP DROP CLASS2

dropped as member of the special class 'DROP' after host reservation lookup: %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after host reservation lookup into the special class 'DROP' and dropped. The packet details are displayed.

#### 9.92 DHCP6\_PACKET\_DROP\_DROP\_CLASS\_EARLY

dropped as member of the special class 'DROP' after early global host reservations∟ ⇒lookup: %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after early global host reservations lookup into the special class 'DROP' and dropped. The packet details are displayed.

#### 9.93 DHCP6\_PACKET\_DROP\_DUPLICATE

dropped as sent by the same client than a packet being processed by another thread: \_\_\_\_dropped %1 %2 by thread %3 as duplicate of %4 %5 processed by %6

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by the same client by dropping new packets until processing is finished. Packet details and thread identifiers are included for both packets in this warning message.

## 9.94 DHCP6\_PACKET\_DROP\_PARSE\_FAIL

%1: failed to parse packet from %2 to %3, received over interface %4, reason: %5, %6

Logged at debug log level 15. The DHCPv6 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

## 9.95 DHCP6\_PACKET\_DROP\_SERVERID\_MISMATCH

%1: dropping packet with server identifier: %2, server is using: %3

Logged at debug log level 15. A debug message noting that server has received message with server identifier option that not matching server identifier that server is using.

## 9.96 DHCP6\_PACKET\_DROP\_UNICAST

%1: dropping unicast %2 packet as this packet should be sent to multicast

Logged at debug log level 15. This debug message is issued when the server drops the unicast packet, because packets of this type must be sent to multicast. The first argument specifies the client and transaction identification information, the second argument specifies packet type.

#### 9.97 DHCP6 PACKET OPTIONS SKIPPED

%1: An error unpacking an option, caused subsequent options to be skipped: %2

Logged at debug log level 50. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

#### 9.98 DHCP6\_PACKET\_PROCESS\_EXCEPTION

%1: exception occurred during packet processing

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

### 9.99 DHCP6\_PACKET\_PROCESS\_EXCEPTION\_MAIN

exception occurred during packet processing

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

## 9.100 DHCP6\_PACKET\_PROCESS\_FAIL

%1: processing of %2 message received from %3 failed: %4

Logged at debug log level 40. This is a general catch-all message indicating that the processing of the specified packet type from the indicated address failed. The reason is given in the message. The server will not send a response but will instead ignore the packet.

### 9.101 DHCP6 PACKET PROCESS STD EXCEPTION

%1: exception occurred during packet processing: %2

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

#### 9.102 DHCP6\_PACKET\_PROCESS\_STD\_EXCEPTION\_MAIN

exception occurred during packet processing: %1

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

### 9.103 DHCP6\_PACKET\_QUEUE\_FULL

multi-threading packet queue is full

Logged at debug log level 40. A debug message noting that the multi-threading packet queue is full so the oldest packet of the queue was dropped to make room for the received one.

### 9.104 DHCP6\_PACKET\_RECEIVED

%1: %2 (type %3) received from %4 to %5 on interface %6

An INFO message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv6 message and its numeric type respectively. The remaining arguments specify the source address, destination IP address and the name of the interface on which the message has been received.

## 9.105 DHCP6\_PACKET\_RECEIVE\_FAIL

error on attempt to receive packet: %1

The IPv6 DHCP server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

### 9.106 DHCP6 PACKET SEND

%1: trying to send packet %2 (type %3) from [%4]:%5 to [%6]:%7 on interface %8

An INFO message noting that the server is attempting to send the specified type of packet. The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv6 address and port, destination IPv6 address and port and the interface name.

#### 9.107 DHCP6 PACKET SEND FAIL

%1: failed to send DHCPv6 packet: %2

This error is output if the IPv6 DHCP server fails to send an assembled DHCP message to a client. The reason for the error is included in the message.

#### 9.108 DHCP6\_PACK\_FAIL

%1: failed to assemble response correctly: %2

This error is output if the server failed to assemble the data to be returned to the client into a valid packet. The reason is most likely to be to a programming error: please raise a bug report.

## 9.109 DHCP6\_PARSER\_COMMIT\_EXCEPTION

parser failed to commit changes

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

## 9.110 DHCP6\_PARSER\_COMMIT\_FAIL

parser failed to commit changes: %1

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

### 9.111 DHCP6 PARSER EXCEPTION

failed to create or run parser for configuration element %1

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information. The most likely cause of this is that the specification file for the server (which details the allowable contents of the configuration) is not correct for this version of Kea. This may be the result of an interrupted installation of an update to Kea.

### 9.112 DHCP6 PARSER FAIL

failed to create or run parser for configuration element %1: %2

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

### 9.113 DHCP6 PD LEASE ADVERT

%1: lease for prefix %2/%3 and iaid=%4 will be advertised

Logged at debug log level 50. This informational message indicates that the server will advertise a prefix to the client in the ADVERTISE message. The client will request allocation of this prefix with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

## 9.114 DHCP6\_PD\_LEASE\_ADVERT\_FAIL

%1: failed to advertise a prefix lease for iaid=%2

Logged at debug log level 50. This message indicates that in response to a received SOLICIT, the server failed to advertise a prefix lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

## 9.115 DHCP6\_PD\_LEASE\_ALLOC

%1: lease for prefix %2/%3 and iaid=%4 has been allocated for %5 seconds

Logged at debug log level 50. This informational message indicates that in response to a client's REQUEST message, the server successfully granted a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length, IAID and validity lifetime.

#### 9.116 DHCP6 PD LEASE ALLOC FAIL

%1: failed to grant a prefix lease for iaid=%2

Logged at debug log level 50. This message indicates that in response to a received REQUEST, the server failed to grant a prefix lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

### 9.117 DHCP6 PD LEASE RENEW

%1: lease for prefix %2/%3 and iaid=%4 has been allocated

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

#### 9.118 DHCP6 PD LEASE REUSE

%1: lease for prefix %2/%3 and iaid=%4 has been reused for %5 seconds

This informational message indicates that in response to a client's message, the server successfully reused a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length, IAID and validity lifetime.

## 9.119 DHCP6 PROCESS IA NA EXTEND

%1: extending lease lifetime for IA\_NA option with iaid=%2

Logged at debug log level 50. This message is logged when the server is starting to extend the lifetime of the address lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

## 9.120 DHCP6\_PROCESS\_IA\_NA\_RELEASE

%1: releasing lease for IA\_NA option with iaid=%2

Logged at debug log level 50. This message is logged when the server is trying to release the client's as a result of receiving the RELEASE message. The first argument includes the client and transaction identification information. The second argument contains the IAID.

## 9.121 DHCP6\_PROCESS\_IA\_NA\_REQUEST

%1: server is processing IA\_NA option with iaid=%2 and hint=%3

Logged at debug log level 50. This is a debug message that indicates the processing of a received IA\_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

### 9.122 DHCP6\_PROCESS\_IA\_NA\_SOLICIT

%1: server is processing IA\_NA option with iaid=%2 and hint=%3

Logged at debug log level 50. This is a debug message that indicates the processing of a received IA\_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

### 9.123 DHCP6\_PROCESS\_IA\_PD\_EXTEND

%1: extending lease lifetime for IA\_PD option with iaid=%2

Logged at debug log level 50. This message is logged when the server is starting to extend the lifetime of the prefix lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

## 9.124 DHCP6\_PROCESS\_IA\_PD\_REQUEST

%1: server is processing IA\_PD option with iaid=%2 and hint=%3

Logged at debug log level 50. This is a debug message that indicates a processing of received IA\_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 9.125 DHCP6\_PROCESS\_IA\_PD\_SOLICIT

%1: server is processing IA\_PD option with iaid=%2 and hint=%3

Logged at debug log level 50. This is a debug message that indicates a processing of received IA\_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

### 9.126 DHCP6 QUERY DATA

#### %1, packet details: %2

Logged at debug log level 55. A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

## 9.127 DHCP6\_QUERY\_LABEL

#### received query: %1

This information message indicates that a query was received. It displays the client and the transaction identification information.

### 9.128 DHCP6 RAPID COMMIT

%1: Rapid Commit option received, following 2-way exchange

Logged at debug log level 50. This debug message is issued when the server found a Rapid Commit option in the client's message and 2-way exchanges are supported by the server for the subnet on which the client is connected. The argument specifies the client and transaction identification information.

### 9.129 DHCP6\_RECLAIM\_EXPIRED\_LEASES\_FAIL

failed to reclaim expired leases: %1

This error message indicates that the reclaim expired leases operation failed and provides the cause of failure.

## 9.130 DHCP6\_RELEASE\_NA

%1: binding for address %2 and iaid=%3 was released properly

This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

### 9.131 DHCP6 RELEASE NA DELETED

%1: binding for address %2 and iaid=%3 was deleted on release

This informational message indicates that an address was deleted on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

#### 9.132 DHCP6 RELEASE NA EXPIRED

%1: binding for address %2 and iaid=%3 expired on release

This informational message indicates that an address expired on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

## 9.133 DHCP6\_RELEASE\_NA\_FAIL

%1: failed to remove address lease for address %2 and iaid=%3

This error message indicates that the software failed to remove an address lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument holds the client and transaction identification information. The second and third argument hold the released address and IAID respectively.

## 9.134 DHCP6 RELEASE NA FAIL WRONG DUID

%1: client tried to release address %2, but it belongs to another client using duid=%3

This warning message indicates that a client tried to release an address that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the address will stop using it anyway, there is a good chance that the situation will correct itself.

## 9.135 DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_IAID

%1: client tried to release address %2, but it used wrong IAID (expected %3, but got %4)

This warning message indicates that client tried to release an address that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple addresses is flawed.

#### 9.136 DHCP6 RELEASE PD

%1: prefix %2/%3 for iaid=%4 was released properly

This informational message indicates that a prefix was released properly. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

#### 9.137 DHCP6 RELEASE PD DELETED

%1: prefix %2/%3 for iaid=%4 was deleted on release

This informational message indicates that a prefix was deleted on release. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

### 9.138 DHCP6\_RELEASE\_PD\_EXPIRED

%1: prefix %2/%3 for iaid=%4 expired on release

This informational message indicates that a prefix expired on release. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

## 9.139 DHCP6 RELEASE PD FAIL

%1: failed to release prefix %2/%3 for iaid=%4

This error message indicates that the software failed to remove a prefix lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument hold the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds the IAID.

## 9.140 DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_DUID

%1: client tried to release prefix %2/%3, but it belongs to another client (duid=%4)

This warning message indicates that client tried to release a prefix that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the prefix will stop using it anyway, there is a good chance that the situation will correct itself. The first argument includes the client and the transaction identification information. The second and third argument include the prefix and prefix length. The last argument holds the DUID of the client holding the lease.

### 9.141 DHCP6 RELEASE PD FAIL WRONG IAID

%1: client tried to release prefix %2/%3, but it used wrong IAID (expected %4, but got  $\rightarrow$ %5)

This warning message indicates that client tried to release a prefix that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple prefixes is flawed. The first argument includes the client and transaction identification information. The second and third argument identify the prefix. The fourth and fifth argument hold the expected IAID and IAID found respectively.

### 9.142 DHCP6\_REQUIRED\_OPTIONS\_CHECK\_FAIL

%1: %2 message received from %3 failed the following check: %4

Logged at debug log level 40. This message indicates that received DHCPv6 packet is invalid. This may be due to a number of reasons, e.g. the mandatory client-id option is missing, the server-id forbidden in that particular type of message is present, there is more than one instance of client-id or server-id present, etc. The exact reason for rejecting the packet is included in the message.

#### 9.143 DHCP6 RESERVATIONS LOOKUP FIRST ENABLED

Multi-threading is enabled and host reservations lookup is always performed first.

This is a message informing that host reservations lookup is performed before lease lookup when multi-threading is enabled overwriting configured value.

## 9.144 DHCP6\_RESPONSE\_DATA

%1: responding with packet %2 (type %3), packet details: %4

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

## 9.145 DHCP6\_SERVER\_FAILED

server failed: %1

The IPv6 DHCP server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

### 9.146 DHCP6\_SHUTDOWN

server shutdown

Logged at debug log level 40. The IPv6 DHCP server has terminated normally.

#### 9.147 DHCP6 SHUTDOWN REQUEST

shutdown of server requested

Logged at debug log level 40. This debug message indicates that a shutdown of the IPv6 server has been requested via a call to the 'shutdown' method of the core Dhcpv6Srv object.

#### 9.148 DHCP6 SRV CONSTRUCT ERROR

error creating Dhcpv6Srv object, reason: %1

This error message indicates that during startup, the construction of a core component within the IPv6 DHCP server (the Dhcpv6 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

### 9.149 DHCP6\_SRV\_D2STOP\_ERROR

error stopping IO with DHCP\_DDNS during shutdown: %1

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv6 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

### 9.150 DHCP6\_SRV\_UNLOAD\_LIBRARIES\_ERROR

error unloading hooks libraries during shutdown: %1

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

110 Chapter 9. DHCP6

### 9.151 DHCP6\_STARTED

Kea DHCPv6 server version %1 started

This informational message indicates that the IPv6 DHCP server has processed all configuration information and is ready to process DHCPv6 packets. The version is also printed.

#### 9.152 DHCP6\_STARTING

Kea DHCPv6 server version %1 (%2) starting

This informational message indicates that the IPv6 DHCP server has processed any command-line switches and is starting. The version is also printed.

### 9.153 DHCP6 START INFO

pid: %1, server port: %2, client port: %3, verbose: %4

Logged at debug log level 0. This is a debug message issued during the IPv6 DHCP server startup. It lists some information about the parameters with which the server is running.

### 9.154 DHCP6\_SUBNET\_DATA

%1: the selected subnet details: %2

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second argument includes the subnet details.

### 9.155 DHCP6\_SUBNET\_DYNAMICALLY\_CHANGED

%1: changed selected subnet %2 to subnet %3 from shared network %4 for client assignments

Logged at debug log level 45. This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

### 9.156 DHCP6\_SUBNET\_SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

#### 9.157 DHCP6 SUBNET SELECTION FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The cause is likely due to a misconfiguration of the server. The packet processing will continue, but the response will only contain generic configuration and no addresses or prefixes. The argument includes the client and the transaction identification information.

### 9.158 DHCP6\_UNKNOWN\_MSG\_RECEIVED

%1: received unknown message (type %2) on interface %3

Logged at debug log level 40. This debug message is printed when server receives a message of unknown type. That could either mean missing functionality or invalid or broken relay or client. The list of formally defined message types is available here: http://www.iana.org/assignments/dhcpv6-parameters.

112 Chapter 9. DHCP6

**CHAPTER** 

**TEN** 

#### **DHCPSRV**

### 10.1 DHCPSRV CFGMGR ADD IFACE

listening on interface %1

An info message issued when a new interface is being added to the collection of interfaces on which the server listens to DHCP messages.

### 10.2 DHCPSRV\_CFGMGR\_ADD\_SUBNET4

adding subnet %1

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is adding the specified IPv4 subnet to its database.

## 10.3 DHCPSRV CFGMGR ADD SUBNET6

adding subnet %1

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is adding the specified IPv6 subnet to its database.

## 10.4 DHCPSRV\_CFGMGR\_ALL\_IFACES\_ACTIVE

enabling listening on all interfaces

Logged at debug log level 40. A debug message issued when the server is being configured to listen on all interfaces.

### 10.5 DHCPSRV\_CFGMGR\_CFG\_DHCP\_DDNS

Setting DHCP-DDNS configuration to: %1

Logged at debug log level 40. A debug message issued when the server's DHCP-DDNS settings are changed.

#### 10.6 DHCPSRV CFGMGR CONFIG4 MERGED

Configuration backend data has been merged.

This is an informational message emitted when the DHCPv4 server has successfully merged configuration data retrieved from its configuration backends into the current configuration.

### 10.7 DHCPSRV\_CFGMGR\_CONFIG6\_MERGED

Configuration backend data has been merged.

This is an informational message emitted when the DHCPv6 server has successfully merged configuration data retrieved from its configuration backends into the current configuration.

#### 10.8 DHCPSRV CFGMGR CONFIGURE SERVERID

server configuration includes specification of a server identifier

This warning message is issued when the server specified configuration of a server identifier. If this new configuration overrides an existing server identifier, this will affect existing bindings of the clients. Clients will use old server identifier when they renew their bindings. The server will not respond to those renews, and the clients will eventually transition to rebinding state. The server should reassign existing bindings and the clients will subsequently use new server identifier. It is recommended to not modify the server identifier, unless there is a good reason for it, to avoid increased number of renewals and a need for rebinding (increase of multicast traffic, which may be received by multiple servers).

## 10.9 DHCPSRV\_CFGMGR\_DEL\_SUBNET4

IPv4 subnet %1 removed

Logged at debug log level 40. This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the removed subnet.

### 10.10 DHCPSRV\_CFGMGR\_DEL\_SUBNET6

IPv6 subnet %1 removed

Logged at debug log level 40. This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the removed subnet.

### 10.11 DHCPSRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_ADDRESS\_LEASES

populating free address leases for the FLQ allocator in subnet %1; it can take a while!

This informational message is issued when the server begins building a queue of free address leases for the given subnet. It can take a considerable amount of time, depending on the size of the address pools.

## 10.12 DHCPSRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_ADDRESS\_LEASES\_DONI

populated %1 free address leases for the FLQ allocator in subnet %2 in %3

This informational message is issued when the server ends building a queue of free address leases for a given subnet. The first argument logs the number of free leases, the second argument logs the subnet, and the third argument logs a duration.

## 10.13 DHCPSRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_PREFIX\_LEASES

populating free prefix leases for the FLQ allocator in subnet %1; it can take a while!

This informational message is issued when the server begins building a queue of free leases for the given subnet. It can take a considerable amount of time, depending on the size of the delegated prefix pools.

### 10.14 DHCPSRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_PREFIX\_LEASES\_DONE

populated %1 free prefix leases for the FLQ allocator in subnet %2 completed in %3

This informational message is issued when the server ends building a queue of free prefix leases for a given subnet. The first argument logs the number of free leases, the second argument logs the subnet, and the third argument logs a duration.

### 10.15 DHCPSRV\_CFGMGR\_IPV4\_RESERVATIONS\_NON\_UNIQUE\_IGNORED

ignoring "ip-reservations-unique" setting because at least one of the host database∟ ⇒backends does not support non-unique IP reservations in a subnet

This warning message is issued when the server failed to use the new setting of the ip-reservations-unique global parameter configured via the configuration backend. Some host database backends used apparently do not support specifying several reservations for the same IP address in a subnet. The administrator should either stop using the backend that does not support this setting or set the value of the ip-reservations-unique to true to resolve the configuration issue.

### 10.16 DHCPSRV CFGMGR IPV6 RESERVATIONS NON UNIQUE IGNORED

ignoring "ip-reservations-unique" setting because at least one of the host database\_ ⇒backends does not support non unique IP reservations in a subnet

This warning message is issued when the server failed to use the new setting of the ip-reservations-unique global parameter configured via the configuration backend. Some host database backends used apparently do not support specifying several reservations for the same IP address or delegated prefix in a subnet. The administrator should either stop using the backend that does not support this setting or set the value of the ip-reservations-unique to true to resolve the configuration issue.

## 10.17 DHCPSRV\_CFGMGR\_IP\_RESERVATIONS\_UNIQUE\_DUPLICATES\_DETEC

the "ip-reservations-unique" flag is set to true and multiple reservations for the IP

→address %1 in subnet %2 are not allowed causing error: %3

This warning message is issued when the DHCP server is configured to not allow multiple reservations for the same IP address. However, the host database backend contains multiple reservations for the IP address logged as the first argument, in the subnet logged as second argument, causing problems with lease allocation logged as third argument.

## 10.18 DHCPSRV\_CFGMGR\_IP\_RESERVATIONS\_UNIQUE\_DUPLICATES\_POSSI

setting "ip-reservations-unique" from false to true poses a risk that some host backends → may still contain multiple reservations for the same IP address

This warning message is issued when the DHCP server is configured to not allow multiple reservations for the same IP address. However, the host database backends may still contain multiple reservations for the same IP addresses causing problems with lease allocation for certain addresses. Please ensure that all such duplicates are removed.

#### 10.19 DHCPSRV CFGMGR NEW SUBNET4

a new subnet has been added to configuration: %1

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

#### 10.20 DHCPSRV CFGMGR NEW SUBNET6

a new subnet has been added to configuration: %1

This is an informational message reporting that the configuration has been extended to include the specified subnet.

#### 10.21 DHCPSRV\_CFGMGR\_OPTION\_DUPLICATE

multiple options with the code: %1 added to the subnet: %2

This warning message is issued on an attempt to configure multiple options with the same option code for the particular subnet. Adding multiple options is uncommon for DHCPv6, but it is not prohibited.

#### 10.22 DHCPSRV CFGMGR RENEW GTR REBIND

A warning message that indicates the configured renew-timer is greater than the configured rebind-timer. The server will ignore the renew timer value and send the rebind timer value only. This is considered a non-fatal configuration error.

## 10.23 DHCPSRV\_CFGMGR\_SOCKET\_RAW\_UNSUPPORTED

use of raw sockets is unsupported on this OS, UDP sockets will be used

This warning message is logged when the user specified that the DHCPv4 server should use the raw sockets to receive the DHCP messages and respond to the clients, but the use of raw sockets is not supported on the particular environment. The raw sockets are useful when the server must respond to the directly connected clients which don't have an address yet. If the raw sockets are not supported by Kea on the particular platform, Kea will fall back to use of the IP/UDP sockets. The responses to the directly connected clients will be broadcast. The responses to relayed clients will be unicast as usual.

### 10.24 DHCPSRV CFGMGR SOCKET TYPE DEFAULT

"dhcp-socket-type" not specified , using default socket type %1

This informational message is logged when the administrator hasn't specified the "dhcp-socket-type" parameter in configuration for interfaces. In such case, the default socket type will be used.

#### 10.25 DHCPSRV\_CFGMGR\_SOCKET\_TYPE\_SELECT

using socket type %1

This informational message is logged when the DHCPv4 server selects the socket type to be used for all sockets that will be opened on the interfaces. Typically, the socket type is specified by the server administrator. If the socket type hasn't been specified, the raw socket will be selected. If the raw socket has been selected but Kea doesn't support the use of raw sockets on the particular OS, it will use an UDP socket instead.

### 10.26 DHCPSRV\_CFGMGR\_SUBNET4

retrieved subnet %1 for address hint %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified as the address is within the subnet.

### 10.27 DHCPSRV\_CFGMGR\_SUBNET4\_ADDR

selected subnet %1 for packet received by matching address %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a received packet. This particular subnet was selected, because an IPv4 address was matched which belonged to that subnet.

### 10.28 DHCPSRV\_CFGMGR\_SUBNET4\_IFACE

selected subnet %1 for packet received over interface %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a packet received over the given interface. This particular subnet was selected, because it was specified as being directly reachable over the given interface. (see 'interface' parameter in the subnet4 definition).

### 10.29 DHCPSRV CFGMGR SUBNET4 RELAY

selected subnet %1, because of matching relay addr %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet, because detected relay agent address matches value specified for this subnet.

#### 10.30 DHCPSRV\_CFGMGR\_SUBNET6

retrieved subnet %1 for address hint %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified as the address is within the subnet.

### 10.31 DHCPSRV\_CFGMGR\_SUBNET6\_IFACE

selected subnet %1 for packet received over interface %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a packet received over given interface. This particular subnet was selected, because it was specified as being directly reachable over given interface. (see 'interface' parameter in the subnet6 definition).

### 10.32 DHCPSRV\_CFGMGR\_SUBNET6\_IFACE\_ID

selected subnet %1 (interface-id match) for incoming packet

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a received packet. This particular subnet was selected, because value of interface-id option matched what was configured in the server's interface-id option for that selected subnet6. (see 'interface-id' parameter in the subnet6 definition).

### 10.33 DHCPSRV\_CFGMGR\_SUBNET6\_RELAY

selected subnet %1, because of matching relay addr %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet, because detected relay agent address matches value specified for this subnet.

### 10.34 DHCPSRV CFGMGR UNICAST LINK LOCAL

specified link local address %1 for unicast traffic on interface %2

This warning message is logged when user specified a link-local address to receive unicast traffic. The warning message is issued because it is an uncommon use.

#### 10.35 DHCPSRV\_CFGMGR\_UPDATE\_SUBNET4

updating subnet %1 (result %2)

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is updating the specified IPv4 subnet in its current configuration. Subnet ID and result (expected to be true) are displayed.

### 10.36 DHCPSRV CFGMGR UPDATE SUBNET6

updating subnet %1 (result %2)

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is replacing the specified IPv6 subnet in its current configuration. Subnet ID and result (expected to be true) are displayed.

#### 10.37 DHCPSRV\_CFGMGR\_USE\_ADDRESS

listening on address %1, on interface %2

A message issued when the server is configured to listen on the explicitly specified IP address on the given interface.

## 10.38 DHCPSRV\_CFGMGR\_USE\_ALLOCATOR

using the %1 allocator for %2 leases in subnet %3

A message issued when the configuration manager starts using a given allocator for a subnet.

## 10.39 DHCPSRV\_CFGMGR\_USE\_UNICAST

listening on unicast address %1, on interface %2

An info message issued when configuring the DHCP server to listen on the unicast address on the specific interface.

### 10.40 DHCPSRV\_CLASS\_WITH\_ADDITIONAL\_AND\_LIFETIMES

class: %1 has 'only-in-additional-list' true while specifying one or more lease life → time values. Life time values will be ignored.

This warning is emitted whenever a class is configured with 'only-in-addition-list' true as well as specifying one or more lease life time parameters (e.g. 'valid-lifetime', 'preferred-lifetime', or 'offer-lifetime'). Additional list classes are evaluated after lease assignment, thus parameters that would otherwise impact lease life times will have no affect.

### 10.41 DHCPSRV\_CLIENT\_CLASS\_DEPRECATED

The parameter 'client-class' is deprecated. Use 'client-classes' list parameter instead

This warning message is emitted when configuration parsing detects the use of the deprecated 'client-class' parameter. It has been replaced by 'client-classes'. Users should migrate to the new list parameter.

### 10.42 DHCPSRV\_CLOSE\_DB

closing currently open %1 database

Logged at debug log level 40. This is a debug message, issued when the DHCP server closes the currently open lease database. It is issued at program shutdown and whenever the database access parameters are changed: in the latter case, the server closes the currently open database, and opens a database using the new parameters.

### 10.43 DHCPSRV DDNS TTL PERCENT TOO SMALL

ddns-ttl-percent %1 of lease lifetime %2 is too small, ignoring it

Logged at debug log level 55. A debug message issued when the DDNS TTL value calculated using the ddns-ttl-percent is zero. Kea will ignore the value and calculate the DDNS TTL as though ddsn-ttl-percent were not specified. The value of ddns-ttl-percent and the lease lifetime are shown in the message details.

## 10.44 DHCPSRV\_DHCP4O6\_RECEIVED\_BAD\_PACKET

received bad DHCPv4o6 packet: %1

A bad DHCPv4o6 packet was received.

### 10.45 DHCPSRV\_DHCP\_DDNS\_ERROR\_EXCEPTION

error handler for DHCP\_DDNS IO generated an expected exception: %1

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails there registered error handler threw an uncaught exception. This is a programmatic error which should not occur. By convention, the error handler should not propagate exceptions. Please report this error.

#### 10.46 DHCPSRV DHCP DDNS HANDLER NULL

error handler for DHCP\_DDNS IO is not set.

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails and there is no registered error handler. This is a programmatic error which should never occur and should be reported.

#### 10.47 DHCPSRV\_DHCP\_DDNS\_NCR\_REJECTED

NameChangeRequest rejected by the sender: %1, ncr: %2

This is an error message indicating that NameChangeSender used to deliver DDNS update requests to kea-dhcp-ddns rejected the request. This most likely cause is the sender's queue has reached maximum capacity. This would imply that requests are being generated faster than they can be delivered.

### 10.48 DHCPSRV\_DHCP\_DDNS\_NCR\_SENT

NameChangeRequest sent to kea-dhcp-ddns: %1

Logged at debug log level 50. A debug message issued when a NameChangeRequest has been successfully sent to kea-dhcp-ddns.

### 10.49 DHCPSRV\_DHCP\_DDNS\_SENDER\_STARTED

NameChangeRequest sender has been started: %1

An informational message issued when a communication with kea-dhcp-ddns has been successfully started.

### 10.50 DHCPSRV\_DHCP\_DDNS\_SENDER\_STOPPED

NameChangeRequest sender has been stopped.

An informational message issued when a communication with kea-dhcp-ddns has been stopped. This normally occurs during reconfiguration and as part of normal shutdown. It may occur if kea-dhcp-ddns communications break down.

#### 10.51 DHCPSRV\_DHCP\_DDNS\_SUSPEND\_UPDATES

DHCP\_DDNS updates are being suspended.

This is a warning message indicating the DHCP\_DDNS updates have been turned off. This should only occur if IO errors communicating with kea-dhcp-ddns have been experienced. Any such errors should have preceding entries in the log with details. No further attempts to communicate with kea-dhcp-ddns will be made without intervention.

#### 10.52 DHCPSRV EVAL ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating an expression of a client class. A description of the problem is printed.

### 10.53 DHCPSRV\_EVAL\_RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of a client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 10.54 DHCPSRV\_HOOK\_LEASE4\_RECOVER\_SKIP

DHCPv4 lease %1 was not recovered from the declined state because a callout set the  $skip_{-} status$ .

Logged at debug log level 40. This debug message is printed when a callout installed on lease4\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

#### 10.55 DHCPSRV HOOK LEASE4 RENEW SKIP

DHCPv4 lease was not renewed because a callout set the skip flag.

Logged at debug log level 40. This debug message is printed when a callout installed on lease4\_renew hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not renew a lease. The server will use existing lease as it is, without extending its lifetime.

#### 10.56 DHCPSRV HOOK LEASE4 SELECT SKIP

Lease4 creation was skipped, because of callout skip flag.

Logged at debug log level 40. This debug message is printed when a callout installed on lease4\_select hook point sets the skip flag. It means that the server was told that no lease4 should be assigned. The server will not put that lease in its database and the client will get a NAK packet.

### 10.57 DHCPSRV\_HOOK\_LEASE6\_EXTEND\_SKIP

DHCPv6 lease lifetime was not extended because a callout set the skip flag for message %1

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_renew or the lease6\_rebind hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not extend the lifetime for a lease. If the client requested renewal of multiple leases (by sending multiple IA options), the server will skip the renewal of the one in question and will proceed with other renewals as usual.

## 10.58 DHCPSRV HOOK LEASE6 RECOVER SKIP

DHCPv6 lease %1 was not recovered from declined state because a callout set the skip ⇒status.

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

### 10.59 DHCPSRV HOOK LEASE6 SELECT SKIP

Lease6 (non-temporary) creation was skipped, because of callout skip flag.

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_select hook point sets the skip flag. It means that the server was told that no lease6 should be assigned. The server will not put that lease in its database and the client will get a NoAddrsAvail for that IA\_NA option.

### 10.60 DHCPSRV\_HOST\_MGR\_DB\_OPEN\_CONNECTION\_WITH\_RETRY\_FAILED

Failed to connect to database: %1 with error: %2

This is an informational message issued when the server failed to connect to the host database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

### 10.61 DHCPSRV LEASE4 EXTENDED INFO SANITY FAIL

extended info for lease %1 failed checks (%2)

This error message is printed when a lease extended info failed to pass sanity checks. The detail of the found problem was displayed and the extended info deleted from the lease user context.

#### 10.62 DHCPSRV\_LEASE4\_EXTENDED\_INFO\_UPGRADED

extended info for lease %1 was upgraded

Logged at debug log level 40. This debug message is printed when a lease extended info was upgraded.

### 10.63 DHCPSRV\_LEASE6\_EXTENDED\_INFO\_SANITY\_FAIL

extended info for lease %1 failed checks (%2)

This error message is printed when a lease extended info failed to pass sanity checks. The detail of the found problem was displayed and the extended info deleted from the lease user context.

## 10.64 DHCPSRV\_LEASE6\_EXTENDED\_INFO\_UPGRADED

extended info for lease %1 was upgraded

Logged at debug log level 40. This debug message is printed when a lease extended info was upgraded.

## 10.65 DHCPSRV\_LEASE\_MGR\_BACKENDS\_REGISTERED

the following lease backend types are available: %1

This informational message lists all possible lease backends that could be used in lease-database.

### 10.66 DHCPSRV\_LEASE\_MGR\_BACKEND\_DEREGISTER

deregistered lease backend type: %1

Logged at debug log level 40. This debug message is issued when a backend factory was deregistered. It is no longer possible to use lease backend of this type.

#### 10.67 DHCPSRV\_LEASE\_MGR\_BACKEND\_REGISTER

registered lease backend type: %1

Logged at debug log level 40. This debug message is issued when a backend factory was successfully registered. It is now possible to use lease backend of this type.

## 10.68 DHCPSRV\_LEASE\_MGR\_CALLBACK\_EXCEPTION

exception occurred in a lease manager callback for callback type %1, subnet id %2, and □ lease %3: %4

This warning message is printed when one of the callback functions registered in the lease manager causes an error. The callback functions can serve different purposes and they likely log the detailed error messages. This error message possibly indicates an unhandled error. The first argument indicates a callback type. The second argument prints the subnet id. The third argument prints the lease for which the error has occurred. The last argument prints the error text.

## 10.69 DHCPSRV\_LEASE\_MGR\_CALLBACK\_UNKNOWN\_EXCEPTION

This warning message is printed when one of the callback functions registered in the lease manager causes an unknown error. The callback functions can serve different purposes and they likely log the detailed error messages. This error message possibly indicates an unhandled error. The first argument indicates a callback type. The second argument prints the subnet id. The third argument prints the lease for which the error has occurred. This log message variant contains no error text because it is triggered by an unknown exception.

## 10.70 DHCPSRV\_LEASE\_MGR\_DB\_OPEN\_CONNECTION\_WITH\_RETRY\_FAILE

Failed to connect to database: %1 with error: %2

This is an informational message issued when the server failed to connect to the lease database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

### 10.71 DHCPSRV\_LEASE\_SANITY\_FAIL

The lease %1 with subnet-id %2 failed subnet-id checks (%3).

This warning message is printed when the lease being loaded does not match the configuration. Due to lease-checks value, the lease will be loaded, but it will most likely be unused by Kea, as there is no subnet that matches the IP address associated with the lease.

#### 10.72 DHCPSRV LEASE SANITY FAIL DISCARD

The lease %1 with subnet-id %2 failed subnet-id checks (%3) and was dropped.

This warning message is printed when a lease was loaded, but Kea was told (by setting lease-checks parameter) to discard leases with inconsistent data. The lease was discarded, because either there is no subnet configured with matching subnet-id or the address of the lease does not belong to the subnet.

### 10.73 DHCPSRV\_LEASE\_SANITY\_FIXED

The lease %1 with subnet-id %2 failed subnet-id checks, but was corrected to subnet-id  $\rightarrow$  %3.

This informational message is printed when a lease was loaded, but had incorrect subnet-id value. The lease-checks parameter was set to a value that told Kea to try to correct the problem. There is a matching subnet, so Kea updated subnet-id and loaded the lease successfully.

## 10.74 DHCPSRV MEMFILE ADD ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. A debug message issued when the server is about to add an IPv4 lease with the specified address to the memory file backend database.

## 10.75 DHCPSRV\_MEMFILE\_ADD\_ADDR6

adding IPv6 lease with address %1

Logged at debug log level 50. A debug message issued when the server is about to add an IPv6 lease with the specified address to the memory file backend database.

### 10.76 DHCPSRV MEMFILE BEGIN BUILD EXTENDED INFO TABLES6

building extended info tables with %1 sanity check level, tables %2

Logged at debug log level 40. A debug message issued when the server is building extended info tables. The extended info sanity check level and the fact tables are enabled or disabled are displayed.

#### 10.77 DHCPSRV\_MEMFILE\_BEGIN\_EXTRACT\_EXTENDED\_INFO4

extract extended info with %1 sanity check level%2

Logged at debug log level 40. A debug message issued when the server is extracting extended info. The extended info sanity check level and update in file when requested are displayed.

### 10.78 DHCPSRV MEMFILE BUILD EXTENDED INFO TABLES6

building extended info tables saw %1 leases, extended info sanity checks modified %2.

→leases and %3 leases were entered into tables

Extended info tables build was finished. Some statistics are displayed, the updated in database is returned to the command interface.

### 10.79 DHCPSRV\_MEMFILE\_BUILD\_EXTENDED\_INFO\_TABLES6\_ERROR

building extended info tables got an exception on the lease for %1: %2

An error message issued when the server is building extended info tables and receives an exception processing a lease.

## 10.80 DHCPSRV\_MEMFILE\_COMMIT

committing to memory file database

Logged at debug log level 50. The code has issued a commit call. For the memory file database this is a no-op.

## 10.81 DHCPSRV\_MEMFILE\_CONVERTING\_LEASE\_FILES

running LFC now to convert lease files to the current schema: %1.%2

A warning message issued when the server has detected lease files that need to be either upgraded or downgraded to match the server's schema, and that the server is automatically running the LFC process to perform the conversion. This should only occur the first time the server is launched following a Kea installation upgrade (or downgrade).

### 10.82 DHCPSRV\_MEMFILE\_DB

opening memory file lease database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a memory file lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

#### 10.83 DHCPSRV MEMFILE DELETE ADDR4

deleting lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

#### 10.84 DHCPSRV\_MEMFILE\_DELETE\_ADDR6

deleting lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

### 10.85 DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED4

deleting reclaimed IPv4 leases that expired more than %1 seconds ago

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.86 DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED6

deleting reclaimed IPv6 leases that expired more than %1 seconds ago

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

### 10.87 DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED\_START

starting deletion of %1 expired-reclaimed leases

Logged at debug log level 50. A debug message issued when the server has found expired-reclaimed leases to be removed. The number of leases to be removed is logged in the message.

#### 10.88 DHCPSRV MEMFILE EXTRACT EXTENDED INFO4

extracting extended info saw %1 leases, extended info sanity checks modified %2 / □ updated %3 leases and %4 leases have relay or remote id

Logged at debug log level 40. Extended info extraction was finished. Some statistics are displayed, the updated in database is returned to the command interface.

#### 10.89 DHCPSRV\_MEMFILE\_EXTRACT\_EXTENDED\_INFO4\_ERROR

extracting extended info got an exception on the lease for %1: %2

Logged at debug log level 40. A debug message issued when the server is extracting extended info and receives an exception processing a lease.

### 10.90 DHCPSRV\_MEMFILE\_GET4

obtaining all IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases from the memory file database.

## 10.91 DHCPSRV\_MEMFILE\_GET6

obtaining all IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases from the memory file database.

### 10.92 DHCPSRV\_MEMFILE\_GET6\_DUID

obtaining IPv6 leases for DUID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain IPv6 leases from the memory file database for the DUID.

#### 10.93 DHCPSRV\_MEMFILE\_GET\_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for the specified address.

### 10.94 DHCPSRV MEMFILE GET ADDR6

obtaining IPv6 lease for address %1 and lease type %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for the specified address.

### 10.95 DHCPSRV\_MEMFILE\_GET\_CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified client identification.

## 10.96 DHCPSRV\_MEMFILE\_GET\_EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 10.97 DHCPSRV\_MEMFILE\_GET\_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

### 10.98 DHCPSRV\_MEMFILE\_GET\_HOSTNAME4

obtaining IPv4 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hostname.

#### 10.99 DHCPSRV\_MEMFILE\_GET\_HOSTNAME6

obtaining IPv6 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified hostname.

### 10.100 DHCPSRV MEMFILE GET HWADDR

obtaining IPv4 leases for hardware address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hardware address.

### 10.101 DHCPSRV\_MEMFILE\_GET\_IAID\_DUID

obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

## 10.102 DHCPSRV\_MEMFILE\_GET\_IAID\_SUBID\_DUID

obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

### 10.103 DHCPSRV\_MEMFILE\_GET\_PAGE4

obtaining at most %1 IPv4 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

#### 10.104 DHCPSRV\_MEMFILE\_GET\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

### 10.105 DHCPSRV MEMFILE GET RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt... ⇒between %4 and %5

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

### 10.106 DHCPSRV\_MEMFILE\_GET\_RELAYID6

obtaining at most %1 IPv6 leases starting from address %2 with relay id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

## 10.107 DHCPSRV\_MEMFILE\_GET\_REMOTEID4

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

### 10.108 DHCPSRV MEMFILE GET REMOTEID6

obtaining at most %1 IPv6 leases starting from address %2 with remote id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

#### 10.109 DHCPSRV\_MEMFILE\_GET\_SUBID4

obtaining IPv4 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the memory file database.

### 10.110 DHCPSRV MEMFILE GET SUBID6

obtaining IPv6 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the memory file database.

#### 10.111 DHCPSRV\_MEMFILE\_GET\_SUBID\_CLIENTID

obtaining IPv4 lease for subnet ID %1 and client ID %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and client ID.

## 10.112 DHCPSRV\_MEMFILE\_GET\_SUBID\_HWADDR

obtaining IPv4 lease for subnet ID %1 and hardware address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and hardware address.

## 10.113 DHCPSRV\_MEMFILE\_GET\_SUBID\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases from the memory file database beginning with the specified address for a given subnet identifier.

### 10.114 DHCPSRV\_MEMFILE\_LEASE\_FILE\_LOAD

loading leases from file %1

An info message issued when the server is about to start reading DHCP leases from the lease file. All leases currently held in the memory will be replaced by those read from the file.

#### 10.115 DHCPSRV\_MEMFILE\_LEASE\_LOAD

loading lease %1

Logged at debug log level 55. A debug message issued when DHCP lease is being loaded from the file to memory.

### 10.116 DHCPSRV MEMFILE LEASE LOAD ROW ERROR

discarding row %1, error: %2

An error message issued if the DHCP lease being loaded from the given row of the lease file fails. The log message should contain the specific reason the row was discarded. The server continues loading the remaining data. This may indicate a corrupt lease file.

### 10.117 DHCPSRV\_MEMFILE\_LFC\_EXECUTE

executing Lease File Cleanup using: %1

An informational message issued when the memfile lease database backend starts a new process to perform Lease File Cleanup.

## 10.118 DHCPSRV\_MEMFILE\_LFC\_LEASE\_FILE\_RENAME\_FAIL

failed to rename the current lease file %1 to %2, reason: %3

An error message logged when the memfile lease database backend fails to move the current lease file to a new file on which the cleanup should be performed. This effectively means that the lease file cleanup does not take place.

## 10.119 DHCPSRV\_MEMFILE\_LFC\_LEASE\_FILE\_REOPEN\_FAIL

An error message logged when the memfile lease database backend failed to re-open or re-create the lease file after renaming the lease file for lease file cleanup. The server continues to operate but leases do not persist to disk.

### 10.120 DHCPSRV MEMFILE LFC SETUP

setting up the Lease File Cleanup interval to %1 sec

An informational message logged when the memfile lease database backend configures the LFC to be executed periodically. The argument holds the interval in seconds in which the LFC will be executed.

#### 10.121 DHCPSRV\_MEMFILE\_LFC\_SPAWN\_FAIL

lease file cleanup failed to run because kea-lfc process couldn't be spawned

This error message is logged when the Kea server fails to run kea-lfc, the program that cleans up the lease file. The server will try again the next time a lease file cleanup is scheduled. Although this message should not appear and the reason why it did investigated, the occasional failure to start the lease file cleanup will not impact operations. Should the failure persist however, the size of the lease file will increase without bound.

### 10.122 DHCPSRV\_MEMFILE\_LFC\_START

starting Lease File Cleanup

An informational message issued when the Memfile lease database backend starts the periodic Lease File Cleanup.

## 10.123 DHCPSRV\_MEMFILE\_LFC\_UNREGISTER\_TIMER\_FAILED

failed to unregister timer 'memfile-lfc': %1

Logged at debug log level 40. This debug message is logged when Memfile backend fails to unregister timer used for lease file cleanup scheduling. There are several reasons why this could occur, although the most likely cause is that the system is being shut down and some other component has unregistered the timer. The message includes the reason for this error.

### 10.124 DHCPSRV\_MEMFILE\_NEEDS\_DOWNGRADING

version of lease file: %1 schema is later than version %2

A warning message issued when the schema of the lease file loaded by the server is newer than the memfile schema of the server. The server converts the lease data from newer schemas to its schema as it is read, therefore the lease information in use by the server will be correct. Note though, that any data stored in newer schema fields will be dropped. What remains is for the file itself to be rewritten using the current schema.

### 10.125 DHCPSRV MEMFILE NEEDS UPGRADING

version of lease file: %1 schema is earlier than version %2

A warning message issued when the schema of the lease file loaded by the server pre-dates the memfile schema of the server. Note that the server converts the lease data from older schemas to the current schema as it is read, therefore the lease information in use by the server will be correct. What remains is for the file itself to be rewritten using the current schema.

#### 10.126 DHCPSRV MEMFILE NO STORAGE

running in non-persistent mode, leases will be lost after restart

A warning message issued when writes of leases to disk have been disabled in the configuration. This mode is useful for some kinds of performance testing but should not be enabled in normal circumstances. Non-persistence mode is enabled when 'persist4=no persist6=no' parameters are specified in the database access string.

#### 10.127 DHCPSRV MEMFILE READ HWADDR FAIL

failed to read hardware address from lease file: %1

A warning message issued when read attempt of the hardware address stored in a disk file failed. The parameter should provide the exact nature of the failure. The database read will continue, but that particular lease will no longer have hardware address associated with it.

## 10.128 DHCPSRV MEMFILE ROLLBACK

rolling back memory file database

Logged at debug log level 50. The code has issued a rollback call. For the memory file database this is a no-op.

## 10.129 DHCPSRV\_MEMFILE\_UPDATE\_ADDR4

updating IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv4 lease from the memory file database for the specified address.

### 10.130 DHCPSRV MEMFILE UPDATE ADDR6

updating IPv6 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv6 lease from the memory file database for the specified address.

#### 10.131 DHCPSRV\_MEMFILE\_WIPE\_LEASES4

removing all IPv4 leases from subnet %1

This informational message is printed when removal of all leases from specified IPv4 subnet is commencing. This is a result of receiving administrative command.

#### 10.132 DHCPSRV MEMFILE WIPE LEASES4 FINISHED

removing all IPv4 leases from subnet %1 finished, removed %2 leases

This informational message is printed when removal of all leases from a specified IPv4 subnet has finished. The number of removed leases is printed.

### 10.133 DHCPSRV\_MEMFILE\_WIPE\_LEASES6

removing all IPv6 leases from subnet %1

This informational message is printed when removal of all leases from specified IPv6 subnet is commencing. This is a result of receiving administrative command.

## 10.134 DHCPSRV\_MEMFILE\_WIPE\_LEASES6\_FINISHED

removing all IPv6 leases from subnet %1 finished, removed %2 leases

This informational message is printed when removal of all leases from a specified IPv6 subnet has finished. The number of removed leases is printed.

## 10.135 DHCPSRV\_MT\_DISABLED\_QUEUE\_CONTROL

disabling dhcp queue control when multi-threading is enabled.

This warning message is issued when dhcp queue control is disabled automatically if multi-threading is enabled. These two options are incompatible and can not both be enabled at the same time.

### 10.136 DHCPSRV\_MULTIPLE\_RAW\_SOCKETS\_PER\_IFACE

current configuration will result in opening multiple broadcast capable sockets on some\_ →interfaces and some DHCP messages may be duplicated

A warning message issued when the current configuration indicates that multiple sockets, capable of receiving broadcast traffic, will be opened on some of the interfaces. It must be noted that this may lead to receiving and processing the same DHCP message multiple times, as it will be received by each socket individually.

### 10.137 DHCPSRV\_NOTYPE\_DB

no 'type' keyword to determine database backend: %1

This is an error message, logged when an attempt has been made to access a database backend, but where no 'type' keyword has been included in the access string. The access string (less any passwords) is included in the message.

## 10.138 DHCPSRV\_NO\_SOCKETS\_OPEN

no interface configured to listen to DHCP traffic

This warning message is issued when the current server configuration specifies no interfaces that the server should listen on, or when the specified interfaces are not configured to receive the traffic.

## 10.139 DHCPSRV\_ONLY\_IF\_REQUIRED\_DEPRECATED

The parameter 'only-if-required' is deprecated. Use 'only-in-additional-list' instead

This warning message is emitted when configuration parsing detects the use of the deprecated 'only-if-required' parameter. It has been replaced by 'only-in-additional-list'. Users should migrate to the new parameter.

### 10.140 DHCPSRV\_OPEN\_SOCKET\_FAIL

failed to open socket: %1

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

### 10.141 DHCPSRV QUEUE NCR

%1: Name change request to %2 DNS entry queued: %3

Logged at debug log level 55. A debug message which is logged when the NameChangeRequest to add or remove a DNS entries for a particular lease has been queued. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument carries the details of the NameChangeRequest.

### 10.142 DHCPSRV\_QUEUE\_NCR\_FAILED

%1: queuing %2 name change request failed for lease %3: %4

This error message is logged when sending a NameChangeRequest to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

### 10.143 DHCPSRV\_QUEUE\_NCR\_SKIP

%1: skip queuing name change request for lease: %2

Logged at debug log level 50. This debug message is issued when the server decides to not queue the name change request because the lease doesn't include the FQDN, the forward and reverse update is disabled for this lease or the DNS updates are disabled in the configuration. The first argument includes the client identification information. The second argument includes the leased address.

## 10.144 DHCPSRV\_REQUIRE\_CLIENT\_CLASSES\_DEPRECATED

The parameter 'require-client-classes' is deprecated. Use 'evaluate-additional-classes'  $_{\mbox{\tiny $\omega$}}$  instead

This warning message is emitted when configuration parsing detects the use of the deprecated 'require-client-classes' parameter. It has been replaced by 'evaluate-additional-classes'. Users should migrate to the new parameter.

## 10.145 DHCPSRV SUBNET406 SELECT FAILED

Failed to select any subnet for the DHCPv4o6 packet

Logged at debug log level 40. A debug message issued when the server was unable to select any subnet for the DHCPv4o6 packet.

### 10.146 DHCPSRV\_SUBNET4\_SELECT\_BY\_ADDRESS\_NO\_MATCH

No subnet matches address: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified address.

#### 10.147 DHCPSRV\_SUBNET4\_SELECT\_BY\_INTERFACE\_NO\_MATCH

No subnet matches interface: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified interface name.

### 10.148 DHCPSRV SUBNET4 SELECT BY RELAY ADDRESS NO MATCH

No subnet matches relay address: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified relay address.

### 10.149 DHCPSRV\_SUBNET4\_SELECT\_NO\_RAI\_OPTIONS

No RAI options found to use for subnet selection.

Logged at debug log level 40. A debug message issued by the server when the client query does not include RAI options suitable for use with subnet selection.

## 10.150 DHCPSRV\_SUBNET4\_SELECT\_NO\_RELAY\_ADDRESS

Relay address (giaddr) in client packet is empty.

Logged at debug log level 40. A debug message issued when no relay address was specified to use for subnet selection.

### 10.151 DHCPSRV\_SUBNET4\_SELECT\_NO\_USABLE\_ADDRESS

No subnet selected because no suitable address to use for subnet selection was found.

Logged at debug log level 40. A debug message issued when the server was find a suitable address to use for subnet selection.

## 10.152 DHCPSRV\_SUBNET6\_SELECT\_BY\_ADDRESS\_NO\_MATCH

No subnet matches address: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified address.

#### 10.153 DHCPSRV SUBNET6 SELECT BY INTERFACE ID NO MATCH

No subnet matches interface id: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified interface id.

## 10.154 DHCPSRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_NO\_MATCH

No subnet matches interface: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified interface name.

### 10.155 DHCPSRV\_TEMPLATE\_EVAL\_ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating an expression of a template client class. A description of the problem is printed.

## 10.156 DHCPSRV\_TEMPLATE\_EVAL\_RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of a template client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 10.157 DHCPSRV\_TIMERMGR\_CALLBACK\_FAILED

running handler for timer %1 caused exception: %2

This error message is emitted when the timer elapsed and the operation associated with this timer has thrown an exception. The timer name and the reason for exception is logged.

### 10.158 DHCPSRV\_TIMERMGR\_REGISTER\_TIMER

registering timer: %1, using interval: %2 ms

Logged at debug log level 40. A debug message issued when the new interval timer is registered in the Timer Manager. This timer will have a callback function associated with it, and this function will be executed according to the interval specified. The unique name of the timer and the interval at which the callback function will be executed is included in the message.

#### 10.159 DHCPSRV TIMERMGR RUN TIMER OPERATION

running operation for timer: %1

Logged at debug log level 50. A debug message issued when the Timer Manager is about to run a periodic operation associated with the given timer. An example of such operation is a periodic cleanup of expired leases. The name of the timer is included in the message.

#### 10.160 DHCPSRV TIMERMGR START TIMER

starting timer: %1

Logged at debug log level 40. A debug message issued when the registered interval timer is being started. If this operation is successful the timer will periodically execute the operation associated with it. The name of the started timer is included in the message.

### 10.161 DHCPSRV TIMERMGR STOP TIMER

stopping timer: %1

Logged at debug log level 40. A debug message issued when the registered interval timer is being stopped. The timer remains registered and can be restarted if necessary. The name of the timer is included in the message.

## 10.162 DHCPSRV\_TIMERMGR\_UNREGISTER\_ALL\_TIMERS

unregistering all timers

Logged at debug log level 40. A debug message issued when all registered interval timers are being unregistered from the Timer Manager.

# 10.163 DHCPSRV\_TIMERMGR\_UNREGISTER\_TIMER

unregistering timer: %1

Logged at debug log level 40. A debug message issued when one of the registered interval timers is unregistered from the Timer Manager. The name of the timer is included in the message.

**CHAPTER** 

**ELEVEN** 

**DHCP** 

#### 11.1 DHCP DDNS ADD FAILED

DHCP\_DDNS Request ID %1: Transaction outcome %2

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry additions have failed. The precise reason for the failure should be documented in preceding log entries.

#### 11.2 DHCP DDNS ADD SUCCEEDED

DHCP\_DDNS Request ID %1: successfully added the DNS mapping addition for this request: %2

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping additions which were received and accepted by an appropriate DNS server.

# 11.3 DHCP\_DDNS\_AT\_MAX\_TRANSACTIONS

application has %1 queued requests but has reached maximum number of %2 concurrent → transactions

Logged at debug log level 55. This is a debug message that indicates that the application has DHCP\_DDNS requests in the queue but is working as many concurrent requests as allowed.

# 11.4 DHCP\_DDNS\_CLEARED\_FOR\_SHUTDOWN

application has met shutdown criteria for shutdown type: %1

Logged at debug log level 0. This is a debug message issued when the application has been instructed to shutdown and has met the required criteria to exit.

## 11.5 DHCP DDNS CONFIGURE

configuration %1 received: %2

Logged at debug log level 40. This is a debug message issued when the DHCP-DDNS application configure method has been invoked.

## 11.6 DHCP\_DDNS\_CONFIGURED\_CALLOUT\_DROP

configuration was rejected because a callout set the next step to 'drop': %1

This error message indicates that the DHCP-DDNS had failed configuration attempt because the next step of the configured callout was set to 'drop' by a hook library. The error message provided by the hook library is displayed.

#### 11.7 DHCP DDNS CONFIG CHECK FAIL

DHCP-DDNS server configuration check failed: %1

This error message indicates that the DHCP-DDNS had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 11.8 DHCP\_DDNS\_CONFIG\_FAIL

DHCP-DDNS server configuration failed: %1

This error message indicates that the DHCP-DDNS had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 11.9 DHCP DDNS CONFIG SYNTAX WARNING

DHCP-DDNS server configuration syntax warning: %1

This warning message indicates that the DHCP-DDNS configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

# 11.10 DHCP\_DDNS\_FAILED

application experienced a fatal error: %1

This is a debug message issued when the DHCP-DDNS application encounters an unrecoverable error from within the event loop.

## 11.11 DHCP\_DDNS\_FORWARD\_ADD\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while adding a⊔ oforward address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was adding a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

#### 11.12 DHCP DDNS FORWARD ADD BUILD FAILURE

```
DNS Request ID %1: update message to add a forward DNS entry could not be constructed. for this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address addition. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

#### 11.13 DHCP DDNS FORWARD ADD IO ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping add for FQDN \rightarrow %2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address add. The application will retry against the same server or others as appropriate.

## 11.14 DHCP DDNS FORWARD ADD REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to add the address mapping _{\!\!\!\!-\!\!\!\!\!-} for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

# 11.15 DHCP DDNS FORWARD ADD RESP CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while →adding forward address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to add a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.16 DHCP DDNS FORWARD ADD TIMEOUT

DHCP\_DDNS Request ID %1: timed out waiting for a response to forward mapping add for  $\Box$   $\rightarrow$  FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a forward address add. The application will retry against the same server or others as appropriate.

# 11.17 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BAD\_DNSCLIENT\_STATUS

DHCP\_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing a⊔ oforward address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

#### 11.18 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BUILD\_FAILURE

DNS Request ID %1: update message to remove a forward DNS Address entry could not be →constructed for this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address (A or AAAA) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue. *\lsame*/

# 11.19 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_IO\_ERROR

DHCP\_DDNS Request ID %1: encountered an IO error sending a forward mapping address.

→removal for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address remove. The application will retry against the same server or others as appropriate.

# 11.20 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to remove the forward\_ →address mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.21 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_RESP\_CORRUPT

DHCP\_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while\_ removing forward address mapping for FQDN, %3

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

#### 11.22 DHCP DDNS FORWARD REMOVE ADDRS TIMEOUT

DHCP\_DDNS Request ID %1: timed out waiting for a response to forward mapping address → removal for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a forward mapping address removal. The application will retry against the same server or others as appropriate.

## 11.23 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BAD\_DNSCLIENT\_STATUS

DHCP\_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing →forward RRs for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing forward RRs. The request will be aborted. This is most likely a programmatic issue and should be reported.

# 11.24 DHCP DDNS FORWARD REMOVE RRS BUILD FAILURE

DNS Request ID %1: update message to remove forward DNS RR entries could not be →constructed for this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting forward RR (DHCID RR) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

# 11.25 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_IO\_ERROR

DHCP\_DDNS Request ID %1: encountered an IO error sending a forward RR removal for FQDN  $_{\rm \hookrightarrow}$  X2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward RR remove. The application will retry against the same server.

## 11.26 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to remove forward RR\_ entries for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

#### 11.27 DHCP DDNS FORWARD REMOVE RRS RESP CORRUPT

DHCP\_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while → removing forward RRs for FQDN, %3

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove forward RRs mapping, is mangled or malformed. The application will retry against the same server or others as appropriate. *\langle sarl* 

## 11.28 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_TIMEOUT

DHCP\_DDNS Request ID %1: timed out waiting for response to forward RR removal for FQDN  ${\sim}$ %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a forward RR removal. The application will retry against the same server or others as appropriate.

# 11.29 DHCP\_DDNS\_FORWARD\_REPLACE\_BAD\_DNSCLIENT\_STATUS

DHCP\_DDNS Request ID %1: received an unknown DNSClient status: %2, while replacing → forward address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

# 11.30 DHCP\_DDNS\_FORWARD\_REPLACE\_BUILD\_FAILURE

DNS Request ID %1: update message to replace a forward DNS entry could not be →constructed from this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

## 11.31 DHCP\_DDNS\_FORWARD\_REPLACE\_IO\_ERROR

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward mapping replace. The application will retry against the same server or others as appropriate.

#### 11.32 DHCP DDNS FORWARD REPLACE REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to replace the address\_ →mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.33 DHCP\_DDNS\_FORWARD\_REPLACE\_RESP\_CORRUPT

DHCP\_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while ⇒replacing forward address mapping for FQDN, %3

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

# 11.34 DHCP\_DDNS\_FORWARD\_REPLACE\_TIMEOUT

DHCP\_DDNS Request ID %1: timed out waiting for a response to forward mapping replace for  $\rightarrow$  FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a forward mapping replace. The application will retry against the same server or others as appropriate.

# 11.35 DHCP\_DDNS\_FWD\_REQUEST\_IGNORED

Request ID %1: Forward updates are disabled, the forward portion of request will be\_ ignored: %2

Logged at debug log level 55. This is a debug message issued when forward DNS updates are disabled and DHCP\_DDNS receives an update request containing a forward DNS update. The forward update will not performed.

## 11.36 DHCP DDNS INVALID NCR

application received an invalid DNS update request: %1

This is an error message that indicates that an invalid request to update a DNS entry was received by the application. Either the format or the content of the request is incorrect. The request will be ignored.

#### 11.37 DHCP\_DDNS\_INVALID\_RESPONSE

received response to DNS Update message is malformed: %1

Logged at debug log level 50. This is a debug message issued when the DHCP-DDNS application encountered an error while decoding a response to DNS Update message. Typically, this error will be encountered when a response message is malformed.

#### 11.38 DHCP\_DDNS\_LISTENING\_ON\_ALL\_INTERFACES

the DHCP-DDNS server has been configured to listen on %1. This is an insecure\_configuration supported for testing purposes only

This is a warning message issued when the DHCP-DDNS server is configured to listen at either 0.0.0.0 or ::. It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, listening on all interfaces should only be used when deploying in containers or for testing purposes. A future version of Kea will disable this ability by default.

## 11.39 DHCP DDNS NCR FLUSH IO ERROR

DHCP-DDNS Last send before stopping did not complete successfully: %1

This is an error message that indicates the DHCP-DDNS client was unable to complete the last send prior to exiting send mode. This is a programmatic error, highly unlikely to occur, and should not impair the application's ability to process requests.

# 11.40 DHCP\_DDNS\_NCR\_LISTEN\_CLOSE\_ERROR

application encountered an error while closing the listener used to receive →NameChangeRequests: %1

This is an error message that indicates the application was unable to close the listener connection used to receive NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the application's ability to process requests but it should be reported for analysis.

## 11.41 DHCP DDNS NCR RECV NEXT ERROR

application could not initiate the next read following a request receive.

This is an error message indicating that NameChangeRequest listener could not start another read after receiving a request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

#### 11.42 DHCP DDNS NCR SEND CLOSE ERROR

DHCP-DDNS client encountered an error while closing the sender connection used to send. NameChangeRequests: %1

This is an error message that indicates the DHCP-DDNS client was unable to close the connection used to send NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the client's ability to send requests but it should be reported for analysis.

#### 11.43 DHCP\_DDNS\_NCR\_SEND\_NEXT\_ERROR

DHCP-DDNS client could not initiate the next request send following send completion: %1

This is an error message indicating that NameChangeRequest sender could not start another send after completing the send of the previous request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

# 11.44 DHCP\_DDNS\_NCR\_UDP\_CLEAR\_READY\_ERROR

NCR UDP watch socket failed to clear: %1

This is an error message that indicates the application was unable to reset the UDP NCR sender ready status after completing a send. This is programmatic error that should be reported. The application may or may not continue to operate correctly.

# 11.45 DHCP\_DDNS\_NCR\_UDP\_RECV\_CANCELED

UDP socket receive was canceled while listening for DNS Update requests

Logged at debug log level 40. This is a debug message indicating that the listening on a UDP socket for DNS update requests has been canceled. This is a normal part of suspending listening operations.

## 11.46 DHCP DDNS NCR UDP RECV ERROR

UDP socket receive error while listening for DNS Update requests: %1

This is an error message indicating that an I/O error occurred while listening over a UDP socket for DNS update requests. This could indicate a network connectivity or system resource issue.

#### 11.47 DHCP\_DDNS\_NCR\_UDP\_SEND\_CANCELED

UDP socket send was canceled while sending a DNS Update request to DHCP\_DDNS: %1

This is an informational message indicating that sending requests via UDP socket to DHCP\_DDNS has been interrupted. This is a normal part of suspending send operations.

#### 11.48 DHCP DDNS NCR UDP SEND ERROR

UDP socket send error while sending a DNS Update request: %1

This is an error message indicating that an IO error occurred while sending a DNS update request to DHCP\_DDNS over a UDP socket. This could indicate a network connectivity or system resource issue.

#### 11.49 DHCP\_DDNS\_NOT\_ON\_LOOPBACK

the DHCP-DDNS server has been configured to listen on %1 which is not the local loopback.

This is an insecure configuration supported for testing purposes only

This is a warning message issued when the DHCP-DDNS server is configured to listen at an address other than the loopback address (127.0.0.1 or ::1). It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, addresses other than the IPv4 or IPv6 loopback addresses should only be used for testing purposes. A future version of Kea will implement authentication to guard against such attacks.

## 11.50 DHCP\_DDNS\_NO\_ELIGIBLE\_JOBS

Logged at debug log level 55. This is a debug message issued when all of the queued requests represent clients for which there is an update already in progress. This may occur under normal operations but should be temporary situation.

## 11.51 DHCP DDNS NO FWD MATCH ERROR

Request ID %1: the configured list of forward DDNS domains does not contain a match for:  $\rightarrow$ %2 The request has been discarded.

This is an error message that indicates that DHCP\_DDNS received a request to update the forward DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

#### 11.52 DHCP DDNS NO MATCH

No DNS servers match FQDN %1

This is warning message issued when there are no domains in the configuration which match the cited fully qualified domain name (FQDN). The DNS Update request for the FQDN cannot be processed.

## 11.53 DHCP\_DDNS\_NO\_REV\_MATCH\_ERROR

Request ID %1: the configured list of reverse DDNS domains does not contain a match for:  $\rightarrow$ %2 The request has been discarded.

This is an error message that indicates that DHCP\_DDNS received a request to update the reverse DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

# 11.54 DHCP DDNS QUEUE MGR QUEUE FULL

application request queue has reached maximum number of entries %1

This an error message indicating that DHCP-DDNS is receiving DNS update requests faster than they can be processed. This may mean the maximum queue needs to be increased, the DHCP-DDNS clients are simply generating too many requests too quickly, or perhaps upstream DNS servers are experiencing load issues.

# 11.55 DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_RECEIVE

Request ID %1: received and queued a request.

Logged at debug log level 55. This is an informational message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive a request has received a request and queued it for further processing.

#### 11.56 DHCP DDNS QUEUE MGR RECONFIGURING

application is reconfiguring the queue manager

Logged at debug log level 40. This is an informational message indicating that DHCP\_DDNS is reconfiguring the queue manager as part of normal startup or in response to a new configuration.

#### 11.57 DHCP\_DDNS\_QUEUE\_MGR\_RECOVERING

application is attempting to recover from a queue manager IO error

This is an informational message indicating that DHCP\_DDNS is attempting to restart the queue manager after it suffered an IO error while receiving requests.

#### 11.58 DHCP DDNS QUEUE MGR RECV ERROR

application's queue manager was notified of a request receive error by its listener.

This is an error message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive requests encountered an IO error. There should be corresponding log messages from the listener layer with more details. This may indicate a network connectivity or system resource issue.

## 11.59 DHCP\_DDNS\_QUEUE\_MGR\_RESUME\_ERROR

application could not restart the queue manager, reason: %1

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be restarted after stopping due to a full receive queue. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that is no longer unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

# 11.60 DHCP\_DDNS\_QUEUE\_MGR\_RESUMING

application is resuming listening for requests now that the request queue size has →reached %1 of a maximum %2 allowed

This is an informational message indicating that DHCP\_DDNS, which had stopped accepting new requests, has processed enough entries from the receive queue to resume accepting requests.

## 11.61 DHCP DDNS QUEUE MGR STARTED

application's queue manager has begun listening for requests.

Logged at debug log level 0. This is a debug message indicating that DHCP\_DDNS's Queue Manager has successfully started and is now listening for NameChangeRequests.

#### 11.62 DHCP\_DDNS\_QUEUE\_MGR\_START\_ERROR

application could not start the queue manager, reason: %1

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be started. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that are unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

# 11.63 DHCP\_DDNS\_QUEUE\_MGR\_STOPPED

application's queue manager has stopped listening for requests.

Logged at debug log level 40. This is a debug message indicating that DHCP\_DDNS's Queue Manager has stopped listening for NameChangeRequests. This may be because of normal event such as reconfiguration or as a result of an error. There should be log messages preceding this one to indicate why it has stopped.

## 11.64 DHCP DDNS QUEUE MGR STOPPING

application is stopping the queue manager for %1

Logged at debug log level 0. This is an informational message indicating that DHCP\_DDNS is stopping the queue manager either to reconfigure it or as part of application shutdown.

# 11.65 DHCP\_DDNS\_QUEUE\_MGR\_STOP\_ERROR

application encountered an error stopping the queue manager: %1

This is an error message indicating that DHCP\_DDNS encountered an error while trying to stop the queue manager. This error is unlikely to occur or to impair the application's ability to function but it should be reported for analysis.

## 11.66 DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_HANDLER\_ERROR

application's queue manager request receive handler experienced an unexpected exception  $\rightarrow$ %1:

This is an error message indicating that an unexpected error occurred within the DHCP\_DDNS's Queue Manager request receive completion handler. This is most likely a programmatic issue that should be reported. The application may recover on its own.

## 11.67 DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_STOP

application's queue manager receive was

aborted unexpectedly while queue manager state is: %1 This is an error message indicating that DHCP\_DDNS's Queue Manager request receive was unexpected interrupted. Normally, the read is receive is only interrupted as a normal part of stopping the queue manager. This is most likely a programmatic issue that should be reported.

#### 11.68 DHCP DDNS REMOVE FAILED

DHCP\_DDNS Request ID %1: Transaction outcome: %2

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry removals have failed. The precise reason for the failure should be documented in preceding log entries.

# 11.69 DHCP\_DDNS\_REMOVE\_SUCCEEDED

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping removals which were received and accepted by an appropriate DNS server.

# 11.70 DHCP\_DDNS\_REQUEST\_DROPPED

Request ID %1: Request contains no enabled update requests and will be dropped: %2

Logged at debug log level 55. This is a debug message issued when DHCP\_DDNS receives a request which does not contain updates in a direction that is enabled. In other words, if only forward updates are enabled and request is received that asks only for reverse updates then the request is dropped.

## 11.71 DHCP\_DDNS\_REVERSE\_REMOVE\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing 

→reverse address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

#### 11.72 DHCP DDNS REVERSE REMOVE BUILD FAILURE

```
DNS Request ID %1: update message to remove a reverse DNS entry could not be constructed. \rightarrow from this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

## 11.73 DHCP\_DDNS\_REVERSE\_REMOVE\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a reverse mapping remove for → FQDN %2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse mapping remove. The application will retry against the same server or others as appropriate.

## 11.74 DHCP DDNS REVERSE REMOVE REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to remove the reverse

→mapping for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.75 DHCP\_DDNS\_REVERSE\_REMOVE\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while_ removing reverse address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.76 DHCP\_DDNS\_REVERSE\_REMOVE\_TIMEOUT

DHCP\_DDNS Request ID %1: timed out waiting for a response to reverse mapping remove for  $\rightarrow$  FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a reverse mapping remove. The application will retry against the same server or others as appropriate.

#### 11.77 DHCP\_DDNS\_REVERSE\_REPLACE\_BAD\_DNSCLIENT\_STATUS

DHCP\_DDNS Request ID %1: received an unknown DNSClient status: %2, while replacing → reverse address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

#### 11.78 DHCP DDNS REVERSE REPLACE BUILD FAILURE

DNS Request ID %1: update message to replace a reverse DNS entry could not be →constructed from this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

# 11.79 DHCP\_DDNS\_REVERSE\_REPLACE\_IO\_ERROR

DHCP\_DDNS Request ID %1: encountered an IO error sending a reverse mapping replacement  $_{\!\!\!\!-}$  for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse mapping replacement. The application will retry against the same server or others as appropriate.

# 11.80 DHCP\_DDNS\_REVERSE\_REPLACE\_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to replace the reverse → mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.81 DHCP DDNS REVERSE REPLACE RESP CORRUPT

DHCP\_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while\_ replacing reverse address mapping for FQDN, %3

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

#### 11.82 DHCP DDNS REVERSE REPLACE TIMEOUT

DHCP\_DDNS Request ID %1: timed out waiting for a response to reverse mapping replacement →for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a reverse mapping replacement. The application will retry against the same server or others as appropriate.

#### 11.83 DHCP DDNS REV REQUEST IGNORED

Request ID %1: Reverse updates are disabled, the reverse portion of request will be ignored: %2

Logged at debug log level 55. This is a debug message issued when reverse DNS updates are disabled and DHCP DDNS receives an update request containing a reverse DNS update. The reverse update will not performed.

## 11.84 DHCP DDNS RUN EXIT

application is exiting the event loop

Logged at debug log level 0. This is a debug message issued when the DHCP-DDNS server exits its event lo

# 11.85 DHCP\_DDNS\_SHUTDOWN\_COMMAND

application received shutdown command with args: %1

Logged at debug log level 0. This is a debug message issued when the application has been instructed to shut down by the controller.

## 11.86 DHCP DDNS STARTED

Kea DHCP-DDNS server version %1 started

This informational message indicates that the DHCP-DDNS server has processed all configuration information and is ready to begin processing. The version is also printed.

#### 11.87 DHCP\_DDNS\_STARTING\_TRANSACTION

Request ID %1:

Logged at debug log level 50. This is a debug message issued when DHCP-DDNS has begun a transaction for a given request.

#### 11.88 DHCP DDNS STATE MODEL UNEXPECTED ERROR

Request ID %1: application encountered an unexpected error while carrying out a\_ →NameChangeRequest: %2

This is error message issued when the application fails to process a NameChangeRequest correctly. Some or all of the DNS updates requested as part of this update did not succeed. This is a programmatic error and should be reported.

## 11.89 DHCP\_DDNS\_TRANS\_SEND\_ERROR

Request ID %1: application encountered an unexpected error while attempting to send a  $\rightarrow$  DNS update: %2

This is error message issued when the application is able to construct an update message but the attempt to send it suffered an unexpected error. This is most likely a programmatic error, rather than a communications issue. Some or all of the DNS updates requested as part of this request did not succeed.

## 11.90 DHCP\_DDNS\_UDP\_SENDER\_WATCH\_SOCKET\_CLOSE\_ERROR

watch socket failed to close: %1

This is an error message that indicates the application was unable to close the inbound or outbound side of a NCR sender's watch socket. While technically possible the error is highly unlikely to occur and should not impair the application's ability to process requests.

# 11.91 DHCP\_DDNS\_UNCAUGHT\_NCR\_RECV\_HANDLER\_ERROR

unexpected exception thrown from the application receive completion handler: %1

This is an error message that indicates that an exception was thrown but not caught in the application's request receive completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the application may or may not continue operating normally.

#### 11.92 DHCP DDNS UPDATE REQUEST SENT

Request ID %1: %2 to server: %3

Logged at debug log level 50. This is a debug message issued when DHCP\_DDNS sends a DNS request to a DNS server.

**CHAPTER** 

**TWELVE** 

**EVAL** 

## 12.1 EVAL\_DEBUG\_AND

%1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that two values are popped from the value stack. Then are then combined via logical and and the result is pushed onto the value stack.

#### 12.2 EVAL DEBUG BRANCH

Branching to %1

Logged at debug log level 55. This debug message indicates that an unconditional branch is performed to the displayed target.

# 12.3 EVAL DEBUG CONCAT

%1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that the two strings are being popped off of the stack. They are then concatenated and the resulting string is pushed onto the stack. The strings are displayed in hex.

# 12.4 EVAL\_DEBUG\_EQUAL

%1: Popping %2 and %3 pushing result %4

Logged at debug log level 55. This debug message indicates that the two strings are being popped off of the value stack and the result of comparing them is being pushed onto the value stack. The strings are displayed in hex.

## 12.5 EVAL DEBUG HEXSTRING

%1: Pushing hex string %2

Logged at debug log level 55. This debug message indicates that the given binary string is being pushed onto the value stack. The string is displayed in hex.

#### 12.6 EVAL\_DEBUG\_IFELSE\_FALSE

%1: Popping %2 (false) and %3, leaving %4

Logged at debug log level 55. This debug message indicates that the condition is false so the iftrue branch value is removed and the ifelse branch value is left on the value stack.

#### 12.7 EVAL DEBUG IFELSE TRUE

%1: Popping %2 (true) and %3, leaving %4

Logged at debug log level 55. This debug message indicates that the condition is true so the ifelse branch value is removed and the iftrue branch value is left on the value stack.

#### 12.8 EVAL DEBUG INT16TOTEXT

%1: Pushing Int16 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 16 bit integer.

# 12.9 EVAL\_DEBUG\_INT32TOTEXT

%1: Pushing Int32 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 32 bit integer.

## 12.10 EVAL\_DEBUG\_INT8TOTEXT

%1: Pushing Int8 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents an 8 bit integer.

166 Chapter 12. EVAL

## 12.11 EVAL DEBUG IPADDRESS

%1: Pushing IPAddress %2

Logged at debug log level 55. This debug message indicates that the given binary string is being pushed onto the value stack. This represents either an IPv4 or IPv6 address. The string is displayed in hex.

#### 12.12 EVAL DEBUG IPADDRESSTOTEXT

%1: Pushing IPAddress %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents either an IPv4 or IPv6 address.

#### 12.13 EVAL DEBUG LCASE

%1: Popping string %2 and pushing converted value to lower case %3

Logged at debug log level 55. This debug message indicates that the given string representation is being converted to lower case and pushed onto the value stack.

#### 12.14 EVAL\_DEBUG\_MATCH

Matching '%1' on %2, result %3

Logged at debug log level 55. This debug message indicates that the given regular expression was matched with the popped value. The result was pushed onto the value stack.

# 12.15 EVAL\_DEBUG\_MATCH\_ERROR

Matching '%1' on %2 raised an error: %3

This error message indicates that an error occurred while evaluating the given regular expression against the popped value.

# 12.16 EVAL\_DEBUG\_MEMBER

%1: Checking membership of '%2', pushing result %3

Logged at debug log level 55. This debug message indicates that the membership of the packet for the client class was checked.

## 12.17 EVAL DEBUG NOT

#### %1: Popping %2 pushing %3

Logged at debug log level 55. This debug message indicates that the first value is popped from the value stack, negated and then pushed onto the value stack. The string is displayed in text.

#### 12.18 EVAL\_DEBUG\_OPTION

#### %1: Pushing option %2 with value %3

Logged at debug log level 55. This debug message indicates that the given string representing the value of the requested option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The option code may be for either an option or a sub-option as requested in the classification statement.

#### 12.19 EVAL\_DEBUG\_OR

#### %1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that two values are popped from the value stack. Then are then combined via logical or and the result is pushed onto the value stack. The string is displayed in text.

## 12.20 EVAL\_DEBUG\_PKT

#### %1: Pushing PKT meta data %2 with value %3

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested meta data is being pushed onto the value stack. The string is displayed in hex at the exception of interface name.

## 12.21 EVAL\_DEBUG\_PKT4

#### %1: Pushing PKT4 field %2 with value %3

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

168 Chapter 12. EVAL

#### 12.22 EVAL DEBUG PKT6

%1: Pushing PKT6 field %2 with value %3

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

#### 12.23 EVAL\_DEBUG\_POP\_AND\_BRANCH\_FALSE

Value is false: branching to %1

Logged at debug log level 55. This debug message indicates that a branch on false condition is performed to the displayed target.

#### 12.24 EVAL DEBUG POP OR BRANCH FALSE

Value is false: keeping it and branching to %1

Logged at debug log level 55. This debug message indicates that a branch on false condition is performed to the displayed target.

#### 12.25 EVAL\_DEBUG\_POP\_OR\_BRANCH\_TRUE

Value is true: keeping it and branching to %1

Logged at debug log level 55. This debug message indicates that a branch on true condition is performed to the displayed target.

# 12.26 EVAL\_DEBUG\_RELAY6

%1: Pushing PKT6 relay field %2 nest %3 with value %4

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

# 12.27 EVAL\_DEBUG\_RELAY6\_RANGE

%1: Pushing PKT6 relay field %2 nest %3 with value %4

Logged at debug log level 55. This debug message is generated if the nest field is out of range. The empty string will always be the value pushed onto the stack.

## 12.28 EVAL DEBUG SPLIT

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that three values are being popped from the stack and a result is being pushed onto the stack. The values being popped are the field, delimiter and string. The result is the extracted field which is pushed onto the stack. The strings are displayed in hex.

#### 12.29 EVAL DEBUG SPLIT DELIM EMPTY

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the delimiter popped from the stack was empty and so the result will be the entire string. The field, delimiter and string are still popped from the stack and the result is still pushed.

## 12.30 EVAL\_DEBUG\_SPLIT\_EMPTY

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The field, delimiter and string are still popped from the stack and the result is still pushed.

# 12.31 EVAL\_DEBUG\_SPLIT\_FIELD\_OUT\_OF\_RANGE

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the field is either less than one or larger than the number of fields in the string popped from the stack. The result will be empty. The field, delimiter and string are still popped from the stack and the result is still pushed.

## 12.32 EVAL\_DEBUG\_STRING

%1: Pushing text string %2

Logged at debug log level 55. This debug message indicates that the given text string is being pushed onto the value stack. The string is displayed in text.

170 Chapter 12. EVAL

#### 12.33 EVAL DEBUG SUBSTRING

%1: Popping length %2, start %3, string %4 pushing result %5

Logged at debug log level 55. This debug message indicates that three values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the starting point and length of a substring to extract from the given string. The resulting string is pushed onto the stack. The strings are displayed in hex.

#### 12.34 EVAL DEBUG SUBSTRING EMPTY

%1: Popping length %2, start %3, string %4 pushing result %5

Logged at debug log level 55. This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The start, length and string are still popped from the stack and the result is still pushed.

#### 12.35 EVAL\_DEBUG\_SUBSTRING\_RANGE

%1: Popping length %2, start %3, string %4 pushing result %5

Logged at debug log level 55. This debug message indicates that the value of start is outside of the string and an empty result will be pushed onto the stack. The start, length and string are still popped from the stack and the result is still pushed. The strings are displayed in hex.

## 12.36 EVAL\_DEBUG\_SUB\_OPTION

%1: Pushing option %2 sub-option %3 with value %4

This debug message indicates that the given string representing the value of the requested sub-option of the requested parent option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The codes are the parent option and the sub-option codes as requested in the classification statement.

# 12.37 EVAL\_DEBUG\_SUB\_OPTION\_NO\_OPTION

%1: Requested option %2 sub-option %3, but the parent option is not present, pushing\_ -result %4

This debug message indicates that the parent option was not found. The codes are the parent option and the sub-option codes as requested in the classification statement.

## 12.38 EVAL\_DEBUG\_TOHEXSTRING

%1: Popping binary value %2 and separator %3, pushing result %4

Logged at debug log level 55. This debug message indicates that two values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the binary value to convert and the separator. The binary value is converted to its hexadecimal string representation and pushed onto the stack. The binary value is displayed in hex.

#### 12.39 EVAL DEBUG UCASE

%1: Popping string %2 and pushing converted value to upper case %3

Logged at debug log level 55. This debug message indicates that the given string representation is being converted to upper case and pushed onto the value stack.

## 12.40 EVAL\_DEBUG\_UINT16TOTEXT

%1: Pushing UInt16 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 16 bit unsigned integer.

## 12.41 EVAL\_DEBUG\_UINT32TOTEXT

%1: Pushing UInt32 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 32 bit unsigned integer.

## 12.42 EVAL\_DEBUG\_UINT8TOTEXT

%1: Pushing UInt8 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents an 8 bit unsigned integer.

172 Chapter 12. EVAL

## 12.43 EVAL DEBUG VENDOR CLASS DATA

%1: Data %2 (out of %3 received) in vendor class found, pushing result '%4'

Logged at debug log level 55. This debug message indicates that vendor class option was found and passed enterpriseid checks and has sufficient number of data chunks. The total number of chunks and value pushed are reported as debugging aid.

#### 12.44 EVAL DEBUG VENDOR CLASS DATA NOT FOUND

%1: Requested data index %2, but option with enterprise-id %3 has only %4 data tuple(s),  $_{\!\!\!\!\!-}$  pushing result '%5'

Logged at debug log level 55. This debug message indicates that vendor class option was found and passed enterprise-id checks, but does not have sufficient number of data chunks. Note that the index starts at 0, so there has to be at least (index + 1) data chunks.

#### 12.45 EVAL DEBUG VENDOR CLASS ENTERPRISE ID

%1: Pushing enterprise-id %2 as result 0x%3

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found and its enterprise-id is being reported.

# 12.46 EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID\_MISMATCH

%1: Was looking for %2, option had %3, pushing result '%4'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found, but has different enterprise-id than specified in the expression.

## 12.47 EVAL\_DEBUG\_VENDOR\_CLASS\_EXISTS

%1: Option with enterprise-id %2 found, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found.

## 12.48 EVAL DEBUG VENDOR CLASS NO OPTION

%1: Option with code %2 missing, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was not found.

## 12.49 EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID

%1: Pushing enterprise-id %2 as result 0x%3

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found and its enterprise-id is being reported.

# 12.50 EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID\_MISMATCH

%1: Was looking for %2, option had %3, pushing result '%4'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found, but has different enterprise-id than specified in the expression.

# 12.51 EVAL\_DEBUG\_VENDOR\_EXISTS

%1: Option with enterprise-id %2 found, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found.

174 Chapter 12. EVAL

**CHAPTER** 

#### **THIRTEEN**

#### **FLEX**

## 13.1 FLEX\_OPTION\_LOAD\_ERROR

loading Flex Option hooks library failed: %1

This error message indicates an error during loading the Flex Option hooks library. The details of the error are provided as argument of the log message.

#### 13.2 FLEX OPTION PROCESS ADD

Added the option code %1 with value %2

Logged at debug log level 40. This debug message is printed when an option was added into the response packet. The option code and the value (between quotes if printable, in hexadecimal if not) are provided.

# 13.3 FLEX OPTION PROCESS CLIENT CLASS

Skip processing of the option code %1 for class '%2'

Logged at debug log level 40. This debug message is printed when the processing for an option is skipped because the query does not belongs to the client class. The option code and the client class name are provided.

# 13.4 FLEX\_OPTION\_PROCESS\_ERROR

An error occurred processing query %1: %2

This error message indicates an error during processing of a query by the Flex Option hooks library. The client identification information from the query and the details of the error are provided as arguments of the log message.

## 13.5 FLEX OPTION PROCESS REMOVE

Removed option code %1

Logged at debug log level 40. This debug message is printed when an option was removed from the response packet. The option code is provided.

# 13.6 FLEX\_OPTION\_PROCESS\_SUB\_ADD

Added the sub-option code %1 in option code %2 with value %3

Logged at debug log level 40. This debug message is printed when an sub-option was added into the response packet. The sub-option and container option codes, and the value (between quotes if printable, in hexadecimal if not) are provided.

## 13.7 FLEX\_OPTION\_PROCESS\_SUB\_CLIENT\_CLASS

Skip processing of the sub-option code %1 in option code %2 for class '%3'

Logged at debug log level 40. This debug message is printed when the processing for a sub-option is skipped because the query does not belongs to the client class. The sub-option and container option codes, and the client class name are provided.

## 13.8 FLEX\_OPTION\_PROCESS\_SUB\_REMOVE

Removed sub-option code %1 in option code %2

Logged at debug log level 40. This debug message is printed when a sub-option was removed from the response packet. The sub-option and container option codes are provided.

# 13.9 FLEX\_OPTION\_PROCESS\_SUB\_SUPERSEDE

Supersedes the sub-option code %1 in option code %2 with value %3

Logged at debug log level 40. This debug message is printed when a sub-option was superseded into the response packet. The sub-option and container option codes, and the value (between quotes if printable, in hexadecimal if not) are provided.

176 Chapter 13. FLEX

# 13.10 FLEX\_OPTION\_PROCESS\_SUPERSEDE

Supersedes the option code %1 with value %2

Logged at debug log level 40. This debug message is printed when an option was superseded into the response packet. The option code and the value (between quotes if printable, in hexadecimal if not) are provided.

## 13.11 FLEX\_OPTION\_PROCESS\_VENDOR\_ID\_MISMATCH

Skip processing of vendor option code %1 with vendor id %2 not matching wanted %3

Logged at debug log level 40. This debug message is printed when a sub-option of a vendor option is processed but vendor ids do not match. The code of the vendor option and the two vendor ids are provided.

178 Chapter 13. FLEX

**CHAPTER** 

#### **FOURTEEN**

**FUZZ** 

# 14.1 FUZZ\_DATA\_READ

read %1 byte(s) from AFL via stdin

Logged at debug log level 50. A debug message output to indicate how much data has been received from the fuzzer via stdin

# 14.2 FUZZ\_INIT\_COMPLETE

fuzz initialization complete: interface %1, address %2, port %3, max loops %4

An informational message output when the fuzzing initialization function has completed successfully. The parameters listed are those which must be/can be set via environment variables.

# 14.3 FUZZ\_INIT\_FAIL

fuzz initialization failure, reason: %1

An error message reported if the fuzzing initialization failed. The reason for the failure is given in the message.

# 14.4 FUZZ\_READ\_FAIL

error reading input from fuzzer: %1

This error is reported if the read of data from the fuzzer (which is received over stdin) fails, or if a read returns zero bytes. If this occurs, the thread will sleep for a short period before retrying the read. The message includes the reason for the failure.

## 14.5 FUZZ\_SEND

sent %1 byte(s) to the socket connected to the Kea interface

Logged at debug log level 50. A debug message stating that the sendto() call in the main fuzzing function has successfully completed and reporting the number of bytes sent. This call sends data received from AFL to the port on which Kea is listening.

#### 14.6 FUZZ SEND ERROR

failed to send data to Kea input socket: %1

This error will be reported if the sendto() call in the fuzzing thread (which sends data received from AFL to the socket on which Kea is listening) fails. The reason for the failure is given in the message. The fuzzing code will attempt to continue from this, but it may cause the fuzzing process to fail.

## 14.7 FUZZ\_SHORT\_SEND

expected to send %1 bytes to Kea input socket but only sent %2

A warning message that is output if the sendto() call (used to send data from the fuzzing thread to the main Kea processing) did not send as much data as that read from AFL. This may indicate a problem in the underlying communications between the fuzzing thread and the main Kea processing.

180 Chapter 14. FUZZ

**CHAPTER** 

#### **FIFTEEN**

HA

### 15.1 HA\_BUFFER4\_RECEIVE\_FAILED

buffer4\_receive callout failed: %1

This error message is issued when the callout for the buffer4\_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

### 15.2 HA BUFFER4 RECEIVE NOT FOR US

%1: dropping query to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

## 15.3 HA BUFFER4 RECEIVE PACKET OPTIONS SKIPPED

an error unpacking an option, caused subsequent options to be skipped: %1

Logged at debug log level 40. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

# 15.4 HA\_BUFFER4\_RECEIVE\_UNPACK\_FAILED

failed to parse query from %1 to %2, received over interface %3, reason: %4

Logged at debug log level 40. This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the buffer4\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

#### 15.5 HA BUFFER6 RECEIVE FAILED

buffer6\_receive callout failed: %1

This error message is issued when the callout for the buffer6\_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

### 15.6 HA\_BUFFER6\_RECEIVE\_NOT\_FOR\_US

%1: dropping query to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

## 15.7 HA\_BUFFER6\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED

an error unpacking an option, caused subsequent options to be skipped: %1

Logged at debug log level 40. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv6 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

## 15.8 HA BUFFER6 RECEIVE UNPACK FAILED

failed to parse query from %1 to %2, received over interface %3, reason: %4

Logged at debug log level 40. This debug message is issued when received DHCPv6 query is malformed and can't be parsed by the buffer6\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

## 15.9 HA\_COMMAND\_PROCESSED\_FAILED

command\_processed callout failed: %1

This error message is issued when the callout for the command\_processed hook point failed. The argument contains a reason for the error.

## 15.10 HA\_COMMUNICATION\_INTERRUPTED

%1: communication with %2 is interrupted

This warning message is issued by the server which discovered that the communication to the active partner has been interrupted for a time period longer than the configured heartbeat-delay time. At this stage the server starts the failover procedure by monitoring the DHCP traffic sent to the partner and checking whether the partner server responds to this traffic. If the max-unacked-clients value is set to 0 such verification is disabled in which case the server will transition to the partner-down state.

### 15.11 HA COMMUNICATION INTERRUPTED CLIENT4

%1: new client %2 attempting to get a lease from the partner

This informational message is issued when the surviving server observes a DHCP packet sent to the partner with which the communication is interrupted. The client whose packet is observed is not yet considered "unacked" because the secs field value does not exceed the configured threshold specified with max-ack-delay.

### 15.12 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT4\_UNACKED

%1: partner server failed to respond to %2, %3 clients unacked so far, %4 clients left. →before transitioning to the partner-down state

This informational message is issued when the surviving server determines that its partner failed to respond to the DHCP query and that this client is considered to not be served by the partner. The surviving server counts such clients and if the number of such clients exceeds the max-unacked-clients threshold, the server will transition to the partner-down state. The first argument specifies the relationship name. The second argument contains client identification information. The third argument specifies the number of clients to which the server has failed to respond. The forth argument specifies the number of additional clients which, if not provisioned, will cause the server to transition to the partner-down state.

## 15.13 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT6

%1: new client %2 attempting to get a lease from the partner

This informational message is issued when the surviving server observes a DHCP packet sent to the partner with which the communication is interrupted. The client whose packet is observed is not yet considered "unacked" because the elapsed time option value does not exceed the configured threshold specified with max-ack-delay. The sole argument specifies client identification information.

# 15.14 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT6\_UNACKED

%1: partner server failed to respond to %2, %3 clients unacked so far, %4 clients left ⇒before transitioning to the partner-down state

This informational message is issued when the surviving server determines that its partner failed to respond to the DHCP query and that this client is considered to not be served by the partner. The surviving server counts such clients and if the number of such clients exceeds the max-unacked-clients threshold, the server will transition to the partner-down state. The first argument specifies the relationship name. The second argument contains client identification information. The third argument specifies the number of clients to which the server has failed to respond. The forth argument specifies the number of additional clients which, if not provisioned, will cause the server to transition to the partner-down state.

## 15.15 HA\_CONFIGURATION\_FAILED

failed to configure High Availability hooks library: %1

This error message is issued when there is an error configuring the HA hooks library. The argument provides the detailed error message.

### 15.16 HA\_CONFIGURATION\_SUCCESSFUL

HA hook library has been successfully configured

This informational message is issued when the HA hook library configuration parser successfully parses and validates the new configuration.

## 15.17 HA\_CONFIG\_AUTO\_FAILOVER\_DISABLED

%1: auto-failover disabled

This warning message is issued to indicate that the 'auto-failover' parameter was administratively disabled for the specified server. The server will not automatically start serving partner's scope when the partner failure is detected. The server administrator will need to enable this scope manually by sending appropriate ha-scopes command.

# 15.18 HA\_CONFIG\_DHCP\_MT\_DISABLED

%1: HA multi-threading has been disabled, it cannot be enabled when Kea global multi
→threading is disabled

This informational message is issued when HA configuration has enabled multi-threading while Kea global configuration has multi-threading disabled.

## 15.19 HA\_CONFIG\_DHCP\_MT\_DISABLED\_AND\_KEA\_MT\_ENABLED

%1: HA multi-threading is disabled while Kea global multi-threading is enabled which →most likely cause performance degradation.

This warning message is issued when HA configuration has disabled multi-threading while Kea global configuration has multi-threading enabled. This will likely cause performance degradation.

### 15.20 HA CONFIG LEASE SYNCING DISABLED

%1: lease database synchronization between HA servers is disabled

This warning message is issued when the lease database synchronization is administratively disabled. This is valid configuration if the leases are replicated between lease databases via some other mechanism, e.g. SQL database replication.

### 15.21 HA\_CONFIG\_LEASE\_SYNCING\_DISABLED\_REMINDER

%1: bypassing SYNCING state because lease database synchronization is administratively\_

→disabled

This informational message is issued as a reminder that lease database synchronization is administratively disabled and therefore the server transitions directly from the "waiting" to "ready" state.

## 15.22 HA CONFIG LEASE UPDATES AND SYNCING DIFFER

%1: unusual configuration where "send-lease-updates": %2 and "sync-leases": %3

This warning message is issued when the configuration values of the send-lease-updates and sync-leases parameters differ. This may be a valid configuration but is unusual. Normally, if the lease database with replication is in use, both values are set to false. If a lease database without replication is in use (e.g. memfile), both values are set to true. Providing different values for those parameters means that an administrator either wants the server to not synchronize leases upon startup but later send lease updates to the partner, or the lease database should be synchronized upon startup, but no lease updates are later sent as a result of leases allocation.

# 15.23 HA\_CONFIG\_LEASE\_UPDATES\_DISABLED

%1: lease updates will not be generated

This warning message is issued when the lease updates are administratively disabled. This is valid configuration if the leases are replicated to the partner's database via some other mechanism, e.g. SQL database replication.

## 15.24 HA\_CONFIG\_LEASE\_UPDATES\_DISABLED\_REMINDER

This informational message is issued as a reminder that the lease updates are administratively disabled and will not be issued in the HA state to which the server has transitioned. The sole argument specifies the state into which the server has transitioned.

### 15.25 HA\_CONFIG\_SYSTEM\_MT\_UNSUPPORTED

%1: HA multi-threading has been disabled, auto-detection of thread support reports 0

This informational message is issued when HA multi-threading configuration has specified auto-detection for the number of threads to use and the system reports the number of concurrent threads as 0. If you know your system can support multiple threads, then you may override this condition by specifying explicit values for http-listener-threads and http-client-threads.

### 15.26 HA\_CONTINUE\_HANDLER\_FAILED

ha-continue command failed: %1

This error message is issued to indicate that the ha-continue command handler failed while processing the command. The argument provides the reason for failure.

## 15.27 HA DEINIT OK

unloading High Availability hooks library successful

This informational message indicates that the High Availability hooks library has been unloaded successfully.

## 15.28 HA\_DHCP4\_START\_SERVICE\_FAILED

failed to start DHCPv4 HA services in dhcp4\_srv\_configured callout: %1

This error message is issued when an attempt to start High Availability services for the DHCPv4 server failed in the dhcp4\_srv\_configured callout. This is internal server error and a bug report should be created.

### 15.29 HA\_DHCP6\_START\_SERVICE\_FAILED

failed to start DHCPv6 HA services in dhcp6\_srv\_configured callout: %1

This error message is issued when an attempt to start High Availability services for the DHCPv6 server failed in the dhcp6\_srv\_configured callout. This is internal server error and a bug report should be created.

#### 15.30 HA\_DHCP\_DISABLE\_COMMUNICATIONS\_FAILED

%1: failed to send request to disable DHCP service of %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-disable command. The first argument specifies the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

#### 15.31 HA DHCP DISABLE FAILED

%1: failed to disable DHCP service of %2: %3

This warning message indicates that a peer returned an error status code in response to a dhcp-disable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.32 HA\_DHCP\_ENABLE\_COMMUNICATIONS\_FAILED

%1: failed to send request to enable DHCP service of %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-enable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.33 HA\_DHCP\_ENABLE\_FAILED

%1: failed to enable DHCP service of %2: %3

This warning message indicates that a peer returned an error status code in response to a dhcp-enable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

### 15.34 HA\_HEARTBEAT\_COMMUNICATIONS\_FAILED

%1: failed to send heartbeat to %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending a heartbeat. This is a first sign that the peer may be down. The server will keep trying to send heartbeats until it considers that communication is interrupted.

### 15.35 HA HEARTBEAT FAILED

%1: heartbeat to %2 failed: %3

This warning message indicates that a peer returned an error status code in response to a heartbeat. This is the sign that the peer may not function properly. The server will keep trying to send heartbeats until it considers that communication is interrupted.

#### 15.36 HA\_HEARTBEAT\_HANDLER\_FAILED

heartbeat command failed: %1

This error message is issued to indicate that the heartbeat command handler failed while processing the command. The argument provides the reason for failure.

## 15.37 HA\_HIGH\_CLOCK\_SKEW

%1: %2, please synchronize clocks!

This warning message is issued when the clock skew between the active servers exceeds 30 seconds. The HA service continues to operate but may not function properly, especially for low lease lifetimes. The administrator should should synchronize the clocks, e.g. using NTP. If the clock skew exceeds 60 seconds, the HA service will terminate.

## 15.38 HA\_HIGH\_CLOCK\_SKEW\_CAUSED\_TERMINATION

%1: %2, causing HA service to terminate

This warning message is issued when the clock skew between the active servers exceeds 60 seconds. The HA service stops. The servers will continue to respond to the DHCP queries but won't exchange lease updates or send heartbeats. The administrator is required to synchronize the clocks and then restart the servers to resume the HA service.

## 15.39 **HA\_INIT\_OK**

loading High Availability hooks library successful

This informational message indicates that the High Availability hooks library has been loaded successfully. Enjoy!

### 15.40 HA INVALID PARTNER STATE COMMUNICATION RECOVERY

%1: partner is in the communication-recovery state unexpectedly

This warning message is issued when a partner is in the communication-recovery state, and this server is not running in the load balancing mode. The server may only transition to the communication-recovery state when it runs in the load balancing mode. The HA mode of both servers must be the same.

### 15.41 HA INVALID PARTNER STATE HOT STANDBY

%1: partner is in the hot-standby state unexpectedly

This warning message is issued when a partner is in the hot-standby state, and this server is not running in the hot standby mode. The server may only transition to the hot-standby state when it runs in the hot standby mode. The HA mode of both servers must be the same.

## 15.42 HA\_INVALID\_PARTNER\_STATE\_LOAD\_BALANCING

%1: partner is in the load-balancing state unexpectedly

This warning message is issued when a partner is in the load-balancing state, and this server is not running in the load balancing mode. The server may only transition to the load-balancing state when it runs in the load balancing mode. The HA mode of both servers must be the same.

## 15.43 HA\_LEASE4\_SERVER\_DECLINE\_FAILED

lease4\_server\_decline callout failed: %1

This error message is issued when the callout for the lease4\_server\_decline hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

15.39. HA INIT OK 189

### 15.44 HA\_LEASES4\_COMMITTED\_FAILED

leases4\_committed callout failed: %1

This error message is issued when the callout for the leases4\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

### 15.45 HA LEASES4 COMMITTED NOTHING TO UPDATE

%1: leases4\_committed callout was invoked without any leases

Logged at debug log level 40. This debug message is issued when the "leases4\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

## 15.46 HA\_LEASES4\_COMMITTED\_NO\_RELATIONSHIP

%1: HA relationship not found: %2

This error message is issued when the relationship for the server name provided by the earlier callouts was not found in the HA configuration. This error is highly unlikely and rather indicates some programming error. The first argument is the client identification information. The second argument holds a more detailed error message.

## 15.47 HA LEASES6 COMMITTED FAILED

leases6\_committed callout failed: %1

This error message is issued when the callout for the leases6\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

## 15.48 HA\_LEASES6\_COMMITTED\_NOTHING\_TO\_UPDATE

%1: leases6\_committed callout was invoked without any leases

Logged at debug log level 40. This debug message is issued when the "leases6\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

## 15.49 HA\_LEASES6\_COMMITTED\_NO\_RELATIONSHIP

%1: HA relationship not found: %2

This error message is issued when the relationship for the server name provided by the earlier callouts was not found in the HA configuration. This error is highly unlikely and rather indicates some programming error. The first argument is the client identification information. The second argument holds a more detailed error message.

### 15.50 HA LEASES BACKLOG COMMUNICATIONS FAILED

%1: failed to communicate with %2 while sending lease updates backlog: %3

This error message is issued to indicate that there was a communication error with a partner server while sending outstanding lease updates after resuming connection. The third argument contains a reason for the error.

#### 15.51 HA\_LEASES\_BACKLOG\_FAILED

%1: failed to send lease updates backlog to %2: %3

This error message is issued to indicate that sending lease updates backlog to a partner server failed. The lease updates backlog is sent to the partner after resuming temporarily broken communication with the partner. If this operation fails the server will transition to the waiting state to initiate full lease database synchronization.

## 15.52 HA\_LEASES\_BACKLOG\_NOTHING\_TO\_SEND

%1: no leases in backlog after communication recovery

This informational message is issued when there are no outstanding leases to be sent after communication recovery with a partner. This means that the communication interruption was short enough that no DHCP clients obtained any leases from the server while it was in the communication-recovery state. The server may now transition to the load-balancing state.

## 15.53 HA\_LEASES\_BACKLOG\_START

%1: starting to send %2 outstanding lease updates to %3

This informational message is issued when the server starts to send outstanding lease updates to the partner after resuming communications. The first argument specifies the local server's name. The second argument specifies the number of lease updates to be sent. The name of the partner is specified with the third argument.

### 15.54 HA\_LEASES\_BACKLOG\_SUCCESS

%1: sending lease updates backlog to %2 successful in %3

This informational message is issued when server successfully completes sending lease updates backlog to the partner. The first argument specifies the local server's name. The second argument specifies the name of the remote server. The third argument specifies the duration of this operation.

### 15.55 HA LEASES SYNC APPLIED LEASES

%1: applied %2 leases received from the partner in the local lease database

This informational message outputs the number of leases received from the partner during the database synchronization and applied in the local database. A typical case when only some leases are applied is when the server has multiple relationships and some of the received leases belong to another relationship. The first argument specifies this server name. The second argument specifies the number of applied leases.

#### 15.56 HA LEASES SYNC COMMUNICATIONS FAILED

%1: failed to communicate with %2 while syncing leases: %3

This error message is issued to indicate that there was a communication error with a partner server while trying to fetch leases from its lease database. The argument contains a reason for the error.

## 15.57 HA LEASES SYNC FAILED

%1: failed to synchronize leases with %2: %3

This error message is issued to indicate that there was a problem while parsing a response from the server from which leases have been fetched for local database synchronization. The third argument contains a reason for the error.

## 15.58 HA\_LEASES\_SYNC\_LEASE\_PAGE\_RECEIVED

%1: received %2 leases from %3

This informational message is issued during lease database synchronization to indicate that a bulk of leases have been received. The first argument specifies the local server's name. The second argument holds the count of leases received. The third argument specifies the partner server name.

### 15.59 HA\_LEASE\_SYNC\_FAILED

%1: synchronization failed for lease: %2, reason: %3

This warning message is issued when creating or updating a lease in the local lease database fails. The lease information in the JSON format is provided as a first argument. The third argument provides a reason for the failure.

### 15.60 HA\_LEASE\_SYNC\_STALE\_LEASE4\_SKIP

%1: skipping stale lease %2 in subnet %3

Logged at debug log level 40. This debug message is issued during lease database synchronization, when fetched IPv4 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies the local server's name. The second argument specifies leased address. The third argument specifies a subnet to which the lease belongs.

#### 15.61 HA LEASE SYNC STALE LEASE6 SKIP

%1: skipping stale lease %2 in subnet %3

Logged at debug log level 40. This debug message is issued during lease database synchronization, when fetched IPv6 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies the local server's name. The second argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

## 15.62 HA\_LEASE\_UPDATES\_DISABLED

%1: lease updates will not be sent to the partner while in %2 state

This informational message is issued to indicate that lease updates will not be sent to the partner while the server is in the current state. The second argument specifies the server's current state name. The lease updates are still sent to the backup servers if they are configured but any possible errors in communication with the backup servers are ignored.

# 15.63 HA\_LEASE\_UPDATES\_ENABLED

%1: lease updates will be sent to the partner while in %2 state

This informational message is issued to indicate that lease updates will be sent to the partner while the server is in the current state. The second specifies the server's current state name.

### 15.64 HA\_LEASE\_UPDATE\_COMMUNICATIONS\_FAILED

%1: failed to send lease update %2 to %3: %4

This warning message indicates that there was a problem in communication with a HA peer while processing a DHCP client query and sending lease update. The client's DHCP message will be dropped.

#### 15.65 HA\_LEASE\_UPDATE\_CONFLICT

%1: lease update %2 sent to %3 returned conflict status code: %4

This warning message indicates that the partner returned a conflict status code in response to a lease update. The client's DHCP message will be dropped. If the server is configured to track conflicting lease updates, it may eventually transition to the terminated state when the configured threshold is exceeded.

### 15.66 HA\_LEASE\_UPDATE\_CREATE\_UPDATE\_FAILED\_ON\_PEER

%1: failed to create or update the lease having type %2 for address %3, reason: %4

This informational message is issued when one of the leases failed to be created or updated on the HA peer while processing the lease updates sent from this server. This may indicate an issue with communication between the peer and its lease database.

## 15.67 HA LEASE UPDATE DELETE FAILED ON PEER

%1: failed to delete the lease having type %2 for address %3, reason: %4

This informational message is issued when one of the leases failed to delete on the HA peer while processing lease updates sent from this server. Typically, the lease fails to delete when it doesn't exist in the peer's database.

## 15.68 HA\_LEASE\_UPDATE\_FAILED

%1: lease update %2 sent to %3 failed: %4

This warning message indicates that a peer returned an error status code in response to a lease update. The client's DHCP message will be dropped.

## 15.69 HA\_LEASE\_UPDATE\_REJECTS\_CAUSED\_TERMINATION

%1: too many rejected lease updates cause the HA service to terminate

This error message is issued when the HA service terminates because the number of lease updates for which a conflict status code was returned by the partner exceeds the limit set with max-rejected-lease-updates configuration parameter.

#### 15.70 HA\_LOAD\_BALANCING\_DUID\_MISSING

%1: load balancing failed for the DHCPv6 message (transaction id: %2) because DUID is → missing

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv6 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

### 15.71 HA\_LOAD\_BALANCING\_IDENTIFIER\_MISSING

%1: load balancing failed for the DHCPv4 message (transaction id: %2) because HW address\_
→and client identifier are missing

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv4 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

## 15.72 HA LOCAL DHCP DISABLE

local DHCP service is disabled while the %1 is in the %2 state

This informational message is issued to indicate that the local DHCP service is disabled because the server remains in a state in which the server should not respond to DHCP clients, e.g. the server hasn't synchronized its lease database. The first argument specifies server name. The second argument specifies server's state.

## 15.73 HA\_LOCAL\_DHCP\_ENABLE

local DHCP service is enabled while the %1 is in the %2 state

This informational message is issued to indicate that the local DHCP service is enabled because the server remains in a state in which it should respond to the DHCP clients. The first argument specifies server name. The second argument specifies server's state.

#### 15.74 HA MAINTENANCE CANCEL HANDLER FAILED

ha-maintenance-cancel command failed: %1

This error message is issued to indicate that the ha-maintenance-cancel command handler failed while processing the command. The argument provides the reason for failure.

### 15.75 HA\_MAINTENANCE\_NOTIFY\_CANCEL\_COMMUNICATIONS\_FAILED

%1: failed to send ha-maintenance-notify to %2 in attempt to cancel its maintenance: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the hamaintenance-notify command with the cancel flag set to true. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

### 15.76 HA\_MAINTENANCE\_NOTIFY\_CANCEL\_FAILED

%1: error returned while processing ha-maintenance-notify by %2 in attempt to cancel its\_ →maintenance: %3

This warning message indicates that a peer returned an error status code in response to a ha-maintenance-notify command with the cancel flag set to true. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.77 HA\_MAINTENANCE\_NOTIFY\_COMMUNICATIONS\_FAILED

%1: failed to send ha-maintenance-notify to %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the hamaintenance-notify command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.78 HA\_MAINTENANCE\_NOTIFY\_FAILED

%1: error returned while processing ha-maintenance-notify by %2: %3

This warning message indicates that a peer returned an error status code in response to a ha-maintenance-notify command. The first argument provides the remote server's name. The second argument provides a reason for failure.

## 15.79 HA\_MAINTENANCE\_NOTIFY\_HANDLER\_FAILED

ha-maintenance-notify command failed: %1

This error message is issued to indicate that the ha-maintenance-notify command handler failed while processing the command. The argument provides the reason for failure.

### 15.80 HA\_MAINTENANCE\_SHUTDOWN\_SAFE

%1: the server can now be shutdown for maintenance as the partner has taken over the\_ —DHCP traffic

This informational message is displayed after the server transitions to the in-maintenance state. This server no longer responds to any DHCP queries and its partner - in partner-in-maintenance state - has taken over the DHCP traffic. When the server in-maintenance state is shut down, the partner moves to the partner-down state immediately.

### 15.81 HA\_MAINTENANCE\_STARTED

%1: the server is now in the partner-in-maintenance state and the partner is in-maintenance state

This informational message is displayed when the server receiving the ha-maintenance-start command transitions to the partner-in-maintenance state. The server does it after sending the ha-maintenance-notify to its partner to put the partner in the in-maintenance state. From now on, the server in the partner-in-maintenance state will be responding to all queries and the partner will respond to no queries. The partner may be safely shut down for maintenance in which case this server will automatically transition from the partner-in-maintenance state to the partner-down state.

## 15.82 HA\_MAINTENANCE\_STARTED\_IN\_PARTNER\_DOWN

%1: the server is now in the partner-down mode as a result of requested maintenance

This informational message is displayed when the server receiving the ha-maintenance-start command transitions to the partner-down state because it was unable to communicate with the partner while receiving the command. It is assumed that in such situation the partner is already offline for the maintenance. Note that in this case the normal failover procedure does not take place. The server does not wait for a heartbeat to fail several times, nor it monitors the DHCP traffic for not responded queries. In the maintenance case the server transitions to the partner-down state when it first encounters a communication problem with the partner.

## 15.83 HA\_MAINTENANCE\_START\_HANDLER\_FAILED

ha-maintenance-start command failed: %1

This error message is issued to indicate that the ha-maintenance-start command handler failed while processing the command. The argument provides the reason for failure.

### 15.84 HA MISSING CONFIGURATION

high-availability parameter not specified for High Availability hooks library

This error message is issued to indicate that the configuration for the High Availability hooks library hasn't been specified. The 'high-availability' parameter must be specified for the hooks library to load properly.

### 15.85 HA PAUSE CLIENT LISTENER FAILED

%1: pausing multi-threaded HTTP processing failed: %2

This error message is emitted when attempting to pause HA's HTTP client and listener threads. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

### 15.86 HA\_PAUSE\_CLIENT\_LISTENER\_ILLEGAL

%1: pausing multi-threaded HTTP processing failed: %2

This error message is emitted when attempting to pause HA's HTTP client or listener thread pools from a worker thread. This error indicates that a command run on the listener threads is trying to use a critical section which would result in a dead-lock.

## 15.87 HA\_RESET\_COMMUNICATIONS\_FAILED

%1: failed to send ha-reset command to %2: %3

This warning message indicates a problem with communication with a HA peer while sending the ha-reset command. The first argument specifies the local server name. The second argument specifies a remote server name. The third argument specifies a reason for failure.

### 15.88 HA RESET FAILED

%1: failed to reset HA state machine of %2: %3

This warning message indicates that a peer returned an error status code in response to the ha-reset command. The first argument specifies a local server name. The second argument specifies a remote server name. The third argument specifies a reason for failure.

### 15.89 HA RESET HANDLER FAILED

ha-reset command failed: %1

This error message is issued to indicate that the ha-reset command handler failed while processing the command. The argument provides the reason for failure.

### 15.90 HA\_RESUME\_CLIENT\_LISTENER\_FAILED

%1: resuming multi-threaded HTTP processing failed: %2

This error message is emitted when attempting to resume HA's HTTP client and listener threads. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

## 15.91 HA\_SCOPES\_HANDLER\_FAILED

ha-scopes command failed: %1

This error message is issued to indicate that the ha-scopes command handler failed while processing the command. The argument provides reason for the failure.

## 15.92 HA\_SERVICE\_STARTED

%1: started high availability service in %2 mode as %3 server

This informational message is issued when the HA service is started as a result of server startup or reconfiguration. The first argument specifies a local server name. The second argument provides the HA mode. The third argument specifies the role of this server instance in this configuration.

### 15.93 HA\_STATE\_MACHINE\_CONTINUED

%1: state machine is un-paused

This informational message is issued when the HA state machine is un-paused. This unlocks the server from the current state. It may transition to any other state if it needs to do so, e.g. 'partner-down' if its partner appears to be offline. The server may also remain in the current state if the HA setup state warrants such behavior.

### 15.94 HA STATE MACHINE PAUSED

%1: state machine paused in state %2

This informational message is issued when the HA state machine is paused. HA state machine may be paused in certain states specified in the HA hooks library configuration. When the state machine is paused, the server remains in the given state until it is explicitly unpaused (via the ha-continue command). If the state machine is paused, the server operates normally but cannot transition to any other state.

#### 15.95 HA STATE TRANSITION

%1: server transitions from %2 to %3 state, partner state is %4

This informational message is issued when the server transitions to a new state as a result of some interaction (or lack of thereof) with its partner. The arguments specify local server name, initial server state, new server state and the partner's state.

## 15.96 HA STATE TRANSITION PASSIVE BACKUP

%1: server transitions from %2 to %3 state

This informational message is issued when the server in passive-backup mode transitions to a new state. The arguments specify local server name, initial server state and a new server state.

## 15.97 HA\_SUBNET4\_SELECT\_FAILED

subnet4\_select callout failed: %1

This error message is issued when the callout for the subnet4\_select hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

## 15.98 HA\_SUBNET4\_SELECT\_INVALID\_HA\_SERVER\_NAME

%1: invalid ha-server-name value for subnet %2

This error message is issued when the received DHCPv4 query is dropped by this server because the specified haserver-name value in the subnet's user-context has non-string type or is empty. It is a server's misconifiguration. The first argument is the client identification information. The second argument is a subnet prefix.

### 15.99 HA SUBNET4 SELECT NOT FOR US

%1: dropping query in relationship %2 to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when a remote primary server is operational. The first argument is the client identification information. The second argument is the relationship name.

## 15.100 HA\_SUBNET4\_SELECT\_NO\_RELATIONSHIP\_FOR\_SUBNET

%1: HA relationship not found for %2

This error message is issued when the received DHCPv4 query is dropped by this server because the server could not find a relationship matching the specified ha-server-name for a subnet. The server name matches no relationship specified in the HA configuration. A typical reason for it is a typo. The first argument is the client identification information. The second argument is the relationship name.

# 15.101 HA\_SUBNET4\_SELECT\_NO\_RELATIONSHIP\_SELECTOR\_FOR\_SUBNET

%1: unable to determine HA relationship because selected subnet %2 lacks the ha-server-  $\hookrightarrow$ name

This error message is issued when the received DHCPv4 query is dropped by this server because it was unable to determine the HA relationship to which the received query belongs. If there are multiple relationships, it is required to specify ha-server-name value in the user-context at the subnet or shared network level for each subnet and/or shared network. The server uses them as a relationship selector. If these selectors are unspecified for any of the subnets it is a configuration error. The first argument is the client identification information. The second argument is a subnet prefix.

## 15.102 HA\_SUBNET4\_SELECT\_NO\_SUBNET\_SELECTED

%1: unable to determine HA relationship because no subnet has been selected for the∟ ⇔client

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it could not select a subnet for this client. Selecting the subnet is required to find a suitable HA relationship. This message is not emitted when the server has only one relationship. The argument is the client identification information.

### 15.103 HA\_SUBNET6\_SELECT\_FAILED

subnet6\_select callout failed: %1

This error message is issued when the callout for the subnet6\_select hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

### 15.104 HA\_SUBNET6\_SELECT\_INVALID\_HA\_SERVER\_NAME

%1: invalid ha-server-name value for subnet %2

This error message is issued when the received DHCPv6 query is dropped by this server because the specified haserver-name value in the subnet's user-context has non-string type or is empty. It is a server's misconifiguration. The first argument is the client identification information. The second argument is a subnet prefix.

### 15.105 HA\_SUBNET6\_SELECT\_NOT\_FOR\_US

%1: dropping query in relationship %2 to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when a remote primary server is operational. The first argument is the client identification information. The second argument is the relationship name.

## 15.106 HA\_SUBNET6\_SELECT\_NO\_RELATIONSHIP\_FOR\_SUBNET

%1: HA relationship not found for %2

This error message is issued when the received DHCPv6 query is dropped by this server because the server could not find a relationship matching the specified ha-server-name for a subnet. The server name matches no relationship specified in the HA configuration. A typical reason for it is a typo. The first argument is the client identification information. The second argument is the relationship name.

## 15.107 HA\_SUBNET6\_SELECT\_NO\_RELATIONSHIP\_SELECTOR\_FOR\_SUBNET

%1: unable to determine HA relationship because selected subnet %2 lacks the ha-server-  $\hookrightarrow$ name

This error message is issued when the received DHCPv6 query is dropped by this server because it was unable to determine the HA relationship to which the received query belongs. If there are multiple relationships, it is required to specify ha-server-name value in the user-context at the subnet or shared network level for each subnet and/or shared network. The server uses them as a relationship selector. If these selectors are unspecified for any of the subnets it is a configuration error. The first argument is the client identification information. The second argument is a subnet prefix.

# 15.108 HA\_SUBNET6\_SELECT\_NO\_SUBNET\_SELECTED

%1: unable to determine HA relationship because no subnet has been selected for the client

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it could not select a subnet for this client. Selecting the subnet is required to find a suitable HA relationship. This message is not emitted when the server has only one relationship. The argument is the client identification information.

## 15.109 HA\_SYNC\_COMPLETE\_NOTIFY\_COMMUNICATIONS\_FAILED

%1: failed to send ha-sync-complete-notify to %2: %3

This warning message indicates that there was a problem in communication with an HA peer while sending the hasync-complete-notify command. The first argument provides a local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.110 HA\_SYNC\_COMPLETE\_NOTIFY\_FAILED

%1: error processing ha-sync-complete-notify command on %2: %3

This warning message indicates that a peer returned an error status code in response to the ha-sync-complete-notify command. The first argument provides a local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.111 HA\_SYNC\_COMPLETE\_NOTIFY\_HANDLER\_FAILED

ha-sync-complete-notify command failed: %1

This error message is issued to indicate that the ha-sync-complete-notify command handler failed while processing the command. The argument provides the reason for failure.

## 15.112 HA\_SYNC\_FAILED

%1: lease database synchronization with %2 failed: %3

This error message is issued to indicate that the lease database synchronization failed. The first argument provides the local server's name. The second argument provides the partner server's name. The third argument provides a reason for the failure.

### 15.113 HA\_SYNC\_HANDLER\_FAILED

ha-sync command failed: %1

This error message is issued to indicate that the ha-sync command handler failed while processing the command. The argument provides the reason for failure.

### 15.114 HA SYNC START

%1: starting lease database synchronization with %2

This informational message is issued when the server starts lease database synchronization with a partner. The arguments specify the local and remote server names.

### 15.115 HA SYNC SUCCESSFUL

%1: lease database synchronization with %2 completed successfully in %3

This informational message is issued when the server successfully completed lease database synchronization with the partner. The first argument specifies local server name. The second argument specifies the name of the partner server. The third argument specifies the duration of the synchronization.

## 15.116 HA\_TERMINATED

HA %1: service terminated due to an unrecoverable condition. Check previous error → message(s), address the problem and restart!

This error message is issued to indicate that the HA service has been stopped due to an unacceptable condition (e.g. too large of a clock skew). The exact cause should appear in a previous error message. Address the condition reported then restart the servers to resume service.

## 15.117 HA\_TERMINATED\_PARTNER\_DID\_NOT\_RESTART

%1: service is terminating because the terminated partner was not restarted within %2.

→minutes

This warning message is issued to indicate that the HA service is terminating because partner server is in the terminated state and was not restarted within an expected time frame. The terminated servers should be restarted after correcting the problem that caused the termination. They can be restarted sequentially but the duration between the restarts should not be too long. If it is long it may mean that the restart of one of the servers was unintentional (e.g., power outage). If the restarted server remains in the waiting state it cannot serve DHCP clients. Moving to the terminated state at least allows for responding to the DHCP traffic.

**CHAPTER** 

#### SIXTEEN

#### **HOOKS**

### 16.1 HOOKS\_ALL\_CALLOUTS\_DEREGISTERED

hook library at index %1 removed all callouts on hook %2

Logged at debug log level 55. A debug message issued when all callouts on the specified hook registered by the library with the given index were removed. This is similar to the HOOKS\_CALLOUTS\_REMOVED message (and the two are likely to be seen together), but is issued at a lower-level in the hook framework.

### 16.2 HOOKS CALLOUTS BEGIN

begin all callouts for hook %1

Logged at debug log level 45. This debug message is issued when callout manager begins to invoke callouts for the hook. The argument specifies the hook name.

## 16.3 HOOKS CALLOUTS COMPLETE

completed callouts for hook %1 (total callouts duration: %2)

Logged at debug log level 45. This debug message is issued when callout manager has completed execution of all callouts for the particular hook. The arguments specify the hook name and total execution time for all callouts in milliseconds.

## 16.4 HOOKS\_CALLOUTS\_REMOVED

callouts removed from hook %1 for library %2

Logged at debug log level 45. This is a debug message issued during library unloading. It notes that one of more callouts registered by that library have been removed from the specified hook. This is similar to the HOOKS\_DEREGISTER\_ALL\_CALLOUTS message (and the two are likely to be seen together), but is issued at a higher-level in the hook framework.

#### 16.5 HOOKS CALLOUT CALLED

hooks library with index %1 has called a callout on hook %2 that has address %3 (callout\_duration: %4)

Logged at debug log level 55. Only output at a high debugging level, this message indicates that a callout on the named hook registered by the library with the given index (in the list of loaded libraries) has been called and returned a success state. The address of the callout is given in the message. The message includes the callout execution time in milliseconds.

### 16.6 HOOKS\_CALLOUT\_DEREGISTERED

hook library at index %1 deregistered a callout on hook %2

Logged at debug log level 55. A debug message issued when all instances of a particular callouts on the hook identified in the message that were registered by the library with the given index have been removed.

#### 16.7 HOOKS CALLOUT ERROR

error returned by callout on hook %1 registered by library with index %2 (callout \_\_ →address %3) (callout duration %4)

If a callout returns an error status when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

## 16.8 HOOKS CALLOUT EXCEPTION

exception thrown by callout on hook %1 registered by library with index %2 (callout →address %3): %4 (callout duration: %5)

If a callout throws an exception when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

# 16.9 HOOKS\_CALLOUT\_REGISTRATION

hooks library with index %1 registering callout for hook '%2'

Logged at debug log level 45. This is a debug message, output when a library (whose index in the list of libraries (being) loaded is given) registers a callout.

### 16.10 HOOKS\_CLOSE\_ERROR

failed to close hook library %1: %2

Kea has failed to close the named hook library for the stated reason. Although this is an error, this should not affect the running system other than as a loss of resources. If this error persists, you should restart Kea.

### 16.11 HOOKS\_HOOK\_LIST\_RESET

the list of hooks has been reset

This is a message indicating that the list of hooks has been reset. While this is usual when running the Kea test suite, it should not be seen when running Kea in a production environment. If this appears, please report a bug through the usual channels.

#### 16.12 HOOKS\_INCORRECT\_VERSION

hook library %1 is at version %2, require version %3

Kea has detected that the named hook library has been built against a version of Kea that is incompatible with the version of Kea running on your system. It has not loaded the library. This is most likely due to the installation of a new version of Kea without rebuilding the hook library. A rebuild and re-install of the library should fix the problem in most cases.

## 16.13 HOOKS\_LIBRARY\_CLOSED

hooks library %1 successfully closed

This information message is issued when a user-supplied hooks library has been successfully closed.

## 16.14 HOOKS\_LIBRARY\_LOADED

hooks library %1 successfully loaded

This information message is issued when a user-supplied hooks library has been successfully loaded.

### 16.15 HOOKS LIBRARY LOADING

loading hooks library %1

Logged at debug log level 40. This is a debug message output just before the specified library is loaded. If the action is successfully, it will be followed by the HOOKS\_LIBRARY\_LOADED informational message.

#### 16.16 HOOKS\_LIBRARY\_MULTI\_THREADING\_COMPATIBLE

hooks library %1 reports its multi-threading compatibility as %2

Logged at debug log level 45. A debug message issued when the "multi\_threading\_compatible" function was called. The returned value (0 means not compatible, others compatible) is displayed.

### 16.17 HOOKS LIBRARY MULTI THREADING NOT COMPATIBLE

hooks library %1 is not compatible with multi-threading

When multi-threading is enabled and the library is not compatible (either because the "multi\_threading\_compatible" function returned 0 or was not implemented) this error message is issued. The library must be removed from the configuration or the multi-threading disabled.

### 16.18 HOOKS\_LIBRARY\_UNLOADED

hooks library %1 successfully unloaded

This information message is issued when a user-supplied hooks library has been successfully unloaded.

## 16.19 HOOKS\_LIBRARY\_UNLOADING

unloading library %1

Logged at debug log level 40. This is a debug message called when the specified library is being unloaded. If all is successful, it will be followed by the HOOKS\_LIBRARY\_UNLOADED informational message.

## 16.20 HOOKS\_LIBRARY\_VERSION

hooks library %1 reports its version as %2

Logged at debug log level 45. A debug message issued when the version check on the hooks library has succeeded.

## 16.21 HOOKS\_LOAD\_ERROR

'load' function in hook library %1 returned error %2

A "load" function was found in the library named in the message and was called. The function returned a non-zero status (also given in the message) which was interpreted as an error. The library has been unloaded and no callouts from it will be installed.

### 16.22 HOOKS LOAD EXCEPTION

'load' function in hook library %1 threw an exception

A "load" function was found in the library named in the message and was called. The function threw an exception (an error indication) during execution, which is an error condition. The library has been unloaded and no callouts from it will be installed.

#### 16.23 HOOKS\_LOAD\_FRAMEWORK\_EXCEPTION

'load' function in hook library %1 threw an exception: reason %2

A "load" function was found in the library named in the message and was called. Either the hooks framework or the function threw an exception (an error indication) during execution, which is an error condition; the cause of the exception is recorded in the message. The library has been unloaded and no callouts from it will be installed.

## 16.24 HOOKS LOAD SUCCESS

'load' function in hook library %1 returned success

Logged at debug log level 40. This is a debug message issued when the "load" function has been found in a hook library and has been successfully called.

## 16.25 HOOKS\_MULTI\_THREADING\_COMPATIBLE\_EXCEPTION

'multi\_threading\_compatible' function in hook library %1 threw an exception

This error message is issued if the multi\_threading\_compatible() function in the specified hooks library was called and generated an exception. The library is considered unusable and will not be loaded.

### 16.26 HOOKS\_NO\_LOAD

no 'load' function found in hook library %1

Logged at debug log level 40. This is a debug message saying that the specified library was loaded but no function called "load" was found in it. Providing the library contained some "standard" functions (i.e. functions with the names of the hooks for the given server), this is not an issue.

### 16.27 HOOKS NO UNLOAD

no 'unload' function found in hook library %1

Logged at debug log level 40. This is a debug message issued when the library is being unloaded. It merely states that the library did not contain an "unload" function.

#### 16.28 HOOKS NO VERSION

no 'version' function found in hook library %1

The shared library named in the message was found and successfully loaded, but Kea did not find a function named "version" in it. This function is required and should return the version of Kea against which the library was built. The value is used to check that the library was built against a compatible version of Kea. The library has not been loaded.

## 16.29 HOOKS\_OPEN\_ERROR

failed to open hook library %1: %2

Kea failed to open the specified hook library for the stated reason. The library has not been loaded. Kea will continue to function, but without the services offered by the library.

## 16.30 HOOKS\_STD\_CALLOUT\_REGISTERED

hooks library %1 registered standard callout for hook %2 at address %3

Logged at debug log level 45. This is a debug message, output when the library loading function has located a standard callout (a callout with the same name as a hook point) and registered it. The address of the callout is indicated.

### 16.31 HOOKS\_UNLOAD\_ERROR

'unload' function in hook library %1 returned error %2

During the unloading of a library, an "unload" function was found. It was called, but returned an error (non-zero) status, resulting in the issuing of this message. The unload process continued after this message and the library has been unloaded.

### 16.32 HOOKS UNLOAD EXCEPTION

'unload' function in hook library %1 threw an exception

During the unloading of a library, an "unload" function was found. It was called, but in the process generated an exception (an error indication). The unload process continued after this message and the library has been unloaded.

### 16.33 HOOKS\_UNLOAD\_FRAMEWORK\_EXCEPTION

'unload' function in hook library %1 threw an exception, reason %2

During the unloading of a library, an "unload" function was found. It was called, but in the process either it or the hooks framework generated an exception (an error indication); the cause of the error is recorded in the message. The unload process continued after this message and the library has been unloaded.

## 16.34 HOOKS\_UNLOAD\_SUCCESS

'unload' function in hook library %1 returned success

Logged at debug log level 40. This is a debug message issued when an "unload" function has been found in a hook library during the unload process, called, and returned success.

212

**CHAPTER** 

#### **SEVENTEEN**

#### **HOSTS**

### 17.1 HOSTS\_BACKENDS\_REGISTERED

the following host backend types are available: %1

This informational message lists all possible host backends that could be used in hosts-database[s].

### 17.2 HOSTS BACKEND DEREGISTER

deregistered host backend type: %1

Logged at debug log level 40. This debug message is issued when a backend factory was deregistered. It is no longer possible to use host backend of this type.

## 17.3 HOSTS\_BACKEND\_REGISTER

registered host backend type: %1

Logged at debug log level 40. This debug message is issued when a backend factory was successfully registered. It is now possible to use host backend of this type.

## 17.4 HOSTS\_CFG\_ADD\_HOST

add the host for reservations: %1

Logged at debug log level 40. This debug message is issued when new host (with reservations) is added to the server's configuration. The argument describes the host and its reservations in detail.

## 17.5 HOSTS\_CFG\_CACHE\_HOST\_DATA\_SOURCE

get host cache data source: %1

This informational message is issued when a host cache data source is detected by the host manager.

# 17.6 HOSTS\_CFG\_CLOSE\_HOST\_DATA\_SOURCE

Closing host data source: %1

Logged at debug log level 40. This is a normal message being printed when the server closes host data source connection.

#### 17.7 HOSTS CFG DEL

deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and address %4

Logged at debug log level 40. This debug message is issued when reservations are deleted for the specified subnet and address. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the IP address.

### 17.8 HOSTS\_CFG\_DEL4

deleted %1 host(s) for subnet id %2 and identifier %3

Logged at debug log level 40. This debug message is issued when IPv4 reservations are deleted for the specified subnet and identifier. The first argument specifies how many hosts have been deleted. The second argument is the subnet identifier. The third argument is the identifier.

## 17.9 HOSTS\_CFG\_DEL6

deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and identifier %4

Logged at debug log level 40. This debug message is issued when IPv6 reservations are deleted for the specified subnet and identifier. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the identifier.

214 Chapter 17. HOSTS

### 17.10 HOSTS CFG DEL ALL SUBNET4

deleted all %1 host(s) for subnet id %2

Logged at debug log level 40. This debug message is issued when all IPv4 reservations are deleted for the specified subnet. The first argument specifies how many reservations have been deleted. The second argument is the subnet identifier.

### 17.11 HOSTS CFG DEL ALL SUBNET6

deleted all %1 host(s) having %2 IPv6 reservation(s) for subnet id %3

Logged at debug log level 40. This debug message is issued when all IPv6 reservations are deleted for the specified subnet. The first argument specifies how many hosts have been deleted. The second argument specifies how many IPv6 (addresses and prefixes) reservations have been deleted. The third argument is the subnet identifier.

### 17.12 HOSTS\_CFG\_GET\_ALL

get all hosts with reservations

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts.

## 17.13 HOSTS\_CFG\_GET\_ALL\_ADDRESS4

get all hosts with reservations for IPv4 address %1

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv4 address, from the configuration. The argument specifies the IPv4 address used to search the hosts.

## 17.14 HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_COUNT

using address %1, found %2 host(s)

Logged at debug log level 45. This debug message logs the number of hosts found using the specified IPv4 address. The arguments specify the IPv4 address used and the number of hosts found respectively.

### 17.15 HOSTS CFG GET ALL ADDRESS4 HOST

using address %1 found host: %2

Logged at debug log level 55. This debug message is issued when found host with the reservation for the specified IPv4 address. The arguments specify the IPv4 address and the detailed description of the host found.

#### 17.16 HOSTS\_CFG\_GET\_ALL\_ADDRESS6

get all hosts with reservations for IPv6 address %1

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv6 address, from the configuration. The argument specifies the IPv6 address used to search the hosts.

### 17.17 HOSTS CFG GET ALL ADDRESS6 COUNT

using address %1, found %2 host(s)

Logged at debug log level 45. This debug message logs the number of hosts found using the specified IPv6 address. The arguments specify the IPv6 address used and the number of hosts found respectively.

### 17.18 HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_HOST

using address %1 found host: %2

Logged at debug log level 55. This debug message is issued when found host with the reservation for the specified IPv6 address. The arguments specify the IPv6 address and the detailed description of the host found.

# 17.19 HOSTS\_CFG\_GET\_ALL\_COUNT

found %1 host(s)

Logged at debug log level 45. This debug message include the details of the host found. The argument specifies the number of hosts found.

## 17.20 HOSTS\_CFG\_GET\_ALL\_HOST

found host: %1

Logged at debug log level 55. This debug message includes the details of the host found. The argument specifies found host details.

216 Chapter 17. HOSTS

## 17.21 HOSTS CFG GET ALL HOSTNAME

get all hosts with reservations for hostname %1

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts with the specific hostname. The argument specifies hostname.

## 17.22 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_COUNT

using hostname %1, found %2 host(s)

Logged at debug log level 45. This debug message include the details of the host found using the hostname. The arguments specify hostname and the number of hosts found respectively.

### 17.23 HOSTS CFG GET ALL HOSTNAME HOST

using hostname %1, found host: %2

Logged at debug log level 55. This debug message includes the details of the host found using the hostname. The arguments specify hostname and found host details respectively.

## 17.24 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4

get all hosts with reservations for hostname %1 and IPv4 subnet %2

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts with the specific hostname connected to the specific DHCPv4 subnet. The argument specifies hostname and subnet id.

## 17.25 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_COUNT

using hostname %1 and IPv4 subnet %2, found %3 host(s)

Logged at debug log level 45. This debug message include the details of the host found using the hostname and the DHCPv4 subnet id. The arguments specify hostname, subnet id and the number of hosts found respectively.

## 17.26 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_HOST

using hostname %1 and IPv4 subnet %2, found host: %3

Logged at debug log level 55. This debug message includes the details of the host found using the hostname and the DHCPv4 subnet id. The arguments specify hostname, subnet id and found host details respectively.

## 17.27 HOSTS CFG GET ALL HOSTNAME SUBNET ID6

get all hosts with reservations for hostname %1 and IPv6 subnet %2

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts with the specific hostname connected to the specific DHCPv6 subnet. The argument specifies hostname and subnet id.

### 17.28 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_COUNT

using hostname %1 and IPv6 subnet %2, found %3 host(s)

Logged at debug log level 45. This debug message include the details of the host found using the hostname and the DHCPv6 subnet id. The arguments specify hostname, subnet id and the number of hosts found respectively.

## 17.29 HOSTS CFG GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_HOST

using hostname %1 and IPv6 subnet %2, found host: %3

Logged at debug log level 55. This debug message includes the details of the host found using the hostname and the DHCPv6 subnet id. The arguments specify hostname, subnet id and found host details respectively.

### 17.30 HOSTS\_CFG\_GET\_ALL\_IDENTIFIER

get all hosts with reservations using identifier: %1

Logged at debug log level 40. This debug message is issued when starting to retrieve reservations for all hosts identified by HW address or DUID. The argument holds both the identifier type and the value.

## 17.31 HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_COUNT

using identifier %1, found %2 host(s)

Logged at debug log level 45. This debug message logs the number of hosts found using the specified identifier. The arguments specify the identifier used and the number of hosts found respectively.

## 17.32 HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_HOST

using identifier: %1, found host: %2

Logged at debug log level 55. This debug message is issued when found host identified by the specific identifier. The arguments specify the identifier and the detailed description of the host found.

218 Chapter 17. HOSTS

## 17.33 HOSTS CFG GET ALL SUBNET ID4

get all hosts with reservations for IPv4 subnet %1

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts connected to the specific DHCPv4 subnet. The argument specifies subnet id.

# 17.34 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4\_COUNT

using IPv4 subnet %1, found %2 host(s)

Logged at debug log level 45. This debug message include the details of the host found using the DHCPv4 subnet id. The arguments specify subnet id and the number of hosts found respectively.

### 17.35 HOSTS CFG GET ALL SUBNET ID4 HOST

using IPv4 subnet %1, found host: %2

Logged at debug log level 55. This debug message includes the details of the host found using the DHCPv4 subnet id. The arguments specify subnet id and found host details respectively.

### 17.36 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6

get all hosts with reservations for IPv6 subnet %1

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts connected to the specific DHCPv6 subnet. The argument specifies subnet id.

## 17.37 HOSTS CFG GET ALL SUBNET ID6 COUNT

using IPv6 subnet %1, found %2 host(s)

Logged at debug log level 45. This debug message include the details of the host found using the DHCPv6 subnet id. The arguments specify subnet id and the number of hosts found respectively.

## 17.38 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_HOST

using IPv6 subnet %1, found host: %2

Logged at debug log level 55. This debug message includes the details of the host found using the DHCPv6 subnet id. The arguments specify subnet id and found host details respectively.

## 17.39 HOSTS CFG GET ALL SUBNET ID ADDRESS4

get all hosts with reservations for subnet id %1 and IPv4 address %2

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts having the reservation for the given IPv4 address within the given subnet. The first argument specifies subnet identifier. The second argument specifies the IPv4 address for which the reservation is to be returned.

### 17.40 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_COUNT

using IPv4 subnet %1 and IPv4 address %2, found %3 host(s)

Logged at debug log level 45. This debug message logs the number of hosts found having the reservation for the specified IPv4 address within the specified subnet. The first argument specifies the subnet identifier. The second argument specifies the reserved IPv4 address. The third argument specifies the number of hosts found.

## 17.41 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_HOST

using IPv4 subnet %1 and IPv4 address %2, found host: %3

Logged at debug log level 55. This debug message is issued when found host having the reservation for the specified IPv4 address in the specified subnet. The first argument specifies the subnet identifier. The second argument specifies the reserved IPv4 address. The third argument specifies host details.

## 17.42 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6

get all hosts with reservations for subnet id %1 and IPv6 address %2

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

## 17.43 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_COUNT

using subnet id %1 and address %2, found %3 host(s)

Logged at debug log level 45. This debug message include the details of the host found using the subnet id and address. The arguments specify subnet id, address and the number of hosts found respectively.

220 Chapter 17. HOSTS

### 17.44 HOSTS CFG GET ALL SUBNET ID ADDRESS6 HOST

using subnet id %1 and address %2, found host: %3

Logged at debug log level 55. This debug message includes the details of the host found using the subnet id and address. The arguments specify subnet id, address and the number of hosts found respectively. found host details respectively.

### 17.45 HOSTS\_CFG\_GET\_ONE\_PREFIX

get one host with reservation for prefix %1/%2

Logged at debug log level 40. This debug message is issued when starting to retrieve a host having a reservation for a specified prefix. The arguments specify a prefix and prefix length.

### 17.46 HOSTS CFG GET ONE PREFIX HOST

using prefix %1/%2, found host: %3

Logged at debug log level 55. This debug message includes the details of the host found using the specific prefix/prefix length. The arguments specify prefix, prefix length and host details respectively.

### 17.47 HOSTS\_CFG\_GET\_ONE\_PREFIX\_NULL

host not found using prefix %1/%2

Logged at debug log level 55. This debug message is issued when no host was found for a specified prefix and prefix length.

## 17.48 HOSTS CFG GET ONE SUBNET ID ADDRESS4

get one host with reservation for subnet id %1 and IPv4 address %2

Logged at debug log level 40. This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv4 address reserved. The arguments specify subnet id and IPv4 address respectively.

## 17.49 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_HOST

using subnet id %1 and address %2, found host: %3

Logged at debug log level 45. This debug message logs the details of the host found using the subnet id and IPv4 address.

## 17.50 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_NULL

host not found using subnet id %1 and address %2

Logged at debug log level 45. This debug message is issued when no host was found for the specified subnet id and IPv4 address.

## 17.51 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6

get one host with reservation for subnet id %1 and having IPv6 address %2

Logged at debug log level 40. This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

## 17.52 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_HOST

using subnet id %1 and address %2, found host: %3

Logged at debug log level 45. This debug message logs the details of the host found using the subnet id and IPv6 address.

### 17.53 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_NULL

host not found using subnet id %1 and address %2

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet if and IPv6 address.

# 17.54 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER

get one host with %1 reservation for subnet id %2, identified by %3

Logged at debug log level 40. This debug message is issued when starting to retrieve a host holding IPv4 or IPv6 reservations, which is connected to a specific subnet and is identified by a specific unique identifier. The first argument identifies if the IPv4 or IPv6 reservation is desired.

222 Chapter 17. HOSTS

## 17.55 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_HOST

using subnet id %1 and identifier %2, found host: %3

Logged at debug log level 45. This debug message includes the details of a host found using a subnet id and specific host identifier.

### 17.56 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_NULL

host not found using subnet id %1 and identifier %2

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

### 17.57 HOSTS CFG UPDATE ADD

add the host for reservations: %1

Logged at debug log level 40. This debug message is issued when a new host (with reservations) is added to the server's configuration during an update. The argument describes the host and its reservations in detail.

### 17.58 HOSTS\_CFG\_UPDATE\_DEL4

deleted %1 host(s) for subnet id %2 and identifier %3

Logged at debug log level 40. This debug message is issued when IPv4 reservations are deleted for the specified subnet and identifier during an update. The first argument specifies how many hosts have been deleted. The second argument is the subnet identifier. The third argument is the identifier.

## 17.59 HOSTS\_CFG\_UPDATE\_DEL6

deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and identifier %4

Logged at debug log level 40. This debug message is issued when IPv6 reservations are deleted for the specified subnet and identifier during an update. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the identifier.

## 17.60 HOSTS MGR ALTERNATE GET4 SUBNET ID ADDRESS4

trying alternate sources for host using subnet id %1 and address %2

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specific IPv4 address, and it is starting to search for this host in alternate host data sources.

### 17.61 HOSTS MGR ALTERNATE GET4 SUBNET ID IDENTIFIER

get one host with IPv4 reservation for subnet id %1, identified by %2

Logged at debug log level 40. This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

### 17.62 HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_HOST

using subnet id %1 and identifier %2, found in %3 host: %4

Logged at debug log level 45. This debug message includes the details of a host returned by an alternate hosts data source using a subnet id and specific host identifier.

## 17.63 HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_NULL

host not found using subnet id %1 and identifier %2

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

## 17.64 HOSTS\_MGR\_ALTERNATE\_GET6\_PREFIX

trying alternate sources for host using prefix %1/%2

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified prefix, and it is starting to search for this host in alternate host data sources.

224 Chapter 17. HOSTS

## 17.65 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_ADDRESS6

trying alternate sources for host using subnet id %1 and IPv6 address %2

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified IPv6 address, and it is starting to search for this host in alternate host data sources.

### 17.66 HOSTS MGR ALTERNATE GET6 SUBNET ID IDENTIFIER

get one host with IPv6 reservation for subnet id %1, identified by %2

Logged at debug log level 40. This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

### 17.67 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_HOST

using subnet id %1 and identifier %2, found in %3 host: %4

Logged at debug log level 45. This debug message includes the details of a host returned by an alternate host data source using a subnet id and specific host identifier.

## 17.68 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_NULL

host not found using subnet id %1 and identifier %2

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

## 17.69 HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS4

trying alternate sources for hosts using subnet id %1 and address %2

Logged at debug log level 40. This debug message is issued when the Host Manager is starting to search for hosts in alternate host data sources by subnet ID and IPv4 address.

# 17.70 HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS6

trying alternate sources for hosts using subnet id %1 and address %2

Logged at debug log level 40. This debug message is issued when the Host Manager is starting to search for hosts in alternate host data sources by subnet ID and IPv6 address.

226 Chapter 17. HOSTS

## **EIGHTEEN**

## **HTTPS**

# 18.1 HTTPS\_REQUEST\_RECEIVE\_START

start receiving request from %1

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The argument specifies the address of the remote endpoint.

228 Chapter 18. HTTPS

#### **NINETEEN**

HTTP

## 19.1 HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED

bad request received from %1: %2

Logged at debug log level 40. This debug message is issued when an HTTP client sends malformed request to the server. This includes HTTP requests using unexpected content types, including malformed JSON etc. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a detailed error message.

## 19.2 HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED\_DETAILS

detailed information about bad request received from %1:\n%2

Logged at debug log level 45. This debug message is issued when an HTTP client sends malformed request to the server. It includes detailed information about the received request rejected by the server. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a request in the textual format. The request is truncated by the logger if it is too large to be printed.

## 19.3 HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED

bad response received when communicating with %1: %2

Logged at debug log level 40. This debug message is issued when an HTTP client fails to receive a response from the server or when this response is malformed. The first argument specifies the server URL. The second argument provides a detailed error message.

## 19.4 HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED\_DETAILS

detailed information about bad response received from %1:\n%2

Logged at debug log level 45. This debug message is issued when an HTTP client receives malformed response from the server. The first argument specifies an URL of the server. The second argument provides a response in the textual format. The request is truncated by the logger if it is too large to be printed.

### 19.5 HTTP CLIENT MT STARTED

HttpClient has been started in multi-threaded mode running %1 threads

Logged at debug log level 40. This debug message is issued when a multi-threaded HTTP client instance has been created. The argument specifies the maximum number of threads.

## 19.6 HTTP\_CLIENT\_QUEUE\_SIZE\_GROWING

queue for URL: %1, now has %2 entries and may be growing too quickly

This warning message is issued when the queue of pending requests for the given URL appears to be growing more quickly than the requests can be handled. It will be emitted periodically as long as the queue size continues to grow. This may occur with a surge of client traffic creating a momentary backlog which then subsides as the surge subsides. If it happens continually then it most likely indicates a deployment configuration that cannot sustain the client load.

# 19.7 HTTP\_CLIENT\_REQUEST\_AUTHORIZED

received HTTP request authorized for '%1'

This information message is issued when the server receives with a matching authentication header. The argument provides the user id.

## 19.8 HTTP\_CLIENT\_REQUEST\_BAD\_AUTH\_HEADER

received HTTP request with malformed authentication header: %1

This information message is issued when the server receives a request with a malformed authentication header. The argument explains the problem.

230 Chapter 19. HTTP

## 19.9 HTTP\_CLIENT\_REQUEST\_NOT\_AUTHORIZED

received HTTP request with not matching authentication header

This information message is issued when the server receives a request with authentication header carrying not recognized credential: the user provided incorrect user id and/or password.

### 19.10 HTTP\_CLIENT\_REQUEST\_RECEIVED

received HTTP request from %1

Logged at debug log level 40. This debug message is issued when the server finished receiving a HTTP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

### 19.11 HTTP CLIENT REQUEST RECEIVED DETAILS

detailed information about well-formed request received from %1:\n%2

Logged at debug log level 45. This debug message is issued when the HTTP server receives a well-formed request. It includes detailed information about the received request. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides the request in the textual format. The request is truncated by the logger if it is too large to be printed.

## 19.12 HTTP\_CLIENT\_REQUEST\_SEND

sending HTTP request %1 to %2

Logged at debug log level 50. This debug message is issued when the client is starting to send a HTTP request to a server. The first argument holds basic information about the request (HTTP version number and status code). The second argument specifies a URL of the server.

## 19.13 HTTP\_CLIENT\_REQUEST\_SEND\_DETAILS

detailed information about request sent to %1:\n%2

Logged at debug log level 55. This debug message is issued right before the client sends an HTTP request to the server. It includes detailed information about the request. The first argument specifies an URL of the server to which the request is being sent. The second argument provides the request in the textual form. The request is truncated by the logger if it is too large to be printed.

## 19.14 HTTP CLIENT REQUEST TIMEOUT OCCURRED

HTTP request timeout occurred when communicating with %1

Logged at debug log level 50. This debug message is issued when the HTTP request timeout has occurred and the server is going to send a response with Http Request timeout status code.

### 19.15 HTTP\_COMMAND\_MGR\_IGNORED\_TLS\_SETUP\_CHANGES

ignore a change in TLS setup of the http control socket

The warning message is issued when the HTTP/HTTPS control socket was reconfigured with a different TLS setup but keeping the address and port. These changes are ignored because they can't be applied without opening a new socket which will conflict with the existing one.

### 19.16 HTTP COMMAND MGR SERVICE STARTED

started %1 service bound to address %2 port %3

This informational message indicates that the server has started HTTP/HTTPS service on the specified address and port for receiving control commands.

## 19.17 HTTP\_CONNECTION\_CLOSE\_CALLBACK\_FAILED

Connection close callback threw an exception

This is an error message emitted when the close connection callback registered on the connection failed unexpectedly. This is a programmatic error that should be submitted as a bug.

# 19.18 HTTP\_CONNECTION\_HANDSHAKE\_FAILED

TLS handshake with %1 failed with %2

This information message is issued when the TLS handshake failed at the server side. The client address and the error message are displayed.

232 Chapter 19. HTTP

## 19.19 HTTP\_CONNECTION\_HANDSHAKE\_START

start TLS handshake with %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts the TLS handshake with the remote endpoint. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

### 19.20 HTTP CONNECTION SHUTDOWN

shutting down HTTP connection from %1

Logged at debug log level 40. This debug message is issued when one of the HTTP connections is shut down. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 19.21 HTTP\_CONNECTION\_SHUTDOWN\_FAILED

shutting down HTTP connection failed

This error message is issued when an error occurred during shutting down a HTTP connection with a client.

### 19.22 HTTP\_CONNECTION\_STOP

stopping HTTP connection from %1

Logged at debug log level 40. This debug message is issued when one of the HTTP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 19.23 HTTP\_CONNECTION\_STOP\_FAILED

stopping HTTP connection failed

This error message is issued when an error occurred during closing a HTTP connection with a client.

## 19.24 HTTP\_CONNECTION\_WATCH\_SOCKET\_CLEAR\_ERROR

clearing connection watch socket failed: %1

This error message is issued when an error occurred during clearing the watch socket associated with a HTTP connection with a client. The error is displayed.

## 19.25 HTTP\_CONNECTION\_WATCH\_SOCKET\_CLOSE\_ERROR

closing connection watch socket failed: %1

This error message is issued when an error occurred during closing the watch socket associated with a HTTP connection with a client. The error is displayed.

### 19.26 HTTP\_CONNECTION\_WATCH\_SOCKET\_MARK\_READY\_ERROR

marking ready connection watch socket failed: %1

This error message is issued when an error occurred during marking as ready the watch socket associated with a HTTP connection with a client. The error is displayed.

### 19.27 HTTP DATA RECEIVED

received %1 bytes from %2

Logged at debug log level 55. This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

### 19.28 HTTP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED

closing persistent connection with %1 as a result of a timeout

Logged at debug log level 50. This debug message is issued when the persistent HTTP connection is being closed as a result of being idle.

## 19.29 HTTP\_PREMATURE\_CONNECTION\_TIMEOUT\_OCCURRED

premature connection timeout occurred: in transaction ? %1, transid: %2, current\_ →transid: %3

This warning message is issued when unexpected timeout occurred during the transaction. This is proven to occur when the system clock is moved manually or as a result of synchronization with a time server. Any ongoing transactions will be interrupted. New transactions should be conducted normally.

234 Chapter 19. HTTP

## 19.30 HTTP\_REQUEST\_RECEIVE\_START

start receiving request from %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

### 19.31 HTTP SERVER RESPONSE RECEIVED

received HTTP response from %1

Logged at debug log level 40. This debug message is issued when the client finished receiving an HTTP response from the server. The URL of the server is specified as an argument.

## 19.32 HTTP\_SERVER\_RESPONSE\_RECEIVED\_DETAILS

detailed information about well-formed response received from %1:\n%2

Logged at debug log level 45. This debug message is issued when the HTTP client receives a well-formed response from the server. It includes detailed information about the received response. The first argument specifies a URL of the server which sent the response. The second argument provides the response in the textual format. The response is truncated by the logger if it is too large to be printed.

## 19.33 HTTP\_SERVER\_RESPONSE\_SEND

sending HTTP response %1 to %2

Logged at debug log level 40. This debug message is issued when the server is starting to send a HTTP response to a remote endpoint. The first argument holds basic information about the response (HTTP version number and status code). The second argument specifies an address of the remote endpoint.

236 Chapter 19. HTTP

#### **TWENTY**

#### **LEASE**

### 20.1 LEASE CMDS ADD4

lease4-add command successful (address: %1)

Logged at debug log level 20. The lease4-add command has been successful. Lease IPv4 address is logged.

## 20.2 LEASE CMDS ADD4 CONFLICT

lease4-add command failed due to conflict (parameters: %1, reason: %2)

The received lease4-add is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

# 20.3 LEASE\_CMDS\_ADD4\_FAILED

lease4-add command failed (parameters: %1, reason: %2)

The lease4-add command has failed. Both the reason as well as the parameters passed are logged.

## 20.4 LEASE\_CMDS\_ADD6

lease6-add command successful (address: %1)

Logged at debug log level 20. The lease6-add command has been successful. Lease IPv6 address is logged.

## 20.5 LEASE\_CMDS\_ADD6\_CONFLICT

lease6-add command failed due to conflict (parameters: %1, reason: %2)

The received lease6-add is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

### 20.6 LEASE\_CMDS\_ADD6\_FAILED

lease6-add command failed (parameters: %1, reason: %2)

The lease6-add command has failed. Both the reason as well as the parameters passed are logged.

## 20.7 LEASE\_CMDS\_BULK\_APPLY6

lease6-bulk-apply command successful (applied addresses count: %1)

Logged at debug log level 20. The lease6-bulk-apply command has been successful. The number of applied addresses is logged.

### 20.8 LEASE CMDS BULK APPLY6 FAILED

lease6-bulk-apply command failed (parameters: %1, reason: %2)

The lease6-bulk-apply command has failed. Both the reason as well as the parameters passed are logged.

## 20.9 LEASE CMDS DEINIT OK

unloading Lease Commands hooks library successful

This info message indicates that the Lease Commands hooks library has been removed successfully.

### 20.10 LEASE\_CMDS\_DEL4

lease4-del command successful (address: %1)

Logged at debug log level 20. The attempt to delete an IPv4 lease (lease4-del command) has been successful. Lease IPv4 address is logged.

238 Chapter 20. LEASE

## 20.11 LEASE CMDS DEL4 FAILED

```
lease4-del command failed (parameters: %1, reason: %2)
```

The attempt to delete an IPv4 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

### 20.12 LEASE\_CMDS\_DEL6

```
lease4-del command successful (address: %1)
```

Logged at debug log level 20. The attempt to delete an IPv4 lease (lease4-del command) has been successful. Lease IPv6 address is logged.

### 20.13 LEASE CMDS DEL6 FAILED

```
lease6-del command failed (parameters: %1, reason: %2)
```

The attempt to delete an IPv6 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

### 20.14 LEASE CMDS GET4 FAILED

```
lease4-get command failed (parameters: %1, reason: %2)
```

The lease4-get command has failed. Both the reason as well as the parameters passed are logged.

# 20.15 LEASE\_CMDS\_GET6\_FAILED

```
lease6-get command failed (parameters: %1, reason: %2)
```

The lease4-get command has failed. Both the reason as well as the parameters passed are logged.

## 20.16 LEASE\_CMDS\_INIT\_OK

loading Lease Commands hooks library successful

This info message indicates that the Lease Commands hooks library has been loaded successfully. Enjoy!

## 20.17 LEASE CMDS RESEND DDNS4

lease4-resend-ddns command successful: %1

A request to update DNS for the requested IPv4 lease has been successfully queued for transmission to kea-dhcp-ddns.

### 20.18 LEASE\_CMDS\_RESEND\_DDNS4\_FAILED

lease4-resend-ddns command failed: %1

A request to update DNS for the requested IPv4 lease has failed. The reason for the failure is logged.

### 20.19 LEASE\_CMDS\_RESEND\_DDNS6

lease6-resend-ddns command successful: %1

A request to update DNS for the requested IPv6 lease has been successfully queued for transmission to kea-dhcp-ddns.

### 20.20 LEASE\_CMDS\_RESEND\_DDNS6\_FAILED

lease6-resend-ddns command failed: %1

A request to update DNS for the requested IPv6 lease has failed. The reason for the failure is logged.

## 20.21 LEASE\_CMDS\_UPDATE4

lease4-update command successful (address: %1)

Logged at debug log level 20. The lease4-update command has been successful. Lease IPv4 address is logged.

# 20.22 LEASE\_CMDS\_UPDATE4\_CONFLICT

lease4-update command failed due to conflict (parameters: %1, reason: %2)

The received lease4-update is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

240 Chapter 20. LEASE

## 20.23 LEASE\_CMDS\_UPDATE4\_FAILED

lease4-update command failed (parameters: %1, reason: %2)

The lease4-update command has failed. Both the reason as well as the parameters passed are logged.

### 20.24 LEASE\_CMDS\_UPDATE6

lease6-update command successful (address: %1)

Logged at debug log level 20. The lease6-update command has been successful. Lease IPv6 address is logged.

## 20.25 LEASE\_CMDS\_UPDATE6\_CONFLICT

lease6-update command failed due to conflict (parameters: %1, reason: %2)

The received lease6-update is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

### 20.26 LEASE CMDS UPDATE6 FAILED

lease6-add command failed (parameters: %1, reason: %2)

The lease6-update command has failed. Both the reason as well as the parameters passed are logged.

## 20.27 LEASE\_CMDS\_WIPE4

lease4-wipe command successful (parameters: %1)

The lease4-wipe command has been successful. Parameters of the command are logged.

## 20.28 LEASE CMDS WIPE4 DEPRECATED

lease4-wipe command is deprecated and it will be removed in the future.

The lease4-wipe command is deprecated and it will be removed in the future.

# 20.29 LEASE\_CMDS\_WIPE4\_FAILED

lease4-wipe command failed (parameters: %1, reason: %2)

The lease4-wipe command has failed. Both the reason as well as the parameters passed are logged.

# 20.30 LEASE\_CMDS\_WIPE6

lease6-wipe command successful (parameters: %1)

The lease6-wipe command has been successful. Parameters of the command are logged.

## 20.31 LEASE\_CMDS\_WIPE6\_DEPRECATED

lease6-wipe command is deprecated and it will be removed in the future.

The lease6-wipe command is deprecated and it will be removed in the future.

242 Chapter 20. LEASE

#### **TWENTYONE**

**LFC** 

## 21.1 LFC\_FAIL\_PID\_CREATE

: %1

This message is issued if LFC detected a failure when trying to create the PID file. It includes a more specific error string.

# 21.2 LFC\_FAIL\_PID\_DEL

: %1

This message is issued if LFC detected a failure when trying to delete the PID file. It includes a more specific error string.

# 21.3 LFC\_FAIL\_PROCESS

: %1

This message is issued if LFC detected a failure when trying to process the files. It includes a more specific error string.

## 21.4 LFC\_FAIL\_ROTATE

: %1

This message is issued if LFC detected a failure when trying to rotate the files. It includes a more specific error string.

## 21.5 LFC\_PROCESSING

Previous file: %1, copy file: %2

This message is issued just before LFC starts processing the lease files.

## 21.6 LFC\_READ\_STATS

Leases: %1, attempts: %2, errors: %3.

This message prints out the number of leases that were read, the number of attempts to read leases and the number of errors encountered while reading.

### 21.7 LFC ROTATING

LFC rotating files

This message is issued just before LFC starts rotating the lease files - removing the old and replacing them with the new

## 21.8 LFC\_RUNNING

LFC instance already running

This message is issued if LFC detects that a previous copy of LFC may still be running via the PID check.

# 21.9 LFC\_START

Starting lease file cleanup

This message is issued as the LFC process starts.

## 21.10 LFC\_TERMINATE

LFC finished processing

This message is issued when the LFC process completes. It does not indicate that the process was successful only that it has finished.

244 Chapter 21. LFC

#### **TWENTYTWO**

#### LOGIMPL

## 22.1 LOGIMPL\_ABOVE\_MAX\_DEBUG

debug level of %1 is too high and will be set to the maximum of %2

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string DEBUGn, where n is an integer, e.g. DEBUG22) is above the maximum allowed value and has been reduced to that value. The appearance of this message may indicate a programming error - please submit a bug report.

### 22.2 LOGIMPL\_BAD\_DEBUG\_STRING

debug string '%1' has invalid format

A message from the interface to the underlying logger implementation reporting that an internally-created string used to set the debug level is not of the correct format (it should be of the form DEBUGn, where n is an integer, e.g. DEBUG22). The appearance of this message indicates a programming error - please submit a bug report.

#### **TWENTYTHREE**

LOG

### 23.1 LOG BAD DESTINATION

unrecognized log destination: %1

This error message is printed when a logger destination value was given that was not recognized. The destination should be one of "console", "file", or "syslog".

### 23.2 LOG BAD SEVERITY

unrecognized log severity: %1

This error message is printed when a logger severity value was given that was not recognized. The severity should be one of "DEBUG", "INFO", "WARN", "ERROR", "FATAL" or "NONE".

## 23.3 LOG BAD STREAM

bad log console output stream: %1

Logging has been configured so that output is written to the terminal (console) but the stream on which it is to be written is not recognized. Allowed values are "stdout" and "stderr".

## 23.4 LOG\_DUPLICATE\_MESSAGE\_ID

duplicate message ID (%1) in compiled code

During start-up, Kea detected that the given message identification had been defined multiple times in the Kea code. This indicates a programming error; please submit a bug report.

## 23.5 LOG DUPLICATE NAMESPACE

line %1: duplicate \$NAMESPACE directive found

When reading a message file, more than one \$NAMESPACE directive was found. (This directive is used to set a C++ namespace when generating header files during software development.) Such a condition is regarded as an error and the read will be abandoned.

### 23.6 LOG INPUT OPEN FAIL

unable to open message file %1 for input: %2

The program was not able to open the specified input message file for the reason given.

## 23.7 LOG\_INVALID\_MESSAGE\_ID

line %1: invalid message identification '%2'

An invalid message identification (ID) has been found during the read of a message file. Message IDs should comprise only alphanumeric characters and the underscore, and should not start with a digit.

### 23.8 LOG\_NAMESPACE\_EXTRA\_ARGS

line %1: \$NAMESPACE directive has too many arguments

The \$NAMESPACE directive in a message file takes a single argument, a namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with more than one argument.

## 23.9 LOG\_NAMESPACE\_INVALID\_ARG

line %1: \$NAMESPACE directive has an invalid argument ('%2')

The \$NAMESPACE argument in a message file should be a valid C++ namespace. This message is output if the simple check on the syntax of the string carried out by the reader fails.

248 Chapter 23. LOG

## 23.10 LOG\_NAMESPACE\_NO\_ARGS

line %1: no arguments were given to the \$NAMESPACE directive

The \$NAMESPACE directive in a message file takes a single argument, a C++ namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with no arguments.

### 23.11 LOG NO MESSAGE ID

line %1: message definition line found without a message ID

Within a message file, message are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and nothing else.

### 23.12 LOG\_NO\_MESSAGE\_TEXT

line %1: line found containing a message ID ('%2') and no text

Within a message file, message are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and message identification, but no text.

## 23.13 LOG NO SUCH MESSAGE

could not replace message text for '%1': no such message

During start-up a local message file was read. A line with the listed message identification was found in the file, but the identification is not one contained in the compiled-in message dictionary. This message may appear a number of times in the file, once for every such unknown message identification. There are several reasons why this message may appear: - The message ID has been misspelled in the local message file. - The program outputting the message may not use that particular message (e.g. it originates in a module not used by the program). - The local file was written for an earlier version of the Kea software and the later version no longer generates that message. Whatever the reason, there is no impact on the operation of Kea.

## 23.14 LOG\_OPEN\_OUTPUT\_FAIL

unable to open %1 for output: %2

Originating within the logging code, the program was not able to open the specified output file for the reason given.

## 23.15 LOG\_PREFIX\_EXTRA\_ARGS

line %1: \$PREFIX directive has too many arguments

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. This error is generated when the compiler finds a \$PREFIX directive with more than one argument. Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

### 23.16 LOG PREFIX INVALID ARG

line %1: \$PREFIX directive has an invalid argument ('%2')

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. As such, it must adhere to restrictions on C++ symbol names (e.g. may only contain alphanumeric characters or underscores, and may nor start with a digit). A \$PREFIX directive was found with an argument (given in the message) that violates those restrictions. Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

### 23.17 LOG\_READING\_LOCAL\_FILE

reading local message file %1

This is an informational message output by Kea when it starts to read a local message file. (A local message file may replace the text of one or more messages; the ID of the message will not be changed though.)

## 23.18 LOG READ ERROR

error reading from message file %1: %2

The specified error was encountered reading from the named message file.

## 23.19 LOG\_UNRECOGNIZED\_DIRECTIVE

line %1: unrecognized directive '%2'

Within a message file, a line starting with a dollar symbol was found (indicating the presence of a directive) but the first word on the line (shown in the message) was not recognized.

250 Chapter 23. LOG

#### **TWENTYFOUR**

MT

## 24.1 MT\_TCP\_LISTENER\_MGR\_STARTED

MtTcpListenerMgr started with %1 threads, listening on %2:%3, use TLS: %4

Logged at debug log level 40. This debug messages is issued when an MtTcpListenerMgr has been started to accept connections. Arguments detail the number of threads that the listener is using, the address and port at which it is listening, and if TLS is used or not.

## 24.2 MT TCP LISTENER MGR STOPPED

MtTcpListenerMgr for %1:%2 stopped.

Logged at debug log level 40. This debug messages is issued when the MtTcpListenerMgr, listening at the given address and port, has completed shutdown.

## 24.3 MT TCP LISTENER MGR STOPPING

Stopping MtTcpListenerMgr for %1:%2

Logged at debug log level 40. This debug messages is issued when the MtTcpListenerMgr, listening at the given address and port, has begun to shutdown.

252 Chapter 24. MT

**CHAPTER** 

#### **TWENTYFIVE**

#### **MYSQL**

### 25.1 MYSQL CB CREATE UPDATE BY POOL OPTION4

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

### 25.2 MYSQL CB CREATE UPDATE BY POOL OPTION6

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

## 25.3 MYSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6

create or update option prefix: %1 prefix len: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by prefix

## 25.4 MYSQL CB CREATE UPDATE BY SUBNET ID OPTION4

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

### 25.5 MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 25.6 MYSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

## 25.7 MYSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

### 25.8 MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 25.9 MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 25.10 MYSQL\_CB\_CREATE\_UPDATE\_OPTION4

create or update option

254

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

### 25.11 MYSQL\_CB\_CREATE\_UPDATE\_OPTION6

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

#### 25.12 MYSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

### 25.13 MYSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF6

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

### 25.14 MYSQL\_CB\_CREATE\_UPDATE\_SERVER4

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv4 server information.

## 25.15 MYSQL\_CB\_CREATE\_UPDATE\_SERVER6

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv6 server information.

## 25.16 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4

create or update shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

## 25.17 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6

create or update shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

## 25.18 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4

create or update shared network: %1 option

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

## 25.19 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6

create or update shared network: %1 option

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

#### 25.20 MYSQL CB CREATE UPDATE SUBNET4

create or update subnet: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 25.21 MYSQL\_CB\_CREATE\_UPDATE\_SUBNET6

create or update subnet: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 25.22 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4

delete all client classes

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

# 25.23 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

### 25.24 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6

delete all client classes

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

# 25.25 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

#### 25.26 MYSQL CB DELETE ALL GLOBAL PARAMETERS4

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 25.27 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

## 25.28 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 25.29 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

### 25.30 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 25.31 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

### 25.32 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 25.33 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

## 25.34 MYSQL CB DELETE ALL SERVERS4

delete all DHCPv4 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

### 25.35 MYSQL\_CB\_DELETE\_ALL\_SERVERS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

### 25.36 MYSQL\_CB\_DELETE\_ALL\_SERVERS6

delete all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

#### 25.37 MYSQL CB DELETE ALL SERVERS6 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

#### 25.38 MYSQL CB DELETE ALL SHARED NETWORKS4

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 25.39 MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

## 25.40 MYSQL CB DELETE ALL SHARED NETWORKS6

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

### 25.41 MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

### 25.42 MYSQL\_CB\_DELETE\_ALL\_SUBNETS4

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

#### 25.43 MYSQL CB DELETE ALL SUBNETS4 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

#### 25.44 MYSQL CB DELETE ALL SUBNETS6

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

## 25.45 MYSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

## 25.46 MYSQL CB DELETE BY POOL OPTION4

delete pool start: %1 pool end: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

### 25.47 MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

#### 25.48 MYSQL CB DELETE BY POOL OPTION6

delete pool start: %1 pool end: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

#### 25.49 MYSQL CB DELETE BY POOL OPTION6 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

#### 25.50 MYSQL CB DELETE BY POOL PREFIX OPTION6

delete prefix: %1 prefix len: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by prefix

## 25.51 MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by prefix

## 25.52 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4

delete subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

### 25.53 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

### 25.54 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6

delete subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

## 25.55 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

#### 25.56 MYSQL CB DELETE BY SUBNET ID OPTION4

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

## 25.57 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

# 25.58 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

### 25.59 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

### 25.60 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 25.61 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

#### 25.62 MYSQL CB DELETE BY SUBNET ID SUBNET6

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 25.63 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

## 25.64 MYSQL\_CB\_DELETE\_CLIENT\_CLASS4

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

### 25.65 MYSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

#### 25.66 MYSQL\_CB\_DELETE\_CLIENT\_CLASS6

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

#### 25.67 MYSQL CB DELETE CLIENT CLASS6 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

### 25.68 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

## 25.69 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

## 25.70 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

# 25.71 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

### 25.72 MYSQL\_CB\_DELETE\_OPTION4

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

#### 25.73 MYSQL CB DELETE OPTION4 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

### 25.74 MYSQL\_CB\_DELETE\_OPTION6

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 25.75 MYSQL\_CB\_DELETE\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

# 25.76 MYSQL\_CB\_DELETE\_OPTION\_DEF4

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

### 25.77 MYSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

### 25.78 MYSQL\_CB\_DELETE\_OPTION\_DEF6

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

#### 25.79 MYSQL CB DELETE OPTION DEF6 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

#### 25.80 MYSQL CB DELETE SERVER4

delete DHCPv4 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

## 25.81 MYSQL\_CB\_DELETE\_SERVER4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

## 25.82 MYSQL CB DELETE SERVER6

delete DHCPv6 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

### 25.83 MYSQL\_CB\_DELETE\_SERVER6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

### 25.84 MYSQL\_CB\_DELETE\_SHARED\_NETWORK4

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

### 25.85 MYSQL\_CB\_DELETE\_SHARED\_NETWORK4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

### 25.86 MYSQL\_CB\_DELETE\_SHARED\_NETWORK6

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

## 25.87 MYSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

## 25.88 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

## 25.89 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

### 25.90 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

### 25.91 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

### 25.92 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 25.93 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

## 25.94 MYSQL CB DELETE SHARED NETWORK SUBNETS6

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 25.95 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

### 25.96 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 25.97 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

#### 25.98 MYSQL CB GET ALL CLIENT CLASSES6

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 25.99 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

## 25.100 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 25.101 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

#### 25.102 MYSQL CB GET ALL GLOBAL PARAMETERS6

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 25.103 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

#### 25.104 MYSQL CB GET ALL OPTIONS4

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

## 25.105 MYSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

## 25.106 MYSQL\_CB\_GET\_ALL\_OPTIONS6

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

# 25.107 MYSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

### 25.108 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 25.109 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

#### 25.110 MYSQL CB GET ALL OPTION DEFS6

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 25.111 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

## 25.112 MYSQL CB GET ALL SERVERS4

retrieving all servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv4 servers

## 25.113 MYSQL CB GET ALL SERVERS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv4 servers

### 25.114 MYSQL\_CB\_GET\_ALL\_SERVERS6

retrieving all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv6 servers

#### 25.115 MYSQL CB GET ALL SERVERS6 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv6 servers

#### 25.116 MYSQL CB GET ALL SHARED NETWORKS4

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

## 25.117 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

## 25.118 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6

retrieving all shared networks

272

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

# 25.119 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

### 25.120 MYSQL\_CB\_GET\_ALL\_SUBNETS4

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

#### 25.121 MYSQL CB GET ALL SUBNETS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

### 25.122 MYSQL\_CB\_GET\_ALL\_SUBNETS6

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

## 25.123 MYSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

## 25.124 MYSQL\_CB\_GET\_CLIENT\_CLASS4

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

## 25.125 MYSQL\_CB\_GET\_CLIENT\_CLASS6

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

# 25.126 MYSQL\_CB\_GET\_GLOBAL\_PARAMETER4

retrieving global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

#### 25.127 MYSQL CB GET GLOBAL PARAMETER6

retrieving global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

### 25.128 MYSQL\_CB\_GET\_HOST4

get host

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

## 25.129 MYSQL\_CB\_GET\_HOST6

get host

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

## 25.130 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4

retrieving modified client classes from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

## 25.131 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

#### 25.132 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6

retrieving modified client classes from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

### 25.133 MYSQL CB GET MODIFIED CLIENT CLASSES6 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

## 25.134 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 25.135 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 25.136 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 25.137 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

#### 25.138 MYSQL CB GET MODIFIED OPTIONS4

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

### 25.139 MYSQL CB GET MODIFIED OPTIONS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

### 25.140 MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

## 25.141 MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

## 25.142 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

276 Chapter 25. MYSQL

### 25.143 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

#### 25.144 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

### 25.145 MYSQL CB GET MODIFIED OPTION DEFS6 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

### 25.146 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 25.147 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

## 25.148 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 25.149 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

#### 25.150 MYSQL CB GET MODIFIED SUBNETS4

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

### 25.151 MYSQL CB GET MODIFIED SUBNETS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

### 25.152 MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

## 25.153 MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

## 25.154 MYSQL\_CB\_GET\_OPTION4

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

### 25.155 MYSQL\_CB\_GET\_OPTION6

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

### 25.156 MYSQL\_CB\_GET\_OPTION\_DEF4

retrieving option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

### 25.157 MYSQL\_CB\_GET\_OPTION\_DEF6

retrieving option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

### 25.158 MYSQL\_CB\_GET\_PORT4

get port

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 25.159 MYSQL\_CB\_GET\_PORT6

get port

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 25.160 MYSQL CB GET RECENT AUDIT ENTRIES4

retrieving audit entries from: %1 %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id.

## 25.161 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

### 25.162 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6

retrieving audit entries from: %1 %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id

### 25.163 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

#### 25.164 MYSQL CB GET SERVER4

retrieving DHCPv4 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv4 server information.

# 25.165 MYSQL\_CB\_GET\_SERVER6

retrieving DHCPv6 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv6 server information.

## 25.166 MYSQL\_CB\_GET\_SHARED\_NETWORK4

retrieving shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

### 25.167 MYSQL\_CB\_GET\_SHARED\_NETWORK6

retrieving shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

### 25.168 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4

retrieving shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

## 25.169 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

#### 25.170 MYSQL CB GET SHARED NETWORK SUBNETS6

retrieving shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

## 25.171 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

## 25.172 MYSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX

retrieving subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 25.173 MYSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID

retrieving subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

### 25.174 MYSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX

retrieving subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 25.175 MYSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID

retrieving subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

### 25.176 MYSQL\_CB\_GET\_TYPE4

get type

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

## 25.177 MYSQL\_CB\_GET\_TYPE6

get type

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

# 25.178 MYSQL\_CB\_NO\_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

# 25.179 MYSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED4

database reconnect failed: %1

Error message issued when an attempt to reconnect has failed.

# 25.180 MYSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED6

database reconnect failed: %1

Error message issued when an attempt to reconnect has failed.

#### 25.181 MYSQL\_CB\_RECONNECT\_ATTEMPT\_SCHEDULE4

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

#### 25.182 MYSQL CB RECONNECT ATTEMPT SCHEDULE6

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 25.183 MYSQL\_CB\_RECONNECT\_FAILED4

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 25.184 MYSQL\_CB\_RECONNECT\_FAILED6

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

### 25.185 MYSQL\_CB\_REGISTER\_BACKEND\_TYPE4

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

#### 25.186 MYSQL\_CB\_REGISTER\_BACKEND\_TYPE6

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

### 25.187 MYSQL\_CB\_TLS\_CIPHER

TLS cipher: %1

Logged at debug log level 40. A debug message issued when a new MySQL connected is created with TLS. The TLS cipher name is logged.

### 25.188 MYSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

## 25.189 MYSQL\_DEINIT\_OK

unloading MySQL hooks library successful

This informational message indicates that the MySQL Backend hooks library has been unloaded successfully.

## 25.190 MYSQL\_HB\_DB

opening MySQL hosts database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

### 25.191 MYSQL HB DB GET VERSION

obtaining schema version information for the MySQL hosts database

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the MySQL hosts database.

#### 25.192 MYSQL HB DB READONLY

MySQL host database opened for read access only

This informational message is issued when the user has configured the MySQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

### 25.193 MYSQL\_HB\_DB\_RECONNECT\_ATTEMPT\_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

### 25.194 MYSQL\_HB\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 25.195 MYSQL\_HB\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 25.196 MYSQL\_HB\_NO\_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

#### 25.197 MYSQL INIT OK

loading MySQL hooks library successful

This informational message indicates that the MySQL Backend hooks library has been loaded successfully. Enjoy!

#### 25.198 MYSQL LB ADD ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. A debug message issued when the server is about to add an IPv4 lease with the specified address to the MySQL backend database.

#### 25.199 MYSQL LB ADD ADDR6

adding IPv6 lease with address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is about to add an IPv6 lease with the specified address to the MySQL backend database.

#### 25.200 MYSQL LB COMMIT

committing to MySQL database

Logged at debug log level 50. The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the commit may not include a write to disk.

## **25.201 MYSQL LB DB**

opening MySQL lease database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

## 25.202 MYSQL\_LB\_DB\_RECONNECT\_ATTEMPT\_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

# 25.203 MYSQL\_LB\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

#### 25.204 MYSQL\_LB\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

#### 25.205 MYSQL LB DELETED EXPIRED RECLAIMED

deleted %1 reclaimed leases from the database

Logged at debug log level 50. A debug message issued when the server has removed a number of reclaimed leases from the database. The number of removed leases is included in the message.

### 25.206 MYSQL\_LB\_DELETE\_ADDR4

deleting lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

## 25.207 MYSQL\_LB\_DELETE\_ADDR6

deleting lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

## 25.208 MYSQL\_LB\_DELETE\_EXPIRED\_RECLAIMED4

deleting reclaimed IPv4 leases that expired more than %1 seconds ago

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

### 25.209 MYSQL LB DELETE EXPIRED RECLAIMED6

deleting reclaimed IPv6 leases that expired more than %1 seconds ago

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

#### **25.210 MYSQL LB GET4**

obtaining all IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases from the MySQL database.

#### **25.211 MYSQL LB GET6**

obtaining all IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases from the MySQL database.

## 25.212 MYSQL\_LB\_GET\_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for the specified address.

## 25.213 MYSQL\_LB\_GET\_ADDR6

obtaining IPv6 lease for address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified address.

## 25.214 MYSQL LB GET CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified client identification.

#### 25.215 MYSQL LB GET DUID

obtaining IPv6 lease for duid %1,

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified duid.

#### 25.216 MYSQL LB GET EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

### 25.217 MYSQL\_LB\_GET\_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 25.218 MYSQL LB GET HOSTNAME4

obtaining IPv4 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hostname.

## 25.219 MYSQL\_LB\_GET\_HOSTNAME6

obtaining IPv6 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified hostname.

### 25.220 MYSQL LB GET HWADDR

obtaining IPv4 leases for hardware address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hardware address.

#### 25.221 MYSQL\_LB\_GET\_IAID\_DUID

obtaining IPv6 leases for IAID %1, DUID %2, lease type %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

### 25.222 MYSQL LB GET IAID SUBID DUID

obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3, lease type %4

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

## 25.223 MYSQL\_LB\_GET\_PAGE4

obtaining at most %1 IPv4 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 25.224 MYSQL\_LB\_GET\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

### 25.225 MYSQL\_LB\_GET\_RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt\_ →between %4 and %5

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

#### 25.226 MYSQL LB GET RELAYID6

obtaining at most %1 IPv6 leases starting from address %2 with relay id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

### 25.227 MYSQL LB GET REMOTEID4

obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt\_ →between %4 and %5

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

## 25.228 MYSQL\_LB\_GET\_REMOTEID6

obtaining at most %1 IPv6 leases starting from address %2 with remote id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

## 25.229 MYSQL\_LB\_GET\_SUBID4

obtaining IPv4 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the MySQL database.

### 25.230 MYSQL LB GET SUBID6

obtaining IPv6 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the MySQL database.

#### 25.231 MYSQL LB GET SUBID CLIENTID

obtaining IPv4 lease for subnet ID %1 and client ID %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and client ID.

### 25.232 MYSQL LB GET SUBID HWADDR

obtaining IPv4 lease for subnet ID %1 and hardware address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and hardware address.

### 25.233 MYSQL\_LB\_GET\_SUBID\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases from the MySQL database beginning with the specified address for the specified subnet identifier.

## 25.234 MYSQL LB GET VERSION

obtaining schema version information

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the MySQL database.

## 25.235 MYSQL\_LB\_NEGATIVE\_LEASES\_STAT

recount of leases returned a negative value

292

This warning message is issued when the recount of leases using counters in the MySQL database returned a negative value. This shows a problem which can be fixed only by an offline direct recount on the database. This message is issued only once.

### 25.236 MYSQL\_LB\_NO\_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

#### 25.237 MYSQL\_LB\_ROLLBACK

rolling back MySQL database

Logged at debug log level 50. The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

#### 25.238 MYSQL LB TLS CIPHER

TLS cipher: %1

Logged at debug log level 40. A debug message issued when a new MySQL connected is created with TLS. The TLS cipher name is logged.

### 25.239 MYSQL LB UPDATE ADDR4

updating IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv4 lease from the MySQL database for the specified address.

## 25.240 MYSQL LB UPDATE ADDR6

updating IPv6 lease for address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv6 lease from the MySQL database for the specified address.

## 25.241 MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO4

upgrading IPv4 leases done in %1 pages with %2 updated leases

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

## 25.242 MYSQL LB UPGRADE EXTENDED INFO4 ERROR

upgrading extending info for IPv4 lease at %1 failed with %2

Logged at debug log level 40. A debug message issued when the server failed to upgrade an extended info. The address of the lease and the error message are displayed.

### 25.243 MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_PAGE

upgrading IPv4 lease extended info at page %1 starting at %2 (updated %3)

Logged at debug log level 50. A debug message issued when the server upgrades IPv4 lease extended info. The page number and started address, and the count of already updated leases are displayed.

#### 25.244 MYSQL LB UPGRADE EXTENDED INFO6

upgrading IPv6 leases done in %1 pages with %2 updated leases

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

#### 25.245 MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO6\_ERROR

upgrading extending info for IPv6 lease at %1 failed with %2

Logged at debug log level 40. A debug message issued when the server failed to upgrade the extended info for a lease. The address of the lease and the error message are displayed.

294 Chapter 25. MYSQL

**CHAPTER** 

#### **TWENTYSIX**

#### **NETCONF**

### 26.1 NETCONF\_BOOT\_UPDATE\_COMPLETED

Boot-update configuration completed for server %1

This informational message is issued when the initial configuration was retrieved using NETCONF and successfully applied to Kea server.

#### 26.2 NETCONF CONFIG CHANGED DETAIL

YANG configuration changed: %1

Logged at debug log level 55. This debug message indicates a YANG configuration change. The format is the change operation (created, modified, deleted or moved) followed by xpaths and values of old and new nodes.

## 26.3 NETCONF\_CONFIG\_CHANGE\_EVENT

Received YANG configuration change %1 event

This informational message is issued when kea-netconf receives a YANG configuration change event. The type of event is printed.

## 26.4 NETCONF\_CONFIG\_CHECK\_FAIL

NETCONF configuration check failed: %1

This error message indicates that kea-netconf had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

### 26.5 NETCONF\_CONFIG\_FAIL

NETCONF configuration failed: %1

This error message indicates that kea-netconf had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

#### 26.6 NETCONF\_CONFIG\_SYNTAX\_WARNING

NETCONF configuration syntax warning: %1

This warning message indicates that the NETCONF configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

#### 26.7 NETCONF FAILED

application experienced a fatal error: %1

This is a fatal error message issued when kea-netconf got an unrecoverable error from within the event loop.

### 26.8 NETCONF\_GET\_CONFIG

got configuration from %1 server: %2

Logged at debug log level 55. This debug message indicates that kea-netconf got the configuration from a Kea server. The server name and the retrieved configuration are printed.

## 26.9 NETCONF GET CONFIG FAILED

getting configuration from %1 server failed: %2

The error message indicates that kea-netconf got an error getting the configuration from a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

## 26.10 NETCONF\_GET\_CONFIG\_STARTED

getting configuration from %1 server

This informational message indicates that kea-netconf is trying to get the configuration from a Kea server.

### 26.11 NETCONF MODULE CHANGE INTERNAL ERROR

an internal error occurred while processing changes for module %1: %2

The error message indicates that kea-netconf got an error while sysrepo was processing modules changes. This usually follows a config validation failure, and can be recovered from. The name of the module and the internal error message are printed.

#### 26.12 NETCONF MODULE MISSING ERR

Missing essential module %1 in sysrepo

This fatal error message indicates that a module required by Netconf configuration is not available in the sysrepo repository. The name of the module is printed.

### 26.13 NETCONF\_MODULE\_MISSING\_WARN

Missing module %1 in sysrepo

This warning message indicates that a module used by Kea is not available in the sysrepo repository. The name of the module is printed.

## 26.14 NETCONF\_MODULE\_REVISION\_ERR

Essential module %1 does NOT have the right revision: expected %2, got %3

This fatal error message indicates that a module required by Netconf configuration is not at the right revision in the sysrepo repository. The name, expected and available revisions of the module are printed.

## 26.15 NETCONF\_MODULE\_REVISION\_WARN

Module %1 does NOT have the right revision: expected %2, got %3

This warning message indicates that a module used by Kea is not at the right revision in the sysrepo repository. The name, expected and available revisions of the module are printed.

### 26.16 NETCONF NOTIFICATION INTERNAL ERROR

an internal error occurred while sending an event notification for module %1: %2

The error message indicates that kea-netconf got an error while sysrepo was sending an event notification. This error is not fatal and can be recovered from. The name of the module and the internal error message are printed.

### 26.17 NETCONF\_NOTIFICATION\_RECEIVED

Received notification of type %1 for module %2: '%3'

This informational message logs any YANG notification that has been signaled by the server, sent to kea-netconf which then was forwarded to subscribed clients. To achieve this, kea-netconf subscribes itself as a client to all notifications for the configured module.

### 26.18 NETCONF\_NOT\_SUBSCRIBED\_TO\_NOTIFICATIONS

subscribing to notifications for %1 server with %2 module failed: %3

The warning message indicates that kea-netconf got an error subscribing to notifications for a Kea server. The most probable cause is probably that the model that kea-netconf subscribed to does not have any notification nodes, but there may be other more unexpected causes as well. The server name, module name and the error are printed.

## 26.19 NETCONF\_RUN\_EXIT

application is exiting the event loop

Logged at debug log level 0. This is a debug message issued when kea-netconf exits its event loop. This is a normal step during kea-netconf shutdown.

## 26.20 NETCONF\_SET\_CONFIG

set configuration to %1 server: %2

Logged at debug log level 55. This debug message indicates that kea-netconf set the configuration to a Kea server. The server name and the applied configuration are printed.

### 26.21 NETCONF\_SET\_CONFIG\_FAILED

setting configuration to %1 server failed: %2

The error message indicates that kea-netconf got an error setting the configuration to a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

#### 26.22 NETCONF SET CONFIG STARTED

setting configuration to %1 server

This informational message indicates that kea-netconf is trying to set the configuration to a Kea server.

## 26.23 NETCONF\_STARTED

kea-netconf (version %1) started

This informational message indicates that kea-netconf has processed all configuration information and is ready to begin processing. The version is also printed.

### 26.24 NETCONF\_SUBSCRIBE\_CONFIG

subscribing configuration changes for %1 server with %2 module

This information message indicates that kea-netconf is trying to subscribe configuration changes for a Kea server. The names of the server and the module are printed.

# 26.25 NETCONF\_SUBSCRIBE\_CONFIG\_FAILED

subscribe configuration changes for %1 server with %2 module failed: %3

The error message indicates that kea-netconf got an error subscribing configuration changes for a Kea server. The names of the server and the module, and the error are printed.

## 26.26 NETCONF\_SUBSCRIBE\_NOTIFICATIONS

subscribing to notifications for %1 server with %2 module

This information message indicates that kea-netconf is trying to subscribe to notifications for a Kea server. The server name and module name are printed.

### 26.27 NETCONF UPDATE CONFIG

updating configuration with %1 server: %2

Logged at debug log level 55. This debug message indicates that kea-netconf update the configuration of a Kea server. The server name and the updated configuration are printed.

#### 26.28 NETCONF\_UPDATE\_CONFIG\_COMPLETED

completed updating configuration for %1 server

This informational message indicates that kea-netconf updated with success the configuration of a Kea server.

### 26.29 NETCONF UPDATE CONFIG FAILED

updating configuration with %1 server: %2

The error message indicates that kea-netconf got an error updating the configuration of a Kea server. This includes a configuration rejected by a Kea server when it tried to apply it. The name of the server and the error are printed.

### 26.30 NETCONF UPDATE CONFIG STARTED

started updating configuration for %1 server

This informational message indicates that kea-netconf is trying to update the configuration of a Kea server.

# 26.31 NETCONF\_VALIDATE\_CONFIG

validating configuration with %1 server: %2

Logged at debug log level 55. This debug message indicates that kea-netconf is validating the configuration with a Kea server. The server name and the validated configuration are printed.

## 26.32 NETCONF\_VALIDATE\_CONFIG\_COMPLETED

completed validating configuration for %1 server

This informational message indicates that kea-netconf validated with success the configuration with a Kea server.

## 26.33 NETCONF\_VALIDATE\_CONFIG\_FAILED

validating configuration with %1 server got an error: %2

The error message indicates that kea-netconf got an error validating the configuration with a Kea server. This message is produced when exception is thrown during an attempt to validate received configuration. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

### 26.34 NETCONF\_VALIDATE\_CONFIG\_REJECTED

validating configuration with %1 server was rejected: %2

The warning message indicates that kea-netconf got an error validating the configuration with a Kea server. This message is printed when the configuration was rejected during normal processing. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

**CHAPTER** 

#### **TWENTYSEVEN**

#### **PERFMON**

#### 27.1 PERFMON ALARM CLEARED

Alarm for %1 has been cleared, reported mean duration %2 is now below low-water-ms: %3

This info message is emitted when the reported mean duration for an alarm that has been triggered has fallen below the value of its low-water-ms parameter. The arguments detail the alarm's key and the most recently reported mean.

#### 27.2 PERFMON ALARM TRIGGERED

Alarm for %1 has been triggered since %2, reported mean duration %3 exceeds high-water-  $\omega$ ms: %4

This warning message is emitted when the reported mean duration for an alarm exceeds its high-water-ms value. As long as the reported averges remain above the low-water-ms value, the alarm will remain triggered and this message will be repeated every alarm-report-secs. Arguments detail the alarm's key, the time the alarm was first triggered, the most recent reported mean, and the high-water-ms value.

## 27.3 PERFMON\_CMDS\_CONTROL\_ERROR

perfmon-control command processing failed: %1

This error message is issued when the PerfMon hook library encounters an error processing a perfmon-control command. The argument explains the command error.

## 27.4 PERFMON CMDS CONTROL OK

perfmon-control command success: active monitoring: %1, stats-mgr-reporting: %2

This info log is issued when perfmon-control command has successfully enabled/disabled active monitoring and/or statistics mgr reporting. Arguments reflect the current state of both.

### 27.5 PERFMON CMDS GET ALL DURATIONS ERROR

perfmon-get-all-durations command processing failed: %1

This error message is issued when the PerfMon hook library encounters an error processing a perfmon-get-all-durations command. The argument explains the command error.

#### 27.6 PERFMON\_CMDS\_GET\_ALL\_DURATIONS\_OK

perfmon-get-all-durations returning %1 durations

This info log is issued when perfmon-get-all-durations command has completed successfully. The argument contains the number of durations returned.

## 27.7 PERFMON\_DEINIT\_OK

unloading PerfMon hooks library successful

This info message indicates that the PerfMon hooks library has been removed successfully.

### 27.8 PERFMON DHCP4 PKT EVENTS

query: %1 events=[%2]

Logged at debug log level 50. This debug message is emitted after an inbound DHCPv4 query has been processed, the arguments are the query label and the dump of the query's packet event stack.

## 27.9 PERFMON\_DHCP4\_PKT\_PROCESS\_ERROR

Packet event stack was not processed for query %1, reason %2

Logged at debug log level 50. This debug message is emitted when the query's event stack could not be processed. This is most likely a programmatic error and should be reported. The arguments identify the query and the reason it could not be processed. These errors should not affect server's normal operations.

## 27.10 PERFMON\_DHCP4\_SOCKET\_RECEIVED\_TIME\_SUPPORT

Kernel supports socket received time? %1

Logged at debug log level 40. This debug message is emitted after a (re)configuration and indicates whether or not the packet filter being used by kea-dhcp4 can supply the timestamp a packet was received by the kernel for recording SOCKET\_RECEIVED events. If it does not, perfmon will still function but will not have data available to determine kernel buffer wait times.

## 27.11 PERFMON\_DHCP6\_PKT\_EVENTS

query: %1 events=[%2]

Logged at debug log level 50. The debug message is emitted after an inbound DHCPv6 query has been processed, the arguments are the query label and the dump of the query's packet event stack.

#### 27.12 PERFMON\_DHCP6\_PKT\_PROCESS\_ERROR

Packet event stack was not processed for query %1, reason %2

Logged at debug log level 50. This debug message is emitted when the query's event stack could not be processed. This is most likely a programmatic error and should be reported. The arguments identify the query and the reason it could not be processed. These errors should not affect server's normal operations.

### 27.13 PERFMON\_DHCP6\_SOCKET\_RECEIVED\_TIME\_SUPPORT

Kernel supports socket received time? %1

Logged at debug log level 40. This debug message is emitted after a (re)configuration and indicates whether or not the packet filter being used by kea-dhcp6 can supply the timestamp a packet was received by the kernel for recording SOCKET\_RECEIVED events. If it does not, perfmon will still function but will not have data available to determine kernel buffer wait times.

## 27.14 PERFMON INIT FAILED

loading PerfMon hooks library failed: %1

This error message indicates an error during loading the PerfMon hooks library. The details of the error are provided as argument of the log message.

**CHAPTER** 

#### **TWENTYEIGHT**

#### **PGSQL**

#### 28.1 PGSQL CB CREATE UPDATE BY POOL OPTION4

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

### 28.2 PGSQL CB CREATE UPDATE BY POOL OPTION6

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

## 28.3 PGSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6

create or update option prefix: %1 prefix len: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by prefix

## 28.4 PGSQL CB CREATE UPDATE BY SUBNET ID OPTION4

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 28.5 PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 28.6 PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

## 28.7 PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

### 28.8 PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 28.9 PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

# 28.10 PGSQL\_CB\_CREATE\_UPDATE\_OPTION4

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

### 28.11 PGSQL\_CB\_CREATE\_UPDATE\_OPTION6

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

#### 28.12 PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

### 28.13 PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF6

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

### 28.14 PGSQL\_CB\_CREATE\_UPDATE\_SERVER4

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv4 server information.

## 28.15 PGSQL\_CB\_CREATE\_UPDATE\_SERVER6

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv6 server information.

## 28.16 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4

create or update shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

### 28.17 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6

create or update shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

### 28.18 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4

create or update shared network: %1 option

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

## 28.19 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6

create or update shared network: %1 option

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

### 28.20 PGSQL CB CREATE UPDATE SUBNET4

create or update subnet: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 28.21 PGSQL\_CB\_CREATE\_UPDATE\_SUBNET6

create or update subnet: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 28.22 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4

delete all client classes

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

# 28.23 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

### 28.24 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6

delete all client classes

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

# 28.25 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

#### 28.26 PGSQL CB DELETE ALL GLOBAL PARAMETERS4

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 28.27 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

## 28.28 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 28.29 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

### 28.30 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 28.31 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

#### 28.32 PGSQL CB DELETE ALL OPTION DEFS6

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 28.33 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

## 28.34 PGSQL CB DELETE ALL SERVERS4

delete all DHCPv4 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

### 28.35 PGSQL\_CB\_DELETE\_ALL\_SERVERS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

### 28.36 PGSQL\_CB\_DELETE\_ALL\_SERVERS6

delete all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

#### 28.37 PGSQL CB DELETE ALL SERVERS6 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

#### 28.38 PGSQL CB DELETE ALL SHARED NETWORKS4

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 28.39 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

# 28.40 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 28.41 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

### 28.42 PGSQL\_CB\_DELETE\_ALL\_SUBNETS4

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

#### 28.43 PGSQL CB DELETE ALL SUBNETS4 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

#### 28.44 PGSQL CB DELETE ALL SUBNETS6

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

## 28.45 PGSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

## 28.46 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4

delete pool start: %1 pool end: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

### 28.47 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

#### 28.48 PGSQL CB DELETE BY POOL OPTION6

delete pool start: %1 pool end: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

## 28.49 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

#### 28.50 PGSQL CB DELETE BY POOL PREFIX OPTION6

delete prefix: %1 prefix len: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by prefix

## 28.51 PGSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by prefix

## 28.52 PGSQL CB DELETE BY PREFIX SUBNET4

delete subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

### 28.53 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

### 28.54 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6

delete subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

## 28.55 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

#### 28.56 PGSQL CB DELETE BY SUBNET ID OPTION4

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

## 28.57 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

## 28.58 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

### 28.59 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

### 28.60 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 28.61 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

#### 28.62 PGSQL CB DELETE BY SUBNET ID SUBNET6

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 28.63 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

## 28.64 PGSQL CB DELETE CLIENT CLASS4

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

### 28.65 PGSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

### 28.66 PGSQL\_CB\_DELETE\_CLIENT\_CLASS6

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

#### 28.67 PGSQL CB DELETE CLIENT CLASS6 RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

### 28.68 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

## 28.69 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

## 28.70 PGSQL CB DELETE GLOBAL PARAMETER6

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

# 28.71 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

### 28.72 PGSQL\_CB\_DELETE\_OPTION4

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 28.73 PGSQL\_CB\_DELETE\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

#### 28.74 PGSQL CB DELETE OPTION6

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 28.75 PGSQL\_CB\_DELETE\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

## 28.76 PGSQL\_CB\_DELETE\_OPTION\_DEF4

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

### 28.77 PGSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

### 28.78 PGSQL\_CB\_DELETE\_OPTION\_DEF6

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

## 28.79 PGSQL\_CB\_DELETE\_OPTION\_DEF6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

#### 28.80 PGSQL CB DELETE SERVER4

delete DHCPv4 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

## 28.81 PGSQL\_CB\_DELETE\_SERVER4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

## 28.82 PGSQL CB DELETE SERVER6

delete DHCPv6 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

### 28.83 PGSQL\_CB\_DELETE\_SERVER6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

### 28.84 PGSQL\_CB\_DELETE\_SHARED\_NETWORK4

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

### 28.85 PGSQL\_CB\_DELETE\_SHARED\_NETWORK4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

#### 28.86 PGSQL CB DELETE SHARED NETWORK6

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

## 28.87 PGSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

## 28.88 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

## 28.89 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

# 28.90 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

### 28.91 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

### 28.92 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 28.93 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT

deleted: %1 entries

322

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

## 28.94 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

### 28.95 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

### 28.96 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 28.97 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

#### 28.98 PGSQL CB GET ALL CLIENT CLASSES6

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 28.99 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

## 28.100 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 28.101 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

## 28.102 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 28.103 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

#### 28.104 PGSQL CB GET ALL OPTIONS4

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

## 28.105 PGSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

## 28.106 PGSQL\_CB\_GET\_ALL\_OPTIONS6

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

### 28.107 PGSQL CB GET ALL OPTIONS6 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

# 28.108 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 28.109 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

#### 28.110 PGSQL CB GET ALL OPTION DEFS6

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

# 28.111 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

## 28.112 PGSQL CB GET ALL SERVERS4

retrieving all servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv4 servers

## 28.113 PGSQL CB GET ALL SERVERS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv4 servers

### 28.114 PGSQL\_CB\_GET\_ALL\_SERVERS6

retrieving all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv6 servers

## 28.115 PGSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv6 servers

#### 28.116 PGSQL CB GET ALL SHARED NETWORKS4

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

# 28.117 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

# 28.118 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

## 28.119 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

### 28.120 PGSQL\_CB\_GET\_ALL\_SUBNETS4

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

### 28.121 PGSQL\_CB\_GET\_ALL\_SUBNETS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

#### 28.122 PGSQL CB GET ALL SUBNETS6

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

# 28.123 PGSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

# 28.124 PGSQL\_CB\_GET\_CLIENT\_CLASS4

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

## 28.125 PGSQL\_CB\_GET\_CLIENT\_CLASS6

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

# 28.126 PGSQL\_CB\_GET\_GLOBAL\_PARAMETER4

retrieving global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

## 28.127 PGSQL\_CB\_GET\_GLOBAL\_PARAMETER6

retrieving global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

#### 28.128 PGSQL\_CB\_GET\_HOST4

get host

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

## 28.129 PGSQL\_CB\_GET\_HOST6

get host

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

# 28.130 PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4

retrieving modified client classes from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

### 28.131 PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

#### 28.132 PGSQL CB GET MODIFIED CLIENT CLASSES6

retrieving modified client classes from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

### 28.133 PGSQL CB GET MODIFIED CLIENT CLASSES6 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

## 28.134 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

# 28.135 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 28.136 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 28.137 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 28.138 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

### 28.139 PGSQL CB GET MODIFIED OPTIONS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

### 28.140 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

# 28.141 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

# 28.142 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

### 28.143 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

#### 28.144 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

### 28.145 PGSQL CB GET MODIFIED OPTION DEFS6 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

### 28.146 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

# 28.147 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

# 28.148 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 28.149 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

## 28.150 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

### 28.151 PGSQL CB GET MODIFIED SUBNETS4 RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

### 28.152 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

# 28.153 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

# 28.154 PGSQL\_CB\_GET\_OPTION4

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

### 28.155 PGSQL\_CB\_GET\_OPTION6

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

### 28.156 PGSQL\_CB\_GET\_OPTION\_DEF4

retrieving option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

#### 28.157 PGSQL CB GET OPTION DEF6

retrieving option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

#### 28.158 PGSQL\_CB\_GET\_PORT4

get port

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 28.159 PGSQL\_CB\_GET\_PORT6

get port

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 28.160 PGSQL CB GET RECENT AUDIT ENTRIES4

retrieving audit entries from: %1 %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id.

## 28.161 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

### 28.162 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6

retrieving audit entries from: %1 %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id

### 28.163 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

#### 28.164 PGSQL CB GET SERVER4

retrieving DHCPv4 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv4 server information.

# 28.165 PGSQL\_CB\_GET\_SERVER6

retrieving DHCPv6 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv6 server information.

# 28.166 PGSQL\_CB\_GET\_SHARED\_NETWORK4

retrieving shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

### 28.167 PGSQL\_CB\_GET\_SHARED\_NETWORK6

retrieving shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

### 28.168 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4

retrieving shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

### 28.169 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

### 28.170 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6

retrieving shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

# 28.171 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

# 28.172 PGSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX

retrieving subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

### 28.173 PGSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID

retrieving subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

### 28.174 PGSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX

retrieving subnet by prefix: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 28.175 PGSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID

retrieving subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

### 28.176 PGSQL\_CB\_GET\_TYPE4

get type

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

## 28.177 PGSQL\_CB\_GET\_TYPE6

get type

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

# 28.178 PGSQL\_CB\_NO\_TLS\_SUPPORT

Attempt to configure TLS (unsupported for PostgreSQL): %1

This error message is printed when TLS support was required in the Kea configuration: Kea was built with this feature disabled for PostgreSQL. The parameters of the connection are logged.

# 28.179 PGSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED4

database reconnect failed: %1

Error message issued when an attempt to reconnect has failed.

### 28.180 PGSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED6

database reconnect failed: %1

Error message issued when an attempt to reconnect has failed.

### 28.181 PGSQL\_CB\_RECONNECT\_ATTEMPT\_SCHEDULE4

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

#### 28.182 PGSQL CB RECONNECT ATTEMPT SCHEDULE6

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

# 28.183 PGSQL\_CB\_RECONNECT\_FAILED4

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

# 28.184 PGSQL\_CB\_RECONNECT\_FAILED6

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 28.185 PGSQL\_CB\_REGISTER\_BACKEND\_TYPE4

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

#### 28.186 PGSQL\_CB\_REGISTER\_BACKEND\_TYPE6

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

### 28.187 PGSQL\_CB\_TLS\_SUPPORT

Attempt to configure TLS: %1

This informational message is printed when TLS support was required in the Kea configuration: The TLS support in PostgreSQL will be initialized but its configuration is fully managed outside the C API. The parameters of the connection are logged.

#### 28.188 PGSQL CB UNREGISTER BACKEND TYPE4

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

# 28.189 PGSQL\_DEINIT\_OK

unloading PostgreSQL hooks library successful

This informational message indicates that the PostgreSQL Backend hooks library has been unloaded successfully.

## 28.190 PGSQL\_HB\_DB

opening PostgreSQL hosts database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

### 28.191 PGSQL\_HB\_DB\_GET\_VERSION

obtaining schema version information for the PostgreSQL hosts database

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the PostgreSQL hosts database.

#### 28.192 PGSQL\_HB\_DB\_READONLY

PostgreSQL host database opened for read access only

This informational message is issued when the user has configured the PostgreSQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

### 28.193 PGSQL\_HB\_DB\_RECONNECT\_ATTEMPT\_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

### 28.194 PGSQL\_HB\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

# 28.195 PGSQL\_HB\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

# 28.196 PGSQL\_HB\_NO\_TLS\_SUPPORT

Attempt to configure TLS (unsupported for PostgreSQL): %1

This error message is printed when TLS support was required in the Kea configuration: Kea was built with this feature disabled for PostgreSQL. The parameters of the connection are logged.

### 28.197 PGSQL INIT OK

loading PostgreSQL hooks library successful

This informational message indicates that the PostgreSQL Backend hooks library has been loaded successfully. Enjoy!

#### 28.198 PGSQL LB ADD ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. A debug message issued when the server is about to add an IPv4 lease with the specified address to the PostgreSQL backend database.

#### 28.199 PGSQL LB ADD ADDR6

adding IPv6 lease with address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is about to add an IPv6 lease with the specified address to the PostgreSQL backend database.

#### 28.200 PGSQL LB COMMIT

committing to PostgreSQL database

Logged at debug log level 50. The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the commit may not include a write to disk.

## 28.201 PGSQL LB DB

opening PostgreSQL lease database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

# 28.202 PGSQL\_LB\_DB\_RECONNECT\_ATTEMPT\_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

# 28.203 PGSQL\_LB\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

#### 28.204 PGSQL\_LB\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

#### 28.205 PGSQL LB DELETE ADDR4

deleting lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

## 28.206 PGSQL\_LB\_DELETE\_ADDR6

deleting lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

# 28.207 PGSQL\_LB\_DELETE\_EXPIRED\_RECLAIMED4

deleting reclaimed IPv4 leases that expired more than %1 seconds ago

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

### 28.208 PGSQL LB DELETE EXPIRED RECLAIMED6

deleting reclaimed IPv6 leases that expired more than %1 seconds ago

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

#### **28.209 PGSQL LB GET4**

obtaining all IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases from the PostgreSQL database.

### **28.210 PGSQL LB GET6**

obtaining all IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases from the PostgreSQL database.

## 28.211 PGSQL\_LB\_GET\_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for the specified address.

## 28.212 PGSQL\_LB\_GET\_ADDR6

obtaining IPv6 lease for address %1 (lease type %2)

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for the specified address.

### 28.213 PGSQL LB GET CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified client identification.

#### 28.214 PGSQL LB GET DUID

obtaining IPv6 leases for DUID %1,

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified DUID (DHCP Unique Identifier).

### 28.215 PGSQL LB GET EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

#### 28.216 PGSQL\_LB\_GET\_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

# 28.217 PGSQL\_LB\_GET\_HOSTNAME4

obtaining IPv4 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hostname.

# 28.218 PGSQL\_LB\_GET\_HOSTNAME6

obtaining IPv6 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified hostname.

### 28.219 PGSQL LB GET HWADDR

obtaining IPv4 leases for hardware address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hardware address.

#### 28.220 PGSQL\_LB\_GET\_IAID\_DUID

obtaining IPv4 leases for IAID %1 and DUID %2, lease type %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

### 28.221 PGSQL LB GET IAID SUBID DUID

obtaining IPv4 leases for IAID %1, Subnet ID %2, DUID %3, and lease type %4

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

# 28.222 PGSQL\_LB\_GET\_PAGE4

obtaining at most %1 IPv4 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 28.223 PGSQL\_LB\_GET\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

### 28.224 PGSQL LB GET RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt\_ →between %4 and %5

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

#### 28.225 PGSQL LB GET RELAYID6

obtaining at most %1 IPv6 leases starting from address %2 with relay id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

### 28.226 PGSQL LB GET REMOTEID4

obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt\_ →between %4 and %5

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

## 28.227 PGSQL\_LB\_GET\_REMOTEID6

obtaining at most %1 IPv6 leases starting from address %2 with remote id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

## 28.228 PGSQL\_LB\_GET\_SUBID4

obtaining IPv4 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the PostgreSQL database.

### 28.229 PGSQL LB GET SUBID6

obtaining IPv6 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the PostgreSQL database.

### 28.230 PGSQL LB GET SUBID CLIENTID

obtaining IPv4 lease for subnet ID %1 and client ID %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and client ID.

### 28.231 PGSQL LB GET SUBID HWADDR

obtaining IPv4 lease for subnet ID %1 and hardware address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and hardware address.

# 28.232 PGSQL\_LB\_GET\_SUBID\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases from the PostgreSQL database beginning with the specified address for the specified subnet identifier.

# 28.233 PGSQL\_LB\_GET\_VERSION

obtaining schema version information

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the PostgreSQL database.

# 28.234 PGSQL\_LB\_NEGATIVE\_LEASES\_STAT

recount of leases returned a negative value

This warning message is issued when the recount of leases using counters in the PostgreSQL database returned a negative value. This shows a problem which can be fixed only by an offline direct recount on the database. This message is issued only once.

## 28.235 PGSQL\_LB\_NO\_TLS\_SUPPORT

Attempt to configure TLS (unsupported for PostgreSQL): %1

This error message is printed when TLS support was required in the Kea configuration: Kea was built with this feature disabled for PostgreSQL. The parameters of the connection are logged.

#### 28.236 PGSQL LB ROLLBACK

rolling back PostgreSQL database

Logged at debug log level 50. The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

### 28.237 PGSQL LB TLS SUPPORT

Attempt to configure TLS: %1

This informational message is printed when TLS support was required in the Kea configuration: The TLS support in PostgreSQL will be initialized but its configuration is fully managed outside the C API. The parameters of the connection are logged.

## 28.238 PGSQL\_LB\_UPDATE\_ADDR4

updating IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv4 lease from the PostgreSQL database for the specified address.

## 28.239 PGSQL\_LB\_UPDATE\_ADDR6

updating IPv6 lease for address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv6 lease from the PostgreSQL database for the specified address.

### 28.240 PGSQL LB UPGRADE EXTENDED INFO4

upgrading IPv4 leases done in %1 pages with %2 updated leases

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

### 28.241 PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_ERROR

upgrading extending info for IPv4 lease at %1 failed with %2

Logged at debug log level 40. A debug message issued when the server failed to upgrade an extended info. The address of the lease and the error message are displayed.

## 28.242 PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_PAGE

upgrading IPv4 lease extended info at page %1 starting at %2 (updated %3)

Logged at debug log level 50. A debug message issued when the server upgrades IPv4 lease extended info. The page number and started address, and the count of already updated leases are displayed.

#### 28.243 PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO6

upgrading IPv6 leases done in %1 pages with %2 updated leases

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

## 28.244 PGSQL LB UPGRADE EXTENDED INFO6 ERROR

upgrading extending info for IPv6 lease at %1 failed with %2

Logged at debug log level 40. A debug message issued when the server failed to upgrade the extended info for a lease. The address of the lease and the error message are displayed.

**CHAPTER** 

### **TWENTYNINE**

### **RUN**

# 29.1 RUN\_SCRIPT\_LOAD

Run Script hooks library has been loaded

This info message indicates that the Run Script hooks library has been loaded.

# 29.2 RUN\_SCRIPT\_LOAD\_ERROR

Run Script hooks library failed: %1

This error message indicates an error during loading the Run Script hooks library. The details of the error are provided as argument of the log message.

350 Chapter 29. RUN

**CHAPTER** 

#### **THIRTY**

#### **STAT**

## 30.1 STAT\_CMDS\_DEINIT\_OK

unloading Stat Commands hooks library successful

This info message indicates that the Stat Commands hooks library has been removed successfully.

## 30.2 STAT\_CMDS\_INIT\_OK

loading Stat Commands hooks library successful

This info message indicates that the Stat Commands hooks library has been loaded successfully. Enjoy!

# 30.3 STAT\_CMDS\_LEASE4\_FAILED

stat-lease4-get command failed: reason: %1

The stat-lease4-get command has failed. The reason for failure is logged.

# 30.4 STAT\_CMDS\_LEASE4\_GET

stat-lease4-get command successful, parameters: %1 rows found: %2

The stat-lease4-get command has been successful. The log will contain the parameters supplied and the number of rows found.

### 30.5 STAT CMDS LEASE4 GET FAILED

```
stat-lease4-get command failed: parameters: %1, reason: %2
```

The stat-lease4-get command has failed. Both the parameters supplied and the reason for failure are logged.

#### 30.6 STAT CMDS LEASE4 GET INVALID

```
stat-lease4-get command is malformed or invalid, reason: %1
```

The stat-lease4-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

## 30.7 STAT\_CMDS\_LEASE4\_GET\_NO\_SUBNETS

```
stat-lease4-get, parameters: %1, %2"
```

The parameters submitted with stat-lease4-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

#### 30.8 STAT CMDS LEASE4 ORPHANED STATS

stat-lease4-get command omitted statistics for one or more non-existent subnets

Logged at debug log level 40. During processing the stat-lease4-get found statistics for subnet IDs for non-existent subnets. These values were omitted from the command response returned to the user. This may occur when subnets have been removed from the configuration in a manner that did not also remove the statistics. While the existence of such statistics is not harmful, steps should be considered to remove them. For memfile lease storage, the problem should disappear upon configuration reload or server restart. For database lease storage the issue is more complicated and as of Kea 2.0.0 we do not yet have a clean solution.

## 30.9 STAT\_CMDS\_LEASE6\_FAILED

```
stat-lease6-get command failed: reason: %1
```

The stat-lease6-get command has failed. The reason for failure is logged.

352 Chapter 30. STAT

## 30.10 STAT\_CMDS\_LEASE6\_GET

stat-lease6-get command successful, parameters: %1 rows found: %2

The stat-lease6-get command has been successful. The log will contain the parameters supplied and the number of rows found.

### 30.11 STAT\_CMDS\_LEASE6\_GET\_FAILED

stat-lease6-get command failed: parameters: %1, reason: %2

The stat-lease6-get command has failed. Both the parameters supplied and the reason for failure are logged.

#### 30.12 STAT CMDS LEASE6 GET INVALID

stat-lease6-get command is malformed or invalid, reason: %1

The stat-lease6-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

### 30.13 STAT\_CMDS\_LEASE6\_GET\_NO\_SUBNETS

stat-lease6-get, parameters: %1, %2"

The parameters submitted with stat-lease6-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

354 Chapter 30. STAT

**CHAPTER** 

#### **THIRTYONE**

**TCP** 

#### 31.1 TCP CLIENT REQUEST RECEIVED

received TCP request from %1

Logged at debug log level 40. This debug message is issued when the server finished receiving a TCP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

#### 31.2 TCP CONNECTION REJECTED BY FILTER

connection from %1 has been denied by the connection filter.

Logged at debug log level 50. This debug message is issued when the server's connection filter rejects a new connection based on the client's ip address.

# 31.3 TCP CONNECTION SHUTDOWN

shutting down TCP connection from %1

Logged at debug log level 40. This debug message is issued when one of the TCP connections is shut down. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 31.4 TCP\_CONNECTION\_SHUTDOWN\_FAILED

shutting down TCP connection failed

This error message is issued when an error occurred during shutting down a TCP connection with a client.

### 31.5 TCP\_CONNECTION\_STOP

stopping TCP connection from %1

Logged at debug log level 40. This debug message is issued when one of the TCP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

### 31.6 TCP\_CONNECTION\_STOP\_FAILED

stopping TCP connection failed

This error message is issued when an error occurred during closing a TCP connection with a client.

#### 31.7 TCP DATA RECEIVED

received %1 bytes from %2

Logged at debug log level 55. This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

### 31.8 TCP\_DATA\_SENT

send %1 bytes to %2

Logged at debug log level 55. This debug message is issued when the server sends a chunk of data to the remote endpoint. This may include the whole response or only a part of the response. The first argument specifies the amount of sent data. The second argument specifies an address of the remote endpoint.

## 31.9 TCP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED

closing connection with %1 as a result of a timeout

Logged at debug log level 50. This debug message is issued when the TCP connection is being closed as a result of being idle.

356 Chapter 31. TCP

## 31.10 TCP\_REQUEST\_RECEIVED\_FAILED

An unexpected error occurred processing a request from %1, error: %2

This error message is issued when an unexpected error occurred while the server attempted to process a received request. The first argument specifies the address of the remote endpoint. The second argument describes the nature error

### 31.11 TCP REQUEST RECEIVE START

start receiving request from %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

### 31.12 TCP\_SERVER\_RESPONSE\_SEND

sending TCP response to %1

Logged at debug log level 40. This debug message is issued when the server is starting to send a TCP response to a remote endpoint. The argument specifies an address of the remote endpoint.

358 Chapter 31. TCP

**CHAPTER** 

#### **THIRTYTWO**

**TLS** 

### 32.1 TLS\_CONNECTION\_HANDSHAKE\_FAILED

TLS handshake with %1 failed with %2

This information message is issued when the TLS handshake failed at the server side. The client address and the error message are displayed.

## 32.2 TLS\_CONNECTION\_HANDSHAKE\_START

start TLS handshake with %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts the TLS handshake with the remote endpoint. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

# 32.3 TLS\_REQUEST\_RECEIVE\_START

start receiving request from %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

360 Chapter 32. TLS

**CHAPTER** 

#### **THIRTYTHREE**

#### **USER**

#### 33.1 USER\_CHK\_HOOK\_LOAD\_ERROR

DHCP UserCheckHook could not be loaded: %1

This is an error message issued when the DHCP UserCheckHook could not be loaded. The exact cause should be explained in the log message. User subnet selection will revert to default processing.

#### 33.2 USER CHK HOOK UNLOAD ERROR

DHCP UserCheckHook an error occurred unloading the library: %1

This is an error message issued when an error occurs while unloading the UserCheckHook library. This is unlikely to occur and normal operations of the library will likely resume when it is next loaded.

# 33.3 USER\_CHK\_SUBNET4\_SELECT\_ERROR

DHCP UserCheckHook an unexpected error occurred in subnet4\_select callout: %1

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

# 33.4 USER\_CHK\_SUBNET4\_SELECT\_REGISTRY\_NULL

DHCP UserCheckHook UserRegistry has not been created.

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook has been invoked but the User-Registry has not been created. This is a programmatic error and should not occur.

# 33.5 USER\_CHK\_SUBNET6\_SELECT\_ERROR

DHCP UserCheckHook an unexpected error occurred in subnet6\_select callout: %1

This is an error message issued when the DHCP UserCheckHook subnet6\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

362 Chapter 33. USER

**CHAPTER** 

#### **THIRTYFOUR**

#### **KEA DEBUG MESSAGES BY LOG LEVEL**

### 34.1 Messages printed on debuglevel 0

- CTRL\_AGENT\_RUN\_EXIT
- DCTL\_INIT\_PROCESS
- DCTL\_RUN\_PROCESS
- DCTL\_SHUTDOWN
- DCTL\_SHUTDOWN\_SIGNAL\_RECVD
- DCTL\_STANDALONE
- DHCP4\_OPEN\_SOCKET
- DHCP4\_START\_INFO
- DHCP6\_OPEN\_SOCKET
- DHCP6\_START\_INFO
- DHCP\_DDNS\_CLEARED\_FOR\_SHUTDOWN
- DHCP\_DDNS\_QUEUE\_MGR\_STARTED
- DHCP\_DDNS\_QUEUE\_MGR\_STOPPING
- DHCP\_DDNS\_RUN\_EXIT
- DHCP\_DDNS\_SHUTDOWN\_COMMAND
- NETCONF\_RUN\_EXIT

# 34.2 Messages printed on debuglevel 10

- COMMAND\_DEREGISTERED
- COMMAND\_EXTENDED\_REGISTERED
- COMMAND\_HTTP\_LISTENER\_COMMAND\_REJECTED
- COMMAND\_HTTP\_LISTENER\_STARTED
- COMMAND\_HTTP\_LISTENER\_STOPPED
- COMMAND\_HTTP\_LISTENER\_STOPPING
- COMMAND\_REGISTERED

- COMMAND\_SOCKET\_CONNECTION\_CLOSED
- COMMAND\_SOCKET\_CONNECTION\_OPENED
- COMMAND\_SOCKET\_READ
- COMMAND\_SOCKET\_WRITE
- CTRL\_AGENT\_COMMAND\_FORWARD\_BEGIN
- CTRL AGENT COMMAND FORWARD FAILED
- DCTL\_CONFIG\_START
- DHCP4\_CONFIG\_RECEIVED
- DHCP4\_CONFIG\_START
- DHCP6\_CONFIG\_RECEIVED
- DHCP6\_CONFIG\_START

### 34.3 Messages printed on debuglevel 15

- DHCP4\_HOOK\_BUFFER\_RCVD\_DROP
- DHCP4 HOOK DDNS UPDATE
- DHCP4\_HOOK\_DECLINE\_SKIP
- DHCP4\_HOOK\_LEASE4\_RELEASE\_SKIP
- DHCP4\_HOOK\_PACKET\_SEND\_DROP
- DHCP4\_HOOK\_SUBNET4\_SELECT\_406\_PARKING\_LOT\_FULL
- DHCP4\_HOOK\_SUBNET4\_SELECT\_PARKING\_LOT\_FULL
- DHCP4\_HOOK\_SUBNET6\_SELECT\_PARKING\_LOT\_FULL
- DHCP4 PACKET DROP 0001
- DHCP4\_PACKET\_DROP\_0002
- DHCP4\_PACKET\_DROP\_0003
- DHCP4\_PACKET\_DROP\_0004
- DHCP4\_PACKET\_DROP\_0005
- DHCP4\_PACKET\_DROP\_0006
- DHCP4\_PACKET\_DROP\_0007
- DHCP4\_PACKET\_DROP\_0008
- DHCP4\_PACKET\_DROP\_0009
- DHCP4\_PACKET\_DROP\_0010
- DHCP4\_PACKET\_DROP\_0011
- DHCP4\_PACKET\_DROP\_0012
- DHCP4\_PACKET\_DROP\_0013
- DHCP4\_PACKET\_DROP\_0014

- DHCP6 HOOK BUFFER RCVD DROP
- DHCP6\_HOOK\_DDNS\_UPDATE
- DHCP6\_HOOK\_DECLINE\_DROP
- DHCP6\_HOOK\_LEASES6\_COMMITTED\_DROP
- DHCP6 HOOK LEASES6 PARKING LOT FULL
- DHCP6 HOOK PACKET SEND DROP
- DHCP6\_PACKET\_DROP\_DHCP\_DISABLED
- DHCP6\_PACKET\_DROP\_DROP\_CLASS
- DHCP6\_PACKET\_DROP\_DROP\_CLASS2
- DHCP6\_PACKET\_DROP\_DROP\_CLASS\_EARLY
- DHCP6\_PACKET\_DROP\_DUPLICATE
- DHCP6\_PACKET\_DROP\_PARSE\_FAIL
- DHCP6\_PACKET\_DROP\_SERVERID\_MISMATCH
- DHCP6\_PACKET\_DROP\_UNICAST

### 34.4 Messages printed on debuglevel 20

- LEASE\_CMDS\_ADD4
- LEASE\_CMDS\_ADD6
- LEASE\_CMDS\_BULK\_APPLY6
- LEASE\_CMDS\_DEL4
- LEASE\_CMDS\_DEL6
- LEASE CMDS UPDATE4
- LEASE\_CMDS\_UPDATE6

# 34.5 Messages printed on debuglevel 40

- ALLOC\_ENGINE\_IGNORING\_UNSUITABLE\_GLOBAL\_ADDRESS
- ALLOC\_ENGINE\_IGNORING\_UNSUITABLE\_GLOBAL\_ADDRESS6
- ALLOC\_ENGINE\_LEASE\_RECLAIMED
- ALLOC\_ENGINE\_V4\_DISCOVER\_HR
- ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_COMPLETE
- ALLOC ENGINE V4 LEASES RECLAMATION START
- ALLOC ENGINE V4 LEASES RECLAMATION TIMEOUT
- ALLOC ENGINE V4 LEASE RECLAIM
- ALLOC\_ENGINE\_V4\_NO\_MORE\_EXPIRED\_LEASES
- ALLOC\_ENGINE\_V4\_OFFER\_EXISTING\_LEASE

- ALLOC ENGINE V4 OFFER NEW LEASE
- ALLOC ENGINE V4 OFFER REQUESTED LEASE
- ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE
- ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_COMPLETE
- ALLOC ENGINE V4 REQUEST ADDRESS RESERVED
- ALLOC ENGINE V4 REQUEST ALLOC REQUESTED
- ALLOC\_ENGINE\_V4\_REQUEST\_EXTEND\_LEASE
- ALLOC\_ENGINE\_V4\_REQUEST\_INVALID
- ALLOC\_ENGINE\_V4\_REQUEST\_IN\_USE
- ALLOC\_ENGINE\_V4\_REQUEST\_OUT\_OF\_POOL
- ALLOC\_ENGINE\_V4\_REQUEST\_PICK\_ADDRESS
- ALLOC\_ENGINE\_V4\_REQUEST\_REMOVE\_LEASE
- ALLOC\_ENGINE\_V4\_REQUEST\_USE\_HR
- ALLOC ENGINE V6 ALLOC HR LEASE EXISTS
- ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_HR
- ALLOC ENGINE V6 ALLOC LEASES NO HR
- ALLOC ENGINE V6 ALLOC NO LEASES HR
- ALLOC\_ENGINE\_V6\_ALLOC\_NO\_V6\_HR
- ALLOC\_ENGINE\_V6\_ALLOC\_UNRESERVED
- ALLOC\_ENGINE\_V6\_CALCULATED\_PREFERRED\_LIFETIME
- ALLOC\_ENGINE\_V6\_EXPIRED\_HINT\_RESERVED
- ALLOC\_ENGINE\_V6\_EXTEND\_ALLOC\_UNRESERVED
- ALLOC\_ENGINE\_V6\_HINT\_RESERVED
- ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_COMPLETE
- ALLOC ENGINE V6 LEASES RECLAMATION START
- ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_TIMEOUT
- ALLOC\_ENGINE\_V6\_LEASE\_RECLAIM
- ALLOC ENGINE V6 NO MORE EXPIRED LEASES
- ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE
- ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_COMPLETE
- ALLOC\_ENGINE\_V6\_RENEW\_HR
- ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_RESERVED
- ASIODNS\_FETCH\_STOPPED
- BOOTP\_BOOTP\_QUERY
- BOOTP PACKET OPTIONS SKIPPED
- BOOTP\_PACKET\_PACK

- BOOTP PACKET UNPACK FAILED
- DHCP4\_ADDITIONAL\_CLASS\_NO\_TEST
- DHCP4\_ADDITIONAL\_CLASS\_UNDEFINED
- DHCP4\_BUFFER\_RECEIVED
- DHCP4 CLASSES ASSIGNED
- DHCP4\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION
- DHCP4\_CLASS\_ASSIGNED
- DHCP4\_CLASS\_UNCONFIGURED
- DHCP4\_DHCP4O6\_HOOK\_SUBNET4\_SELECT\_DROP
- DHCP4\_DHCP4O6\_HOOK\_SUBNET4\_SELECT\_SKIP
- DHCP4\_DHCP4O6\_PACKET\_RECEIVED
- DHCP4\_DHCP4O6\_PACKET\_SEND
- DHCP4\_FLEX\_ID
- DHCP4 HOOK BUFFER SEND SKIP
- DHCP4\_HOOK\_PACKET\_RCVD\_SKIP
- DHCP4\_HOOK\_PACKET\_SEND\_SKIP
- DHCP4 HOOK SUBNET4 SELECT DROP
- DHCP4\_HOOK\_SUBNET4\_SELECT\_PARK
- DHCP4\_HOOK\_SUBNET4\_SELECT\_SKIP
- DHCP4\_PACKET\_QUEUE\_FULL
- DHCP4\_SHUTDOWN
- DHCP4\_SHUTDOWN\_REQUEST
- DHCP6\_ADDITIONAL\_CLASS\_NO\_TEST
- DHCP6\_ADDITIONAL\_CLASS\_UNDEFINED
- DHCP6 BUFFER RECEIVED
- DHCP6\_CLASSES\_ASSIGNED
- DHCP6\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION
- DHCP6 CLASS ASSIGNED
- DHCP6\_CLASS\_UNCONFIGURED
- DHCP6\_DHCP4O6\_PACKET\_RECEIVED
- DHCP6\_FLEX\_ID
- DHCP6\_HOOK\_BUFFER\_SEND\_SKIP
- DHCP6\_HOOK\_LEASE6\_RELEASE\_NA\_SKIP
- DHCP6\_HOOK\_LEASE6\_RELEASE\_PD\_SKIP
- DHCP6\_HOOK\_LEASES6\_COMMITTED\_PARK
- DHCP6 HOOK PACKET RCVD SKIP

- DHCP6 HOOK PACKET SEND SKIP
- DHCP6\_HOOK\_SUBNET6\_SELECT\_DROP
- DHCP6\_HOOK\_SUBNET6\_SELECT\_PARK
- DHCP6\_HOOK\_SUBNET6\_SELECT\_SKIP
- DHCP6 PACKET PROCESS FAIL
- DHCP6 PACKET QUEUE FULL
- DHCP6\_REQUIRED\_OPTIONS\_CHECK\_FAIL
- DHCP6\_SHUTDOWN
- DHCP6\_SHUTDOWN\_REQUEST
- DHCP6\_UNKNOWN\_MSG\_RECEIVED
- DHCPSRV\_CFGMGR\_ADD\_SUBNET4
- DHCPSRV\_CFGMGR\_ADD\_SUBNET6
- DHCPSRV\_CFGMGR\_ALL\_IFACES\_ACTIVE
- DHCPSRV\_CFGMGR\_CFG\_DHCP\_DDNS
- DHCPSRV\_CFGMGR\_DEL\_SUBNET4
- DHCPSRV\_CFGMGR\_DEL\_SUBNET6
- DHCPSRV CFGMGR SUBNET4
- DHCPSRV\_CFGMGR\_SUBNET4\_ADDR
- DHCPSRV\_CFGMGR\_SUBNET4\_IFACE
- DHCPSRV\_CFGMGR\_SUBNET4\_RELAY
- DHCPSRV\_CFGMGR\_SUBNET6
- DHCPSRV\_CFGMGR\_SUBNET6\_IFACE
- DHCPSRV\_CFGMGR\_SUBNET6\_IFACE\_ID
- DHCPSRV\_CFGMGR\_SUBNET6\_RELAY
- DHCPSRV\_CFGMGR\_UPDATE\_SUBNET4
- DHCPSRV\_CFGMGR\_UPDATE\_SUBNET6
- DHCPSRV\_CLOSE\_DB
- DHCPSRV HOOK LEASE4 RECOVER SKIP
- DHCPSRV\_HOOK\_LEASE4\_RENEW\_SKIP
- DHCPSRV\_HOOK\_LEASE4\_SELECT\_SKIP
- DHCPSRV\_HOOK\_LEASE6\_EXTEND\_SKIP
- DHCPSRV\_HOOK\_LEASE6\_RECOVER\_SKIP
- DHCPSRV\_HOOK\_LEASE6\_SELECT\_SKIP
- DHCPSRV\_LEASE4\_EXTENDED\_INFO\_UPGRADED
- DHCPSRV LEASE6 EXTENDED INFO UPGRADED
- DHCPSRV\_LEASE\_MGR\_BACKEND\_DEREGISTER

- DHCPSRV LEASE MGR BACKEND REGISTER
- DHCPSRV MEMFILE BEGIN BUILD EXTENDED INFO TABLES6
- DHCPSRV\_MEMFILE\_BEGIN\_EXTRACT\_EXTENDED\_INFO4
- DHCPSRV\_MEMFILE\_EXTRACT\_EXTENDED\_INFO4
- DHCPSRV MEMFILE EXTRACT EXTENDED INFO4 ERROR
- DHCPSRV MEMFILE LFC UNREGISTER TIMER FAILED
- DHCPSRV\_SUBNET4O6\_SELECT\_FAILED
- DHCPSRV\_SUBNET4\_SELECT\_BY\_ADDRESS\_NO\_MATCH
- DHCPSRV\_SUBNET4\_SELECT\_BY\_INTERFACE\_NO\_MATCH
- DHCPSRV\_SUBNET4\_SELECT\_BY\_RELAY\_ADDRESS\_NO\_MATCH
- DHCPSRV\_SUBNET4\_SELECT\_NO\_RAI\_OPTIONS
- DHCPSRV\_SUBNET4\_SELECT\_NO\_RELAY\_ADDRESS
- DHCPSRV\_SUBNET4\_SELECT\_NO\_USABLE\_ADDRESS
- DHCPSRV SUBNET6 SELECT BY ADDRESS NO MATCH
- DHCPSRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_ID\_NO\_MATCH
- DHCPSRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_NO\_MATCH
- DHCPSRV TIMERMGR REGISTER TIMER
- DHCPSRV TIMERMGR START TIMER
- DHCPSRV\_TIMERMGR\_STOP\_TIMER
- DHCPSRV TIMERMGR UNREGISTER ALL TIMERS
- DHCPSRV\_TIMERMGR\_UNREGISTER\_TIMER
- DHCP\_DDNS\_CONFIGURE
- DHCP\_DDNS\_NCR\_UDP\_RECV\_CANCELED
- DHCP\_DDNS\_QUEUE\_MGR\_RECONFIGURING
- DHCP DDNS QUEUE MGR STOPPED
- FLEX\_OPTION\_PROCESS\_ADD
- FLEX\_OPTION\_PROCESS\_CLIENT\_CLASS
- FLEX OPTION PROCESS REMOVE
- FLEX\_OPTION\_PROCESS\_SUB\_ADD
- FLEX\_OPTION\_PROCESS\_SUB\_CLIENT\_CLASS
- FLEX\_OPTION\_PROCESS\_SUB\_REMOVE
- FLEX\_OPTION\_PROCESS\_SUB\_SUPERSEDE
- FLEX\_OPTION\_PROCESS\_SUPERSEDE
- FLEX\_OPTION\_PROCESS\_VENDOR\_ID\_MISMATCH
- HA\_BUFFER4\_RECEIVE\_NOT\_FOR\_US
- HA BUFFER4 RECEIVE PACKET OPTIONS SKIPPED

- HA BUFFER4 RECEIVE UNPACK FAILED
- HA\_BUFFER6\_RECEIVE\_NOT\_FOR\_US
- HA\_BUFFER6\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED
- HA\_BUFFER6\_RECEIVE\_UNPACK\_FAILED
- HA LEASES4 COMMITTED NOTHING TO UPDATE
- HA\_LEASES6\_COMMITTED\_NOTHING\_TO\_UPDATE
- HA\_LEASE\_SYNC\_STALE\_LEASE4\_SKIP
- HA\_LEASE\_SYNC\_STALE\_LEASE6\_SKIP
- HA\_LOAD\_BALANCING\_DUID\_MISSING
- HA\_LOAD\_BALANCING\_IDENTIFIER\_MISSING
- HA\_SUBNET4\_SELECT\_NOT\_FOR\_US
- HA\_SUBNET4\_SELECT\_NO\_SUBNET\_SELECTED
- HA\_SUBNET6\_SELECT\_NOT\_FOR\_US
- HA\_SUBNET6\_SELECT\_NO\_SUBNET\_SELECTED
- HOOKS\_LIBRARY\_LOADING
- HOOKS\_LIBRARY\_UNLOADING
- HOOKS\_LOAD\_SUCCESS
- HOOKS\_NO\_LOAD
- HOOKS\_NO\_UNLOAD
- HOOKS\_UNLOAD\_SUCCESS
- HOSTS\_BACKEND\_DEREGISTER
- HOSTS\_BACKEND\_REGISTER
- HOSTS\_CFG\_ADD\_HOST
- HOSTS\_CFG\_CLOSE\_HOST\_DATA\_SOURCE
- HOSTS CFG DEL
- HOSTS\_CFG\_DEL4
- HOSTS\_CFG\_DEL6
- HOSTS CFG DEL ALL SUBNET4
- HOSTS\_CFG\_DEL\_ALL\_SUBNET6
- HOSTS\_CFG\_GET\_ALL
- HOSTS\_CFG\_GET\_ALL\_ADDRESS4
- HOSTS\_CFG\_GET\_ALL\_ADDRESS6
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6
- HOSTS\_CFG\_GET\_ALL\_IDENTIFIER

- HOSTS CFG GET ALL SUBNET ID4
- HOSTS CFG GET ALL SUBNET ID6
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6
- HOSTS CFG GET ONE PREFIX
- HOSTS CFG GET ONE SUBNET ID ADDRESS4
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER
- HOSTS CFG UPDATE ADD
- HOSTS CFG UPDATE DEL4
- HOSTS\_CFG\_UPDATE\_DEL6
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_ADDRESS4
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER
- HOSTS MGR ALTERNATE GET6 PREFIX
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_ADDRESS6
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER
- HOSTS MGR ALTERNATE GET ALL SUBNET ID ADDRESS4
- HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS6
- HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED
- HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED
- HTTP\_CLIENT\_MT\_STARTED
- HTTP\_CLIENT\_REQUEST\_RECEIVED
- HTTP\_CONNECTION\_SHUTDOWN
- HTTP\_CONNECTION\_STOP
- HTTP SERVER RESPONSE RECEIVED
- HTTP\_SERVER\_RESPONSE\_SEND
- MT\_TCP\_LISTENER\_MGR\_STARTED
- MT TCP LISTENER MGR STOPPED
- MT\_TCP\_LISTENER\_MGR\_STOPPING
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6
- MYSQL CB CREATE UPDATE CLIENT CLASS4
- MYSQL CB CREATE UPDATE CLIENT CLASS6

- MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4
- MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6
- MYSQL\_CB\_CREATE\_UPDATE\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_OPTION6
- MYSQL CB CREATE UPDATE OPTION DEF4
- MYSQL CB CREATE UPDATE OPTION DEF6
- MYSQL\_CB\_CREATE\_UPDATE\_SERVER4
- MYSQL\_CB\_CREATE\_UPDATE\_SERVER6
- MYSQL CB CREATE UPDATE SHARED NETWORK4
- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6
- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_SUBNET4
- MYSQL CB CREATE UPDATE SUBNET6
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT
- MYSQL CB DELETE ALL CLIENT CLASSES6
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4
- MYSOL CB DELETE ALL GLOBAL PARAMETERS4 RESULT
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT
- MYSQL CB DELETE ALL OPTION DEFS6
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SERVERS4
- MYSQL CB DELETE ALL SERVERS4 RESULT
- MYSQL\_CB\_DELETE\_ALL\_SERVERS6
- MYSQL\_CB\_DELETE\_ALL\_SERVERS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SUBNETS4
- MYSQL CB DELETE ALL SUBNETS4 RESULT

- MYSOL CB DELETE ALL SUBNETS6
- MYSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4
- MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT
- MYSQL CB DELETE BY POOL OPTION6
- MYSQL CB DELETE BY POOL OPTION6 RESULT
- MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6
- MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT
- MYSOL CB DELETE BY PREFIX SUBNET4
- MYSQL CB DELETE BY PREFIX SUBNET4 RESULT
- MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6
- MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT
- MYSQL CB DELETE BY SUBNET ID SUBNET4
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS4
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS6
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS6\_RESULT
- MYSQL CB DELETE GLOBAL PARAMETER4
- MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT
- MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6
- MYSQL CB DELETE GLOBAL PARAMETER6 RESULT
- MYSQL\_CB\_DELETE\_OPTION4
- MYSQL\_CB\_DELETE\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_OPTION6
- MYSQL\_CB\_DELETE\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_OPTION\_DEF4
- MYSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT
- MYSQL CB DELETE OPTION DEF6
- MYSQL CB DELETE OPTION DEF6 RESULT

- MYSQL\_CB\_DELETE\_SERVER4
- MYSQL\_CB\_DELETE\_SERVER4\_RESULT
- MYSQL\_CB\_DELETE\_SERVER6
- MYSQL\_CB\_DELETE\_SERVER6\_RESULT
- MYSQL CB DELETE SHARED NETWORK4
- MYSQL CB DELETE SHARED NETWORK4 RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK6
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6
- MYSQL CB DELETE SHARED NETWORK SUBNETS6 RESULT
- MYSQL CB GET ALL CLIENT CLASSES4
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTIONS4
- MYSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTIONS6
- MYSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_SERVERS4
- MYSQL\_CB\_GET\_ALL\_SERVERS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_SERVERS6
- MYSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT

- MYSOL CB GET ALL SHARED NETWORKS4
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT
- MYSQL CB GET ALL SUBNETS4
- MYSQL CB GET ALL SUBNETS4 RESULT
- MYSQL\_CB\_GET\_ALL\_SUBNETS6
- MYSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_CLIENT\_CLASS4
- MYSQL\_CB\_GET\_CLIENT\_CLASS6
- MYSQL\_CB\_GET\_GLOBAL\_PARAMETER4
- MYSQL\_CB\_GET\_GLOBAL\_PARAMETER6
- MYSQL\_CB\_GET\_HOST4
- MYSQL CB GET HOST6
- MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4
- MYSQL CB GET MODIFIED CLIENT CLASSES4 RESULT
- MYSQL CB GET MODIFIED CLIENT CLASSES6
- MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4
- MYSOL CB GET MODIFIED GLOBAL PARAMETERS4 RESULT
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS4
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS4\_RESULT
- MYSQL CB GET MODIFIED OPTIONS6
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4
- MYSQL CB GET MODIFIED OPTION DEFS4 RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4
- MYSOL CB GET MODIFIED SHARED NETWORKS4 RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SUBNETS4
- MYSQL CB GET MODIFIED SUBNETS4 RESULT

- MYSOL CB GET MODIFIED SUBNETS6
- MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_OPTION4
- MYSQL\_CB\_GET\_OPTION6
- MYSQL CB GET OPTION DEF4
- MYSQL\_CB\_GET\_OPTION\_DEF6
- MYSQL\_CB\_GET\_PORT4
- MYSQL\_CB\_GET\_PORT6
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT
- MYSQL\_CB\_GET\_SERVER4
- MYSQL\_CB\_GET\_SERVER6
- MYSQL\_CB\_GET\_SHARED\_NETWORK4
- MYSQL\_CB\_GET\_SHARED\_NETWORK6
- MYSQL CB GET SHARED NETWORK SUBNETS4
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX
- MYSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID
- MYSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX
- MYSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID
- MYSQL CB GET TYPE4
- MYSQL\_CB\_GET\_TYPE6
- MYSQL\_CB\_REGISTER\_BACKEND\_TYPE4
- MYSQL\_CB\_REGISTER\_BACKEND\_TYPE6
- MYSQL\_CB\_TLS\_CIPHER
- MYSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4
- MYSQL\_CB\_UNREGISTER\_BACKEND\_TYPE6
- MYSQL\_HB\_TLS\_CIPHER
- MYSQL\_LB\_TLS\_CIPHER
- MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO4
- MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_ERROR
- MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO6

- MYSOL LB UPGRADE EXTENDED INFO6 ERROR
- PERFMON\_DHCP4\_SOCKET\_RECEIVED\_TIME\_SUPPORT
- PERFMON\_DHCP6\_SOCKET\_RECEIVED\_TIME\_SUPPORT
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION4
- PGSOL CB CREATE UPDATE BY POOL OPTION6
- PGSQL CB CREATE UPDATE BY PREFIX OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION4
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4
- PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6
- PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4
- PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6
- PGSQL\_CB\_CREATE\_UPDATE\_OPTION4
- PGSQL CB CREATE UPDATE OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4
- PGSQL CB CREATE UPDATE OPTION DEF6
- PGSQL CB CREATE UPDATE SERVER4
- PGSQL\_CB\_CREATE\_UPDATE\_SERVER6
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_SUBNET4
- PGSQL\_CB\_CREATE\_UPDATE\_SUBNET6
- PGSQL CB DELETE ALL CLIENT CLASSES4
- PGSQL CB DELETE ALL CLIENT CLASSES4 RESULT
- PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6
- PGSQL CB DELETE ALL CLIENT CLASSES6 RESULT
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4
- PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT
- PGSQL CB DELETE ALL OPTION DEFS6
- PGSQL CB DELETE ALL OPTION DEFS6 RESULT

- PGSQL\_CB\_DELETE\_ALL\_SERVERS4
- PGSQL CB DELETE ALL SERVERS4 RESULT
- PGSQL\_CB\_DELETE\_ALL\_SERVERS6
- PGSQL\_CB\_DELETE\_ALL\_SERVERS6\_RESULT
- PGSQL CB DELETE ALL SHARED NETWORKS4
- PGSQL CB DELETE ALL SHARED NETWORKS4 RESULT
- PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6
- PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS4
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS6
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4
- PGSQL CB DELETE BY POOL OPTION4 RESULT
- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6
- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6\_RESULT
- PGSQL CB DELETE BY POOL PREFIX OPTION6
- PGSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT
- PGSQL CB DELETE BY SUBNET ID OPTION6
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS4
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS6
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS6\_RESULT
- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4
- PGSQL CB DELETE GLOBAL PARAMETER4 RESULT

- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6
- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT
- PGSQL\_CB\_DELETE\_OPTION4
- PGSQL\_CB\_DELETE\_OPTION4\_RESULT
- PGSQL CB DELETE OPTION6
- PGSQL CB DELETE OPTION6 RESULT
- PGSQL\_CB\_DELETE\_OPTION\_DEF4
- PGSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT
- PGSQL\_CB\_DELETE\_OPTION\_DEF6
- PGSQL\_CB\_DELETE\_OPTION\_DEF6\_RESULT
- PGSQL\_CB\_DELETE\_SERVER4
- PGSQL\_CB\_DELETE\_SERVER4\_RESULT
- PGSQL\_CB\_DELETE\_SERVER6
- PGSQL CB DELETE SERVER6 RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK4
- PGSQL CB DELETE SHARED NETWORK4 RESULT
- PGSQL CB DELETE SHARED NETWORK6
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4
- PGSQL CB DELETE SHARED NETWORK OPTION4 RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- PGSQL CB DELETE SHARED NETWORK SUBNETS6
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4
- PGSQL CB GET ALL CLIENT CLASSES4 RESULT
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_OPTIONS4
- PGSQL CB GET ALL OPTIONS4 RESULT

- PGSQL\_CB\_GET\_ALL\_OPTIONS6
- PGSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4
- PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT
- PGSQL CB GET ALL OPTION DEFS6
- PGSQL CB GET ALL OPTION DEFS6 RESULT
- PGSQL\_CB\_GET\_ALL\_SERVERS4
- PGSQL\_CB\_GET\_ALL\_SERVERS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_SERVERS6
- PGSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_SUBNETS4
- PGSQL\_CB\_GET\_ALL\_SUBNETS4\_RESULT
- PGSQL CB GET ALL SUBNETS6
- PGSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_CLIENT\_CLASS4
- PGSQL\_CB\_GET\_CLIENT\_CLASS6
- PGSQL\_CB\_GET\_GLOBAL\_PARAMETER4
- PGSQL\_CB\_GET\_GLOBAL\_PARAMETER6
- PGSQL\_CB\_GET\_HOST4
- PGSQL\_CB\_GET\_HOST6
- PGSQL CB GET MODIFIED CLIENT CLASSES4
- PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6
- PGSQL CB GET MODIFIED CLIENT CLASSES6 RESULT
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT

- PGSOL CB GET MODIFIED OPTION DEFS4
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6\_RESULT
- PGSQL CB GET MODIFIED SHARED NETWORKS4
- PGSQL CB GET MODIFIED SHARED NETWORKS4 RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6
- PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_OPTION4
- PGSQL\_CB\_GET\_OPTION6
- PGSQL\_CB\_GET\_OPTION\_DEF4
- PGSQL CB GET OPTION DEF6
- PGSQL CB GET PORT4
- PGSQL\_CB\_GET\_PORT6
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT
- PGSQL\_CB\_GET\_SERVER4
- PGSQL\_CB\_GET\_SERVER6
- PGSQL\_CB\_GET\_SHARED\_NETWORK4
- PGSQL\_CB\_GET\_SHARED\_NETWORK6
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4
- PGSQL CB GET SHARED NETWORK SUBNETS4 RESULT
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX
- PGSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID
- PGSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX
- PGSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID
- PGSQL CB GET TYPE4
- PGSQL CB GET TYPE6

- PGSQL\_CB\_REGISTER\_BACKEND\_TYPE4
- PGSQL\_CB\_REGISTER\_BACKEND\_TYPE6
- PGSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4
- PGSQL\_CB\_UNREGISTER\_BACKEND\_TYPE6
- PGSQL LB UPGRADE EXTENDED INFO4
- PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_ERROR
- PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO6
- PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO6\_ERROR
- STAT\_CMDS\_LEASE4\_ORPHANED\_STATS
- STAT\_CMDS\_LEASE6\_ORPHANED\_STATS
- TCP\_CLIENT\_REQUEST\_RECEIVED
- TCP\_CONNECTION\_SHUTDOWN
- TCP\_CONNECTION\_STOP
- TCP\_SERVER\_RESPONSE\_SEND
- TLS\_SERVER\_RESPONSE\_SEND

### 34.6 Messages printed on debuglevel 45

- DHCP4\_DHCP4O6\_SUBNET\_SELECTED
- DHCP4\_SUBNET\_DYNAMICALLY\_CHANGED
- DHCP4\_SUBNET\_SELECTED
- DHCP6\_SUBNET\_DYNAMICALLY\_CHANGED
- DHCP6 SUBNET SELECTED
- HOOKS\_CALLOUTS\_BEGIN
- HOOKS\_CALLOUTS\_COMPLETE
- HOOKS\_CALLOUTS\_REMOVED
- HOOKS\_CALLOUT\_REGISTRATION
- HOOKS\_LIBRARY\_MULTI\_THREADING\_COMPATIBLE
- HOOKS\_LIBRARY\_VERSION
- HOOKS\_STD\_CALLOUT\_REGISTERED
- HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_COUNT
- HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_COUNT
- HOSTS\_CFG\_GET\_ALL\_COUNT
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_COUNT
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_COUNT
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_COUNT

- HOSTS CFG GET ALL IDENTIFIER COUNT
- HOSTS CFG GET ALL SUBNET ID4 COUNT
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_COUNT
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_COUNT
- HOSTS CFG GET ALL SUBNET ID ADDRESS6 COUNT
- HOSTS CFG GET ONE SUBNET ID ADDRESS4 HOST
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_NULL
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_HOST
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_NULL
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_HOST
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_NULL
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_HOST
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_NULL
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_HOST
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_NULL
- HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED\_DETAILS
- HTTP BAD SERVER RESPONSE RECEIVED DETAILS
- HTTP\_CLIENT\_REQUEST\_RECEIVED\_DETAILS
- HTTP\_SERVER\_RESPONSE\_RECEIVED\_DETAILS
- HTTP SERVER RESPONSE SEND DETAILS

# 34.7 Messages printed on debuglevel 50

- ALLOC ENGINE V6 EXTEND LEASE
- ASIODNS\_READ\_TIMEOUT
- DHCP4\_ADDITIONAL\_CLASS\_EVAL\_RESULT
- DHCP4\_BUFFER\_UNPACK
- DHCP4\_BUFFER\_WAIT\_SIGNAL
- DHCP4\_CLIENTID\_IGNORED\_FOR\_LEASES
- DHCP4\_CLIENT\_FQDN\_PROCESS
- DHCP4 CLIENT\_HOSTNAME\_MALFORMED
- DHCP4\_CLIENT\_HOSTNAME\_PROCESS
- DHCP4\_DEFERRED\_OPTION\_MISSING
- DHCP4\_DEFERRED\_OPTION\_UNPACK\_FAIL
- DHCP4 DHCP4O6 BAD PACKET
- DHCP4 DHCP4O6 RECEIVE FAIL

- DHCP4 DHCP4O6 RECEIVING
- DHCP4\_DHCP4O6\_SUBNET\_SELECTION\_FAILED
- DHCP4\_DISCOVER
- DHCP4\_EMPTY\_HOSTNAME
- DHCP4 HOOK BUFFER RCVD SKIP
- DHCP4\_INFORM\_DIRECT\_REPLY
- DHCP4\_NO\_LEASE\_INIT\_REBOOT
- DHCP4\_PACKET\_NAK\_0002
- DHCP4\_PACKET\_NAK\_0003
- DHCP4\_PACKET\_NAK\_0004
- DHCP4\_PACKET\_OPTIONS\_SKIPPED
- DHCP4\_PACKET\_PACK
- DHCP4\_RELEASE
- DHCP4\_RELEASE\_FAIL
- DHCP4\_RELEASE\_FAIL\_NO\_LEASE
- DHCP4 RELEASE FAIL WRONG CLIENT
- DHCP4 REQUEST
- DHCP4\_RESPONSE\_HOSTNAME\_GENERATE
- DHCP4\_SUBNET\_SELECTION\_FAILED
- DHCP4\_UNKNOWN\_ADDRESS\_REQUESTED
- DHCP6\_ADDITIONAL\_CLASS\_EVAL\_RESULT
- DHCP6\_ADD\_GLOBAL\_STATUS\_CODE
- DHCP6\_ADD\_STATUS\_CODE\_FOR\_IA
- DHCP6\_BUFFER\_UNPACK
- DHCP6\_BUFFER\_WAIT\_SIGNAL
- DHCP6\_DDNS\_CREATE\_ADD\_NAME\_CHANGE\_REQUEST
- DHCP6\_DDNS\_GENERATE\_FQDN
- DHCP6 DDNS RECEIVE FQDN
- DHCP6\_DDNS\_REMOVE\_OLD\_LEASE\_FQDN
- DHCP6\_DDNS\_RESPONSE\_FQDN\_DATA
- DHCP6\_DECLINE\_PROCESS\_IA
- DHCP6\_DHCP4O6\_RECEIVE\_FAIL
- DHCP6\_DHCP4O6\_RECEIVING
- DHCP6\_HOOK\_BUFFER\_RCVD\_SKIP
- DHCP6\_HOOK\_DECLINE\_SKIP
- DHCP6\_LEASE\_ADVERT

- DHCP6 LEASE ADVERT FAIL
- DHCP6 LEASE ALLOC
- DHCP6\_LEASE\_ALLOC\_FAIL
- DHCP6\_PACKET\_OPTIONS\_SKIPPED
- DHCP6 PD LEASE ADVERT
- DHCP6 PD LEASE ADVERT FAIL
- DHCP6\_PD\_LEASE\_ALLOC
- DHCP6\_PD\_LEASE\_ALLOC\_FAIL
- DHCP6\_PROCESS\_IA\_NA\_EXTEND
- DHCP6\_PROCESS\_IA\_NA\_RELEASE
- DHCP6\_PROCESS\_IA\_NA\_REQUEST
- DHCP6\_PROCESS\_IA\_NA\_SOLICIT
- DHCP6\_PROCESS\_IA\_PD\_EXTEND
- DHCP6\_PROCESS\_IA\_PD\_REQUEST
- DHCP6\_PROCESS\_IA\_PD\_SOLICIT
- DHCP6\_RAPID\_COMMIT
- DHCP6 SUBNET SELECTION FAILED
- DHCPSRV\_DHCP\_DDNS\_NCR\_SENT
- DHCPSRV\_EVAL\_RESULT
- DHCPSRV\_MEMFILE\_ADD\_ADDR4
- DHCPSRV\_MEMFILE\_ADD\_ADDR6
- DHCPSRV\_MEMFILE\_COMMIT
- DHCPSRV\_MEMFILE\_DELETE\_ADDR4
- DHCPSRV\_MEMFILE\_DELETE\_ADDR6
- DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED4
- DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED6
- DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED\_START
- DHCPSRV MEMFILE GET4
- DHCPSRV\_MEMFILE\_GET6
- DHCPSRV\_MEMFILE\_GET6\_DUID
- DHCPSRV\_MEMFILE\_GET\_ADDR4
- DHCPSRV\_MEMFILE\_GET\_ADDR6
- DHCPSRV\_MEMFILE\_GET\_CLIENTID
- DHCPSRV\_MEMFILE\_GET\_EXPIRED4
- DHCPSRV\_MEMFILE\_GET\_EXPIRED6
- DHCPSRV\_MEMFILE\_GET\_HOSTNAME4

- DHCPSRV MEMFILE GET HOSTNAME6
- DHCPSRV\_MEMFILE\_GET\_HWADDR
- DHCPSRV\_MEMFILE\_GET\_IAID\_DUID
- DHCPSRV\_MEMFILE\_GET\_IAID\_SUBID\_DUID
- DHCPSRV MEMFILE GET PAGE4
- DHCPSRV MEMFILE GET PAGE6
- DHCPSRV\_MEMFILE\_GET\_RELAYID4
- DHCPSRV\_MEMFILE\_GET\_RELAYID6
- DHCPSRV\_MEMFILE\_GET\_REMOTEID4
- DHCPSRV\_MEMFILE\_GET\_REMOTEID6
- DHCPSRV\_MEMFILE\_GET\_SUBID4
- DHCPSRV\_MEMFILE\_GET\_SUBID6
- DHCPSRV\_MEMFILE\_GET\_SUBID\_CLIENTID
- DHCPSRV\_MEMFILE\_GET\_SUBID\_HWADDR
- DHCPSRV\_MEMFILE\_GET\_SUBID\_PAGE6
- DHCPSRV\_MEMFILE\_ROLLBACK
- DHCPSRV MEMFILE UPDATE ADDR4
- DHCPSRV\_MEMFILE\_UPDATE\_ADDR6
- DHCPSRV\_QUEUE\_NCR\_SKIP
- DHCPSRV\_TEMPLATE\_EVAL\_RESULT
- DHCPSRV\_TIMERMGR\_RUN\_TIMER\_OPERATION
- DHCP\_DDNS\_INVALID\_RESPONSE
- DHCP\_DDNS\_STARTING\_TRANSACTION
- DHCP\_DDNS\_UPDATE\_REQUEST\_SENT
- DHCP DDNS UPDATE RESPONSE RECEIVED
- FUZZ\_DATA\_READ
- FUZZ\_SEND
- HTTPS REQUEST RECEIVE START
- HTTP\_CLIENT\_REQUEST\_SEND
- HTTP\_CLIENT\_REQUEST\_TIMEOUT\_OCCURRED
- HTTP\_CONNECTION\_HANDSHAKE\_START
- HTTP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED
- HTTP\_REQUEST\_RECEIVE\_START
- MYSQL\_HB\_DB\_GET\_VERSION
- MYSQL LB ADD ADDR4
- MYSQL\_LB\_ADD\_ADDR6

- MYSQL\_LB\_COMMIT
- MYSQL\_LB\_DELETED\_EXPIRED\_RECLAIMED
- MYSQL\_LB\_DELETE\_ADDR4
- MYSQL\_LB\_DELETE\_ADDR6
- MYSQL\_LB\_DELETE\_EXPIRED\_RECLAIMED4
- MYSQL LB DELETE EXPIRED RECLAIMED6
- MYSQL\_LB\_GET4
- MYSQL\_LB\_GET6
- MYSQL\_LB\_GET\_ADDR4
- MYSQL\_LB\_GET\_ADDR6
- MYSQL\_LB\_GET\_CLIENTID
- MYSQL\_LB\_GET\_DUID
- MYSQL\_LB\_GET\_EXPIRED4
- MYSQL\_LB\_GET\_EXPIRED6
- MYSQL\_LB\_GET\_HOSTNAME4
- MYSQL\_LB\_GET\_HOSTNAME6
- MYSQL\_LB\_GET\_HWADDR
- MYSQL\_LB\_GET\_IAID\_DUID
- MYSQL\_LB\_GET\_IAID\_SUBID\_DUID
- MYSQL\_LB\_GET\_PAGE4
- MYSQL\_LB\_GET\_PAGE6
- MYSQL\_LB\_GET\_RELAYID4
- MYSQL\_LB\_GET\_RELAYID6
- MYSQL\_LB\_GET\_REMOTEID4
- MYSQL\_LB\_GET\_REMOTEID6
- MYSQL\_LB\_GET\_SUBID4
- MYSQL\_LB\_GET\_SUBID6
- MYSQL\_LB\_GET\_SUBID\_CLIENTID
- MYSQL\_LB\_GET\_SUBID\_HWADDR
- MYSQL\_LB\_GET\_SUBID\_PAGE6
- MYSQL\_LB\_GET\_VERSION
- MYSQL\_LB\_ROLLBACK
- MYSQL\_LB\_UPDATE\_ADDR4
- MYSQL\_LB\_UPDATE\_ADDR6
- MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_PAGE
- MYSQL\_LB\_UPGRADE\_EXTENDED\_INFO6\_PAGE

- PERFMON DHCP4 PKT EVENTS
- PERFMON\_DHCP4\_PKT\_PROCESS\_ERROR
- PERFMON\_DHCP6\_PKT\_EVENTS
- PERFMON\_DHCP6\_PKT\_PROCESS\_ERROR
- PGSQL\_HB\_DB\_GET\_VERSION
- PGSQL\_LB\_ADD\_ADDR4
- PGSQL\_LB\_ADD\_ADDR6
- PGSQL\_LB\_COMMIT
- PGSQL\_LB\_DELETE\_ADDR4
- PGSQL\_LB\_DELETE\_ADDR6
- PGSQL\_LB\_DELETE\_EXPIRED\_RECLAIMED4
- PGSQL\_LB\_DELETE\_EXPIRED\_RECLAIMED6
- PGSQL\_LB\_GET4
- PGSQL\_LB\_GET6
- PGSQL\_LB\_GET\_ADDR4
- PGSQL\_LB\_GET\_ADDR6
- PGSQL\_LB\_GET\_CLIENTID
- PGSQL\_LB\_GET\_DUID
- PGSQL\_LB\_GET\_EXPIRED4
- PGSQL\_LB\_GET\_EXPIRED6
- PGSQL\_LB\_GET\_HOSTNAME4
- PGSQL\_LB\_GET\_HOSTNAME6
- PGSQL\_LB\_GET\_HWADDR
- PGSQL\_LB\_GET\_IAID\_DUID
- PGSQL\_LB\_GET\_IAID\_SUBID\_DUID
- PGSQL\_LB\_GET\_PAGE4
- PGSQL\_LB\_GET\_PAGE6
- PGSQL\_LB\_GET\_RELAYID4
- PGSQL\_LB\_GET\_RELAYID6
- PGSQL\_LB\_GET\_REMOTEID4
- PGSQL\_LB\_GET\_REMOTEID6
- PGSQL\_LB\_GET\_SUBID4
- PGSQL\_LB\_GET\_SUBID6
- PGSQL\_LB\_GET\_SUBID\_CLIENTID
- PGSQL LB GET SUBID HWADDR
- PGSQL\_LB\_GET\_SUBID\_PAGE6

- PGSQL\_LB\_GET\_VERSION
- PGSQL\_LB\_ROLLBACK
- PGSQL\_LB\_UPDATE\_ADDR4
- PGSQL\_LB\_UPDATE\_ADDR6
- PGSQL\_LB\_UPGRADE\_EXTENDED\_INFO4\_PAGE
- PGSQL LB UPGRADE EXTENDED INFO6 PAGE
- TCP\_CONNECTION\_REJECTED\_BY\_FILTER
- TCP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED
- TCP\_REQUEST\_RECEIVE\_START
- TLS\_CONNECTION\_HANDSHAKE\_START
- TLS\_REQUEST\_RECEIVE\_START

### 34.8 Messages printed on debuglevel 55

- ALLOC ENGINE V4 REUSE EXPIRED LEASE DATA
- ALLOC\_ENGINE\_V6\_EXTEND\_LEASE\_DATA
- ALLOC\_ENGINE\_V6\_EXTEND\_NEW\_LEASE\_DATA
- ALLOC\_ENGINE\_V6\_REUSE\_EXPIRED\_LEASE\_DATA
- DHCP4\_CLIENT\_FQDN\_DATA
- DHCP4\_CLIENT\_HOSTNAME\_DATA
- DHCP4\_CLIENT\_NAME\_PROC\_FAIL
- DHCP4\_DHCP4O6\_RESPONSE\_DATA
- DHCP4\_DHCP4O6\_SUBNET\_DATA
- DHCP4 GENERATE FQDN
- DHCP4\_QUERY\_DATA
- DHCP4\_RECOVERED\_STASHED\_RELAY\_AGENT\_INFO
- DHCP4\_RESERVED\_HOSTNAME\_ASSIGNED
- DHCP4\_RESPONSE\_DATA
- DHCP4\_RESPONSE\_FQDN\_DATA
- DHCP4\_RESPONSE\_HOSTNAME\_DATA
- DHCP4\_SUBNET\_DATA
- DHCP6\_DDNS\_FQDN\_GENERATED
- DHCP6\_DHCP4O6\_RESPONSE\_DATA
- DHCP6 LEASE DATA
- DHCP6\_QUERY\_DATA
- DHCP6 RESPONSE DATA

- DHCP6\_SUBNET\_DATA
- DHCPSRV\_DDNS\_TTL\_PERCENT\_TOO\_SMALL
- DHCPSRV\_MEMFILE\_LEASE\_LOAD
- DHCPSRV\_QUEUE\_NCR
- DHCP DDNS AT MAX TRANSACTIONS
- DHCP\_DDNS\_FWD\_REQUEST\_IGNORED
- DHCP\_DDNS\_NO\_ELIGIBLE\_JOBS
- DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_RECEIVE
- DHCP\_DDNS\_REQUEST\_DROPPED
- DHCP\_DDNS\_REV\_REQUEST\_IGNORED
- EVAL\_DEBUG\_AND
- EVAL\_DEBUG\_BRANCH
- EVAL\_DEBUG\_CONCAT
- EVAL\_DEBUG\_EQUAL
- EVAL\_DEBUG\_HEXSTRING
- EVAL\_DEBUG\_IFELSE\_FALSE
- EVAL\_DEBUG\_IFELSE\_TRUE
- EVAL\_DEBUG\_INT16TOTEXT
- EVAL\_DEBUG\_INT32TOTEXT
- EVAL\_DEBUG\_INT8TOTEXT
- EVAL\_DEBUG\_IPADDRESS
- EVAL\_DEBUG\_IPADDRESSTOTEXT
- EVAL\_DEBUG\_LCASE
- EVAL\_DEBUG\_MATCH
- EVAL\_DEBUG\_MEMBER
- EVAL\_DEBUG\_NOT
- EVAL\_DEBUG\_OPTION
- EVAL\_DEBUG\_OR
- EVAL\_DEBUG\_PKT
- EVAL\_DEBUG\_PKT4
- EVAL\_DEBUG\_PKT6
- EVAL\_DEBUG\_POP\_AND\_BRANCH\_FALSE
- EVAL\_DEBUG\_POP\_OR\_BRANCH\_FALSE
- EVAL\_DEBUG\_POP\_OR\_BRANCH\_TRUE
- EVAL\_DEBUG\_RELAY6
- EVAL\_DEBUG\_RELAY6\_RANGE

- EVAL DEBUG SPLIT
- EVAL\_DEBUG\_SPLIT\_DELIM\_EMPTY
- EVAL\_DEBUG\_SPLIT\_EMPTY
- EVAL\_DEBUG\_SPLIT\_FIELD\_OUT\_OF\_RANGE
- EVAL DEBUG STRING
- EVAL DEBUG SUBSTRING
- EVAL\_DEBUG\_SUBSTRING\_EMPTY
- EVAL\_DEBUG\_SUBSTRING\_RANGE
- EVAL\_DEBUG\_TOHEXSTRING
- EVAL\_DEBUG\_UCASE
- EVAL\_DEBUG\_UINT16TOTEXT
- EVAL\_DEBUG\_UINT32TOTEXT
- EVAL\_DEBUG\_UINT8TOTEXT
- EVAL DEBUG VENDOR CLASS DATA
- EVAL\_DEBUG\_VENDOR\_CLASS\_DATA\_NOT\_FOUND
- EVAL DEBUG VENDOR CLASS ENTERPRISE ID
- EVAL DEBUG VENDOR CLASS ENTERPRISE ID MISMATCH
- EVAL DEBUG VENDOR CLASS EXISTS
- EVAL\_DEBUG\_VENDOR\_CLASS\_NO\_OPTION
- EVAL DEBUG VENDOR ENTERPRISE ID
- EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID\_MISMATCH
- EVAL\_DEBUG\_VENDOR\_EXISTS
- EVAL\_DEBUG\_VENDOR\_NO\_OPTION
- HOOKS ALL CALLOUTS DEREGISTERED
- HOOKS CALLOUT CALLED
- HOOKS\_CALLOUT\_DEREGISTERED
- HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_HOST
- HOSTS CFG GET ALL ADDRESS6 HOST
- HOSTS\_CFG\_GET\_ALL\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_HOST
- HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_HOST

- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_HOST
- HOSTS\_CFG\_GET\_ONE\_PREFIX\_HOST
- HOSTS\_CFG\_GET\_ONE\_PREFIX\_NULL
- HTTP\_CLIENT\_REQUEST\_SEND\_DETAILS
- HTTP\_DATA\_RECEIVED
- NETCONF\_CONFIG\_CHANGED\_DETAIL
- NETCONF\_GET\_CONFIG
- NETCONF\_SET\_CONFIG
- NETCONF\_UPDATE\_CONFIG
- NETCONF\_VALIDATE\_CONFIG
- TCP\_DATA\_RECEIVED
- TCP\_DATA\_SENT

# 34.9 Messages printed on debuglevel 70

• ASIODNS\_FETCH\_COMPLETED